



Intel(R) IXP400 Software API Reference Manual

Automatically generated from sources, July 12, 2006.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. Intel products are not intended for use in medical, life saving, life sustaining, critical control or safety systems, or in nuclear facility applications.

Intel may make changes to specifications and product descriptions at any time, without notice.

Intel Corporation may have patents or pending patent applications, trademarks, copyrights, or other intellectual property rights that relate to the presented subject matter. The furnishing of documents and other materials and information does not provide any license, express or implied, by estoppel or otherwise, to any such patents, trademarks, copyrights, or other intellectual property rights.

Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/products/processor_number for details.

Intel® IXP400 Software may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

MPEG is an international standard for video compression/decompression promoted by ISO. Implementations of MPEG CODECs, or MPEG enabled platforms may require licenses from various entities, including Intel Corporation.

This document and the software described in it are furnished under license and may only be used or copied in accordance with the terms of the license. The information in this document is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Intel Corporation. Intel Corporation assumes no responsibility or liability for any errors or inaccuracies that may appear in this document or any software that may be provided in association with this document. Except as permitted by such license, no part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means without the express written consent of Intel Corporation.

Except as permitted by such license, no part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means without the express written consent of Intel Corporation.

Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order.

Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's website at <http://www.intel.com>.

Intel, the Intel logo, and Intel XScale are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

*Other names and brands may be claimed as the property of others.

Copyright © Intel Corporation 2006

Table of Contents

Intel (R) IXP400 Software Component Co-exist.....	1
Defines.....	1
Detailed Description.....	1
Define Documentation.....	1
Intel (R) IXP400 Software ADSL Driver API.....	2
Typedefs.....	2
Enumerations.....	2
Functions.....	3
Detailed Description.....	3
Typedef Documentation.....	4
Enumeration Type Documentation.....	4
Function Documentation.....	5
Intel (R) IXP400 Software Assertion Macros (IxAssert) API.....	13
Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) API.....	14
Defines.....	14
Typedefs.....	15
Enumerations.....	15
Functions.....	16
Detailed Description.....	17
Define Documentation.....	18
Typedef Documentation.....	19
Enumeration Type Documentation.....	22
Function Documentation.....	23
Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Control API.....	37
Modules.....	37
Defines.....	37
Typedefs.....	37
Functions.....	38
Detailed Description.....	40
Define Documentation.....	40
Typedef Documentation.....	40
Function Documentation.....	44
Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Control API].....	59
Data Structures.....	59
Detailed Description.....	60
Intel (R) IXP400 Software ATM Manager (IxAtmm) API.....	61
Data Structures.....	61
Defines.....	61
Typedefs.....	62
Enumerations.....	62
Functions.....	63

Table of Contents

Intel (R) IXP400 Software ATM Manager (IxAtmm) API	
Detailed Description.....	64
Define Documentation.....	64
Typedef Documentation.....	66
Enumeration Type Documentation.....	66
Function Documentation.....	67
Intel (R) IXP400 Software ATM Transmit Scheduler (IxAtmSch) API.....	78
Defines.....	78
Functions.....	78
Detailed Description.....	79
Define Documentation.....	79
Function Documentation.....	80
Intel (R) IXP400 Software ATM Types (IxAtmTypes).....	87
Data Structures.....	87
Defines.....	87
Typedefs.....	88
Enumerations.....	89
Detailed Description.....	89
Define Documentation.....	89
Typedef Documentation.....	92
Enumeration Type Documentation.....	93
Intel (R) IXP400 Software DMA Types (IxDmaTypes).....	95
Enumerations.....	95
Detailed Description.....	96
Enumeration Type Documentation.....	96
Intel (R) IXP400 Software DMA Access Driver (IxDmaAcc) API.....	99
Defines.....	99
Typedefs.....	99
Functions.....	99
Detailed Description.....	100
Define Documentation.....	100
Typedef Documentation.....	100
Function Documentation.....	100
IXP400 Soft-Error Handler Driver (ixErrHdlAcc) API.....	103
Data Structures.....	103
Defines.....	103
Typedefs.....	103
Enumerations.....	103
Functions.....	104
Detailed Description.....	105
Define Documentation.....	105
Typedef Documentation.....	106
Enumeration Type Documentation.....	106

Table of Contents

IXP400 Soft–Error Handler Driver (ixErrHdlAcc) API	
Function Documentation.....	107
Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API.....	114
Data Structures.....	114
Defines.....	114
Typedefs.....	116
Enumerations.....	117
Functions.....	118
Detailed Description.....	122
Define Documentation.....	122
Typedef Documentation.....	132
Enumeration Type Documentation.....	134
Function Documentation.....	137
Intel (R) IXP400 Software Ethernet Database (IxEthDB) API.....	165
Data Structures.....	165
Defines.....	165
Typedefs.....	167
Enumerations.....	167
Functions.....	169
Detailed Description.....	175
Define Documentation.....	175
Typedef Documentation.....	179
Enumeration Type Documentation.....	180
Function Documentation.....	184
Intel (R) IXP400 Software Ethernet Database Port Definitions (IxEthDBPortDefs).....	232
Data Structures.....	232
Defines.....	232
Enumerations.....	233
Variables.....	233
Detailed Description.....	233
Define Documentation.....	233
Enumeration Type Documentation.....	235
Variable Documentation.....	236
Intel (R) IXP400 Software Ethernet Phy Access (IxEthMii) API.....	237
Functions.....	237
Detailed Description.....	237
Function Documentation.....	238
Intel(R) IXP Software Feature Control (featureCtrl) Public API.....	242
Modules.....	242
Defines.....	242
Typedefs.....	243
Functions.....	244
Detailed Description.....	244

Table of Contents

Intel(R) IXP Software Feature Control (featureCtrl) Public API	
Define Documentation.....	244
Typedef Documentation.....	247
Function Documentation.....	248
Software Configuration for featureCtrl Component [Intel(R) IXP Software Feature Control (featureCtrl) Public API].....	251
Defines.....	251
Enumerations.....	251
Detailed Description.....	252
Define Documentation.....	252
Enumeration Type Documentation.....	253
Intel (R) IXP400 Software HSS Access (IxHssAcc) APL.....	255
Data Structures.....	255
Defines.....	255
Typedefs.....	256
Enumerations.....	257
Functions.....	260
Detailed Description.....	263
Define Documentation.....	264
Typedef Documentation.....	267
Enumeration Type Documentation.....	269
Function Documentation.....	276
Intel (R) IXP400 Software I2C Driver(IxI2cDrv) APL.....	287
Data Structures.....	287
Defines.....	287
Typedefs.....	287
Enumerations.....	288
Functions.....	289
Detailed Description.....	291
Define Documentation.....	291
Typedef Documentation.....	291
Enumeration Type Documentation.....	293
Function Documentation.....	295
Intel (R) IXP NPE–Downloader (IxNpeDI) APL.....	304
Modules.....	304
Defines.....	304
Functions.....	304
Detailed Description.....	305
Define Documentation.....	305
Function Documentation.....	306
Intel (R) IXP Image ID Definition [Intel (R) IXP NPE–Downloader (IxNpeDI) API].....	312
Data Structures.....	312
Defines.....	312

Table of Contents

Intel (R) IXP Image ID Definition [Intel (R) IXP NPE–Downloader (IxNpeDI) API]	
Typedefs.....	312
Enumerations.....	313
Detailed Description.....	313
Define Documentation.....	313
Typedef Documentation.....	314
Enumeration Type Documentation.....	315
Intel (R) IXP Software NPE Message Handler (IxNpeMh) APL.....	317
Data Structures.....	317
Defines.....	317
Typedefs.....	317
Enumerations.....	317
Functions.....	318
Detailed Description.....	319
Define Documentation.....	319
Typedef Documentation.....	319
Enumeration Type Documentation.....	320
Function Documentation.....	321
IXP400 NPE Microcode Image Library.....	327
Defines.....	327
Detailed Description.....	329
Define Documentation.....	329
Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) APL.....	336
Data Structures.....	336
Typedefs.....	338
Enumerations.....	338
Functions.....	340
Detailed Description.....	341
Typedef Documentation.....	341
Enumeration Type Documentation.....	342
Function Documentation.....	345
Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) APL.....	352
Data Structures.....	352
Defines.....	352
Enumerations.....	353
Functions.....	357
Detailed Description.....	359
Define Documentation.....	359
Enumeration Type Documentation.....	360
Function Documentation.....	370
IXP Queue Manager (qmgr) Public APL.....	382
Defines.....	382
Typedefs.....	382

Table of Contents

IXP Queue Manager (qmgr) Public API	
Enumerations.....	382
Functions.....	382
Detailed Description.....	383
Define Documentation.....	383
Typedef Documentation.....	384
Enumeration Type Documentation.....	384
Function Documentation.....	385
Intel (R) IXP400 Software Queue Assignments.....	387
Defines.....	387
Detailed Description.....	389
Define Documentation.....	389
Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API.....	396
Data Structures.....	396
Typedefs.....	396
Enumerations.....	396
Functions.....	399
Detailed Description.....	401
Typedef Documentation.....	401
Enumeration Type Documentation.....	402
Function Documentation.....	404
Intel (R) IXP400 Software Timer Control (IxTimerCtrl) API.....	419
Defines.....	419
Typedefs.....	419
Enumerations.....	419
Functions.....	419
Detailed Description.....	420
Define Documentation.....	420
Typedef Documentation.....	420
Enumeration Type Documentation.....	421
Function Documentation.....	421
Intel (R) IXP400 Software Time Sync Access Component API.....	424
Data Structures.....	424
Typedefs.....	425
Enumerations.....	425
Functions.....	426
Detailed Description.....	427
Typedef Documentation.....	428
Enumeration Type Documentation.....	428
Function Documentation.....	430
Intel (R) IXP400 Software Types (IxTypes).....	439
Defines.....	439
Typedefs.....	439

Table of Contents

Intel (R) IXP400 Software Types (IxTypes)	
Detailed Description.....	439
Intel (R) IXP400 Software UART Access (IxUARTAcc) APL.....	440
Modules.....	440
Data Structures.....	440
Enumerations.....	440
Functions.....	440
Detailed Description.....	441
Enumeration Type Documentation.....	441
Function Documentation.....	441
Defines for Default Values [Intel (R) IXP400 Software UART Access (IxUARTAcc) API].....	444
Defines.....	444
Detailed Description.....	444
Define Documentation.....	444
Defines for IOCTL Commands [Intel (R) IXP400 Software UART Access (IxUARTAcc) API].....	446
Defines.....	446
Detailed Description.....	446
Define Documentation.....	446
Defines for IOCTL Arguments [Intel (R) IXP400 Software UART Access (IxUARTAcc) API].....	448
Defines.....	448
Detailed Description.....	448
Define Documentation.....	449
Intel (R) IXP400 Software Version ID (IxVersionId).....	451
Defines.....	451
Detailed Description.....	451
Define Documentation.....	451
IX_OSAL_ATTRIBUTE_PACKED Struct Reference [Intel (R) IXP400 Software Ethernet Database (IxEthDB) API].....	454
Data Fields.....	454
Detailed Description.....	454
IxAtmdAccUtopiaConfig Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	455
Data Fields.....	455
Detailed Description.....	456
Field Documentation.....	456
IxAtmdAccUtopiaConfig::UtRxConfig_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	460
Data Fields.....	460
Detailed Description.....	461
Field Documentation.....	461

Table of Contents

IxAtmdAccUtopiaConfig::UtRxDefineIdle_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	466
Data Fields.....	466
Detailed Description.....	466
Field Documentation.....	467
IxAtmdAccUtopiaConfig::UtRxEnableFields_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	468
Data Fields.....	468
Detailed Description.....	470
Field Documentation.....	470
IxAtmdAccUtopiaConfig::UtRxStatsConfig_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	476
Data Fields.....	476
Detailed Description.....	476
Field Documentation.....	477
IxAtmdAccUtopiaConfig::UtRxTransTable0_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	478
Data Fields.....	478
Detailed Description.....	478
Field Documentation.....	478
IxAtmdAccUtopiaConfig::UtRxTransTable1_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	481
Data Fields.....	481
Detailed Description.....	481
Field Documentation.....	481
IxAtmdAccUtopiaConfig::UtRxTransTable2_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	484
Data Fields.....	484
Detailed Description.....	484
Field Documentation.....	484
IxAtmdAccUtopiaConfig::UtRxTransTable3_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	487
Data Fields.....	487
Detailed Description.....	487
Field Documentation.....	487
IxAtmdAccUtopiaConfig::UtRxTransTable4_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	490
Data Fields.....	490
Detailed Description.....	490
Field Documentation.....	490

Table of Contents

IxAtmdAccUtopiaConfig::UtRxTransTable5_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	493
Data Fields.....	493
Detailed Description.....	493
Field Documentation.....	493
 IxAtmdAccUtopiaConfig::UtSysConfig_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	 494
Data Fields.....	494
Detailed Description.....	495
Field Documentation.....	495
 IxAtmdAccUtopiaConfig::UtTxConfig_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	 497
Data Fields.....	497
Detailed Description.....	498
Field Documentation.....	498
 IxAtmdAccUtopiaConfig::UtTxDefineIdle_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	 502
Data Fields.....	502
Detailed Description.....	502
Field Documentation.....	503
 IxAtmdAccUtopiaConfig::UtTxEnableFields_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	 504
Data Fields.....	504
Detailed Description.....	505
Field Documentation.....	505
 IxAtmdAccUtopiaConfig::UtTxStatsConfig_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	 509
Data Fields.....	509
Detailed Description.....	509
Field Documentation.....	510
 IxAtmdAccUtopiaConfig::UtTxTransTable0_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	 511
Data Fields.....	511
Detailed Description.....	511
Field Documentation.....	511
 IxAtmdAccUtopiaConfig::UtTxTransTable1_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	 514
Data Fields.....	514
Detailed Description.....	514
Field Documentation.....	514

Table of Contents

IxAtmdAccUtopiaConfig::UtTxTransTable2_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	517
Data Fields.....	517
Detailed Description.....	517
Field Documentation.....	517
IxAtmdAccUtopiaConfig::UtTxTransTable3_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	520
Data Fields.....	520
Detailed Description.....	520
Field Documentation.....	520
IxAtmdAccUtopiaConfig::UtTxTransTable4_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	523
Data Fields.....	523
Detailed Description.....	523
Field Documentation.....	523
IxAtmdAccUtopiaConfig::UtTxTransTable5_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	526
Data Fields.....	526
Detailed Description.....	526
Field Documentation.....	526
IxAtmdAccUtopiaStatus Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	527
Data Fields.....	527
Detailed Description.....	527
Field Documentation.....	528
IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	530
Data Fields.....	530
Detailed Description.....	531
Field Documentation.....	531
IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_ Struct Reference [Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API].....	533
Data Fields.....	533
Detailed Description.....	533
Field Documentation.....	533
IxAtmmPortCfg Struct Reference [Intel (R) IXP400 Software ATM Manager (IxAtmm) API].....	536
Data Fields.....	536
Detailed Description.....	536
Field Documentation.....	536

Table of Contents

IxAtmmVc Struct Reference [Intel (R) IXP400 Software ATM Manager (IxAtmm) API].....	538
Data Fields.....	538
Detailed Description.....	538
Field Documentation.....	538
IxAtmScheduleTable Struct Reference [Intel (R) IXP400 Software ATM Types (IxAtmTypes)].....	540
Data Fields.....	540
Detailed Description.....	540
Field Documentation.....	540
IxAtmScheduleTableEntry Struct Reference [Intel (R) IXP400 Software ATM Types (IxAtmTypes)].....	542
Data Fields.....	542
Detailed Description.....	542
Field Documentation.....	542
IxAtmTrafficDescriptor Struct Reference [Intel (R) IXP400 Software ATM Types (IxAtmTypes)]... 	544
Data Fields.....	544
Detailed Description.....	544
Field Documentation.....	545
IxErrHdlAccRecoveryStatistics Struct Reference [IXP400 Soft–Error Handler Driver (ixErrHdlAcc) API].....	547
Data Fields.....	547
Detailed Description.....	547
IxEthAccMacAddr Struct Reference [Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API].....	548
Data Fields.....	548
Detailed Description.....	548
Field Documentation.....	548
IxEthAccNe Struct Reference [Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API, Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API, Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API].....	549
Data Fields.....	549
Detailed Description.....	550
Field Documentation.....	550
IxEthDBPortDefinition Struct Reference [Intel (R) IXP400 Software Ethernet Database Port Definitions (IxEthDBPortDefs)].....	552
Data Fields.....	552
Detailed Description.....	552
IxEthDBWiFiRecData Struct Reference [Intel (R) IXP400 Software Ethernet Database (IxEthDB) API].....	553
Data Fields.....	553
Detailed Description.....	553

Table of Contents

IxEthEthObjStats Struct Reference [Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API].....	554
Data Fields.....	554
Detailed Description.....	555
Field Documentation.....	556
IxHssAccConfigParams Struct Reference [Intel (R) IXP400 Software HSS Access (IxHssAcc) API].....	560
Data Fields.....	560
Detailed Description.....	560
Field Documentation.....	560
IxHssAccHdlcMode Struct Reference [Intel (R) IXP400 Software HSS Access (IxHssAcc) API].....	563
Data Fields.....	563
Detailed Description.....	563
Field Documentation.....	563
IxHssAccPktHdlcFraming Struct Reference [Intel (R) IXP400 Software HSS Access (IxHssAcc) API].....	565
Data Fields.....	565
Detailed Description.....	565
Field Documentation.....	565
IxHssAccPortConfig Struct Reference [Intel (R) IXP400 Software HSS Access (IxHssAcc) API].....	567
Data Fields.....	567
Detailed Description.....	568
Field Documentation.....	568
IxI2cInitVars Struct Reference [Intel (R) IXP400 Software I2C Driver(IxI2cDrv) API].....	572
Data Fields.....	572
Detailed Description.....	572
Field Documentation.....	573
IxI2cStatsCounters Struct Reference [Intel (R) IXP400 Software I2C Driver(IxI2cDrv) API].....	575
Data Fields.....	575
Detailed Description.....	575
Field Documentation.....	576
IxNpeDllImageId Struct Reference [Intel (R) IXP Image ID Definition].....	578
Data Fields.....	578
Detailed Description.....	578
Field Documentation.....	578
IxNpeMhMessage Struct Reference [Intel (R) IXP Software NPE Message Handler (IxNpeMh) API].....	580
Data Fields.....	580
Detailed Description.....	580
Field Documentation.....	580

Table of Contents

IxParityENAccAHBErrorTransaction Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	581
Data Fields.....	581
Detailed Description.....	581
Field Documentation.....	581
IxParityENAccEbcConfig Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	583
Data Fields.....	583
Detailed Description.....	583
Field Documentation.....	584
IxParityENAccEbcParityErrorStats Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	586
Data Fields.....	586
Detailed Description.....	586
Field Documentation.....	586
IxParityENAccHWParityConfig Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	587
Data Fields.....	587
Detailed Description.....	587
Field Documentation.....	587
IxParityENAccMcuConfig Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	590
Data Fields.....	590
Detailed Description.....	590
Field Documentation.....	590
IxParityENAccMcuParityErrorStats Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	592
Data Fields.....	592
Detailed Description.....	592
Field Documentation.....	592
IxParityENAccNpeConfig Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	594
Data Fields.....	594
Detailed Description.....	594
Field Documentation.....	594

Table of Contents

IxParityENAccNpeParityErrorStats Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	595
Data Fields.....	595
Detailed Description.....	595
Field Documentation.....	595
 IxParityENAccParityErrorMessage Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	597
Data Fields.....	597
Detailed Description.....	597
Field Documentation.....	597
 IxParityENAccParityErrorStats Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	599
Data Fields.....	599
Detailed Description.....	599
Field Documentation.....	599
 IxParityENAccPbcConfig Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	601
Data Fields.....	601
Detailed Description.....	601
Field Documentation.....	601
 IxParityENAccPbcParityErrorStats Struct Reference [Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API].....	602
Data Fields.....	602
Detailed Description.....	602
Field Documentation.....	602
 IxPerfProfAccBusPmuResults Struct Reference [Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API].....	603
Data Fields.....	603
Detailed Description.....	603
Field Documentation.....	603
 IxPerfProfAccXcycleResults Struct Reference [Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API].....	604
Data Fields.....	604
Detailed Description.....	604
Field Documentation.....	604

Table of Contents

IxPerfProfAccXscalePmuEvtCnt Struct Reference [Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API].....	606
Data Fields.....	606
Detailed Description.....	606
Field Documentation.....	606
IxPerfProfAccXscalePmuResults Struct Reference [Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API].....	607
Data Fields.....	607
Detailed Description.....	607
Field Documentation.....	608
IxPerfProfAccXscalePmuSamplePcProfile Struct Reference [Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API].....	610
Data Fields.....	610
Detailed Description.....	610
Field Documentation.....	610
IxSspAccStatsCounters Struct Reference [Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API, Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API].....	611
Data Fields.....	611
Detailed Description.....	611
Field Documentation.....	611
IxSspInitVars Struct Reference [Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API, Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API].....	613
Data Fields.....	613
Detailed Description.....	614
Field Documentation.....	614
IxTimeSyncAccPtpMsgData Struct Reference [Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API].....	617
Data Fields.....	617
Detailed Description.....	617
Field Documentation.....	617
IxTimeSyncAccStats Struct Reference [Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API].....	619
Data Fields.....	619
Detailed Description.....	619
Field Documentation.....	619
IxTimeSyncAccTimeValue Struct Reference [Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API].....	620
Data Fields.....	620

Table of Contents

IxTimeSyncAccTimeValue Struct Reference [Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API]	
Detailed Description.....	620
Field Documentation.....	620
 IxTimeSyncAccUuid Struct Reference [Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API].....	621
Data Fields.....	621
Detailed Description.....	621
Field Documentation.....	621
 ixUARTDev Struct Reference [Intel (R) IXP400 Software UART Access (IxUARTAcc) API, Intel (R) IXP400 Software UART Access (IxUARTAcc) API].....	622
Data Fields.....	622
Detailed Description.....	622
Field Documentation.....	622
 ixUARTStats Struct Reference [Intel (R) IXP400 Software UART Access (IxUARTAcc) API, Intel (R) IXP400 Software UART Access (IxUARTAcc) API].....	624
Data Fields.....	624
Detailed Description.....	624

Intel (R) IXP400 Software Component Co-exist

component coexist information

Defines

```
#define IX_ETH_HSS_COM_MUT_UNLOCK()  
    macros for common mutex control for ETH & HSS co-existence  
  
#define IX_ETH_HSS_COM_MUT_LOCK(result)  
    macros for common mutex control for ETH & HSS co-existence
```

Detailed Description

component coexist information

Define Documentation

```
#define IX_ETH_HSS_COM_MUT_LOCK ( result )
```

macros for common mutex control for ETH & HSS co-existence

Definition at line **77** of file **IxAccCommon.h**.

```
#define IX_ETH_HSS_COM_MUT_UNLOCK ( )
```

macros for common mutex control for ETH & HSS co-existence

Definition at line **65** of file **IxAccCommon.h**.

Intel (R) IXP400 Software ADSL Driver API

The public API for the IXP400 ADSL Driver.

Typedefs

```
typedef void(* IxAdslStateChangeCallback )(UINT32 lineNum, IxAdslLineState lineState)
```

Callback function to indicate of the changes on the line state.

Enumerations

```
enum IxAdslStatus {  
    IX_ADSL_STATUS_SUCCESS,  
    IX_ADSL_STATUS_FAIL,  
    IX_ADSL_STATUS_UNSUPPORTED_MODE,  
    IX_ADSL_STATUS_ALREADY_DOWN  
}
```

These status will be used by the APIs to return to the client.

```
enum IxAdslLineState {  
    IX_ADSL_LINE_STATE_UP_DUAL_LATENCY,  
    IX_ADSL_LINE_STATE_WAIT_FOR_ACTIVATING,  
    IX_ADSL_LINE_STATE_ACTIVATING,  
    IX_ADSL_LINE_STATE_DOWN,  
    IX_ADSL_LINE_STATE_UP_FASTCHANNEL,  
    IX_ADSL_LINE_STATE_UP_INTERLEAVECHANNEL,  
    IX_ADSL_LINE_STATE_INVALID  
}
```

These status will be used to indicate the line state.

```
enum IxAdslLineType {  
    IX_ADSL_AUTOSELECT,  
    IX_ADSL_GLITE,  
    IX_ADSL_DMT,  
    IX_ADSL_ANSI,  
    IX_ADSL_LOOPBACK,  
    IX_ADSL_INVALID_MODE  
}
```

Used to indicate the type of ADSL line type used.

```
enum IxAdslPhyType {  
    IX_ADSL_PHY_CPE,  
    IX_ADSL_PHY_INVALID  
}
```

Used to indicate the ADSL physical type – CPE.

Functions

PUBLIC **ixAdslLineOpen** (UINT32 lineNum, **ixAdslLineType** lineType, **ixAdslPhyType** phyType)
ixAdslStatus

Open the given ADSL line in the specified mode and type.

PUBLIC

ixAdslStatus **ixAdslLineClose** (UINT32 lineNum)

Closes a previously opened ADSL line.

PUBLIC **ixAdslLineStateChangeCallbackRegister** (UINT32 lineNum,
ixAdslStatus **ixAdslStateChangeCallback** lineChangeCallbackFn)

This is a notification registration procedure that gets called if the line state of the given ADSL line changes. The maximum callbacks that can be registered is defined as IX_ADSL_SIZEOF_CALLBACK_LIST (The default value is 10).

PUBLIC

ixAdslLineState **ixAdslLineStateGet** (UINT32 lineNum)

Returns the current state of the given ADSL line.

PUBLIC **UINT32** **ixAdslLineRateUpstreamGet** (UINT32 lineNum)

Return the current upstream line speed of the given ADSL line.

PUBLIC **UINT32** **ixAdslLineRateDownstreamGet** (UINT32 lineNum)

Return the current downstream line speed of the given ADSL line.

PUBLIC

ixAdslStatus **ixAdslDyingGaspEnable** (UINT32 lineNum)

Enables the function that informs ATU-C when condition that leads to shutdown of the given Adsl line has been detected.

PUBLIC **ixAdslVendorCodeSet** (UINT32 lineNum, **UINT8** ixAdslItuVendoridCountrycode,
ixAdslStatus **UINT8** ixAdslItuVendoridVendorcode1, **UINT8** ixAdslItuVendoridVendorcode2, **UINT8** ixAdslItuVendoridVendorcode3, **UINT8** ixAdslItuVendoridVendorcode4, **UINT8** ixAdslItuVendoridVendorspecific1, **UINT8** ixAdslItuVendoridVendorspecific2)

Set the vendor specific bytes in the given ADSL line.

PUBLIC **void** **ixAdslShow** (UINT32 lineNum)

This function will show the current statistics associated with the given ADSL Line.

PUBLIC **void** **ixAdslMemoryUnmap** (**void**)

This function will unmap the dynamically allocated addresses.

Detailed Description

The public API for the IXP400 ADSL Driver.

Typedef Documentation

```
typedef void(* IxAdslStateChangeCallback)( UINT32 lineNum, IxAdslLineState lineState)
```

Callback function to indicate of the changes on the line state.

Definition at line **142** of file **IxAdsl.h**.

Enumeration Type Documentation

```
enum IxAdslLineState
```

These status will be used to indicate the line state.

Enumeration values:

<i>IX_ADSL_LINE_STATE_UP_DUAL_LATENCY</i>	The line is in showtime state.
<i>IX_ADSL_LINE_STATE_WAIT_FOR_ACTIVATING</i>	Fast & Interleaved Channel The line is waiting for the peer to activate.
<i>IX_ADSL_LINE_STATE_ACTIVATING</i>	The line is negotiating with its peer.
<i>IX_ADSL_LINE_STATE_DOWN</i>	The line is down.
<i>IX_ADSL_LINE_STATE_UP_FASTCHANNEL</i>	The line is in showtime state. Fast Channel
<i>IX_ADSL_LINE_STATE_UP_INTERLEAVECHANNEL</i>	The line is in showtime state. Interleaved Channel
<i>IX_ADSL_LINE_STATE_INVALID</i>	ADSL line in an unknown state.

Definition at line **55** of file **IxAdsl.h**.

```
enum IxAdslLineType
```

Used to indicate the type of ADSL line type used.

Enumeration values:

<i>IX_ADSL_AUTOSELECT</i>	This is an auto-select mode for the CPE to auto-configure based on the CO/DSLAM line type; DMT, ANSI or G.lite.
<i>IX_ADSL_GLITE</i>	G.lite line type.
<i>IX_ADSL_DMT</i>	DMT line type.
<i>IX_ADSL_ANSI</i>	ANSI line type.
<i>IX_ADSL_LOOPBACK</i>	Utopia Loopback line type.

IX_ADSL_INVALID_MODE Used internally to indicate last valid enum.

Definition at line **96** of file **IxAdsl.h**.

enum IxAdslPhyType

Used to indicate the ADSL physical type – CPE.

Note:

IxAdslPhyType is declared as an enum due to forward compatibility to support CO (fast and interleaved mode) in the future.

Enumeration values:

IX_ADSL_PHY_CPE Adsl type is CPE.

IX_ADSL_PHY_INVALID Adsl type is invalid.

Definition at line **125** of file **IxAdsl.h**.

enum IxAdslStatus

These status will be used by the APIs to return to the client.

Enumeration values:

IX_ADSL_STATUS_SUCCESS Successful API execution.

IX_ADSL_STATUS_FAIL Failed API execution.

IX_ADSL_STATUS_UNSUPPORTED_MODE Unsupported mode type for IxAdslLineOpen function.

IX_ADSL_STATUS_ALREADY_DOWN Line is already down.

Definition at line **34** of file **IxAdsl.h**.

Function Documentation

ixAdslDyingGaspEnable (UINT32 *lineNum*)

Enables the function that informs ATU–C when condition that leads to shutdown of the given Adsl line has been detected.

Note:

The parameter lineNum exists for future Multi–PHY support. Only lineNum = 0 is valid.

Blocking : This call is a non–blocking

Impacts On Global Data: None

Pre–Conditions: Task level calls only. Only Available in ATU–R.

Post-Conditions: None.

Exceptions: None.

Parameters:

lineNum UINT32 [in] – is the parameter showing which ADSL line is being used.

Returns:

◇ IX_ADSL_STATUS_SUCCESS – Dying Gasp is enabled. successfully.

◇ IX_ADSL_STATUS_FAILED – Failed to enable Dying Gasp.

```
ixAdslLineClose ( UINT32 lineNum )
```

Closes a previously opened ADSL line.

The line will closed and put in the idle state.

Note:

The parameter *lineNum* exists for future Multi-PHY support. Only *lineNum* = 0 is valid.

Blocking : Non-blocking

Impacts On Global Data: Sets the lineEnable State . Notifies a callback routine.

Pre-Conditions: Code should only be called from task level.

Post-Conditions: No cleanup after this call is required.

Parameters:

lineNum UINT32 [in] – is the parameter showing which ADSL line is being used and to be closed.

Returns:

◇ IX_ADSL_STATUS_SUCCESS – Line was closed successfully.

◇ IX_ADSL_STATUS_FAILED – Line failed to close properly.

◇ IX_ADSL_STATUS_ALREADY_DOWN – Line was not open before close.

```
ixAdslLineOpen ( UINT32 lineNum,  
                  IxAdslLineType lineType,  
                  IxAdslPhyType phyType  
                  )
```

Open the given ADSL line in the specified mode and type.

Opens the given ADSL line in the specified mode and puts it in the 'Showtime' state, i.e. available to carry user data.

Note:

- The parameter lineNum exists for future Multi-PHY support. Only lineNum = 0 is valid.
- The parameter phyType exists for future CO support.

Blocking : This call may block for several seconds while the link is established.

Impacts On Global Data: Sets the lineEnable State .

Pre-Conditions: The code must only be called once the operating system is running, i.e. do not call as part of the hardware init as this code requires base services such as Atmd, Atmm, Atm scheduler and Utopia. The code should only be called from task level.

Post-Conditions: No cleanup after this call is required.

Exceptions: None.

Parameters:

lineNum **UINT32** [in] – is the parameter showing which ADSL line is being used.

lineType **IxAdslLineType** [in] – indicates type of ADSL to be opened.

phyType **IxAdslPhyType** [in] – is the type of Phy used – CPE.

Returns:

◇ **IX_ADSL_STATUS_SUCCESS** – Line was opened and is in 'showtime' state

◇ **IX_ADSL_STATUS_FAILED** – Line failed to open properly.

◇ **IX_ADSL_STATUS_UNSUPPORTED_MODE** – Illegal ADSL type for IxAdslLineOpen function.

ixAdslLineRateDownstreamGet (**UINT32 *lineNum*)**

Return the current downstream line speed of the given ADSL line.

The data returned by this API is the received (Rx) rate of the line the ATU device.

Note:

The parameter lineNum exists for future Multi-PHY support. Only lineNum = 0 is valid.

Blocking : This call is a non-blocking

Impacts On Global Data: None

Pre-Conditions: Task level calls only.

Post-Conditions: None.

Exceptions: None.

Parameters:

lineNum UINT32 [in] – is the parameter showing which ADSL line is being used.

Returns:

◇ Integer – bit rate in kbits/second. N.B. Returns zero if the line is not in 'Showtime' state.

```
ixAdslLineRateUpstreamGet ( UINT32 lineNum )
```

Return the current upstream line speed of the given ADSL line.

Note:

The parameter *lineNum* exists for future Multi-PHY support. Only *lineNum* = 0 is valid.

The data returned by this API represents the transmit (Tx) rate of the line from the ATU device.

Blocking : This call is a non-blocking

Impacts On Global Data: None

Pre-Conditions: Task level calls only.

Post-Conditions: None.

Exceptions: None.

Parameters:

lineNum UINT32 [in] – is the parameter showing which ADSL line is being used.

Returns:

◇ Integer – bit rate in kbits/second. N.B. Returns zero if the line is not in 'Showtime' state.

```
ixAdslLineStateChangeCallbackRegister ( UINT32 lineNum,  
                                         IxAdslStateChangeCallback lineChangeCallbackFn  
                                         )
```

This is a notification registration procedure that gets called if the line state of the given ADSL line changes. The maximum callbacks that can be registered is defined as IX_ADSL_SIZEOF_CALLBACK_LIST (The default value is 10).

Note:

The parameter *lineNum* exists for future Multi-PHY support. Only *lineNum* = 0 is valid.

Blocking : This call is a non-blocking function.

Impacts On Global Data: This sets a global callback handler.

Pre-Conditions: There are no pre conditions to this call.

Post-Conditions: A global line state handler for ADSL line state changes shall be registered. It is advisable to register the callback before the given ADSL line is opened.

Exceptions: None.

Parameters:

lineNum UINT32 [in] – is the parameter showing which ADSL line is being used.
lineChangeCallbackFn **IxAdslStateChangeCallback** [in] – is the callback function that will be invoked when there is a state change

Returns:

- ◇ IX_ADSL_STATUS_SUCCESS – The callback function was registered successfully.
- ◇ IX_ADSL_STATUS_FAILED – Internal error, registration of the callback function failed.

```
ixAdslLineStateGet ( UINT32 lineNum )
```

Returns the current state of the given ADSL line.

Note:

The parameter lineNum exists for future Multi-PHY support. Only lineNum = 0 is valid.

Blocking : This call is a non-blocking

Impacts On Global Data: None

Pre-Conditions: Task level calls only.

Post-Conditions: None.

Exceptions: None.

Parameters:

lineNum UINT32 [in] – is the parameter showing which ADSL line is being used.

Returns:

- ◇ IX_ADSL_LINE_STATE_UP_FAST – The line is in show time state.
- ◇ IX_ADSL_LINE_STATE_WAIT_FOR_ACTIVATING – The line is waiting fo the peer to activate.
- ◇ IX_ADSL_LINE_STATE_ACTIVATING – The line is negotiating with its peer.
- ◇ IX_ADSL_LINE_STATE_DOWN – The line is idle.
- ◇ IX_ADSL_LINE_STATE_INVALID – The line is in an unknown state.

ixAdslMemoryUnmap (void)

This function will unmap the dynamically allocated addresses.

Blocking : This call is non-blocking.

Impacts On Global Data: None

Pre-Conditions: Task level calls only.

Post-Conditions: None.

Exceptions: None.

Parameters:

None

Returns:

None

ixAdslShow (UINT32 lineNum)

This function will show the current statistics associated with the given ADSL Line.

Note:

The parameter lineNum exists for future Multi-PHY support. Only lineNum = 0 is valid.

The list of statistics to be shown by IxAdslShow:

- Controller SW Version
- ADSL Line State
- Line Number
- Upstream and Downstream Rate
- Training Statistics for Upstream and Downstream Rates
- ADSL Near End Operational Data such as Upstream Relative Capacity Occupancy, Noise Margin Upstream, Output Pwr Downstream, Attenuation Upstream, Downstream Fast Bitrate, Downstream Interleaved Bitrate, Near-end defect bitmap, Loss of Frame (secs), Loss of Cell delineation (secs), Loss of Signal (secs), Loss of Margin (secs), Errored seconds, HEC and FEC Errors.
- ADSL Far End Operational Data such as Downstream Relative Capacity Occupancy, Noise Margin Downstream, Output Pwr Upstream, Attenuation Downstream, Upstream Fast Bitrate, Upstream Interleaved Bitrate, Far-end defect bitmap
- Tx and Rx ATM Cell Counters

Blocking : This call is non-blocking.

Impacts On Global Data: None

Pre-Conditions: Task level calls only.

Post-Conditions: None.

Exceptions: None.

Parameters:

lineNum UINT32 [in] – is the parameter showing which ADSL line is being used.

Returns:

None

```
ixAdslVendorCodeSet ( UINT32 lineNum,  
                      UINT8  ixAdslItuVendoridCountrycode,  
                      UINT8  ixAdslItuVendoridVendorcode1,  
                      UINT8  ixAdslItuVendoridVendorcode2,  
                      UINT8  ixAdslItuVendoridVendorcode3,  
                      UINT8  ixAdslItuVendoridVendorcode4,  
                      UINT8  ixAdslItuVendoridVendorspecific1,  
                      UINT8  ixAdslItuVendoridVendorspecific2  
                      )
```

Set the vendor specific bytes in the given ADSL line.

The vendor ID must be set before the line is open, if not the default vendor ID shall be sent to the peer modem upon request.

Note:

- Vendor specific values are taken by the phy and linked together to form a single code
- Note that the parameter lineNum exists for future Multi-PHY support. Only lineNum = 0 is valid.

Blocking : This call is a non-blocking

Impacts On Global Data: Sets an internal ADSL global data structure. This shall be used for all subsequent ADSL line open commands.

Pre-Conditions: Task level calls only.

Post-Conditions: None.

Exceptions: None.

Parameters:

<i>lineNum</i>	UINT32 [in] – is the parameter showing which ADSL line is being used.
<i>ixAdslItuVendoridCountrycode</i>	UINT8 [in] – is the vendor country code that are predefined in standards.
<i>ixAdslItuVendoridVendorcode1</i>	UINT8 [in] – is the vendor code 1 that are predefined in

	standards.
<i>ixAdslItuVendoridVendorcode2</i>	UINT8 [in] – is the vendor code 2 that are predefined in standards.
<i>ixAdslItuVendoridVendorcode3</i>	UINT8 [in] – is the vendor code 3 that are predefined in standards.
<i>ixAdslItuVendoridVendorcode4</i>	UINT8 [in] – is the vendor code 4 that are predefined in standards.
<i>ixAdslItuVendoridVendorspecific1</i>	UINT8 [in] – is the vendor specific 1 that are predefined in standards.
<i>ixAdslItuVendoridVendorspecific2</i>	UINT8 [in] – is the vendor specific 2 that are predefined in standards.

Returns:

- ◇ IX_ADSL_STATUS_SUCCESS – Set Vendor Code successful.
- ◇ IX_ADSL_STATUS_FAILED – Set Vendor Code failed because the line is up.

Intel (R) IXP400 Software Assertion Macros (IxAssert) API

Assertion support.

Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) API

The public API for the IXP400 Atm Driver Data component.

Defines

#define IX_ATMDACC_WARNING
Warning return code.

#define IX_ATMDACC_BUSY
Busy return code.

#define IX_ATMDACC_RESOURCES_STILL_ALLOCATED
Disconnect return code.

#define IX_ATMDACC_DEFAULT_REPLENISH_COUNT
Default resources usage for RxVcFree replenish mechanism.

#define IX_ATMDACC_OAM_TX_VPI
The reserved value used for the dedicated OAM Tx connection. This "well known" value is used by atmdAcc and its clients to discriminate the OAM channel, and should be chosen so that it does not coincide with the VPI value used in an AAL0/AAL5 connection. Any attempt to connect a service type other than OAM on this VPI will fail.

#define IX_ATMDACC_OAM_TX_VCI
The reserved value used for the dedicated OAM Tx connection. This "well known" value is used by atmdAcc and its clients to discriminate the OAM channel, and should be chosen so that it does not coincide with the VCI value used in an AAL0/AAL5 connection. Any attempt to connect a service type other than OAM on this VCI will fail.

#define IX_ATMDACC_OAM_RX_PORT
The reserved dummy PORT used for all dedicated OAM Rx connections. Note that this is not a real port but must have a value that lies within the valid range of port values.

#define IX_ATMDACC_OAM_RX_VPI
The reserved value value used for the dedicated OAM Rx connection. This value should be chosen so that it does not coincide with the VPI value used in an AAL0/AAL5 connection. Any attempt to connect a service type other than OAM on this VPI will fail.

#define IX_ATMDACC_OAM_RX_VCI
The reserved value value used for the dedicated OAM Rx connection. This value should be chosen so that it does not coincide with the VCI value used in an AAL0/AAL5 connection. Any attempt to connect a service type other than OAM on this VCI will fail.

Typedefs

typedef
unsigned int **IxAtmdAccUserId**
User-supplied Id.

typedef void(* **IxAtmdAccRxVcRxCallback**)(IxAtmLogicalPort port, **IxAtmdAccUserId** userId,
IxAtmdAccPduStatus status, **IxAtmdAccClpStatus** clp, IX_OSAL_MBUF *mbufPtr)
Rx callback prototype.

typedef void(* **IxAtmdAccRxVcFreeLowCallback**)(IxAtmdAccUserId userId)
Callback prototype for free buffer level is low.

typedef void(* **IxAtmdAccTxVcBufferReturnCallback**)(IxAtmdAccUserId userId, IX_OSAL_MBUF
*mbufPtr)
Buffer callback prototype.

Enumerations

enum **IxAtmdAccPduStatus** {
 IX_ATMDACC_AAL0_VALID,
 IX_ATMDACC_OAM_VALID,
 IX_ATMDACC_AAL2_VALID,
 IX_ATMDACC_AAL5_VALID,
 IX_ATMDACC_AAL5_PARTIAL,
 IX_ATMDACC_AAL5_CRC_ERROR,
 IX_ATMDACC_MBUF_RETURN
}
IxAtmdAcc Pdu status .:

enum **IxAtmdAccAalType** {
 IX_ATMDACC_AAL5,
 IX_ATMDACC_AAL2,
 IX_ATMDACC_AAL0_48,
 IX_ATMDACC_AAL0_52,
 IX_ATMDACC_OAM,
 IX_ATMDACC_MAX_SERVICE_TYPE
}
IxAtmdAcc AAL Service Type .:

enum **IxAtmdAccClpStatus** {
 IX_ATMDACC_CLP_NOT_SET,
 IX_ATMDACC_CLP_SET
}
IxAtmdAcc CLP indication.

Functions

PUBLIC

IX_STATUS **ixAtmdAccInit** (void)
Initialise the IxAtmdAcc Component.

PUBLIC

IX_STATUS **ixAtmdAccUninit** (void)
Uninitialise the IxAtmdAcc Component.

PUBLIC void **ixAtmdAccShow** (void)
Show IxAtmdAcc configuration on a per port basis.

PUBLIC void **ixAtmdAccStatsShow** (void)
Show all IxAtmdAcc stats.

PUBLIC void **ixAtmdAccStatsReset** (void)
Reset all IxAtmdAcc stats.

PUBLIC **ixAtmdAccRxVcConnect** (**IxAtmLogicalPort** port, unsigned int vpi, unsigned int vci,
IX_STATUS **ixAtmdAccAalType** aalServiceType, **IxAtmRxQueueId** rxQueueId, **IxAtmdAccUserId**
userCallbackId, **IxAtmdAccRxVcRxCallback** rxCallback, unsigned int
minimumReplenishCount, **IxAtmConnId** *connIdPtr, **IxAtmNpeRxVcId** *npeVcIdPtr)
Connect to a Aal Pdu receive service for a particular port/vpi/vci, and service type.

PUBLIC

IX_STATUS **ixAtmdAccRxVcFreeReplenish** (**IxAtmConnId** connId, IX_OSAL_MBUF *mbufPtr)
Provide free mbufs for data reception on a connection.

PUBLIC **ixAtmdAccRxVcFreeLowCallbackRegister** (**IxAtmConnId** connId, unsigned int
IX_STATUS numberOfMbufs, **IxAtmdAccRxVcFreeLowCallback** callback)
Configure the RX Free threshold value and register a callback to handle threshold notifications.

PUBLIC **ixAtmdAccRxVcFreeEntriesQuery** (**IxAtmConnId** connId, unsigned int
IX_STATUS *numberOfMbufsPtr)
Get the number of rx mbufs the system can accept to replenish the the rx reception mechanism on a particular channel.

PUBLIC

IX_STATUS **ixAtmdAccRxVcEnable** (**IxAtmConnId** connId)
Start the RX service on a VC.

PUBLIC

IX_STATUS **ixAtmdAccRxVcDisable** (**IxAtmConnId** connId)
Stop the RX service on a VC.

PUBLIC

IX_STATUS **ixAtmdAccRxVcTryDisconnect** (**IxAtmConnId** connId)
Disconnect a VC from the RX service.

PUBLIC**ixAtmdAccTxVcConnect** (**ixAtmLogicalPort** port, unsigned int vpi, unsigned int vci, IX_STATUS **ixAtmdAccAalType** aalServiceType, **ixAtmdAccUserId** userId, **ixAtmdAccTxVcBufferReturnCallback** bufferFreeCallback, **ixAtmConnId** *connIdPtr)
Connect to a Aal Pdu transmit service for a particular port/vpi/vci and service type.

PUBLIC**ixAtmdAccTxVcPduSubmit** (**ixAtmConnId** connId, IX_OSAL_MBUF *mbufPtr, IX_STATUS **ixAtmdAccClpStatus** clp, unsigned int numberOfCells)
Submit a Pdu for transmission on connection.

PUBLIC
IX_STATUS ixAtmdAccTxVcTryDisconnect (**ixAtmConnId** connId)
Disconnect from a Aal Pdu transmit service for a particular port/vpi/vci.

Detailed Description

The public API for the IXP400 Atm Driver Data component.

ixAtmdAcc is the low level interface by which AAL0/AAL5 and OAM data gets transmitted to, and received from the Utopia bus.

For AAL0/AAL5 services transmit and receive connections may be established independently for unique combinations of port, VPI, and VCI.

Two AAL0 services supporting 48 or 52 byte cell data are provided. Submitted AAL0 PDUs must be a multiple of the cell data size (48/52). AAL0_52 is a raw cell service the client must format the PDU with an ATM cell header (excluding HEC) at the start of each cell, note that AtmdAcc does not validate the cell headers in a submitted PDU.

OAM cells cannot be received over the AAL0 service but instead are received over a dedicated OAM service.

For the OAM service an "OAM Tx channel" may be enabled for a port by establishing a single dedicated OAM Tx connection on that port. A single "OAM Rx channel" for all ports may be enabled by establishing a dedicated OAM Rx connection.

The OAM service allows buffers containing 52 byte OAM F4/F5 cells to be transmitted and received over the dedicated OAM channels. HEC is appended/removed, and CRC-10 performed by the NPE. The OAM service offered by AtmdAcc is a raw cell transport service. It is assumed that ITU I.610 procedures that make use of this service are implemented above AtmdAcc.

Note that the dedicated OAM connections are established on reserved VPI, VCI, and (in the case of Rx) port values defined below. These values are used purely to discriminate the dedicated OAM channels and do not identify a particular OAM F4/F5 flow. F4/F5 flows may be realised for particular VPI/VCIs by manipulating the VPI, VCI fields of the ATM cell headers of cells in the buffers passed to AtmdAcc. Note that AtmdAcc does not validate the cell headers in a submitted OAM PDU.

This part is related to the User datapath processing

Define Documentation

```
#define IX_ATMDACC_BUSY
```

Busy return code.

This constant is used to tell IxAtmDACC user that the request is correct, but cannot be processed because the IxAtmAcc resources are already used. The user has to retry its request later

Definition at line **107** of file **IxAtmdAcc.h**.

```
#define IX_ATMDACC_DEFAULT_REPLENISH_COUNT
```

Default resources usage for RxVcFree replenish mechanism.

This constant is used to tell IxAtmDACC to allocate and use the minimum of resources for rx free replenish.

See also:

ixAtmdAccRxVcConnect

Definition at line **138** of file **IxAtmdAcc.h**.

```
#define IX_ATMDACC_OAM_RX_PORT
```

The reserved dummy PORT used for all dedicated OAM Rx connections. Note that this is not a real port but must have a value that lies within the valid range of port values.

Definition at line **179** of file **IxAtmdAcc.h**.

```
#define IX_ATMDACC_OAM_RX_VCI
```

The reserved value value used for the dedicated OAM Rx connection. This value should be chosen so that it does not coincide with the VCI value used in an AAL0/AAL5 connection. Any attempt to connect a service type other than OAM on this VCI will fail.

Definition at line **203** of file **IxAtmdAcc.h**.

```
#define IX_ATMDACC_OAM_RX_VPI
```

The reserved value value used for the dedicated OAM Rx connection. This value should be chosen so that it does not coincide with the VPI value used in an AAL0/AAL5 connection. Any attempt to connect a service type other than OAM on this VPI will fail.

Definition at line **191** of file **IxAtmdAcc.h**.

```
#define IX_ATMDACC_OAM_TX_VCI
```

The reserved value used for the dedicated OAM Tx connection. This "well known" value is used by atmDacc and its clients to discriminate the OAM channel, and should be chosen so that it does not coincide with the VCI value used in an AAL0/AAL5 connection. Any attempt to connect a service type other than OAM on this VCI will fail.

Definition at line **167** of file **IxAtmdAcc.h**.

```
#define IX_ATMDACC_OAM_TX_VPI
```

The reserved value used for the dedicated OAM Tx connection. This "well known" value is used by atmDacc and its clients to discriminate the OAM channel, and should be chosen so that it does not coincide with the VPI value used in an AAL0/AAL5 connection. Any attempt to connect a service type other than OAM on this VPI will fail.

Definition at line **154** of file **IxAtmdAcc.h**.

```
#define IX_ATMDACC_RESOURCES_STILL_ALLOCATED
```

Disconnect return code.

This constant is used to tell IxAtmDacc user that the disconnect functions are not complete because the resources used by the driver are not yet released. The user has to retry the disconnect call later.

Definition at line **123** of file **IxAtmdAcc.h**.

```
#define IX_ATMDACC_WARNING
```

Warning return code.

This constant is used to tell IxAtmDacc user about a special case.

Definition at line **92** of file **IxAtmdAcc.h**.

Typedef Documentation

```
typedef void(* IxAtmdAccRxVcFreeLowCallback)(IxAtmdAccUserId userId)
```

Callback prototype for free buffer level is low.

IxAtmdAccRxVcFreeLowCallback is the prototype of the user function which get called on a per-VC basis, when more mbufs are needed to continue the ATM data reception. This function is likely to supply more available mbufs by one or many calls to the replenish function ***ixAtmdAccRxVcFreeReplenish()***

This function is called when the number of available buffers for reception is going under the threshold level as defined in *ixAtmdAccRxVcFreeLowCallbackRegister()*

This function is called inside an Qmgr dispatch context. No system resource or interrupt–unsafe feature should be used inside this callback.

See also:

ixAtmdAccRxVcFreeLowCallbackRegister

IxAtmdAccRxVcFreeLowCallback

ixAtmdAccRxVcFreeReplenish

ixAtmdAccRxVcFreeEntriesQuery

ixAtmdAccRxVcConnect

Parameters:

userId **IxAtmdAccUserId** [in] – user Id provided in the call to *ixAtmdAccRxVcConnect()*

Returns:

None

Definition at line **372** of file **IxAtmdAcc.h**.

```
typedef void(* IxAtmdAccRxVcRxCallback)(IxAtmLogicalPort port, IxAtmdAccUserId userId,
IxAtmdAccPduStatus status, IxAtmdAccClpStatus clp, IX_OSAL_MBUF * mbufPtr)
```

Rx callback prototype.

IxAtmdAccRxVcRxCallback is the prototype of the Rx callback user function called once per PDU to pass a receive Pdu to a user on a particular connection. The callback is likely to push the mbufs to a protocol layer, and recycle the mbufs for a further use.

Note:

–This function is called ONLY in the context of the *ixAtmdAccRxDispatch()* function

See also:

ixAtmdAccRxDispatch

ixAtmdAccRxVcConnect

Parameters:

port **IxAtmLogicalPort** [in] – the port on which this PDU was received a logical PHY port [IX_UTOPIA_PORT_0 .. IX_UTOPIA_MAX_PORTS – 1]

userId **IxAtmdAccUserId** [in] – user Id provided in the call to *ixAtmdAccRxVcConnect()*

status **IxAtmdAccPduStatus** [in] – an indication about the PDU validity. In the case of AAL0 the only possible value is AAL0_VALID, in this case the client may optionally determine that an rx timeout occurred by checking if the mbuf is completely or only

partially filled, the later case indicating a timeout. In the case of OAM the only possible value is OAM valid. The status is set to `IX_ATMDACC_MBUF_RETURN` when the mbuf is released during a disconnect process.

- clp* **IxAtmdAccClpStatus** [in] – clp indication for this PDU. For AAL5/AAL0_48 this information is set if the clp bit of any rx cell is set For AAL0–52/OAM the client may inspect the CLP in individual cell headers in the PDU, and this parameter is set to 0.
- *mbufPtr* [in] – depending on the servive type a pointer to an mbuf (AAL5/AAL0/OAM) or mbuf chain (AAL5 only), that comprises the complete PDU data.

This parameter is guaranteed not to be a null pointer.

Definition at line **334** of file **IxAtmdAcc.h**.

```
typedef void(* IxAtmdAccTxVcBufferReturnCallback)(IxAtmdAccUserId userId, IX_OSAL_MBUF *
mbufPtr)
```

Buffer callback prototype.

This function is called to relinquish ownership of a transmitted buffer chain to the user.

Note:

–In the case of a chained mbuf the AmtdAcc component can chain many user buffers together and pass ownership to the user in one function call.

Parameters:

- userId* **IxAtmdAccUserId** [in] – user If provided at registration of this callback.
- mbufPtr* [in] – a pointer to mbufs or chain of mbufs and is guaranteed not to be a null pointer.

Definition at line **397** of file **IxAtmdAcc.h**.

IxAtmdAccUserId

User–supplied Id.

IxAtmdAccUserId is passed through callbacks and allows the IxAtmdAcc user to identify the source of a call back. The range of this user–owned Id is [0...2³²–1].

The user provides this own Ids on a per–channel basis as a parameter in a call to *ixAtmdAccRxVcConnect()* or *ixAtmdAccRxVcConnect()*

See also:

ixAtmdAccRxVcConnect

ixAtmdAccTxVcConnect

Definition at line **286** of file **IxAtmdAcc.h**.

Enumeration Type Documentation

enum IxAtmdAccAalType

IxAtmdAcc AAL Service Type :.

IxAtmdAccAalType defines the type of traffic to run on this VC

Enumeration values:

<i>IX_ATMDACC_AAL5</i>	ITU-T AAL5.
<i>IX_ATMDACC_AAL2</i>	ITU-T AAL2 reserved for future use.
<i>IX_ATMDACC_AAL0_48</i>	AAL0 48 byte payloads (cell header is added by NPE).
<i>IX_ATMDACC_AAL0_52</i>	AAL0 52 byte cell data (HEC is added by NPE).
<i>IX_ATMDACC_OAM</i>	OAM cell transport service (HEC is added by NPE).
<i>IX_ATMDACC_MAX_SERVICE_TYPE</i>	not a service, used for parameter validation

Definition at line **241** of file **IxAtmdAcc.h**.

enum IxAtmdAccClpStatus

IxAtmdAcc CLP indication.

IxAtmdAccClpStatus defines the CLP status of the current PDU

Enumeration values:

<i>IX_ATMDACC_CLP_NOT_SET</i>	CLP indication is not set.
<i>IX_ATMDACC_CLP_SET</i>	CLP indication is set.

Definition at line **262** of file **IxAtmdAcc.h**.

enum IxAtmdAccPduStatus

IxAtmdAcc Pdu status :.

IxAtmdAccPduStatus is used during a RX operation to indicate the status of the received PDU

Enumeration values:

<i>IX_ATMDACC_AAL0_VALID</i>	aal0 pdu
<i>IX_ATMDACC_OAM_VALID</i>	OAM pdu.

<i>IX_ATMDACC_AAL2_VALID</i>	aal2 pdu reserved for future use
<i>IX_ATMDACC_AAL5_VALID</i>	aal5 pdu complete and trailer is valid
<i>IX_ATMDACC_AAL5_PARTIAL</i>	aal5 pdu not complete, trailer is missing
<i>IX_ATMDACC_AAL5_CRC_ERROR</i>	aal5 pdu not complete, crc error/length error
<i>IX_ATMDACC_MBUF_RETURN</i>	empty buffer returned to the user

Definition at line **218** of file **IxAtmdAcc.h**.

Function Documentation

```
ixAtmdAccInit ( void )
```

Initialise the IxAtmdAcc Component.

This function initialise the IxAtmdAcc component. This function shall be called before any other function of the API. Its role is to initialise all internal resources of the IxAtmdAcc component.

The ixQmgr component needs to be initialized prior the use of ***ixAtmdAccInit()***

Parameters:

none Failing to initialize the IxAtmdAcc API before any use of it will result in a failed status. If the specified component is not present, a success status will still be returned, however, a warning indicating the NPE to download to is not present will be issued.

Returns:

- ◇ **IX_SUCCESS** initialisation is complete (in case of component not being present, a warning is clearly indicated)
- ◇ **IX_FAIL** unable to process this request either because this IxAtmdAcc is already initialised or some unspecified error has occurred.

```
ixAtmdAccRxVcConnect ( IxAtmLogicalPort      port,
                      unsigned int             vpi,
                      unsigned int             vci,
                      IxAtmdAccAalType        aalServiceType,
                      IxAtmRxQueueId          rxQueueId,
                      IxAtmdAccUserId         userCallbackId,
                      IxAtmdAccRxVcRxCallback rxCallback,
                      unsigned int             minimumReplenishCount,
                      IxAtmConnId *          connIdPtr,
                      IxAtmNpeRxVcId *       npeVcIdPtr
                      )
```

Connect to a Aal Pdu receive service for a particular port/vpi/vci, and service type.

This function allows a user to connect to an Aal5/Aal0/OAM Pdu receive service for a particular port/vpi/vci. It registers the callback and allocates internal resources and a Connection Id to be used in further API calls related to this VCC.

The function will setup VC receive service on the specified rx queue.

This function is blocking and makes use internal locks, and hence should not be called from an interrupt context.

On return from ***ixAtmdAccRxVcConnect()*** with a failure status, the connection Id parameter is unspecified. Its value cannot be used. A connId is the reference by which IxAtmdAcc refers to a connected VC. This identifier is the result of a succesful call to a connect function. This identifier is invalid after a sucessful call to a disconnect function.

Calling this function for the same combination of Vpi, Vci and more than once without calling ***ixAtmdAccRxVcTryDisconnect()*** will result in a failure status.

If this function returns success the user should supply receive buffers by calling ***ixAtmdAccRxVcFreeReplenish()*** and then call ***ixAtmdAccRxVcEnable()*** to begin receiving pdus.

There is a choice of two receive Qs on which the VC pdus could be receive. The user must associate the VC with one of these. Essentially having two qs allows more flexible system configuration such as have high prioriy traffic on one q (e.g. voice) and low priority traffic on the other (e.g. data). The high priority Q could be serviced in preference to the low priority Q. One queue may be configured to be serviced as soon as there is traffic, the other queue may be configured to be serviced by a polling mechanism running at idle time.

Two AAL0 services supporting 48 or 52 byte cell data are provided. Received AAL0 PDUs will be be a multiple of the cell data size (48/52). AAL0_52 is a raw cell service and includes an ATM cell header (excluding HEC) at the start of each cell.

A single "OAM Rx channel" for all ports may be enabled by establishing a dedicated OAM Rx connection.

The OAM service allows buffers containing 52 byte OAM F4/F5 cells to be transmitted and received over the dedicated OAM channels. HEC is appended/removed, and CRC-10 performed by the NPE. The OAM service offered by AtmdAcc is a raw cell transport service. It is assumed that ITU I.610 procedures that make use of this service are implemented above AtmdAcc.

Note that the dedicated OAM connections are established on reserved VPI,VCI, and (in the case of Rx) port values. These values are used purely to descriminate the dedicated OAM channels and do not identify a particular OAM F4/F5 flow. F4/F5 flows may be realised for particluar VPI/VCIs by manipulating the VPI,VCI fields of the ATM cell headers of cells in the buffers passed to AtmdAcc.

Calling this function prior to enable the port will fail.

See also:

ixAtmdAccRxDispatch

ixAtmdAccRxVcEnable

ixAtmdAccRxVcDisable

ixAtmdAccRxVcTryDisconnect

ixAtmdAccPortEnable

Parameters:

<i>port</i>	IxAtmLogicalPort [in] – VC identification : logical PHY port [IX_UTOPIA_PORT_0 .. IX_UTOPIA_MAX_PORTS – 1]
<i>vpi</i>	unsigned int [in] – VC identification : ATM Vpi [0..255] or IX_ATMDACC_OAM_VPI
<i>vci</i>	unsigned int [in] – VC identification : ATM Vci [0..65535] or IX_ATMDACC_OAM_VCI
<i>aalServiceType</i>	IxAtmdAccAalType [in] – type of service: AAL5, AAL0_48, AAL0_52, or OAM
<i>rxQueueId</i>	IxAtmRxQueueId [in] – this identifies which of two Qs the VC should use when incoming traffic is processed
<i>userCallbackId</i>	IxAtmdAccUserId [in] – user Id used later as a parameter to the supplied rxCallback.
<i>rxCallback</i>	[in] – function called when mbufs are received. This parameter cannot be a null pointer.
<i>bufferFreeCallback</i>	[in] – function to be called to return ownership of buffers to IxAtmdAcc user.
<i>minimumReplenishCount</i>	unsigned int [in] – For AAL5/AAL0 the number of free mbufs to be used with this channel. Use a high number when the expected traffic rate on this channel is high, or when the user's mbufs are small, or when the RxVcFreeLow Notification has to be invoked less often. When this value is IX_ATMDACC_DEFAULT_REPLENISH_COUNT, the minimum of resources will be used. Depending on traffic rate, pdu size and mbuf size, rxfree queue size, polling/interrupt rate, this value may require to be replaced by a different value in the range 1–128 For OAM the rxFree queue size is fixed by atmdAcc and this parameter is ignored.
<i>connIdPtr</i>	IxAtmConnId [out] – pointer to a connection Id This parameter cannot be a null pointer.
<i>npeVcIdPtr</i>	IxAtmNpeRxVcId [out] – pointer to an npe Vc Id This parameter cannot be a null pointer.

Returns:

- ◇ IX_SUCCESS successful call to IxAtmdAccRxVcConnect
- ◇ IX_ATMDACC_BUSY cannot process this request : no VC is available
- ◇ IX_FAIL parameter error, VC already in use, attempt to connect AAL service on reserved OAM VPI/VCI, attempt to connect OAM service on VPI/VCI other than the reserved OAM VPI/VCI, port is not initialised, or some other error occurs during processing.

ixAtmdAccRxVcDisable (**IxAtmConnId** *connId*)

Stop the RX service on a VC.

This functions stops the traffic reception for a particular VC connection.

Once invoked, incoming Pdus are discarded by the hardware. Any Pdus pending will be freed to the user

Hence once this function returns no more receive callbacks will be called for that VC. However, buffer free callbacks will be invoked until such time as all buffers supplied by the user have been freed back to the user

Calling this function doe not invalidate the connId. ***ixAtmdAccRxVcEnable()*** can be invoked to enable Pdu reception again.

If the traffic is already stopped, this function returns IX_SUCCESS.

This function is not reentrant and should not be used inside an interrupt context.

See also:

ixAtmdAccRxVcConnect

ixAtmdAccRxVcEnable

ixAtmdAccRxVcDisable

Parameters:

connId ***IxAtmConnId*** [in] – connection Id as resulted from a succesfull call to *IxAtmdAccRxVcConnect()*

Returns:

- ◇ IX_SUCCESS successful call to ***ixAtmdAccRxVcDisable()***.
- ◇ IX_ATMDACC_WARNING the channel is already disabled
- ◇ IX_FAIL invalid parameters or some unspecified internal error occurred

```
ixAtmdAccRxVcEnable ( IxAtmConnId connId )
```

Start the RX service on a VC.

This functions kicks–off the traffic reception for a particular VC. Once invoked, incoming PDUs will be made available by the hardware and are eventually directed to the ***IxAtmdAccRxVcRxCallback()*** callback registered for the connection.

If the traffic is already running, this function returns IX_SUCCESS. This function can be invoked many times.

IxAtmdAccRxVcFreeLowCallback event will occur only after ***ixAtmdAccRxVcEnable()*** function is invoked.

Before using this function, the ***ixAtmdAccRxVcFreeReplenish()*** function has to be used to replenish the

RX Free queue. If not, incoming traffic may be discarded. and in the case of interrupt driven reception the ***IxAtmdAccRxVcFreeLowCallback()*** callback may be invoked as a side effect during a replenish action.

This function is not reentrant and should not be used inside an interrupt context.

For an VC connection this function can be called after a call to ***ixAtmdAccRxVcDisable()*** and should not be called after ***ixAtmdAccRxVcTryDisconnect()***

See also:

ixAtmdAccRxVcDisable

ixAtmdAccRxVcConnect

ixAtmdAccRxVcFreeReplenish

Parameters:

connId ***IxAtmConnId*** [in] – connection Id as resulted from a succesfull call to ***IxAtmdAccRxVcConnect()***

Returns:

- ◇ IX_SUCCESS successful call to ixAtmdAccRxVcEnable
- ◇ IX_ATMDACC_WARNING the channel is already enabled
- ◇ IX_FAIL invalid parameters or some unspecified internal error occurred.

```
ixAtmdAccRxVcFreeEntriesQuery ( IxAtmConnId connId,  
                                unsigned int * numberOfMbufsPtr  
                                )
```

Get the number of rx mbufs the system can accept to replenish the the rx reception mechanism on a particular channel.

The ixAtmdAccRxVcFreeEntriesQuery function is used to retrieve the current number of available mbuf entries for reception, on a per-VC basis. This function can be used to know the number of mbufs which can be provided using ***ixAtmdAccRxVcFreeReplenish()***.

This function can be used from a timer context, or can be associated with a threshold event, or can be used inside an active polling mechanism which is under user control.

This function is reentrant and does not use system resources and can be invoked from an interrupt context.

Parameters:

connId ***IxAtmConnId*** [in] – connection Id as resulted from a succesfull call to ***IxAtmdAccRxVcConnect()***

numberOfMbufsPtr unsigned int [out] – Pointer to the number of available entries. . This parameter cannot be a null pointer.

Returns:

◇ IX_SUCCESS the current number of mbufs not yet used for incoming traffic

◇ IX_FAIL invalid parameter

See also:

ixAtmdAccRxVcFreeReplenish

```
ixAtmdAccRxVcFreeLowCallbackRegister ( IxAtmConnId                connId,  
                                         unsigned int                numberOfMbufs,  
                                         IxAtmdAccRxVcFreeLowCallback callback  
                                         )
```

Configure the RX Free threshold value and register a callback to handle threshold notifications.

The function `ixAtmdAccRxVcFreeLowCallbackRegister` sets the threshold value for a particular RX VC. When the number of buffers reaches this threshold the callback is invoked.

This function should be called once per VC before RX traffic is enabled. This function will fail if the current level of the free buffers is equal or less than the threshold value.

See also:

ixAtmdAccRxVcFreeLowCallbackRegister

IxAtmdAccRxVcFreeLowCallback

ixAtmdAccRxVcFreeReplenish

ixAtmdAccRxVcFreeEntriesQuery

ixAtmdAccRxVcConnect

Parameters:

<i>connId</i>	IxAtmConnId [in] – connection Id as resulted from a successful call to <code>IxAtmdAccRxVcConnect()</code>
<i>numberOfMbufs</i>	unsigned int [in] – threshold number of buffers. This number has to be a power of 2, one of the values 0,1,2,4,8,16,32.... The maximum value cannot be more than half of the rxFree queue size (which can be retrieved using <code>ixAtmdAccRxVcFreeEntriesQuery()</code> before any use of the <code>ixAtmdAccRxVcFreeReplenish()</code> function)
<i>callback</i>	IxAtmdAccRxVcFreeLowCallback [in] – function telling the user that the number of free buffers has reduced to the threshold value.

Returns:

◇ IX_SUCCESS Threshold set successfully.

◇ IX_FAIL parameter error or the current number of free buffers is less than or equal to the threshold supplied or some unspecified error has occurred.

Note:

- the callback will be called when the threshold level will drop from exactly (numberOfMbufs + 1) to (numberOfMbufs).

```
ixAtmdAccRxVcFreeReplenish ( IxAtmConnId      connId,
                             IX_OSAL_MBUF * mbufPtr
                             )
```

Provide free mbufs for data reception on a connection.

This function provides mbufs for data reception by the hardware. This function needs to be called by the user on a regular basis to ensure no packet loss. Providing free buffers is a connection-based feature; each connection can have different requirements in terms of buffer size number of buffers, recycling rate. This function could be invoked from within the context of a ***IxAtmdAccRxVcFreeLowCallback()*** callback for a particular VC

Mbufs provided through this function call can be chained. They will be unchained internally. A call to this function with chained mbufs or multiple calls with unchained mbufs are equivalent, but calls with unchained mbufs are more efficient.

Mbufs provided to this interface need to be able to hold at least one full cell payload (48/52 bytes, depending on service type). Chained buffers with a size less than the size supported by the hardware will be returned through the rx callback provided during the connect step.

Failing to invoke this function prior to enabling the RX traffic can result in packet loss.

This function is not reentrant for the same connId.

This function does not use system resources and can be invoked from an interrupt context.

Note:

- Over replenish is detected, and extra mbufs are returned through the rx callback provided during the connect step.
- Mbuf provided to the replenish function should have a length greater or equal to 48/52 bytes according to service type.
- The memory cache of mMbuf payload should be invalidated prior to Mbuf submission. Flushing the Mbuf headers is handled by IxAtmdAcc.
- When a chained mbuf is provided, this function process the mbufs up to the hardware limit and invokes the user-supplied callback to release extra buffers.

See also:

ixAtmdAccRxVcFreeLowCallbackRegister

IxAtmdAccRxVcFreeLowCallback

ixAtmdAccRxVcConnect

Parameters:

connId **IxAtmConnId** [in] – connection Id as returned from a successful call to *IxAtmdAccRxVcConnect()*
mbufPtr [in] – pointer to a mbuf structure to be used for data reception. The mbuf pointed to by this parameter can be chained to an other mbuf.

Returns:

- ◇ IX_SUCCESS successful call to *ixAtmdAccRxVcFreeReplenish()* and the mbuf is now ready to use for incoming traffic.
- ◇ IX_ATMDACC_BUSY cannot process this request because the max number of outstanding free buffers has been reached or the internal resources have exhausted for this VC. The user is responsible for retrying this request later.
- ◇ IX_FAIL cannot process this request because of parameter errors or some unspecified internal error has occurred.

Note:

- It is not always guaranteed the replenish step to be as fast as the hardware is consuming Rx Free mbufs. There is nothing in *IxAtmdAcc* to guarantee that replenish reaches the rxFree threshold level. If the threshold level is not reached, the next rxFree low notification for this channel will not be triggered. The preferred ways to replenish can be as follows (depending on applications and implementations) :
 - ◇ Replenish in a rxFree low notification until the function *ixAtmdAccRxVcFreeReplenish()* returns IX_ATMDACC_BUSY
 - ◇ Query the queue level using

See also:

- ixAtmdAccRxVcFreeEntriesQuery*, then , replenish using *ixAtmdAccRxVcFreeReplenish()*, then query the queue level again, and replenish if the threshold is still not reached.
 - ◇ Trigger replenish from an other event source and use rxFree starvation to throttle the Rx traffic.

ixAtmdAccRxVcTryDisconnect (**IxAtmConnId** *connId*)

Disconnect a VC from the RX service.

This function deregisters the VC and guarantees that all resources associated with this VC are free. After its execution, the connection Id is not available.

This function will fail until such time as all resources allocated to the VC connection have been freed. The user is responsible to delay and call again this function many times until a success status is returned.

This function needs internal locks and should not be called from an interrupt context

Parameters:

connId **IxAtmConnId** [in] – connection Id as resulted from a successful call to *IxAtmdAccRxVcConnect()*

Returns:

- ◇ IX_SUCCESS successful call to ixAtmdAccRxVcDisable
- ◇ IX_ATMDACC_RESOURCES_STILL_ALLOCATED not all resources associated with the connection have been freed.
- ◇ IX_FAIL cannot process this request because of a parameter error

ixAtmdAccShow (void)

Show IxAtmdAcc configuration on a per port basis.

Parameters:

none

Returns:

none

Note:

- Display use printf() and are redirected to stdout

ixAtmdAccStatsReset (void)

Reset all IxAtmdAcc stats.

Parameters:

none

Returns:

none

ixAtmdAccStatsShow (void)

Show all IxAtmdAcc stats.

Parameters:

none

Returns:

none

Note:

- Stats display use printf() and are redirected to stdout

```

ixAtmdAccTxVcConnect ( IxAtmLogicalPort          port,
                        unsigned int                vpi,
                        unsigned int                vci,
                        IxAtmdAccAalType           aalServiceType,
                        IxAtmdAccUserId           userId,
                        IxAtmdAccTxVcBufferReturnCallback bufferFreeCallback,
                        IxAtmConnId *             connIdPtr
                        )

```

Connect to a Aal Pdu transmit service for a particular port/vpi/vci and service type.

This function allows a user to connect to an Aal5/Aal0/OAM Pdu transmit service for a particular port/vpi/vci. It registers the callback and allocates internal resources and a Connection Id to be used in further API calls related to this VC.

The function will setup VC transmit service on the specified on the specified port. A connId is the reference by which IxAtmdAcc refers to a connected VC. This identifier is the result of a succesful call to a connect function. This identifier is invalid after a sucessful call to a disconnect function.

This function needs internal locks, and hence should not be called from an interrupt context.

On return from **ixAtmdAccTxVcConnect()** with a failure status, the connection Id parameter is unspecified. Its value cannot be used.

Calling this function for the same combination of port, Vpi, Vci and more than once without calling **ixAtmdAccTxVcTryDisconnect()** will result in a failure status.

Two AAL0 services supporting 48 or 52 byte cell data are provided. Submitted AAL0 PDUs must be a multiple of the cell data size (48/52). AAL0_52 is a raw cell service the client must format the PDU with an ATM cell header (excluding HEC) at the start of each cell, note that AtmdAcc does not validate the cell headers in a submitted PDU.

For the OAM service an "OAM Tx channel" may be enabled for a port by establishing a single dedicated OAM Tx connection on that port.

The OAM service allows buffers containing 52 byte OAM F4/F5 cells to be transmitted and received over the dedicated OAM channels. HEC is appended/removed, and CRC-10 performed by the NPE. The OAM service offered by AtmdAcc is a raw cell transport service. It is assumed that ITU I.610 procedures that make use of this service are implemented above AtmdAcc.

Note that the dedicated OAM connections are established on reserved VPI,VCI, and (in the case of Rx) port values. These values are used purely to descriminate the dedicated OAM channels and do not identify a particular OAM F4/F5 flow. F4/F5 flows may be realised for particluar VPI/VCI by manipulating the VPI,VCI fields of the ATM cell headers of cells in the buffers passed to AtmdAcc.

Calling this function before enabling the port will fail.

See also:

ixAtmdAccTxVcTryDisconnect

ixAtmdAccPortTxScheduledModeEnable

ixAtmdAccPortEnable

Parameters:

<i>port</i>	IxAtmLogicalPort [in] – VC identification : logical PHY port [IX_UTOPIA_PORT_0 .. IX_UTOPIA_MAX_PORTS – 1]
<i>vpi</i>	unsigned int [in] – VC identification : ATM Vpi [0..255] or IX_ATMDACC_OAM_VPI
<i>vci</i>	unsigned int [in] – VC identification : ATM Vci [0..65535] or IX_ATMDACC_OAM_VCI
<i>aalServiceType</i>	IxAtmdAccAalType [in] – type of service AAL5, AAL0_48, AAL0_52, or OAM
<i>userId</i>	IxAtmdAccUserId [in] – user id to be used later during callbacks related to this channel
<i>bufferFreeCallback</i>	IxAtmdAccTxVcBufferReturnCallback [in] – function called when mbufs transmission is complete. This parameter cannot be a null pointer.
<i>connIdPtr</i>	IxAtmConnId [out] – Pointer to a connection Id. This parameter cannot be a null pointer.

Returns:

- ◇ IX_SUCCESS successful call to *IxAtmdAccRxVcConnect()*.
- ◇ IX_ATMDACC_BUSY cannot process this request because no VC is available
- ◇ IX_FAIL parameter error, VC already in use, attempt to connect AAL service on reserved OAM VPI/VCI, attempt to connect OAM service on VPI/VCI other than the reserved OAM VPI/VCI, port is not initialised, or some other error occurs during processing.

```
ixAtmdAccTxVcPduSubmit ( IxAtmConnId      connId,  
                        IX_OSAL_MBUF * mbufPtr,  
                        IxAtmdAccClpStatus clp,  
                        unsigned int      numberOfCells  
                        )
```

Submit a Pdu for transmission on connection.

A data user calls this function to submit an mbufs containing a Pdu to be transmitted. The buffer supplied can be chained and the Pdu it contains must be complete.

The transmission behavior of this call depends on the operational mode of the port on which the connection is made.

In unscheduled mode the mbuf will be submitted to the hardware immediately if sufficient resource is available. Otherwise the function will return failure.

In scheduled mode the buffer is queued internally in IxAtmdAcc. The cell demand is made known to the traffic shaping entity. Cells from the buffers are MUXed onto the port some time later as dictated by the traffic shaping entity. The traffic shaping entity does this by sending transmit schedules to IxAtmdAcc via

ixAtmdAccPortTxProcess() function call.

Note that the dedicated OAM channel is scheduled just like any other channel. This means that any OAM traffic relating to an active AAL0/AAL5 connection will be scheduled independantly of the AAL0/AAL5 traffic for that connection.

When transmission is complete, the TX Done mechanism will give the ownnership of these buffers back to the customer. The tx done mechanism must be in operation before transmission is attempted.

For AAL0/OAM submitted AAL0 PDUs must be a multiple of the cell data size (48/52). AAL0_52 and OAM are raw cell services, and the client must format the PDU with an ATM cell header (excluding HEC) at the start of each cell, note that AtmdAcc does not validate the cell headers in a submitted PDU.

See also:

ixAtmdAccTxVcBufferReturnCallback

ixAtmdAccTxDoneDispatch

Parameters:

<i>connId</i>	<i>ixAtmConnId</i> [in] – connection Id as resulted from a succesfull call to <i>ixAtmdAccTxVcConnect()</i>
<i>mbufPtr</i>	[in] – pointer to a chained structure of mbufs to transmit. This parameter cannot be a null pointer.
<i>clp</i>	<i>ixAtmdAccClpStatus</i> [in] – clp indication for this PDU. All cells of this pdu will be sent with the clp bit set
<i>numberOfCells</i>	unsigned int [in] – number of cells in the PDU.

Returns:

- ◇ IX_SUCCESS successful call to ***ixAtmdAccTxVcPduSubmit()*** The pdu pointed by the mbufPtr parameter will be transmitted
- ◇ IX_ATMDACC_BUSY unable to process this request because internal resources are all used. The caller is responsible for retrying this request later.
- ◇ IX_FAIL unable to process this request because of error in the parameters (wrong connId supplied, or wrong mbuf pointer supplied), the total length of all buffers in the chain should be a multiple of the cell size (48/52 depending on the service type), or unspecified error during processing

Note:

- This function in not re–entrant for the same VC (e.g. : two thread cannot send PDUs for the same VC). But two threads can safely call this function with a different connection Id
- In unscheduled mode, this function is not re–entrant on a per port basis. The size of pdus is limited to 8Kb.
- 0–length mbufs should be removed from the chain before submission. The total length of the pdu (sdu + padding +trailer) has to be updated in the header of the first mbuf of a chain of mbufs.
- Aal5 trailer information (UUI, CPI, SDU length) has to be supplied before submission.

- The payload memory cache should be flushed, if needed, prior to transmission. Mbuf headers are flushed by `IxAtmdAcc`
- This function does not use system resources and can be used inside an interrupt context

`ixAtmdAccTxVcTryDisconnect (IxAtmConnId connId)`

Disconnect from a Aal Pdu transmit service for a particular port/vpi/vci.

This function deregisters the VC and guarantees that all resources associated with this VC are free. After its execution, the connection Id is not available.

This function will fail until such time as all resources allocated to the VC connection have been freed. The user is responsible to delay and call again this function many times until a success status is returned.

After its execution, the connection Id is not available.

Parameters:

connId **IxAtmConnId** [in] – connection Id as resulted from a successful call to `ixAtmdAccTxVcConnect()`

Returns:

- ◇ `IX_SUCCESS` successful call to `ixAtmdAccTxVcTryDisconnect()`
- ◇ `IX_ATMDACC_RESOURCES_STILL_ALLOCATED` not all resources associated with the connection have been freed. This condition will disappear after Tx and TxDone is complete for this channel.
- ◇ `IX_FAIL` unable to process this request because of errors in the parameters (wrong *connId* supplied)

Note:

- This function needs internal locks and should not be called from an interrupt context
- If the `IX_ATMDACC_RESOURCES_STILL_ALLOCATED` error does not clear after a while, this may be linked to a previous problem of cell overscheduling. Disabling the port and retry a disconnect will free the resources associated with this channel.

See also:

ixAtmdAccPortTxProcess

`ixAtmdAccUninit (void)`

Uninitialise the `IxAtmdAcc` Component.

This function uninitialises the `IxAtmdAcc` component. Its role is to uninitialise all internal resources of the `IxAtmdAcc` component. It de-allocates all the buffers allocated during initialization and also destroys the mutex taken. This should be the last function to be called to clean up all resources.

Parameters:

none

Returns:

- ◇ IX_SUCCESS uninitialisation is complete
- ◇ IX_FAIL unable to process this request either because this IxAtmdAcc is already uninitialised or some unspecified error has occurred.

Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Control API

The public API for the IXP400 Atm Driver Control component.

Modules

Intel (R) IXP400 Software ATM Driver Access
(IxAtmdAcc) Utopia Control API

The public API for the IXP400 Atm Driver Control component.

Defines

#define **IX_ATMDACC_PORT_DISABLE_IN_PROGRESS**
Port enable return code.

#define **IX_ATMDACC_ALLPDUS**
All PDUs.

Typedefs

typedef **IxAtmdAccRxDispatcher**)(IxAtmRxQueueId rxQueueId, unsigned int
IX_STATUS(* numberOfPdusToProcess, unsigned int *reservedPtr)
Callback prototype for notification of available PDUs for an Rx Q.

typedef **IxAtmdAccTxDoneDispatcher**)(unsigned int numberOfPdusToProcess, unsigned int
IX_STATUS(* *reservedPtr)
Callback prototype for transmitted mbuf when threshold level is crossed.

typedef void(* **IxAtmdAccPortTxLowCallback**)(IxAtmLogicalPort port, unsigned int
numberOfAvailableCells)
Notification that the threshold number of scheduled cells remains in a port's transmit Q.

typedef **IxAtmdAccTxVcDemandUpdateCallback**)(IxAtmLogicalPort port, int vcId, unsigned
IX_STATUS(* int numberOfCells)
Prototype to submit cells for transmission.

typedef void(* **IxAtmdAccTxVcDemandClearCallback**)(IxAtmLogicalPort port, int vcId)
prototype to remove all currently queued cells from a registered VC

typedef **IxAtmdAccTxSchVcIdGetCallback**)(IxAtmLogicalPort port, unsigned int vpi, unsigned
IX_STATUS(* int vci, **IxAtmConnId** connId, int *vcId)
prototype to get a scheduler vc id

Functions

PUBLIC
IX_STATUS **IxAtmdAccRxDispatcherRegister** (**IxAtmRxQueueId** queueId,
IX_STATUS **IxAtmdAccRxDispatcher** callback)
Register a notification callback to be invoked when there is at least one entry on a particular Rx queue.

PUBLIC
IX_STATUS **IxAtmdAccRxDispatcherUnregister** (**IxAtmRxQueueId** atmdQueueId)
UnRegister a notification callback to be invoked when there is at least one entry on a particular Rx queue.

PUBLIC**IxAtmdAccRxDispatch** (**IxAtmRxQueueId** rxQueueId, unsigned int
IX_STATUS numberOfPdusToProcess, unsigned int *numberOfPdusProcessedPtr)
Control function which executes Rx processing for a particular Rx stream.

PUBLIC**IxAtmdAccRxLevelQuery** (**IxAtmRxQueueId** rxQueueId, unsigned int
IX_STATUS *numberOfPdusPtr)
Query the number of entries in a particular RX queue.

PUBLIC**IxAtmdAccRxQueueSizeQuery** (**IxAtmRxQueueId** rxQueueId, unsigned int
IX_STATUS *numberOfPdusPtr)
Query the size of a particular RX queue.

PUBLIC**IxAtmdAccPortTxFreeEntriesQuery** (**IxAtmLogicalPort** port, unsigned int
IX_STATUS *numberOfCellsPtr)
Get the number of available cells the system can accept for transmission.

PUBLIC**IxAtmdAccPortTxCallbackRegister** (**IxAtmLogicalPort** port, unsigned int
IX_STATUS numberOfCells, **IxAtmdAccPortTxLowCallback** callback)
Configure the Tx port threshold value and register a callback to handle threshold notifications.

PUBLIC void **IxAtmdAccPortTxCallbackUnregister** (**IxAtmLogicalPort** port)
Unregister a callback to handle threshold notifications.

PUBLIC**IxAtmdAccPortTxScheduledModeEnable** (**IxAtmLogicalPort** port,
IX_STATUS **IxAtmdAccTxVcDemandUpdateCallback** vcDemandUpdateCallback,
IxAtmdAccTxVcDemandClearCallback vcDemandClearCallback,
IxAtmdAccTxSchVcIdGetCallback vcIdGetCallback)
Put the port into Scheduled Mode.

PUBLIC
IX_STATUS **IxAtmdAccPortTxScheduledModeDisable** (**IxAtmLogicalPort** port)
Put the port into UnScheduled Mode.

PUBLIC**IxAtmdAccPortTxProcess** (**IxAtmLogicalPort** port, **IxAtmScheduleTable**
IX_STATUS *scheduleTablePtr)

Transmit queue cells to the H/W based on the supplied schedule table.

PUBLIC
IX_STATUS **ixAtmdAccTxDoneDispatch** (unsigned int numberOfPdsToProcess, unsigned int
*numberOfPdsProcessedPtr)

Process a number of pending transmit done pdus from the hardware.

PUBLIC
IX_STATUS **ixAtmdAccTxDoneLevelQuery** (unsigned int *numberOfPdsPtr)
Query the current number of transmit pdus ready for recycling.

PUBLIC
IX_STATUS **ixAtmdAccTxDoneQueueSizeQuery** (unsigned int *numberOfPdsPtr)
Query the TxDone queue size.

PUBLIC
IX_STATUS **ixAtmdAccTxDoneDispatcherRegister** (unsigned int numberOfPds,
IX_STATUS **ixAtmdAccTxDoneDispatcher** notificationCallback)
Configure the Tx Done stream threshold value and register a callback to handle threshold notifications.

PUBLIC void **ixAtmdAccTxDoneDispatcherUnregister** (void)
Unregister a callback to handle threshold notifications.

PUBLIC
IX_STATUS **ixAtmdAccUtopiaConfigSet** (const **ixAtmdAccUtopiaConfig**
*ixAtmdAccUtopiaConfigPtr)
Send the configuration structure to the Utopia interface.

PUBLIC
IX_STATUS **ixAtmdAccUtopiaStatusGet** (**ixAtmdAccUtopiaStatus** *ixAtmdAccUtopiaStatus)
Get the Utopia interface configuration.

PUBLIC
IX_STATUS **ixAtmdAccPortEnable** (**ixAtmLogicalPort** port)
enable a PHY logical port

PUBLIC
IX_STATUS **ixAtmdAccPortDisable** (**ixAtmLogicalPort** port)
disable a PHY logical port

PUBLIC **BOOL** **ixAtmdAccPortDisableComplete** (**ixAtmLogicalPort** port)
disable a PHY logical port

PUBLIC
IX_STATUS **ixAtmdAccUtopiaConfigReset** (const **ixAtmdAccUtopiaConfig** *utConfig)
Reset the configuration structure to the Utopia interface initializes configuration registers and write to NPE-A Load and get response from NPE-A and resets the Utopia interface.

Detailed Description

The public API for the IXP400 Atm Driver Control component.

IxAtmdAcc is the low level interface by which AAL PDU get transmitted to, and received from the Utopia bus

This part is related to the Control configuration

Define Documentation

```
#define IX_ATMDACC_ALLPDUS
```

All PDUs.

This constant is used to tell IxAtmdAcc to process all PDUs from the RX queue or the TX Done

See also:

IxAtmdAccRxDispatcher

IxAtmdAccTxDoneDispatcher

Definition at line **74** of file **IxAtmdAccCtrl.h**.

```
#define IX_ATMDACC_PORT_DISABLE_IN_PROGRESS
```

Port enable return code.

This constant is used to tell IxAtmdAcc user that the port disable functions are not complete. The user can call **ixAtmdAccPortDisableComplete()** to find out when the disable has finished. The port enable can then proceed.

Definition at line **57** of file **IxAtmdAccCtrl.h**.

Typedef Documentation

```
typedef void(* IxAtmdAccPortTxLowCallback)(IxAtmLogicalPort port, unsigned int  
numberOfAvailableCells)
```

Notification that the threshold number of scheduled cells remains in a port's transmit Q.

This is the prototype for the user notification function which gets called on a per-port basis, when the number of remaining scheduled cells to be transmitted decreases to the threshold level. The number of cells passed as a parameter can be used for scheduling purposes as the maximum number of cells that can be passed in a schedule table to the **ixAtmdAccPortTxProcess()** function.

See also:

ixAtmdAccPortTxCallbackRegister

ixAtmdAccPortTxProcess

ixAtmdAccPortTxFreeEntriesQuery

Parameters:

port

IxAtmLogicalPort [in] – logical PHY port [*IX_UTOPIA_PORT_0* .. *IX_UTOPIA_MAX_PORTS* – 1]

numberOfAvailableCells unsigned int [in] – number of available cell entries.for the port

Note:

– This functions shall not use system resources when used inside an interrupt context.

Definition at line **188** of file **IxAtmdAccCtrl.h**.

```
typedef IX_STATUS(* IxAtmdAccRxDispatcher)(IxAtmRxQueueId rxQueueId, unsigned int
numberOfPdusToProcess, unsigned int *reservedPtr)
```

Callback prototype for notification of available PDUs for an Rx Q.

This a prototype for a function which is called when there is at least one Pdu available for processing on a particular Rx Q.

This function should call *ixAtmdAccRxDispatch()* with the appropriate number of parameters to read and process the Rx Q.

See also:

ixAtmdAccRxDispatch

ixAtmdAccRxVcConnect

ixAtmdAccRxDispatcherRegister

Parameters:

rxQueueId

IxAtmRxQueueId [in] indicates which RX queue to has Pdus to process.

numberOfPdusToProcess

unsigned int [in] indicates the minimum number of PDUs available to process all PDUs from the queue.

reservedPtr

unsigned int* [out] pointer to a int location which can be written to, but does not retain written values. This is provided to make this prototype compatible with *ixAtmdAccRxDispatch()*

Returns:

◇ int – ignored.

Definition at line **108** of file **IxAtmdAccCtrl.h**.

```
typedef IX_STATUS(* IxAtmdAccTxDoneDispatcher)(unsigned int numberOfPdusToProcess, unsigned int
*reservedPtr)
```

Callback prototype for transmitted mbuf when threshold level is crossed.

IxAtmdAccTxDoneDispatcher is the prototype of the user function which get called when pdus are completely transmitted. This function is likely to call the *ixAtmdAccTxDoneDispatch()* function.

This function is called when the number of available pdus for reception is crossing the threshold level as defined in *ixAtmdAccTxDoneDispatcherRegister()*

This function is called inside an Qmgr dispatch context. No system resource or interrupt–unsafe feature should be used inside this callback.

Transmitted buffers recycling implementation is a sytem–wide mechanism and needs to be set before any traffic is started. If this threshold mechanism is not used, the user is responsible for polling the transmitted buffers with *ixAtmdAccTxDoneDispatch()* and *ixAtmdAccTxDoneLevelQuery()* functions.

See also:

ixAtmdAccTxDoneDispatcherRegister

ixAtmdAccTxDoneDispatch

ixAtmdAccTxDoneLevelQuery

Parameters:

numberOfPdusToProcess unsigned int [in] – The current number of pdus currently available for recycling
**reservedPtr* unsigned int [out] – pointer to a int location which can be written to but does not retain written values. This is provided to make this prototype compatible with *ixAtmdAccTxDoneDispatch()*

Returns:

- ◇ **IX_SUCCESS** This is provided to make this prototype compatible with *ixAtmdAccTxDoneDispatch()*
- ◇ **IX_FAIL** invalid parameters or some unspecified internal error occurred. This is provided to make this prototype compatible with *ixAtmdAccTxDoneDispatch()*

Definition at line **159** of file **IxAtmdAccCtrl.h**.

```
typedef IX_STATUS(* IxAtmdAccTxSchVcIdGetCallback)(IxAtmLogicalPort port, unsigned int vpi,
unsigned int vci, IxAtmConnId connId, int *vcId)
```

prototype to get a scheduler vc id

IxAtmdAccTxSchVcIdGetCallback is the prototype of the function to get a scheduler vcId

See also:

IxAtmdAccTxVcDemandUpdateCallback

IxAtmdAccTxVcDemandClearCallback

IxAtmdAccTxSchVcIdGetCallback

ixAtmdAccPortTxScheduledModeEnable

Parameters:

port **IxAtmLogicalPort** [in] – Specifies the ATM logical port on which the VC is established
vpi unsigned int [in] – For AAL0/AAL5 specifies the ATM vpi on which the VC is established.
For OAM specifies the dedicated "OAM Tx channel" VPI.
vci unsigned int [in] – For AAL0/AAL5 specifies the ATM vci on which the VC is established.
For OAM specifies the dedicated "OAM Tx channel" VCI.
connId **IxAtmConnId** [in] – specifies the IxAtmdAcc connection Id already associated with this VC
vcId int* [out] – pointer to a vcId

Returns:

◇ IX_SUCCESS the function is returning a Scheduler vcId for this VC

◇ IX_FAIL the function cannot process scheduling for this VC. the contents of vcId is unspecified

Definition at line **288** of file **IxAtmdAccCtrl.h**.

```
typedef void(* IxAtmdAccTxVcDemandClearCallback)(IxAtmLogicalPort port, int vcId)
```

prototype to remove all currently queued cells from a registered VC

IxAtmdAccTxVcDemandClearCallback is the prototype of the function to remove all currently queued cells from a registered VC. The pending cell count for the specified VC is reset to zero. After the use of this callback, the scheduler shall not schedule more cells for this VC.

This callback function is called during a VC disconnection *ixAtmdAccTxVcTryDisconnect()*

See also:

IxAtmdAccTxVcDemandUpdateCallback

IxAtmdAccTxVcDemandClearCallback

IxAtmdAccTxSchVcIdGetCallback

ixAtmdAccPortTxScheduledModeEnable

ixAtmdAccTxVcTryDisconnect

Parameters:

port

IxAtmLogicalPort [in] – Specifies the ATM port on which the VC to be cleared is established

vcId int [in] – Identifies the VC to be cleared. This is the value returned by the **IxAtmdAccTxSchVcIdGetCallback()** call .

Returns:

none

Definition at line **253** of file **IxAtmdAccCtrl.h**.

```
typedef IX_STATUS(* IxAtmdAccTxVcDemandUpdateCallback)(IxAtmLogicalPort port, int vcId, unsigned int numberOfCells)
```

Prototype to submit cells for transmission.

IxAtmdAccTxVcDemandUpdateCallback is the prototype of the callback function used by AtmD to notify an ATM Scheduler that the user of a VC has submitted cells for transmission.

See also:

IxAtmdAccTxVcDemandUpdateCallback

IxAtmdAccTxVcDemandClearCallback

IxAtmdAccTxSchVcIdGetCallback

ixAtmdAccPortTxScheduledModeEnable

Parameters:

port **IxAtmLogicalPort** [in] – Specifies the ATM port on which the VC to be updated is established

vcId int [in] – Identifies the VC to be updated. This is the value returned by the **IxAtmdAccTxSchVcIdGetCallback()** call .

numberOfCells unsigned int [in] – Indicates how many ATM cells should be added to the queue for this VC.

Returns:

◇ IX_SUCCESS the function is registering the cell demand for this VC.

◇ IX_FAIL the function cannot register cell for this VC : the scheduler maybe overloaded or misconfigured

Definition at line **219** of file **IxAtmdAccCtrl.h**.

Function Documentation

```
ixAtmdAccPortDisable ( IxAtmLogicalPort port )
```

disable a PHY logical port

This function disable the transmission over one port.

When a port is disabled, the cell transmission to the Utopia interface is stopped.

Parameters:

port **IxAtmLogicalPort** [in] – logical PHY port [IX_UTOPIA_PORT_0 .. IX_UTOPIA_MAX_PORTS – 1]

Returns:

- ◇ IX_SUCCESS disable is complete
- ◇ IX_ATMDACC_WARNING port already disabled
- ◇ IX_FAIL disable failed, wrong parameter .

Note:

- This function needs internal locks and should not be called from an interrupt context
- The response from hardware is done through the txDone mechanism to ensure the synchronisation with tx resources. Therefore, the txDone mechanism needs to be serviced to make a PortDisable complete.

See also:

ixAtmdAccPortEnable

ixAtmdAccPortDisableComplete

ixAtmdAccTxDoneDispatch

```
ixAtmdAccPortDisableComplete ( IxAtmLogicalPort port )
```

disable a PHY logical port

This function indicates if the port disable for a port has completed. This function will return TRUE if the port has never been enabled.

Parameters:

port **IxAtmLogicalPort** [in] – logical PHY port [IX_UTOPIA_PORT_0 .. IX_UTOPIA_MAX_PORTS – 1]

Returns:

- ◇ TRUE disable is complete
- ◇ FALSE disable failed, wrong parameter .

Note:

- This function needs internal locks and should not be called from an interrupt context

See also:

ixAtmdAccPortEnable

ixAtmdAccPortDisable

```
ixAtmdAccPortEnable ( IxAtmLogicalPort port )
```

enable a PHY logical port

This function enables the transmission over one port. It should be called before accessing any resource from this port and before the establishment of a VC.

When a port is enabled, the cell transmission to the Utopia interface is started. If there is no traffic already running, idle cells are sent over the interface.

This function can be called multiple times.

Parameters:

port **IxAtmLogicalPort** [in] – logical PHY port [IX_UTOPIA_PORT_0 .. IX_UTOPIA_MAX_PORTS – 1]

Returns:

◇ IX_SUCCESS enable is complete

◇ IX_ATMDACC_WARNING port already enabled

◇ IX_FAIL enable failed, wrong parameter, or cannot initialise this port (the port is maybe already in use, or there is a hardware issue)

Note:

– This function needs internal locks and should not be called from an interrupt context

See also:

ixAtmdAccPortDisable

```
ixAtmdAccPortTxCallbackRegister ( IxAtmLogicalPort port,  
                                unsigned int numberOfCells,  
                                IxAtmdAccPortTxLowCallback callback  
                                )
```

Configure the Tx port threshold value and register a callback to handle threshold notifications.

This function sets the threshold in cells

See also:

ixAtmdAccPortTxCallbackRegister

ixAtmdAccPortTxProcess

ixAtmdAccPortTxFreeEntriesQuery

Parameters:

- port* **IxAtmLogicalPort** [in] – logical PHY port [*IX_UTOPIA_PORT_0* .. *IX_UTOPIA_MAX_PORTS* – 1]
- numberOfCells* unsigned int [in] – threshold value which triggers the callback invocation, This number has to be one of the values 0,1,2,4,8,16,32 The maximum value cannot be more than half of the txVc queue size (which can be retrieved using **ixAtmdAccPortTxFreeEntriesQuery()** before any Tx traffic is sent for this port)
- callback* **IxAtmdAccPortTxLowCallback** [in] – callback function to invoke when the threshold level is reached. This parameter cannot be a null pointer.

Returns:

- ◇ **IX_SUCCESS** Successful call to **ixAtmdAccPortTxCallbackRegister()**
- ◇ **IX_FAIL** error in the parameters, Tx channel already set for this port threshold level is not correct or within the range regarding the queue size:or unspecified error during processing:

Note:

- This callback function get called when the threshold level drops from (numberOfCells+1) cells to (numberOfCells) cells
- This function should be called during system initialisation, outside an interrupt context

```
ixAtmdAccPortTxCallbackUnregister ( IxAtmLogicalPort port )
```

Unregister a callback to handle threshold notifications.

Parameters:

- port* **IxAtmLogicalPort** [in] – logical PHY port [*IX_UTOPIA_PORT_0* .. *IX_UTOPIA_MAX_PORTS* – 1]

Returns:

- ◇ none

Note:

- This function should be called during system un-initialisation, outside an interrupt context

```
ixAtmdAccPortTxFreeEntriesQuery ( IxAtmLogicalPort port,  
                                unsigned int * numberOfCellsPtr  
                                )
```

Get the number of available cells the system can accept for transmission.

The function is used to retrieve the number of cells that can be queued for transmission to the hardware.

This number is based on the worst schedule table where one cell is stored in one schedule table entry, depending on the pdu size and mbuf size and fragmentation.

This function doesn't use system resources and can be used from a timer context, or can be associated with a threshold event, or can be used inside an active polling mechanism

Parameters:

port **IxAtmLogicalPort** [in] – logical PHY port [*IX_UTOPIA_PORT_0* .. *IX_UTOPIA_MAX_PORTS* – 1]
numberOfCellsPtr unsigned int* [out] – number of available cells. This parameter cannot be a null pointer.

See also:

ixAtmdAccPortTxProcess

Returns:

- ◇ *IX_SUCCESS* *numberOfCellsPtr* contains the number of cells that can be scheduled for this port.
- ◇ *IX_FAIL* error in the parameters, or some processing error occurred.

```
ixAtmdAccPortTxProcess ( IxAtmLogicalPort     port,  
                         IxAtmScheduleTable * scheduleTablePtr  
                         )
```

Transmit queue cells to the H/W based on the supplied schedule table.

This function **ixAtmdAccPortTxProcess()** process the schedule table provided as a parameter to the function. As a result cells are sent to the underlying hardware for transmission.

The schedule table is executed in its entirety or not at all. So the onus is on the caller not to submit a table containing more cells than can be transmitted at that point. The maximum numbers that can be transmitted is guaranteed to be the number of cells as returned by the function **ixAtmdAccPortTxFreeEntriesQuery()**.

When the scheduler is invoked on a threshold level, IxAtmdAcc gives the minimum number of cells (to ensure the callback will fire again later) and the maximum number of cells that **ixAtmdAccPortTxProcess()** will be able to process (assuming the ATM scheduler is able to produce the worst-case schedule table, i.e. one entry per cell).

When invoked outside a threshold level, the overall number of cells of the schedule table should be less than the number of cells returned by the **ixAtmdAccPortTxFreeEntriesQuery()** function.

After invoking the **ixAtmdAccPortTxProcess()** function, it is the user choice to query again the queue level with the function **ixAtmdAccPortTxFreeEntriesQuery()** and, depending on a new cell number, submit an other schedule table.

IxAtmdAcc will check that the number of cells in the schedule table is compatible with the current transmit level. If the

Obsolete or invalid connection Id will be silently discarded.

This function is not reentrant for the same port.

This functions doesn't use system resources and can be used inside an interrupt context.

This function is used as a response to the hardware requesting more cells to transmit.

See also:

ixAtmdAccPortTxScheduledModeEnable

ixAtmdAccPortTxFreeEntriesQuery

ixAtmdAccPortTxCallbackRegister

ixAtmdAccPortEnable

Parameters:

port **IxAtmLogicalPort** [in] – logical PHY port [*IX_UTOPIA_PORT_0* .. *IX_UTOPIA_MAX_PORTS* – 1]

scheduleTablePtr **IxAtmScheduleTable*** [in] – pointer to a scheduler update table. The content of this table is not modified by this function. This parameter cannot be a null pointer.

Returns:

- ◇ **IX_SUCCESS** the schedule table process is complete and cells are transmitted to the hardware
- ◇ **IX_ATMDACC_WARNING** : Traffic will be dropped: the schedule table exceed the hardware capacity If this error is ignored, further traffic and schedule will work correctly. Overscheduling does not occur when the schedule table does not contain more entries that the number of free entries returned by **ixAtmdAccPortTxFreeEntriesQuery()**. However, Disconnect attempts just after this error will fail permanently with the error code **IX_ATMDACC_RESOURCES_STILL_ALLOCATED**, and it is necessary to disable the port to make **ixAtmdAccTxVcTryDisconnect()** successful.
- ◇ **IX_FAIL** a wrong parameter is supplied, or the format of the schedule table is invalid, or the port is not Enabled, or an internal severe error occurred. No cells is transmitted to the hardware

Note:

- If the failure is linked to an overschedule of data cells the result is an inconsistency in the output traffic (one or many cells may be missing and the traffic contract is not respected).

```
ixAtmdAccPortTxScheduledModeDisable ( IxAtmLogicalPort port )
```

Put the port into UnScheduled Mode.

Parameters:

port **IxAtmLogicalPort** [in] – logical PHY port [*IX_UTOPIA_PORT_0* .. *IX_UTOPIA_MAX_PORTS* – 1]

Returns:

◇ IX_SUCCESS scheduler unregistration is complete and the port is now in unscheduled mode.

◇ IX_FAIL failed (wrong parameters)

```
ixAtmdAccPortTxScheduledModeEnable ( IxAtmLogicalPort port,  
                                     IxAtmdAccTxVcDemandUpdateCallback vcDemandUpdateCallback,  
                                     IxAtmdAccTxVcDemandClearCallback vcDemandClearCallback,  
                                     IxAtmdAccTxSchVcIdGetCallback vcIdGetCallback  
                                     )
```

Put the port into Scheduled Mode.

This function puts the specified port into scheduled mode of transmission which means an external s/w entity controls the transmission of cells on this port. This facilitates traffic shaping on the port.

Any buffers submitted on a VC for this port will be queued in IxAtmdAcc. The transmission of these buffers to and by the hardware will be driven by a transmit schedule submitted regularly in calls to **ixAtmdAccPortTxProcess()** by traffic shaping entity.

The transmit schedule is expected to be dynamic in nature based on the demand in cells for each VC on the port. Hence the callback parameters provided to this function allow IxAtmdAcc to inform the shaping entity of demand changes for each VC on the port.

By default a port is in Unscheduled Mode so if this function is not called, transmission of data is done without scheduling rules, on a first-come, first-out basis.

Once a port is put in scheduled mode it cannot be reverted to un-scheduled mode.

Note:

- This function should be called before any VCs have be connected on a port. Otherwise this function call will return failure.
- This function uses internal locks and should not be called from an interrupt context

See also:

IxAtmdAccTxVcDemandUpdateCallback

IxAtmdAccTxVcDemandClearCallback

IxAtmdAccTxSchVcIdGetCallback

ixAtmdAccPortTxProcess

Parameters:

port **IxAtmLogicalPort** [in] – logical PHY port [*IX_UTOPIA_PORT_0* .. *IX_UTOPIA_MAX_PORTS* – 1]

vcDemandUpdateCallback **IxAtmdAccTxVcDemandUpdateCallback** [in] – callback function used to update the number of outstanding cells for transmission. This

parameter cannot be a null pointer.

vcDemandClearCallback **IxAtmdAccTxVcDemandClearCallback** [in] – callback function used to remove all clear the number of outstanding cells for a VC. This parameter cannot be a null pointer.

vcIdGetCallback **IxAtmdAccTxSchVcIdGetCallback** [in] – callback function used to exchange vc Identifiers between IxAtmdAcc and the entity supplying the transmit schedule. This parameter cannot be a null pointer.

Returns:

- ◇ IX_SUCCESS scheduler registration is complete and the port is now in scheduled mode.
- ◇ IX_FAIL failed (wrong parameters, or traffic is already enabled on this port, possibly without ATM shaping)

```

ixAtmdAccRxDispatch ( IxAtmRxQueueId rxQueueId,
                      unsigned int      numberOfPdusToProcess,
                      unsigned int *     numberOfPdusProcessedPtr
                      )

```

Control function which executes Rx processing for a particular Rx stream.

The *IxAtmdAccRxDispatch()* function is used to process received Pdus available from one of the two incoming RX streams. When this function is invoked, the incoming traffic (up to the number of PDUs passed as a parameter) will be transferred to the IxAtmdAcc users through the callback ***IxAtmdAccRxVcRxCallback()***, as registered during the ***ixAtmdAccRxVcConnect()*** call.

The user receive callbacks will be executed in the context of this function.

Failing to use this function on a regular basis when there is traffic will block incoming traffic and can result in Pdus being dropped by the hardware.

This should be used to control when received pdus are handed off from the hardware to Aal users from a particular stream. The function can be used from a timer context, or can be registered as a callback in response to an rx stream threshold event, or can be used inside an active polling mechanism which is under user control.

Note:

- The signature of this function is directly compatible with the callback prototype which can be register with ***ixAtmdAccRxDispatcherRegister()***.

See also:

ixAtmdAccRxDispatcherRegister

IxAtmdAccRxVcRxCallback

ixAtmdAccRxVcFreeEntriesQuery

Parameters:

rxQueueId **IxAtmRxQueueId** [in] – indicates which RX queue to process.

numberOfPdusToProcess unsigned int [in] – indicates the maximum number of PDU to remove from the RX queue. A value of IX_ATMDACC_ALLPDUS indicates to process all PDUs from the queue. This includes at least the PDUs in the queue when the function is invoked. Because of real-time constraints, there is no guarantee that the queue will be empty when the function exits. If this parameter is greater than the number of entries of the queues, the function will succeed and the parameter *numberOfPdusProcessedPtr* will reflect the exact number of PDUs processed.

**numberOfPdusProcessedPtr* unsigned int [out] – indicates the actual number of PDU processed during this call. This parameter cannot be a null pointer.

Returns:

- ◇ IX_SUCCESS the number of PDUs as indicated in *numberOfPdusProcessedPtr* are removed from the RX queue and the VC callback are called.
- ◇ IX_FAIL invalid parameters or some unspecified internal error occurred.

```
ixAtmdAccRxDispatcherRegister ( IxAtmRxQueueId      queueId,
                                IxAtmdAccRxDispatcher callback
                                )
```

Register a notification callback to be invoked when there is at least one entry on a particular Rx queue.

This function registers a callback to be invoked when there is at least one entry in a particular queue. The registered callback is called every time when the hardware adds one or more pdus to the specified Rx queue.

This function cannot be used when a Rx Vc using this queue is already existing.

Note:

–The callback function can be the API function *ixAtmdAccRxDispatch()* : every time the threshold level of the queue is reached, the *ixAtmdAccRxDispatch()* is invoked to remove all entries from the queue.

See also:

ixAtmdAccRxDispatch

IxAtmdAccRxDispatcher

Parameters:

queueId **IxAtmRxQueueId** [in] RX queue identification

callback **IxAtmdAccRxDispatcher** [in] function triggering the delivery of incoming traffic. This parameter cannot be a null pointer.

Returns:

- ◇ IX_SUCCESS Successful call to *ixAtmdAccRxDispatcherRegister()*
- ◇ IX_FAIL error in the parameters, or there is an already active RX VC for this queue or

some unspecified internal error occurred.

```
ixAtmdAccRxDispatcherUnregister ( IxAtmRxQueueId atmdQueueId )
```

UnRegister a notification callback to be invoked when there is at least one entry on a particular Rx queue.

Parameters:

queueId **IxAtmRxQueueId** [in] RX queue identification

Returns:

- ◇ IX_SUCCESS Successful call
- ◇ IX_FAIL error in the parameters

```
ixAtmdAccRxLevelQuery ( IxAtmRxQueueId rxQueueId,  
                        unsigned int * numberOfPdusPtr  
                        )
```

Query the number of entries in a particular RX queue.

This function is used to retrieve the number of pdus received by the hardware and ready for distribution to users.

Parameters:

rxQueueId **IxAtmRxQueueId** [in] – indicates which of two RX queues to query.
numberOfPdusPtr unsigned int* [out] – Pointer to store the number of available PDUs in the RX queue. This parameter cannot be a null pointer.

Returns:

- ◇ IX_SUCCESS the value in *numberOfPdusPtr* specifies the number of incoming pdus waiting in this queue
- ◇ IX_FAIL an error occurs during processing. The value in *numberOfPdusPtr* is unspecified.

Note:

- This function is reentrant, doesn't use system resources and can be used from an interrupt context.

```
ixAtmdAccRxQueueSizeQuery ( IxAtmRxQueueId rxQueueId,  
                           unsigned int * numberOfPdusPtr  
                           )
```

Query the size of a particular RX queue.

This function is used to retrieve the number of pdus the system is able to queue when reception is complete.

Parameters:

rxQueueId **IxAtmRxQueueId** [in] – indicates which of two RX queues to query.

numberOfPduPtr unsigned int* [out] – Pointer to store the number of pdus the system is able to queue in the RX queue. This parameter cannot be a null pointer.

Returns:

◇ IX_SUCCESS the value in *numberOfPduPtr* specifies the number of pdus the system is able to queue.

◇ IX_FAIL an error occurs during processing. The value in *numberOfPduPtr* is unspecified.

Note:

– This function is reentrant, doesn't use system resources and can be used from an interrupt context.

```
ixAtmdAccTxDoneDispatch ( unsigned int    numberOfPduToProcess,  
                          unsigned int * numberOfPduProcessedPtr  
                          )
```

Process a number of pending transmit done pdus from the hardware.

As a by-product of Atm transmit operation buffers which transmission is complete need to be recycled to users. This function is invoked to service the outstanding list of transmitted buffers and pass them to VC users.

Users are handed back pdus by invoking the free callback registered during the *ixAtmdAccTxVcConnect()* call.

There is a single Tx done stream servicing all active Atm Tx ports which can contain a maximum of 64 entries. If this stream fills port transmission will stop so this function must be call sufficently frequently to ensure no disruption to the transmit operation.

This function can be used from a timer context, or can be associated with a TxDone level threshold event (see *ixAtmdAccTxDoneDispatcherRegister()*), or can be used inside an active polling mechanism under user control.

For ease of use the signature of this function is compatible with the TxDone threshold event callback prototype.

This functions can be used inside an interrupt context.

See also:

ixAtmdAccTxDoneDispatcherRegister

IxAtmdAccTxVcBufferReturnCallback

ixAtmdAccTxDoneLevelQuery

Parameters:

numberOfPduToProcess unsigned int [in] – maximum number of pdus to remove from the TX Done queue

**numberOfPduProcessedPtr* unsigned int [out] – number of pdus removed from the TX Done

queue. This parameter cannot be a null pointer.

Returns:

- ◇ IX_SUCCESS the number of pdus as indicated in numberOfPdusToProcess are removed from the TX Done hardware and passed to the user through the Tx Done callback registered during a call to **ixAtmdAccTxVcConnect()**
- ◇ IX_FAIL invalid parameters or numberOfPdusProcessedPtr is a null pointer or some unspecified internal error occurred.

```
ixAtmdAccTxDoneDispatcherRegister ( unsigned int          numberOfPdus,  
                                   IxAtmdAccTxDoneDispatcher notificationCallback  
                                   )
```

Configure the Tx Done stream threshold value and register a callback to handle threshold notifications.

This function sets the threshold level in term of number of pdus at which the supplied notification function should be called.

The higher the threshold value is, the less events will be necessary to process transmitted buffers.

Transmitted buffers recycling implementation is a sytem-wide mechanism and needs to be set prior any traffic is started. If this threshold mechanism is not used, the user is responsible for polling the transmitted buffers thanks to **ixAtmdAccTxDoneDispatch()** and **ixAtmdAccTxDoneLevelQuery()** functions.

This function should be called during system initialisation outside an interrupt context

See also:

ixAtmdAccTxDoneDispatcherRegister

ixAtmdAccTxDoneDispatch

ixAtmdAccTxDoneLevelQuery

Parameters:

numberOfPdus

unsigned int [in] – The number of TxDone pdus which triggers the callback invocation This number has to be a power of 2, one of the values 0,1,2,4,8,16,32 ... The maximum value cannot be more than half of the txDone queue size (which can be retrieved using **ixAtmdAccTxDoneQueueSizeQuery()**)

notificationCallback

IxAtmdAccTxDoneDispatcher [in] – The function to invoke. (This parameter can be **ixAtmdAccTxDoneDispatch()**). This parameter ust not be a null pointer.

Returns:

- ◇ IX_SUCCESS Successful call to ixAtmdAccTxDoneDispatcherRegister

◇ IX_FAIL error in the parameters:

Note:

- The notificationCallback will be called exactly when the threshold level will increase from (numberOfPdus) to (numberOfPdus+1)
- If there is no Tx traffic, there is no guarantee that TxDone Pdus will be released to the user (when txDone level is permanently under the threshold level. One of the preferred way to return resources to the user is to use a mix of txDone notifications, used together with a slow rate timer and an exclusion mechanism protecting from re-entrancy
- The TxDone threshold will only hand back buffers when the threshold level is crossed. Setting this threshold to a great number reduce the interrupt rate and the cpu load, but also increase the number of outstanding mbufs and has a system wide impact when these mbufs are needed by other components.

```
ixAtmdAccTxDoneDispatcherUnregister ( void )
```

Unregister a callback to handle threshold notifications.

Parameters:

NONE.

Returns:

NONE

```
ixAtmdAccTxDoneLevelQuery ( unsigned int * numberOfPdusPtr )
```

Query the current number of transmit pdus ready for recycling.

This function is used to get the number of transmitted pdus which the hardware is ready to hand back to user.

This function can be used from a timer context, or can be associated with a threshold event, on can be used inside an active polling mechanism

See also:

ixAtmdAccTxDoneDispatch

Parameters:

*numberOfPdusPtr unsigned int [out] – Pointer to the number of pdus transmitted at the time of this function call, and ready for recycling This parameter cannot be a null pointer.

Returns:

◇ IX_SUCCESS numberOfPdusPtr contains the number of pdus ready for recycling at the time of this function call

◇ IX_FAIL wrong parameter (null pointer as parameter).or unspecified rocessing error occurs..The value in numberOfPdusPtr is unspecified.

```
ixAtmdAccTxDoneQueueSizeQuery ( unsigned int * numberOfPdusPtr )
```

Query the TxDone queue size.

This function is used to get the number of pdus which the hardware is able to store after transmission is complete

The returned value can be used to set a threshold and enable a callback to be notified when the number of pdus is going over the threshold.

See also:

ixAtmdAccTxDoneDispatcherRegister

Parameters:

**numberOfPdusPtr* unsigned int [out] – Pointer to the number of pdus the system is able to queue after transmission

Returns:

◇ IX_SUCCESS numberOfPdusPtr contains the the number of pdus the system is able to queue after transmission

◇ IX_FAIL wrong parameter (null pointer as parameter).or unspecified rocessing error occurs..The value in numberOfPdusPtr is unspecified.

Note:

– This function is reentrant, doesn't use system resources and can be used from an interrupt context.

```
ixAtmdAccUtopiaConfigReset ( const IxAtmdAccUtopiaConfig * utConfig )
```

Reset the configuration structure to the Utopia interface initializes configuration registers and write to NPE–A Load and get response from NPE–A and resets the Utopia interface.

Parameters:

ixAtmdAccNPEConfigPtr* **IxAtmdAccUtopiaConfig [in] – pointer to a structure to download to

Returns:

◇ IX_SUCCESS successful unload

◇ IX_FAIL error in the parameters

```
ixAtmdAccUtopiaConfigSet ( const IxAtmdAccUtopiaConfig * ixAtmdAccUtopiaConfigPtr )
```

Send the configuration structure to the Utopia interface.

This function downloads the ***IxAtmdAccUtopiaConfig*** structure to the Utopia and has the following effects

- setup the Utopia interface
- initialise the NPE
- reset the Utopia cell counters and status registers to known values

This action has to be done once at initialisation. A lock is preventing the concurrent use of ***ixAtmdAccUtopiaStatusGet()*** and ***ixAtmdAccUtopiaConfigSet()***

Parameters:

ixAtmdAccNPEConfigPtr* **IxAtmdAccUtopiaConfig [in] – pointer to a structure to download to Utopia. This parameter cannot be a null pointer.

Returns:

- ◇ IX_SUCCESS successful download
- ◇ IX_FAIL error in the parameters, or configuration is not complete or failed

See also:

ixAtmdAccUtopiaStatusGet

```
ixAtmdAccUtopiaStatusGet ( IxAtmdAccUtopiaStatus * ixAtmdAccUtopiaStatus )
```

Get the Utopia interface configuration.

This function reads the Utopia registers and the Cell counts and fills the ***IxAtmdAccUtopiaStatus*** structure

A lock is preventing the concurrent use of ***ixAtmdAccUtopiaStatusGet()*** and ***ixAtmdAccUtopiaConfigSet()***

Parameters:

ixAtmdAccUtopiaStatus **IxAtmdAccUtopiaStatus** [out] – pointer to structure to be updated from internal hardware counters. This parameter cannot be a NULL pointer.

Returns:

- ◇ IX_SUCCESS successful read
- ◇ IX_FAIL error in the parameters null pointer, or configuration read is not complete or failed

See also:

ixAtmdAccUtopiaConfigSet

Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Control API]

The public API for the IXP400 Atm Driver Control component.

Data Structures

struct **IxAtmdAccUtopiaConfig**
Utopia configuration.

struct **IxAtmdAccUtopiaConfig::UtRxConfig_**
Utopia Rx config Register.

struct **IxAtmdAccUtopiaConfig::UtRxDefineIdle_**
Utopia Rx idle cells config Register.

struct **IxAtmdAccUtopiaConfig::UtRxEnableFields_**
Utopia Rx enable Register.

struct **IxAtmdAccUtopiaConfig::UtRxStatsConfig_**
Utopia Rx stats config Register.

struct **IxAtmdAccUtopiaConfig::UtRxTransTable0_**
Utopia Rx translation table Register.

struct **IxAtmdAccUtopiaConfig::UtRxTransTable1_**
Utopia Rx translation table Register.

struct **IxAtmdAccUtopiaConfig::UtRxTransTable2_**
Utopia Rx translation table Register.

struct **IxAtmdAccUtopiaConfig::UtRxTransTable3_**
Utopia Rx translation table Register.

struct **IxAtmdAccUtopiaConfig::UtRxTransTable4_**
Utopia Rx translation table Register.

struct **IxAtmdAccUtopiaConfig::UtRxTransTable5_**
Utopia Rx translation table Register.

struct **IxAtmdAccUtopiaConfig::UtSysConfig_**
NPE setup Register.

struct **IxAtmdAccUtopiaConfig::UtTxConfig_**
Utopia Tx Config Register.

```

struct IxAtmdAccUtopiaConfig::UtTxDefineIdle_
    Utopia Tx idle cells Register.

struct IxAtmdAccUtopiaConfig::UtTxEnableFields_
    Utopia Tx ienable fields Register.

struct IxAtmdAccUtopiaConfig::UtTxStatsConfig_
    Utopia Tx stats Register.

struct IxAtmdAccUtopiaConfig::UtTxTransTable0_
    Utopia Tx translation table Register.

struct IxAtmdAccUtopiaConfig::UtTxTransTable1_
    Utopia Tx translation table Register.

struct IxAtmdAccUtopiaConfig::UtTxTransTable2_
    Utopia Tx translation table Register.

struct IxAtmdAccUtopiaConfig::UtTxTransTable3_
    Utopia Tx translation table Register.

struct IxAtmdAccUtopiaConfig::UtTxTransTable4_
    Utopia Tx translation table Register.

struct IxAtmdAccUtopiaConfig::UtTxTransTable5_
    Utopia Tx translation table Register.

struct IxAtmdAccUtopiaStatus
    Utopia status.

struct IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_
    Utopia Rx Status Register.

struct IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_
    Utopia Tx Status Register.

```

Detailed Description

The public API for the IXP400 Atm Driver Control component.

IxAtmdAcc is the low level interface by which AAL PDU get transmitted to, and received from the Utopia bus

This part is related to the UTOPIA configuration.

Intel (R) IXP400 Software ATM Manager (IxAtmm) API

IXP400 ATM Manager component Public API.

Data Structures

struct **IxAtmmPortCfg**

Structure contains port-specific information required to initialize IxAtmm, and specifically, the IXP400 UTOPIA Level-2 device.

struct **IxAtmmVc**

This structure describes the required attributes of a virtual connection.

Defines

#define **IX_ATMM_RET_ALREADY_INITIALIZED**

Component has already been initialized.

#define **IX_ATMM_RET_INVALID_PORT**

Specified port does not exist or is out of range.

#define **IX_ATMM_RET_INVALID_VC_DESCRIPTOR**

The VC description does not adhere to ATM standards.

#define **IX_ATMM_RET_VC_CONFLICT**

The VPI/VCI values supplied are either reserved, or they conflict with a previously registered VC on this port.

#define **IX_ATMM_RET_PORT_CAPACITY_IS_FULL**

The virtual connection cannot be established on the port because the remaining port capacity is not sufficient to support it.

#define **IX_ATMM_RET_NO_SUCH_VC**

No registered VC, as described by the supplied VCI/VPI or VC identifier values, exists on this port.

#define **IX_ATMM_RET_INVALID_VC_ID**

The specified VC identifier is out of range.

#define **IX_ATMM_RET_INVALID_PARAM_PTR**

A pointer parameter was NULL.

#define **IX_ATMM_UTOPIA_SPHY_ADDR**

The phy address when in SPHY mode.


```
#define IX_ATMM_THREAD_PRI_HIGH  
    The value of high priority thread.
```

Typedefs

```
typedef void(* IxAtmmVcChangeCallback )(IxAtmmVcChangeEvent eventType, IxAtmLogicalPort  
port, const IxAtmmVc *vcChanged)  
Callback type used with ixAtmmVcChangeCallbackRegister interface Defines a callback  
type which will be used to notify registered users of registration/deregistration events on a  
particular port.
```

Enumerations

```
enum IxAtmmVcDirection {  
    IX_ATMM_VC_DIRECTION_TX,  
    IX_ATMM_VC_DIRECTION_RX,  
    IX_ATMM_VC_DIRECTION_INVALID  
}  
Definition for use in the IxAtmmVc structure. Indicates the direction of a VC.
```

```
enum IxAtmmVcChangeEvent {  
    IX_ATMM_VC_CHANGE_EVENT_REGISTER,  
    IX_ATMM_VC_CHANGE_EVENT_DEREGISTER,  
    IX_ATMM_VC_CHANGE_EVENT_INVALID  
}  
Definition for use with IxAtmmVcChangeCallback callback. Indicates that the event type  
represented by the callback for this VC.
```

```
enum IxAtmmUtopiaLoopbackMode {  
    IX_ATMM_UTOPIA_LOOPBACK_DISABLED,  
    IX_ATMM_UTOPIA_LOOPBACK_ENABLED,  
    IX_ATMM_UTOPIA_LOOPBACK_INVALID  
}  
Definitions for use with interface to indicate that UTOPIA loopback should be enabled or  
disabled on initialisation.
```

```
enum IxAtmmPhyMode {  
    IX_ATMM_MPHY_MODE,  
    IX_ATMM_SPHY_MODE,  
    IX_ATMM_PHY_MODE_INVALID  
}  
Definitions for use with ixAtmmUtopiaInit interface to indicate that UTOPIA  
multi-phy/single-phy mode is used.
```

Functions

- PUBLIC**
IX_STATUS ixAtmmInit (void)
Interface to initialize the IxAtmm software component. Can be called once only.
- PUBLIC**
IX_STATUS ixAtmmUninit (void)
Interface to uninitialize the IxAtmm software component. This function deallocates/destroys the allocated buffer/Mutex done during initialization. Should be the last function to be called.
- PUBLIC**
IX_STATUS ixAtmmUtopiaInit (unsigned numPorts, **IxAtmmPhyMode** phyMode, **IxAtmmPortCfg** portCfgs[], **IxAtmmUtopiaLoopbackMode** loopbackMode)
Interface to initialize the UTOPIA Level-2 ATM coprocessor for the specified number of physical ports. The function must be called before the ixAtmmPortInitialize interface can operate successfully.
- PUBLIC**
IX_STATUS ixAtmmUtopiaUninit (void)
Interface to uninitialize the UTOPIA Level-2 ATM coprocessor.
- PUBLIC**
IX_STATUS ixAtmmPortInitialize (**IxAtmLogicalPort** port, unsigned txPortRate, unsigned rxPortRate)
*The interface is called following **ixAtmmUtopiaInit** () and before calls to any other IxAtmm interface. It serves to activate the registered ATM port with IxAtmm.*
- PUBLIC**
IX_STATUS ixAtmmPortUninitialize (**IxAtmLogicalPort** port)
It serves to uninitialise the respective port passed as a parameter. Executes only if Utopia Initialization is done. Uninitializes the Data Path. Uninitializes the specified port.
- PUBLIC**
IX_STATUS ixAtmmPortModify (**IxAtmLogicalPort** port, unsigned txPortRate, unsigned rxPortRate)
A client may call this interface to change the existing port rate (expressed in bits/second) on an established ATM port.
- PUBLIC**
IX_STATUS ixAtmmPortQuery (**IxAtmLogicalPort** port, unsigned *txPortRate, unsigned *rxPortRate)
The client may call this interface to request details on currently registered transmit and receive rates for an ATM port.
- PUBLIC**
IX_STATUS ixAtmmPortEnable (**IxAtmLogicalPort** port)
The client call this interface to enable transmit for an ATM port. At initialisation, all the ports are disabled.
- PUBLIC**
IX_STATUS ixAtmmPortDisable (**IxAtmLogicalPort** port)
The client call this interface to disable transmit for an ATM port. At initialisation, all the ports are disabled.

PUBLIC
IX_STATUS IxAtmmVcRegister (IxAtmLogicalPort port, IxAtmmVc *vcToAdd,
IxAtmSchedulerVcId *vcId)
This interface is used to register an ATM Virtual Connection on the specified ATM port.

PUBLIC
IX_STATUS IxAtmmVcDeregister (IxAtmLogicalPort port, IxAtmSchedulerVcId vcId)
Function called by a client to deregister a VC from the system.

PUBLIC
IX_STATUS IxAtmmVcQuery (IxAtmLogicalPort port, unsigned vpi, unsigned vci,
IxAtmmVcDirection direction, IxAtmSchedulerVcId *vcId, IxAtmmVc *vcDesc)
This interface supplies information about an active VC on a particular port when supplied with the VPI, VCI and direction of that VC.

PUBLIC
IX_STATUS IxAtmmVcIdQuery (IxAtmLogicalPort port, IxAtmSchedulerVcId vcId, IxAtmmVc
***vcDesc)**
This interface supplies information about an active VC on a particular port when supplied with a vcId for that VC.

PUBLIC
IX_STATUS IxAtmmVcChangeCallbackRegister (IxAtmmVcChangeCallback callback)
This interface is invoked to supply a function to IxAtmm which will be called to notify the client if a new VC is registered with IxAtmm or an existing VC is removed.

PUBLIC
IX_STATUS IxAtmmVcChangeCallbackDeregister (IxAtmmVcChangeCallback callback)
This interface is invoked to deregister a previously supplied callback function.

PUBLIC
IX_STATUS IxAtmmUtopiaStatusShow (void)
Display utopia status counters.

PUBLIC
IX_STATUS IxAtmmUtopiaCfgShow (void)
Display utopia information(config registers and status registers).

Detailed Description

IXP400 ATM Manager component Public API.

Define Documentation

```
#define IX_ATMM_RET_ALREADY_INITIALIZED
```

Component has already been initialized.

Definition at line **40** of file **IxAtmm.h**.

```
#define IX_ATMM_RET_INVALID_PARAM_PTR
```

A pointer parameter was NULL.

Definition at line **86** of file **IxAtmm.h**.

```
#define IX_ATMM_RET_INVALID_PORT
```

Specified port does not exist or is out of range.

Definition at line **46** of file **IxAtmm.h**.

```
#define IX_ATMM_RET_INVALID_VC_DESCRIPTOR
```

The VC description does not adhere to ATM standards.

Definition at line **52** of file **IxAtmm.h**.

```
#define IX_ATMM_RET_INVALID_VC_ID
```

The specified VC identifier is out of range.

Definition at line **80** of file **IxAtmm.h**.

```
#define IX_ATMM_RET_NO_SUCH_VC
```

No registered VC, as described by the supplied VCI/VPI or VC identifier values, exists on this port.

Definition at line **74** of file **IxAtmm.h**.

```
#define IX_ATMM_RET_PORT_CAPACITY_IS_FULL
```

The virtual connection cannot be established on the port because the remaining port capacity is not sufficient to support it.

Definition at line **67** of file **IxAtmm.h**.

```
#define IX_ATMM_RET_VC_CONFLICT
```

The VPI/VCI values supplied are either reserved, or they conflict with a previously registered VC on this port.

Definition at line **59** of file **IxAtmm.h**.

```
#define IX_ATMM_THREAD_PRI_HIGH
```

The value of high priority thread.

Definition at line **98** of file **IxAtmm.h**.

```
#define IX_ATMM_UTOPIA_SPHY_ADDR
```

The phy address when in SPHY mode.

Definition at line **92** of file **IxAtmm.h**.

Typedef Documentation

```
typedef void(* IxAtmmVcChangeCallback)(IxAtmmVcChangeEvent eventType, IxAtmLogicalPort port,  
const IxAtmmVc* vcChanged)
```

Callback type used with **ixAtmmVcChangeCallbackRegister** interface Defines a callback type which will be used to notify registered users of registration/deregistration events on a particular port.

Parameters:

<i>eventType</i>	IxAtmmVcChangeEvent [in] – Event indicating whether the VC supplied has been added or removed
<i>port</i>	IxAtmLogicalPort [in] – Specifies the port on which the event has occurred
<i>vcChanged</i>	IxAtmmVc* [in] – Pointer to a structure which gives details of the VC which has been added or removed on the port

Definition at line **189** of file **IxAtmm.h**.

Enumeration Type Documentation

```
enum IxAtmmPhyMode
```

Definitions for use with **ixAtmmUtopiaInit** interface to indicate that UTOPIA multi-phy/single-phy mode is used.

Enumeration values:

IX_ATMM_MPHY_MODE	Atmm phy mode mphy.
IX_ATMM_SPHY_MODE	Atmm phy mode sphy.
IX_ATMM_PHY_MODE_INVALID	Atmm phy mode invalid.

Definition at line **150** of file **IxAtmm.h**.

enum IxAtmmUtopiaLoopbackMode

Definitions for use with interface to indicate that UTOPIA loopback should be enabled or disabled on initialisation.

Enumeration values:

<i>IX_ATMM_UTOPIA_LOOPBACK_DISABLED</i>	Atmm Utopia loopback mode disabled.
<i>IX_ATMM_UTOPIA_LOOPBACK_ENABLED</i>	Atmm Utopia loopback mode enabled.
<i>IX_ATMM_UTOPIA_LOOPBACK_INVALID</i>	Atmm Utopia loopback mode invalid.

Definition at line **126** of file **IxAtmm.h**.

enum IxAtmmVcChangeEvent

Definition for use with **IxAtmmVcChangeCallback** callback. Indicates that the event type represented by the callback for this VC.

Enumeration values:

<i>IX_ATMM_VC_CHANGE_EVENT_REGISTER</i>	Atmm Vc event register.
<i>IX_ATMM_VC_CHANGE_EVENT_DEREGISTER</i>	Atmm Vc event de-register.
<i>IX_ATMM_VC_CHANGE_EVENT_INVALID</i>	Atmm Vc event invalid.

Definition at line **116** of file **IxAtmm.h**.

enum IxAtmmVcDirection

Definition for use in the **IxAtmmVc** structure. Indicates the direction of a VC.

Enumeration values:

<i>IX_ATMM_VC_DIRECTION_TX</i>	Atmm Vc direction transmit.
<i>IX_ATMM_VC_DIRECTION_RX</i>	Atmm Vc direction receive.
<i>IX_ATMM_VC_DIRECTION_INVALID</i>	Atmm Vc direction invalid.

Definition at line **106** of file **IxAtmm.h**.

Function Documentation

ixAtmmInit (void)

Interface to initialize the IxAtmm software component. Can be called once only.

Must be called before any other IxAtmm API is called.

Parameters:

none

Returns:

◇ IX_SUCCESS : IxAtmm has been successfully initialized. Calls to other IxAtmm interfaces may now be performed.

◇ IX_FAIL : IxAtmm has already been initialized.

ixAtmmPortDisable (IxAtmLogicalPort port)

The client call this interface to disable transmit for an ATM port. At initialisation, all the ports are disabled.

Parameters:

port **IxAtmLogicalPort** [in] – Value identifies the port

Returns:

◇ IX_SUCCESS : Transmission over this port is stopped.

◇ IX_FAIL : The port parameter is not valid, or the port is already disabled

Note:

- When a port is disabled, Rx and Tx VC Connect requests will fail
- This function call does not stop RX traffic. It is supposed that this function is invoked when a serious problem is detected (e.g. physical layer broken). Then, the RX traffic is not passing.
- This function is blocking until the hw acknowledge that the transmission is stopped.
- This function uses system resources and should not be used inside an interrupt context.

See also:

ixAtmmPortEnable

ixAtmmPortEnable (IxAtmLogicalPort port)

The client call this interface to enable transmit for an ATM port. At initialisation, all the ports are disabled.

Parameters:

port **IxAtmLogicalPort** [in] – Value identifies the port

Returns:

◇ IX_SUCCESS : Transmission over this port is started.

◇ IX_FAIL : The port parameter is not valid, or the port is already enabled

Note:

- When a port is disabled, Rx and Tx VC Connect requests will fail

– This function uses system resources and should not be used inside an interrupt context.

See also:

ixAtmmPortDisable

```
ixAtmmPortInitialize ( IxAtmLogicalPort port,  
                      unsigned          txPortRate,  
                      unsigned          rxPortRate  
                      )
```

The interface is called following **ixAtmmUtopiaInit ()** and before calls to any other IxAtmm interface. It serves to activate the registered ATM port with IxAtmm.

The transmit and receive port rates are specified in bits per second. This translates to ATM cells per second according to the following formula: $\text{CellsPerSecond} = \text{portRate} / (53 * 8)$ The IXP400 device supports only 53 byte cells. The client shall make sure that the off-chip physical layer device has already been initialized.

IxAtmm will configure IxAtmdAcc and IxAtmSch to enable scheduling on the port.

This interface must be called once for each active port in the system. The first time the interface is invoked, it will configure the mechanism by which the handling of transmit, transmit-done and receive are driven with the IxAtmdAcc component.

This function is reentrant.

Note:

The minimum tx rate that will be accepted is 424 bit/s which equates to 1 cell (53 bytes) per second.

Parameters:

port **IxAtmLogicalPort** [in] – Identifies the port which is to be initialized.
txPortRate unsigned [in] – Value specifies the transmit port rate for this port in bits/second. This value is used by the ATM Scheduler component is evaluating VC access requests for the port.
rxPortRate unsigned [in] – Value specifies the receive port rate for this port in bits/second.

Returns:

- ◇ **IX_SUCCESS** : The specified ATM port has been successfully initialized. IxAtmm is ready to accept VC registrations on this port.
- ◇ **IX_ATMM_RET_ALREADY_INITIALIZED** : ixAtmmPortInitialize has already been called successfully on this port. The current call is rejected.
- ◇ **IX_ATMM_RET_INVALID_PORT** : The port value indicated in the input is not valid. The request is rejected.
- ◇ **IX_FAIL** : IxAtmm could not initialize the port because the inputs are not understood.

See also:

ixAtmmPortEnable, ixAtmmPortDisable

```
ixAtmmPortModify ( IxAtmLogicalPort port,  
                  unsigned txPortRate,  
                  unsigned rxPortRate  
                  )
```

A client may call this interface to change the existing port rate (expressed in bits/second) on an established ATM port.

Parameters:

port **IxAtmLogicalPort** [in] – Identifies the port which is to be initialized.
txPortRate unsigned [in] – Value specifies the transmit port rate for this port in bits/second. This value is used by the ATM Scheduler component is evaluating VC access requests for the port.
rxPortRate unsigned [in] – Value specifies the receive port rate for this port in bits/second.

Returns:

- ◇ IX_SUCCESS : The indicated ATM port rates have been successfully modified.
- ◇ IX_ATMM_RET_INVALID_PORT : The port value indicated in the input is not valid. The request is rejected.
- ◇ IX_FAIL : IxAtmm could not update the port because the inputs are not understood, or the interface was called before the port was initialized.

```
ixAtmmPortQuery ( IxAtmLogicalPort port,  
                 unsigned * txPortRate,  
                 unsigned * rxPortRate  
                 )
```

The client may call this interface to request details on currently registered transmit and receive rates for an ATM port.

Parameters:

port **IxAtmLogicalPort** [in] – Value identifies the port from which the rate details are requested.
**txPortRate* unsigned [out] – Pointer to a value which will be filled with the value of the transmit port rate specified in bits/second.
**rxPortRate* unsigned [out] – Pointer to a value which will be filled with the value of the receive port rate specified in bits/second.

Returns:

- ◇ IX_SUCCESS : The information requested on the specified port has been successfully supplied in the output.
- ◇ IX_ATMM_RET_INVALID_PORT : The port value indicated in the input is not valid. The request is rejected.

◇ IX_ATMM_RET_INVALID_PARAM_PTR : A pointer parameter was NULL.

◇ IX_FAIL : IxAtmm could not update the port because the inputs are not understood, or the interface was called before the port was initialized.

ixAtmmPortUninitialize (IxAtmLogicalPort port)

It serves to uninitialise the respective port passed as a parameter. Executes only if Utopia Initialization is done. Uninitializes the Data Path. Uninitializes the specified port.

Parameters:

port **IxAtmLogicalPort** [in] – Identifies the port which is to be uninitialized.

Returns:

◇ IX_SUCCESS : The specified ATM port has been successfully uninitialized.

◇ IX_FAIL : IxAtmm could not uninitialized the port because the inputs are not understood or because of some other internal error.

ixAtmmUninit (void)

Interface to uninitialized the IxAtmm software component. This function deallocates/destroys the allocated buffer/Mutex done during initialization Should be the last function to be called.

Parameters:

none

Returns:

◇ IX_SUCCESS : IxAtmm has been successfully uninitialized. Calls to other IxAtmm interfaces cannot be performed after this.

◇ IX_FAIL : IxAtmm has already been uninitialized.

ixAtmmUtopiaCfgShow (void)

Display utopia information(config registers and status registers).

Parameters:

none

Returns:

◇ IX_SUCCESS : Show function was successful

◇ IX_FAIL : Internal failure

```

ixAtmmUtopiaInit ( unsigned          numPorts,
                   IxAtmmPhyMode      phyMode,
                   IxAtmmPortCfg      portCfgs[],
                   IxAtmmUtopiaLoopbackMode loopbackMode
                   )

```

Interface to initialize the UTOPIA Level-2 ATM coprocessor for the specified number of physical ports. The function must be called before the ixAtmmPortInitialize interface can operate successfully.

Parameters:

numPorts unsigned [in] – Indicates the total number of logical ports that are active on the device. Up to 12 ports are supported.

phyMode **IxAtmmPhyMode** [in] – Put the Utopia coprocessor in SPHY or MPHY mode.

portCfgs[] **IxAtmmPortCfg** [in] – Pointer to an array of elements detailing the UTOPIA specific port characteristics. The length of the array must be equal to the number of ports activated. ATM ports are referred to by the relevant offset in this array in all subsequent IxAtmm interface calls.

loopbackMode **IxAtmmUtopiaLoopbackMode** [in] – Value must be one of **IX_ATMM_UTOPIA_LOOPBACK_ENABLED** or **IX_ATMM_UTOPIA_LOOPBACK_DISABLED** indicating whether loopback should be enabled on the device. Loopback can only be supported on a single PHY, therefore the numPorts parameter must be 1 if loopback is enabled.

Returns:

- ◇ **IX_SUCCESS** : Indicates that the UTOPIA device has been successfully initialized for the supplied ports.
- ◇ **IX_ATMM_RET_ALREADY_INITIALIZED** : The UTOPIA device has already been initialized.
- ◇ **IX_FAIL** : The supplied parameters are invalid or have been rejected by the UTOPIA-NPE device.

Warning:

This interface may only be called once. Port identifiers are assumed to range from 0 to (numPorts – 1) in all instances. In all subsequent calls to interfaces supplied by IxAtmm, the specified port value is expected to represent the offset in the portCfgs array specified in this interface. i.e. The first port in this array will subsequently be represented as port 0, the second port as port 1, and so on.

```

ixAtmmUtopiaStatusShow ( void )

```

Display utopia status counters.

Parameters:

none

Returns:

- ◇ **IX_SUCCESS** : Show function was successful

◇ IX_FAIL : Internal failure

ixAtmmUtopiaUninit (void)

Interface to uninitialized the UTOPIA Level-2 ATM coprocessor.

Parameters:

none

Returns:

◇ IX_SUCCESS : Indicates that the UTOPIA device has been successfully uninitialized .

◇ IX_FAIL :Uninitialise of the UTOPIA-NPE device did not work.

ixAtmmVcChangeCallbackDeregister (IxAtmmVcChangeCallback callback)

This interface is invoked to deregister a previously supplied callback function.

Parameters:

callback **IxAtmmVcChangeCallback** [in] – Callback which complies with the **IxAtmmVcChangeCallback** definition. This function will removed from the table of callbacks.

Returns:

◇ IX_SUCCESS : The specified callback has been deregistered successfully from IxAtmm.

◇ IX_FAIL : Either the supplied callback is invalid, or is not currently registered with IxAtmm.

ixAtmmVcChangeCallbackRegister (IxAtmmVcChangeCallback callback)

This interface is invoked to supply a function to IxAtmm which will be called to notify the client if a new VC is registered with IxAtmm or an existing VC is removed.

The callback, when invoked, will run within the context of the call to **ixAtmmVcRegister** or **ixAtmmVcDeregister** which caused the change of state.

A maximum of 32 calbacks may be registered in with IxAtmm.

Parameters:

callback **IxAtmmVcChangeCallback** [in] – Callback which complies with the **IxAtmmVcChangeCallback** definition. This function will be invoked by IxAtmm with the appropriate parameters for the relevant VC when any VC has been registered or deregistered with IxAtmm.

Returns:

- ◇ IX_SUCCESS : The specified callback has been registered successfully with IxAtmm and will be invoked when appropriate.
- ◇ IX_FAIL : Either the supplied callback is invalid, or IxAtmm has already registered 32 and cannot accommodate any further registrations of this type. The request is rejected.

Warning:

The client must not call either the **ixAtmmVcRegister** or **ixAtmmVcDeregister** interfaces from within the supplied callback function.

```
ixAtmmVcDeregister ( IxAtmLogicalPort    port,
                    IxAtmSchedulerVcId vclId
                    )
```

Function called by a client to deregister a VC from the system.

With the removal of each new VC from a port, a series of registered callback functions are invoked by the IxAtmm component to notify possible external components of the change. The callback functions are registered using the **ixAtmmVcChangeCallbackRegister**.

The IxAtmSch component is notified of the removal of transmit VCs.

Parameters:

port **IxAtmLogicalPort** [in] – Identifies port on which the VC to be removed is currently registered.

vclId **IxAtmSchedulerVcId** [in] – VC identifier value of the VC to be deregistered. This value was supplied to the client when the VC was originally registered. This value can also be queried from the IxAtmm component through the **ixAtmmVcQuery** interface.

Returns:

- ◇ IX_SUCCESS : The specified VC has been successfully removed from this port.
- ◇ IX_ATMM_RET_INVALID_PORT : The port value indicated in the input is not valid or has not been initialized. The request is rejected.
- ◇ IX_FAIL : There is no registered VC associated with the supplied identifier registered on this port.

```
ixAtmmVcIdQuery ( IxAtmLogicalPort    port,
                  IxAtmSchedulerVcId vclId,
                  IxAtmmVc *          vcDesc
                  )
```

This interface supplies information about an active VC on a particular port when supplied with a vclId for that VC.

Parameters:

port

- IxAtmLogicalPort** [in] – Identifies port on which the VC to be queried is currently registered.
- vcId* **IxAtmSchedulerVcId** [in] – Value returned by **ixAtmmVcRegister** which uniquely identifies the requested VC on this port.
- *vcDesc* **IxAtmmVc** [out] – Pointer to an **IxAtmmVc** structure which will be filled with the specific details of the requested VC, if it exists on this port.

Returns:

- ◇ **IX_SUCCESS** : The specified VC has been found on this port and the requested details have been returned.
- ◇ **IX_ATMM_RET_INVALID_PORT** : The port value indicated in the input is not valid or has not been initialized. The request is rejected.
- ◇ **IX_ATMM_RET_NO_SUCH_VC** : No VC exists on the specified port which matches the supplied identifier. No data is returned.
- ◇ **IX_ATMM_RET_INVALID_PARAM_PTR** : A pointer parameter was NULL.

```

ixAtmmVcQuery ( IxAtmLogicalPort    port,
                unsigned              vpi,
                unsigned              vci,
                IxAtmmVcDirection    direction,
                IxAtmSchedulerVcId * vcId,
                IxAtmmVc *           vcDesc
            )

```

This interface supplies information about an active VC on a particular port when supplied with the VPI, VCI and direction of that VC.

Parameters:

- port* **IxAtmLogicalPort** [in] – Identifies port on which the VC to be queried is currently registered.
- vpi* unsigned [in] – ATM VPI value of the requested VC.
- vci* unsigned [in] – ATM VCI value of the requested VC.
- direction* **IxAtmmVcDirection** [in] – One of **IX_ATMM_VC_DIRECTION_TX** or **IX_ATMM_VC_DIRECTION_RX** indicating the direction (Tx or Rx) of the requested VC.
- *vcId* **IxAtmSchedulerVcId** [out] – Pointer to an integer value which will be filled with the VC identifier value for the requested VC (as returned by **ixAtmmVcRegister**), if it exists on this port.
- *vcDesc* **IxAtmmVc** [out] – Pointer to an **IxAtmmVc** structure which will be filled with the specific details of the requested VC, if it exists on this port.

Returns:

- ◇ **IX_SUCCESS** : The specified VC has been found on this port and the requested details have been returned.

- ◇ IX_ATMM_RET_INVALID_PORT : The port value indicated in the input is not valid or has not been initialized. The request is rejected.
- ◇ IX_ATMM_RET_NO_SUCH_VC : No VC exists on the specified port which matches the search criteria (VPI, VCI, direction) given. No data is returned.
- ◇ IX_ATMM_RET_INVALID_PARAM_PTR : A pointer parameter was NULL.

```

ixAtmmVcRegister ( IxAtmLogicalPort      port,
                  IxAtmmVc *          vcToAdd,
                  IxAtmSchedulerVcId * vcId
                  )

```

This interface is used to register an ATM Virtual Connection on the specified ATM port.

Each call to this interface registers a unidirectional virtual connection with the parameters specified. If a bi-directional VC is needed, the function should be called twice (once for each direction, Tx & Rx) where the VPI and VCI and port parameters in each call are identical.

With the addition of each new VC to a port, a series of callback functions are invoked by the IxAtmm component to notify possible external components of the change. The callback functions are registered using the **ixAtmmVcChangeCallbackRegister** interface.

The IxAtmSch component is notified of the registration of transmit VCs.

Parameters:

- port* **IxAtmLogicalPort** [in] – Identifies port on which the specified VC is to be registered.
- *vcToAdd* **IxAtmmVc** [in] – Pointer to an **IxAtmmVc** structure containing a description of the VC to be registered. The client shall fill the vpi, vci and direction and relevant trafficDesc members of this structure before calling this function.
- *vcId* **IxAtmSchedulerVcId** [out] – Pointer to an integer value which is filled with the per-port unique identifier value for this VC. This identifier will be required when a request is made to deregister or change this VC. VC identifiers for transmit VCs will have a value between 0–43, i.e. 32 data Tx VCs + 12 OAM Tx Port VCs. Receive VCs will have a value between 44–66, i.e. 32 data Rx VCs + 1 OAM Rx VC.

Returns:

- ◇ IX_SUCCESS : The VC has been successfully registered on this port. The VC is ready for a client to configure IxAtmdAcc for receive and transmit operations on the VC.
- ◇ IX_ATMM_RET_INVALID_PORT : The port value indicated in the input is not valid or has not been initialized. The request is rejected.
- ◇ IX_ATMM_RET_INVALID_VC_DESCRIPTOR : The descriptor pointed to by vcToAdd is invalid. The registration request is rejected.
- ◇ IX_ATMM_RET_VC_CONFLICT : The VC requested conflicts with reserved VPI and/or VCI values or with another VC already activated on this port.

◇ IX_ATMM_RET_PORT_CAPACITY_IS_FULL : The VC cannot be registered in the port because the port capacity is insufficient to support the requested ATM traffic contract. The registration request is rejected.

◇ IX_ATMM_RET_INVALID_PARAM_PTR : A pointer parameter was NULL.

Warning:

IxAtmm has no capability of signaling or negotiating a virtual connection. Negotiation of the admission of the VC to the network is beyond the scope of this function. This is assumed to be performed by the calling client, if appropriate, before or after this function is called.

Intel (R) IXP400 Software ATM Transmit Scheduler (IxAtmSch) API

IXP400 ATM scheduler component Public API.

Defines

#define **IX_ATMSCH_RET_NOT_ADMITTED**

Indicates that CAC function has rejected VC registration due to insufficient line capacity.

#define **IX_ATMSCH_RET_QUEUE_FULL**

Indicates that the VC queue is full, no more demand can be queued at this time.

#define **IX_ATMSCH_RET_QUEUE_EMPTY**

Indicates that all VC queues on this port are empty and therefore there are no cells to be scheduled at this time.

Functions

PUBLIC

IX_STATUS **ixAtmSchInit** (void)

This function is used to initialize the ixAtmSch component. It should be called before any other IxAtmSch API function.

PUBLIC

IX_STATUS **ixAtmSchUninit** (void)

This function is used to uninitialize the ixAtmSch component.

PUBLIC **ixAtmSchPortModelInitialize** (**IxAtmLogicalPort** port, UINT64 portRate, unsigned int
IX_STATUS minCellsToSchedule)

This function shall be called first to initialize an ATM port before any other ixAtmSch API calls may be made for that port.

PUBLIC

IX_STATUS **ixAtmSchPortModelUninitialize** (**IxAtmLogicalPort** port)

This function shall be called to uninitialize an ATM port.

PUBLIC

IX_STATUS **ixAtmSchPortRateModify** (**IxAtmLogicalPort** port, UINT64 portRate)

This function is called to modify the portRate on a previously initialized port, typically in the event that the line condition of the port changes.

PUBLIC **ixAtmSchVcModelSetup** (**IxAtmLogicalPort** port, **IxAtmTrafficDescriptor** *trafficDesc,
IX_STATUS **IxAtmSchedulerVcId** *vcId)

*A client calls this interface to set up an upstream (transmitting) virtual connection model (VC) on the specified ATM port. This function also provides the virtual *connection*

admission control (CAC) service to the client.

PUBLIC
IX_STATUS IxAtmSchVcConnIdSet (**IxAtmLogicalPort** port, **IxAtmSchedulerVcId** vcId, **IxAtmConnId** vcUserConnId)

A client calls this interface to set the vcUserConnId for a VC on the specified ATM port. This vcUserConnId will default to IX_ATM_IDLE_CELLS_CONNID if this function is not called for a VC. Hence if the client does not call this function for a VC then only idle cells will be scheduled for this VC.

PUBLIC
IX_STATUS IxAtmSchVcModelRemove (**IxAtmLogicalPort** port, **IxAtmSchedulerVcId** vcId)

Interface called by the client to remove a previously established VC on a particular port.

PUBLIC
IX_STATUS IxAtmSchVcQueueUpdate (**IxAtmLogicalPort** port, **IxAtmSchedulerVcId** vcId, **UINT64** numberOfCells)

The client calls this function to notify IxAtmSch that the user of a VC has submitted cells for transmission.

PUBLIC
IX_STATUS IxAtmSchVcQueueClear (**IxAtmLogicalPort** port, **IxAtmSchedulerVcId** vcId)

The client calls this function to remove all currently queued cells from a registered VC. The pending cell count for the specified VC is reset to zero.

PUBLIC
IX_STATUS IxAtmSchTableUpdate (**IxAtmLogicalPort** port, **UINT64** maxCells, **IxAtmScheduleTable** **rettable)

The client calls this function to request an update of the schedule table for a particular ATM port.

PUBLIC void IxAtmSchShow (void)

Utility function which will print statistics on the current and accumulated state of VCs and traffic in the ATM scheduler component. Output is sent to the default output device.

PUBLIC void IxAtmSchStatsClear (void)

Utility function which will reset all counter statistics in the ATM scheduler to zero.

Detailed Description

IXP400 ATM scheduler component Public API.

Define Documentation

```
#define IX_ATMSCH_RET_NOT_ADMITTED
```

Indicates that CAC function has rejected VC registration due to insufficient line capacity.

Definition at line 52 of file **IxAtmSch.h**.

```
#define IX_ATMSCH_RET_QUEUE_EMPTY
```

Indicates that all VC queues on this port are empty and therefore there are no cells to be scheduled at this time.

Definition at line **70** of file **IxAtmSch.h**.

```
#define IX_ATMSCH_RET_QUEUE_FULL
```

Indicates that the VC queue is full, no more demand can be queued at this time.

Definition at line **61** of file **IxAtmSch.h**.

Function Documentation

```
ixAtmSchInit ( void )
```

This function is used to initialize the ixAtmSch component. It should be called before any other IxAtmSch API function.

Parameters:

None

Returns:

- ◇ **IX_SUCCESS** : indicates that
 1. The ATM scheduler component has been successfully initialized.
 2. The scheduler is ready to accept Port modelling requests.
- ◇ **IX_FAIL** : Some internal error has prevented the scheduler component from initialising.

```
ixAtmSchPortModelInitialize ( IxAtmLogicalPort port,  
                               UINT64 portRate,  
                               unsigned int minCellsToSchedule  
                               )
```

This function shall be called first to initialize an ATM port before any other ixAtmSch API calls may be made for that port.

Parameters:

<i>port</i>	IxAtmLogicalPort [in] – The specific port to initialize. Valid values range from 0 to IX_UTOPIA_MAX_PORTS – 1, representing a maximum of IX_UTOPIA_MAX_PORTS possible ports.
<i>portRate</i>	UINT64 [in] – Value indicating the upstream capacity of the indicated port. The value should be supplied in units of ATM (53 bytes) cells per second. A port rate of 800Kbits/s is the equivalent of 1886 cells per second
<i>minCellsToSchedule</i>	unsigned int [in] – This parameter specifies the minimum number of cells

which the scheduler will put in a schedule table for this port. This value sets the worst case CDVT for VCs on this port i.e. $CDVT = 1 * \text{minCellsToSchedule} / \text{portRate}$.

Returns:

- ◇ **IX_SUCCESS** : indicates that
 1. The ATM scheduler has been successfully initialized.
 2. The requested port model has been established.
 3. The scheduler is ready to accept VC modelling requests on the ATM port.
- ◇ **IX_FAIL** : indicates the requested port could not be initialized.

```
ixAtmSchPortModelUninitialize ( IxAtmLogicalPort port )
```

This function shall be called to uninitialize an ATM port.

Parameters:

port **IxAtmLogicalPort** [in] – The specific port to uninitialize. Valid values range from 0 to **IX_UTOPIA_MAX_PORTS** – 1, representing a maximum of **IX_UTOPIA_MAX_PORTS** possible ports.

Returns:

- ◇ **IX_SUCCESS** : indicates that
 1. The ATM scheduler has been successfully uninitialized.
- ◇ **IX_FAIL** : indicates the requested port could not be uninitialized.

```
ixAtmSchPortRateModify ( IxAtmLogicalPort port,  
                          UINT64 portRate  
                          )
```

This function is called to modify the portRate on a previously initialized port, typically in the event that the line condition of the port changes.

Parameters:

port **IxAtmLogicalPort** [in] – Specifies the ATM port which is to be modified.
portRate **UINT64** [in] – Value indicating the new upstream capacity for this port in cells/second. A port rate of 800Kbits/s is the equivalent of 1886 cells per second

Returns:

- ◇ **IX_SUCCESS** : The port rate has been successfully modified.
- ◇ **IX_FAIL** : The port rate could not be modified, either because the input data was invalid, or the new port rate is insufficient to support established ATM VC contracts on this port.

Warning:

The IxAtmSch component will validate the supplied port rate is sufficient to support all established VC contracts on the port. If the new port rate is insufficient to support all established contracts then the request to modify the port rate will be rejected. In this event, the user is expected to remove established contracts using the ixAtmSchVcModelRemove interface and then retry this interface.

See also:

ixAtmSchVcModelRemove()

ixAtmSchShow (void)

Utility function which will print statistics on the current and accumulated state of VCs and traffic in the ATM scheduler component. Output is sent to the default output device.

Parameters:

none

Returns:

none

ixAtmSchStatsClear (void)

Utility function which will reset all counter statistics in the ATM scheduler to zero.

Parameters:

none

Returns:

none

```
ixAtmSchTableUpdate ( IxAtmLogicalPort      port,  
                      UINT64                maxCells,  
                      IxAtmScheduleTable ** rettable  
                      )
```

The client calls this function to request an update of the schedule table for a particular ATM port.

This is called when the client decides it needs a new sequence of cells to send (probably because the transmit queue is near to empty for this ATM port). The scheduler will use its stored information on the cells submitted for transmit (i.e. data supplied via **ixAtmSchVcQueueUpdate** function) with the traffic descriptor information of all established VCs on the ATM port to decide the sequence of cells to be sent and fill the schedule table for a period of time into the future.

IxAtmSch will guarantee a minimum of minCellsToSchedule if there is at least one cell ready to send. If there are no cells then IX_ATMSCH_RET_QUEUE_EMPTY is returned.

This implementation of ixAtmSchTableUpdate uses no operating system or external facilities, either directly or indirectly. This allows clients to call this function from within an FIQ interrupt handler.

Parameters:

port **IxAtmLogicalPort** [in] – Specifies the ATM port for which requested schedule table is to be generated.

maxCells

UINT64 [in] – Specifies the maximum number of cells that must be scheduled in the supplied table during any call to the interface.

****table IxAtmScheduleTable** [out] – A pointer to an area of storage is returned which contains the generated schedule table. The client should not modify the contents of this table.

Returns:

- ◇ **IX_SUCCESS** : The schedule table has been published. Currently there is at least one VC queue that is nonempty.
- ◇ **IX_ATMSCH_RET_QUEUE_EMPTY** : Currently all VC queues on this port are empty. The schedule table returned is set to NULL. The client is not expected to invoke this function again until more cells have been submitted on this port through the **ixAtmSchVcQueueUpdate** function.
- ◇ **IX_FAIL** : The input are invalid. No action is taken.

Warning:

IxAtmSch assumes that the calling software ensures that calls to ixAtmSchVcQueueUpdate, ixAtmSchVcQueueClear and ixAtmSchTableUpdate are both self and mutually exclusive for the same port.

Subsequent calls to this function for the same port will overwrite the contents of previously supplied schedule tables. The client must be completely finished with the previously supplied schedule table before calling this function again for the same port.

See also:

ixAtmSchVcQueueUpdate(), ixAtmSchVcQueueClear(), ixAtmSchTableUpdate().

```
ixAtmSchUninit ( void )
```

This function is used to uninitialize the ixAtmSch component.

Parameters:

None

Returns:

- ◇ **IX_SUCCESS** : indicates that
 1. The ATM scheduler component has been successfully uninitialized.
- ◇ **IX_FAIL** : Some internal error has prevented the scheduler component from uninitialising.

```
ixAtmSchVcConnIdSet ( IxAtmLogicalPort    port,  
                     IxAtmSchedulerVcId  vcId,  
                     IxAtmConnId         vcUserConnId  
                     )
```

A client calls this interface to set the vcUserConnId for a VC on the specified ATM port. This vcUserConnId will default to IX_ATM_IDLE_CELLS_CONNID if this function is not called for a VC. Hence if the client does not call this function for a VC then only idle cells will be scheduled for this VC.

Parameters:

- port* **IxAtmLogicalPort** [in] – Specifies the ATM port on which the upstream VC is has been established.
- vcId* **IxAtmSchedulerVcId** [in] – This is the unique identifier for this virtual connection. A valid identification is a non-negative number and is all ports.
- vcUserConnId* **IxAtmConnId** [in] – The connId is used to refer to a VC in schedule table entries. It is treated as the Id by which the scheduler client knows the VC. It is used in any communications from the Scheduler to the scheduler user e.g. schedule table entries.

Returns:

- ◇ **IX_SUCCESS** : The id has successfully been set.
- ◇ **IX_FAIL** :Input data are invalid. connId id is not established.

```
ixAtmSchVcModelRemove ( IxAtmLogicalPort    port,  
                        IxAtmSchedulerVcId vcId  
                        )
```

Interface called by the client to remove a previously established VC on a particular port.

Parameters:

- port* **IxAtmLogicalPort** [in] – Specifies the ATM port on which the VC to be removed is established.
- vcId* **IxAtmSchedulerVcId** [in] – Identifies the VC to be removed. This is the value returned by the **ixAtmSchVcModelSetup** call which established the relevant VC.

Returns:

- ◇ **IX_SUCCESS** : The VC has been successfully removed from this port. It is no longer modelled on this port.
- ◇ **IX_FAIL** :Input data are invalid. The VC is still being modeled by the traffic shaper.

See also:

ixAtmSchVcModelSetup()

```
ixAtmSchVcModelSetup ( IxAtmLogicalPort    port,  
                      IxAtmTrafficDescriptor * trafficDesc,  
                      IxAtmSchedulerVcId *   vcId  
                      )
```

A client calls this interface to set up an upstream (transmitting) virtual connection model (VC) on the specified ATM port. This function also provides the virtual * connection admission control (CAC) service to the client.

Parameters:

- port* **IxAtmLogicalPort** [in] – Specifies the ATM port on which the upstream VC is to be established.
- *trafficDesc* **IxAtmTrafficDescriptor** [in] – Pointer to a structure describing the requested traffic contract of the VC to be established. This structure contains the typical ATM traffic

descriptor values (e.g. PCR, SCR, MBS, CDVT, etc.) defined by the ATM standard.

vcId* **IxAtmSchedulerVcId [out] – This value will be filled with the port–unique identifier for this virtual connection. A valid identification is a non–negative number.

Returns:

- ◇ **IX_SUCCESS** : The VC has been successfully established on this port. The client may begin to submit demand on this VC.
- ◇ **IX_ATMSCH_RET_NOT_ADMITTED** : The VC cannot be established on this port because there is insufficient upstream capacity available to support the requested traffic contract descriptor
- ◇ **IX_FAIL** : Input data are invalid. VC has not been established.

```

IxAtmSchVcQueueClear ( IxAtmLogicalPort    port,
                       IxAtmSchedulerVcId vcId
                       )

```

The client calls this function to remove all currently queued cells from a registered VC. The pending cell count for the specified VC is reset to zero.

This interface is structurally compatible with the IxAtmdAccSchQueueClear callback type definition required for IXP400 ATM scheduler interoperability.

Parameters:

- port* **IxAtmLogicalPort** [in] – Specifies the ATM port on which the VC to be cleared is established.
- vcId* **IxAtmSchedulerVcId** [in] – Identifies the VC to be cleared. This is the value returned by the **ixAtmSchVcModelSetup** call which established the relevant VC.

Returns:

- ◇ **IX_SUCCESS** : The VC queue has been successfully cleared.
- ◇ **IX_FAIL** : The input are invalid. No VC queue is modified.

Warning:

IxAtmSch assumes that the calling software ensures that calls to ixAtmSchVcQueueUpdate, ixAtmSchVcQueueClear and ixAtmSchTableUpdate are both self and mutually exclusive for the same port.

See also:

ixAtmSchVcQueueUpdate(), ixAtmSchVcQueueClear(), ixAtmSchTableUpdate().

```

IxAtmSchVcQueueUpdate ( IxAtmLogicalPort    port,
                       IxAtmSchedulerVcId vcId,
                       UINT64                numberOfCells
                       )

```

The client calls this function to notify IxAtmSch that the user of a VC has submitted cells for transmission.

This information is stored, aggregated from a number of calls to `ixAtmSchVcQueueUpdate` and eventually used in the call to `ixAtmSchTableUpdate`.

Normally `IxAtmSch` will update the VC queue by adding the number of cells to the current queue length. However, if `IxAtmSch` determines that the user has over-submitted for the VC and exceeded its transmission quota the queue request can be rejected. The user should resubmit the request later when the queue has been depleted.

This implementation of `ixAtmSchVcQueueUpdate` uses no operating system or external facilities, either directly or indirectly. This allows clients to call this function from within an interrupt handler.

This interface is structurally compatible with the `IxAtmdAccSchQueueUpdate` callback type definition required for IXP400 ATM scheduler interoperability.

Parameters:

<i>port</i>	IxAtmLogicalPort [in] – Specifies the ATM port on which the VC to be updated is established.
<i>vcId</i>	IxAtmSchedulerVcId [in] – Identifies the VC to be updated. This is the value returned by the ixAtmSchVcModelSetup call which established the relevant VC.
<i>numberOfCells</i>	UINT64 [in] – Indicates how many ATM cells should be added to the queue for this VC.

Returns:

- ◇ **IX_SUCCESS** : The VC queue has been successfully updated.
- ◇ **IX_ATMSCH_RET_QUEUE_FULL** : The VC queue has reached a preset limit. This indicates the client has over-submitted and exceeded its transmission quota. The request is rejected. The VC queue is not updated. The VC user is advised to resubmit the request later.
- ◇ **IX_FAIL** : The input are invalid. No VC queue is updated.

Warning:

`IxAtmSch` assumes that the calling software ensures that calls to `ixAtmSchVcQueueUpdate`, `ixAtmSchVcQueueClear` and `ixAtmSchTableUpdate` are both self and mutually exclusive for the same port.

See also:

`ixAtmSchVcQueueUpdate()`, `ixAtmSchVcQueueClear()`, `ixAtmSchTableUpdate()`.

Intel (R) IXP400 Software ATM Types (IxAtmTypes)

The common set of types used in many Atm components.

Data Structures

struct **IxAtmScheduleTable**

This structure defines a schedule table which gives details on which data (from which VCs) should be transmitted for a forthcoming period of time for a particular port and the order in which that data should be transmitted.

struct **IxAtmScheduleTableEntry**

ATM Schedule Table entry.

struct **IxAtmTrafficDescriptor**

Structure describing an ATM traffic contract for a Virtual Connection (VC).

Defines

#define **IX_ATM_CELL_PAYLOAD_SIZE**

Size of a ATM cell payload.

#define **IX_ATM_CELL_SIZE**

Size of a ATM cell, including header.

#define **IX_ATM_CELL_SIZE_NO_HEC**

Size of a ATM cell, excluding HEC byte.

#define **IX_ATM_OAM_CELL_SIZE_NO_HEC**

Size of a OAM cell, excluding HEC byte.

#define **IX_ATM_AAL0_48_CELL_PAYLOAD_SIZE**

Size of a AAL0 48 Cell payload.

#define **IX_ATM_AAL5_CELL_PAYLOAD_SIZE**

Size of a AAL5 Cell payload.

#define **IX_ATM_AAL0_52_CELL_SIZE_NO_HEC**

Size of a AAL0 52 Cell, excluding HEC byte.

#define **IX_ATM_MAX_VPI**

Maximum value of an ATM VPI.

#define **IX_ATM_MAX_VCI**

Maximum value of an ATM VCI.

#define **IX_ATM_MAX_NUM_AAL_VCS**

Maximum number of active AAL5/AAL0 VCs in the system.

#define IX_ATM_MAX_NUM_VC

Maximum number of active AAL5/AAL0 VCs in the system The use of this macro is depreciated, it is retained for backward compatiblity. For current software release and beyond the define IX_ATM_MAX_NUM_AAL_VC should be used.

#define IX_ATM_MAX_NUM_OAM_TX_VCS

Maximum number of active OAM Tx VCs in the system, 1 OAM VC per port.

#define IX_ATM_MAX_NUM_OAM_RX_VCS

Maximum number of active OAM Rx VCs in the system, 1 OAM VC shared accross all ports.

#define IX_ATM_MAX_NUM_AAL_OAM_TX_VCS

Maximum number of active AAL5/AAL0/OAM Tx VCs in the system.

#define IX_ATM_MAX_NUM_AAL_OAM_RX_VCS

Maximum number of active AAL5/AAL0/OAM Rx VCs in the system.

#define IX_ATM_IDLE_CELLS_CONNID

VC Id used to indicate idle cells in the returned schedule table.

#define IX_ATM_CELL_HEADER_VCI_GET(cellHeader)

get the VCI field from a cell header

#define IX_ATM_CELL_HEADER_VPI_GET(cellHeader)

get the VPI field from a cell header

#define IX_ATM_CELL_HEADER_PTI_GET(cellHeader)

get the PTI field from a cell header

Typedefs

typedef

unsigned

int **IxAtmCellHeader**

ATM Cell Header, does not contain 4 byte HEC, added by NPE-A.

typedef

unsigned

int **IxAtmConnId**

ATM VC data connection identifier.

typedef int **IxAtmSchedulerVcId**

ATM VC scheduling connection identifier.

typedef

unsigned

int **IxAtmNpeRxVcId**

ATM Rx VC identifier used by the ATM Npe.

Enumerations

```
enum IxAtmLogicalPort {  
    IX_UTOPIA_PORT_0,  
    IX_UTOPIA_MAX_PORTS  
}
```

Logical Port Definitions :.

```
enum IxAtmServiceCategory {  
    IX_ATM_CBR,  
    IX_ATM_RTVBR,  
    IX_ATM_VBR,  
    IX_ATM_UBR,  
    IX_ATM_ABR  
}
```

Enumerated type representing available ATM service categories. For more informatoin on these categories, see "Traffic Management Specification" v4.1, published by the ATM Forum – <http://www.atmforum.com>.

```
enum IxAtmRxQueueId {  
    IX_ATM_RX_A,  
    IX_ATM_RX_B,  
    IX_ATM_MAX_RX_STREAMS  
}
```

Rx Queue Type for RX traffic.

Detailed Description

The common set of types used in many Atm components.

Define Documentation

```
#define IX_ATM_AAL0_48_CELL_PAYLOAD_SIZE
```

Size of a AAL0 48 Cell payload.

Definition at line **92** of file **IxAtmTypes.h**.

```
#define IX_ATM_AAL0_52_CELL_SIZE_NO_HEC
```

Size of a AAL0 52 Cell, excluding HEC byte.

Definition at line **104** of file **IxAtmTypes.h**.

```
#define IX_ATM_AAL5_CELL_PAYLOAD_SIZE
```

Size of a AAL5 Cell payload.

Definition at line **98** of file **IxAtmTypes.h**.

```
#define IX_ATM_CELL_HEADER_PTI_GET ( cellHeader )
```

get the PTI field from a cell header

Definition at line **187** of file **IxAtmTypes.h**.

```
#define IX_ATM_CELL_HEADER_VCI_GET ( cellHeader )
```

get the VCI field from a cell header

Definition at line **173** of file **IxAtmTypes.h**.

```
#define IX_ATM_CELL_HEADER_VPI_GET ( cellHeader )
```

get the VPI field from a cell header

Definition at line **180** of file **IxAtmTypes.h**.

```
#define IX_ATM_CELL_PAYLOAD_SIZE
```

Size of a ATM cell payload.

Definition at line **68** of file **IxAtmTypes.h**.

```
#define IX_ATM_CELL_SIZE
```

Size of a ATM cell, including header.

Definition at line **74** of file **IxAtmTypes.h**.

```
#define IX_ATM_CELL_SIZE_NO_HEC
```

Size of a ATM cell, excluding HEC byte.

Definition at line **80** of file **IxAtmTypes.h**.

```
#define IX_ATM_IDLE_CELLS_CONNID
```

VC Id used to indicate idle cells in the returned schedule table.

Definition at line **166** of file **IxAtmTypes.h**.

```
#define IX_ATM_MAX_NUM_AAL_OAM_RX_VCS
```

Maximum number of active AAL5/AAL0/OAM Rx VCs in the system.

Definition at line **160** of file **IxAtmTypes.h**.

```
#define IX_ATM_MAX_NUM_AAL_OAM_TX_VCS
```

Maximum number of active AAL5/AAL0/OAM Tx VCs in the system.

Definition at line **154** of file **IxAtmTypes.h**.

```
#define IX_ATM_MAX_NUM_AAL_VCS
```

Maximum number of active AAL5/AAL0 VCs in the system.

Definition at line **123** of file **IxAtmTypes.h**.

```
#define IX_ATM_MAX_NUM_OAM_RX_VCS
```

Maximum number of active OAM Rx VCs in the system, 1 OAM VC shared accross all ports.

Definition at line **148** of file **IxAtmTypes.h**.

```
#define IX_ATM_MAX_NUM_OAM_TX_VCS
```

Maximum number of active OAM Tx VCs in the system, 1 OAM VC per port.

Definition at line **141** of file **IxAtmTypes.h**.

```
#define IX_ATM_MAX_NUM_VC
```

Maximum number of active AAL5/AAL0 VCs in the system The use of this macro is depreciated, it is

retained for backward compatibility. For current software release and beyond the define `IX_ATM_MAX_NUM_AAL_VC` should be used.

Definition at line **132** of file **`IxAtmTypes.h`**.

```
#define IX_ATM_MAX_VCI
```

Maximum value of an ATM VCI.

Definition at line **117** of file **`IxAtmTypes.h`**.

```
#define IX_ATM_MAX_VPI
```

Maximum value of an ATM VPI.

Definition at line **111** of file **`IxAtmTypes.h`**.

```
#define IX_ATM_OAM_CELL_SIZE_NO_HEC
```

Size of a OAM cell, excluding HEC byte.

Definition at line **86** of file **`IxAtmTypes.h`**.

Typedef Documentation

```
IxAtmCellHeader
```

ATM Cell Header, does not contain 4 byte HEC, added by NPE–A.

Definition at line **195** of file **`IxAtmTypes.h`**.

```
IxAtmConnId
```

ATM VC data connection identifier.

This is generated by `IxAtmdAcc` when a successful connection is made on a VC. This is the ID by which `IxAtmdAcc` knows an active VC and should be used in `IxAtmdAcc` API calls to reference a specific VC.

Definition at line **283** of file **`IxAtmTypes.h`**.

```
IxAtmNpeRxVcId
```

ATM Rx VC identifier used by the ATM Npe.

This Id is generated by IxAtmdAcc when a successful data connection is made on a rx VC.

Definition at line **307** of file **IxAtmTypes.h**.

IxAtmSchedulerVcId

ATM VC scheduling connection identifier.

This id is generated and used by ATM Tx controller, generally the traffic shaper (e.g. IxAtmSch). The IxAtmdAcc component will request one of these Ids whenever a data connection on a Tx VC is requested. This ID will be used in callbacks to the ATM Transmission Ctrl s/w (e.g. IxAtmm) to reference a particular VC.

Definition at line **297** of file **IxAtmTypes.h**.

Enumeration Type Documentation

enum IxAtmLogicalPort

Logical Port Definitions :.

Only 1 port is available in SPHY configuration 4 ports are enabled in ATMMPORT configuration 12 ports are enabled in MPHY configuration

Enumeration values:

IX_UTOPIA_PORT_0 Port 0.

IX_UTOPIA_MAX_PORTS Not a port – just a definition for the maximum possible ports.

Definition at line **37** of file **IxAtmTypes.h**.

enum IxAtmRxQueueId

Rx Queue Type for RX traffic.

IxAtmRxQueueId defines the queues involved for receiving data.

There are two queues to facilitate prioritisation handling and processing the 2 queues with different algorithms and constraints

e.g. : one queue can carry voice (or time–critical traffic), the other queue can carry non–voice traffic

Enumeration values:

IX_ATM_RX_A RX queue A.

IX_ATM_RX_B RX queue B.

IX_ATM_MAX_RX_STREAMS Maximum number of RX streams.

Definition at line **232** of file **IxAtmTypes.h**.

```
enum IxAtmServiceCategory
```

Enumerated type representing available ATM service categories. For more informatoin on these categories, see "Traffic Management Specification" v4.1, published by the ATM Forum – <http://www.atmforum.com>.

Enumeration values:

IX_ATM_CBR Constant Bit Rate.

IX_ATM_RTVBR Real Time Variable Bit Rate.

IX_ATM_VBR Variable Bit Rate.

IX_ATM_UBR Unspecified Bit Rate.

IX_ATM_ABR Available Bit Rate (not supported).

Definition at line **206** of file **IxAtmTypes.h**.

Intel (R) IXP400 Software DMA Types (IxDmaTypes)

The common set of types used in the DMA component.

Enumerations

```
enum IxDmaReturnStatus {  
    IX_DMA_SUCCESS,  
    IX_DMA_FAIL,  
    IX_DMA_INVALID_TRANSFER_WIDTH,  
    IX_DMA_INVALID_TRANSFER_LENGTH,  
    IX_DMA_INVALID_TRANSFER_MODE,  
    IX_DMA_INVALID_ADDRESS_MODE,  
    IX_DMA_REQUEST_FIFO_FULL  
}
```

Dma return status definitions.

```
enum IxDmaTransferMode {  
    IX_DMA_COPY_CLEAR,  
    IX_DMA_COPY,  
    IX_DMA_COPY_BYTE_SWAP,  
    IX_DMA_COPY_REVERSE,  
    IX_DMA_TRANSFER_MODE_INVALID  
}
```

Dma transfer mode definitions.

```
enum IxDmaAddressingMode {  
    IX_DMA_INC_SRC_INC_DST,  
    IX_DMA_INC_SRC_FIX_DST,  
    IX_DMA_FIX_SRC_INC_DST,  
    IX_DMA_FIX_SRC_FIX_DST,  
    IX_DMA_ADDRESSING_MODE_INVALID  
}
```

Dma addressing mode definitions.

```
enum IxDmaTransferWidth {  
    IX_DMA_32_SRC_32_DST,  
    IX_DMA_32_SRC_16_DST,  
    IX_DMA_32_SRC_8_DST,  
    IX_DMA_16_SRC_32_DST,  
    IX_DMA_16_SRC_16_DST,  
    IX_DMA_16_SRC_8_DST,  
    IX_DMA_8_SRC_32_DST,  
    IX_DMA_8_SRC_16_DST,  
    IX_DMA_8_SRC_8_DST,  
    IX_DMA_8_SRC_BURST_DST,  
    IX_DMA_16_SRC_BURST_DST,  
    IX_DMA_32_SRC_BURST_DST,  
}
```

```

IX_DMA_BURST_SRC_8_DST,
IX_DMA_BURST_SRC_16_DST,
IX_DMA_BURST_SRC_32_DST,
IX_DMA_BURST_SRC_BURST_DST,
IX_DMA_TRANSFER_WIDTH_INVALID
}

```

Dma transfer width definitions Fixed addresses (either source or destination) do not support burst transfer width.

```

enum IxDmaNpeId {
    IX_DMA_NPEID_NPEA,
    IX_DMA_NPEID_NPEB,
    IX_DMA_NPEID_NPEC,
    IX_DMA_NPEID_MAX
}

```

NpeId numbers to identify NPE A, B or C.

Detailed Description

The common set of types used in the DMA component.

Enumeration Type Documentation

```
enum IxDmaAddressingMode
```

Dma addressing mode definitions.

Note:

Fixed source address to fixed destination address addressing mode is not supported.

Enumeration values:

<i>IX_DMA_INC_SRC_INC_DST</i>	Incremental source address to incremental destination address.
<i>IX_DMA_INC_SRC_FIX_DST</i>	Incremental source address to incremental destination address.
<i>IX_DMA_FIX_SRC_INC_DST</i>	Incremental source address to incremental destination address.
<i>IX_DMA_FIX_SRC_FIX_DST</i>	Incremental source address to incremental destination address.
<i>IX_DMA_ADDRESSING_MODE_INVALID</i>	Invalid Addressing Mode.

Definition at line **65** of file **IxDmaAcc.h**.

```
enum IxDmaNpeId
```

NpeId numbers to identify NPE A, B or C.

Warning:

This enum is deprecated and will be removed in future IXP400 Software release. Please use IxNpeDINpeId enum instead.

Enumeration values:

IX_DMA_NPEID_NPEA Identifies NPE A.
IX_DMA_NPEID_NPEB Identifies NPE B.
IX_DMA_NPEID_NPEC Identifies NPE C.
IX_DMA_NPEID_MAX Total Number of NPEs.

Definition at line **109** of file **IxDmaAcc.h**.

enum IxDmaReturnStatus

Dma return status definitions.

Enumeration values:

<i>IX_DMA_SUCCESS</i>	DMA Transfer Success.
<i>IX_DMA_FAIL</i>	DMA Transfer Fail.
<i>IX_DMA_INVALID_TRANSFER_WIDTH</i>	Invalid transfer width.
<i>IX_DMA_INVALID_TRANSFER_LENGTH</i>	Invalid transfer length.
<i>IX_DMA_INVALID_TRANSFER_MODE</i>	Invalid transfer mode.
<i>IX_DMA_INVALID_ADDRESS_MODE</i>	Invalid address mode.
<i>IX_DMA_REQUEST_FIFO_FULL</i>	DMA request queue is full.

Definition at line **33** of file **IxDmaAcc.h**.

enum IxDmaTransferMode

Dma transfer mode definitions.

Note:

Copy and byte swap, and copy and reverse modes only support multiples of word data length.

Enumeration values:

<i>IX_DMA_COPY_CLEAR</i>	copy and clear source
<i>IX_DMA_COPY</i>	copy

<i>IX_DMA_COPY_BYTE_SWAP</i>	copy and byte swap (endian)
<i>IX_DMA_COPY_REVERSE</i>	copy and reverse
<i>IX_DMA_TRANSFER_MODE_INVALID</i>	Invalid transfer mode.

Definition at line **50** of file **IxDmaAcc.h**.

enum IxDmaTransferWidth

Dma transfer width definitions Fixed addresses (either source or destination) do not support burst transfer width.

Enumeration values:

<i>IX_DMA_32_SRC_32_DST</i>	32-bit src to 32-bit dst
<i>IX_DMA_32_SRC_16_DST</i>	32-bit src to 16-bit dst
<i>IX_DMA_32_SRC_8_DST</i>	32-bit src to 8-bit dst
<i>IX_DMA_16_SRC_32_DST</i>	16-bit src to 32-bit dst
<i>IX_DMA_16_SRC_16_DST</i>	16-bit src to 16-bit dst
<i>IX_DMA_16_SRC_8_DST</i>	16-bit src to 8-bit dst
<i>IX_DMA_8_SRC_32_DST</i>	8-bit src to 32-bit dst
<i>IX_DMA_8_SRC_16_DST</i>	8-bit src to 16-bit dst
<i>IX_DMA_8_SRC_8_DST</i>	8-bit src to 8-bit dst
<i>IX_DMA_8_SRC_BURST_DST</i>	8-bit src to burst dst – Not supported for fixed destination address
<i>IX_DMA_16_SRC_BURST_DST</i>	16-bit src to burst dst – Not supported for fixed destination address
<i>IX_DMA_32_SRC_BURST_DST</i>	32-bit src to burst dst – Not supported for fixed destination address
<i>IX_DMA_BURST_SRC_8_DST</i>	burst src to 8-bit dst – Not supported for fixed source address
<i>IX_DMA_BURST_SRC_16_DST</i>	burst src to 16-bit dst – Not supported for fixed source address
<i>IX_DMA_BURST_SRC_32_DST</i>	burst src to 32-bit dst – Not supported for fixed source address
<i>IX_DMA_BURST_SRC_BURST_DST</i>	burst src to burst dst – Not supported for fixed source and destination address
<i>IX_DMA_TRANSFER_WIDTH_INVALID</i>	Invalid transfer width.

Definition at line **80** of file **IxDmaAcc.h**.

Intel (R) IXP400 Software DMA Access Driver (IxDmaAcc) API

The public API for the Intel (R) IXP400 Software IxDmaAcc component.

Defines

```
#define IX_DMA_REQUEST_FULL  
DMA request queue is full This constant is a return value used to tell the user that the IxDmaAcc queue is full.
```

Typedefs

```
typedef UINT32 IxDmaAccRequestId  
DMA Request Id type.  
  
typedef void(* IxDmaAccDmaCompleteCallback)(IxDmaReturnStatus status)  
DMA completion notification This function is called to notify a client that the DMA has been completed.
```

Functions

```
PUBLIC IX_STATUS ixDmaAccInit (IxNpeDlNpeId npeId)  
Initialise the DMA Access component This function will initialise the DMA Access component internals.  
  
PUBLIC IX_STATUS ixDmaAccUninit (IxNpeDlNpeId npeId)  
Uninitialise the DMA Access component This function will uninitialise the DMA Access component internals.  
  
PUBLIC IxDmaReturnStatus ixDmaAccDmaTransfer (IxDmaAccDmaCompleteCallback callback, UINT32 SourceAddr, UINT32 DestinationAddr, UINT16 TransferLength, IxDmaTransferMode TransferMode, IxDmaAddressingMode AddressingMode, IxDmaTransferWidth TransferWidth)  
Perform DMA transfer This function will perform DMA transfer between devices within the Intel (R) IXP400 Software memory map.  
  
PUBLIC IX_STATUS ixDmaAccShow (void)  
Display some component information for debug purposes Show some internal operation information relating to the DMA service. At a minimum the following will show. –the number of the DMA pend (in queue).
```

Detailed Description

The public API for the Intel (R) IXP400 Software IxDmaAcc component.

Define Documentation

```
#define IX_DMA_REQUEST_FULL
```

DMA request queue is full This constant is a return value used to tell the user that the IxDmaAcc queue is full.

Definition at line **140** of file **IxDmaAcc.h**.

Typedef Documentation

```
typedef void(* IxDmaAccDmaCompleteCallback)(IxDmaReturnStatus status)
```

DMA completion notification This function is called to notify a client that the DMA has been completed.

Parameters:

status **IxDmaReturnStatus** [out] – reporting to client

Definition at line **149** of file **IxDmaAcc.h**.

```
typedef UINT32 IxDmaAccRequestId
```

DMA Request Id type.

Definition at line **130** of file **IxDmaAcc.h**.

Function Documentation

```
ixDmaAccDmaTransfer ( IxDmaAccDmaCompleteCallback callback,  
                     UINT32 SourceAddr,  
                     UINT32 DestinationAddr,  
                     UINT16 TransferLength,  
                     IxDmaTransferMode TransferMode,  
                     IxDmaAddressingMode AddressingMode,  
                     IxDmaTransferWidth TransferWidth  
                     )
```

Perform DMA transfer This function will perform DMA transfer between devices within the Intel (R) IXP400 Software memory map.

Note:

The following are restrictions for IxDmaAccDmaTransfer:

- ◇ The function is non re-entrant.
- ◇ The function assumes host devices are operating in big-endian mode.
- ◇ Fixed address does not support burst transfer width
- ◇ Fixed source address to fixed destination address mode is not supported
- ◇ The incrementing source address for expansion bus will not support a burst transfer width and copy and clear mode

Parameters:

<i>callback</i>	IxDmaAccDmaCompleteCallback [in] – function pointer to be stored and called when the DMA transfer is completed. This cannot be NULL.
<i>SourceAddr</i>	UINT32 [in] – Starting address of DMA source. Must be a valid Intel (R) IXP400 Software memory map address.
<i>DestinationAddr</i>	UINT32 [in] – Starting address of DMA destination. Must be a valid Intel (R) IXP400 Software memory map address.
<i>TransferLength</i>	UINT16 [in] – The size of DMA data transfer. The range must be from 1–64Kbyte
<i>TransferMode</i>	IxDmaTransferMode [in] – The DMA transfer mode
<i>AddressingMode</i>	IxDmaAddressingMode [in] – The DMA addressing mode
<i>TransferWidth</i>	IxDmaTransferWidth [in] – The DMA transfer width

Returns:

- ◇ IX_DMA_SUCCESS Notification that the DMA request is succesful
- ◇ IX_DMA_FAIL IxDmaAcc not yet initialised or some internal error has occurred
- ◇ IX_DMA_INVALID_TRANSFER_WIDTH Transfer width is nit valid
- ◇ IX_DMA_INVALID_TRANSFER_LENGTH Transfer length outside of valid range
- ◇ IX_DMA_INVALID_TRANSFER_MODE Transfer Mode not valid
- ◇ IX_DMA_REQUEST_FIFO_FULL IxDmaAcc request queue is full

ixDmaAccInit (IxNpeDINpeId npeId)

Initialise the DMA Access component This function will initialise the DMA Access component internals.

Parameters:

npeId **IxNpeDINpeId** [in] – NPE to use for Dma Transfer

Returns:

- ◇ IX_SUCCESS succesfully initialised the component
- ◇ IX_FAIL Initialisation failed for some unspecified internal reason.

ixDmaAccShow (void)

Display some component information for debug purposes Show some internal operation information relating to the DMA service. At a minimum the following will show. –the number of the DMA pend (in queue).

Parameters:

None

Returns:

◇ None

ixDmaAccUninit (**IxNpeDlnPpeId** *npeId*)

Uninitialise the DMA Access component This function will uninitialise the DMA Access component internals.

Parameters:

npeId **IxNpeDlnPpeId** [in] – NPE to use for Dma Transfer

Returns:

◇ IX_SUCCESS succesfully uninitialised the component

◇ IX_FAIL Unnitalisation failed for some unspecified internal reason.

IXP400 Soft–Error Handler Driver (ixErrHdlAcc) API

The public API for the IXP400 Soft–Error Handler Driver (ixErrHdlAcc).

Data Structures

struct **IxErrHdlAccRecoveryStatistics**
Debug Statistical Data Structure.

Defines

#define **IX_ERRHDLACC_NPEA_ERROR_MASK_BIT**
Definition of the NPE A Error Mask Bit.

#define **IX_ERRHDLACC_NPEB_ERROR_MASK_BIT**
Definition of the NPE B Error Mask Bit.

#define **IX_ERRHDLACC_NPEC_ERROR_MASK_BIT**
Definition of the NPE C Error Mask Bit.

#define **IX_ERRHDLACC_AQM_SRAM_PARITY_ERROR_MASK_BIT**
Definition of the AQM Error Mask Bit.

Typedefs

typedef void(* **IxErrHdlAccRecoveryDoneCallback**)(**IxErrHdlAccErrorEventType**)
Definition of the Recovery Done Call–back type Function pointer with IxErrHdlAccErrorEventType type as the argument.

typedef
IX_STATUS(* **IxErrHdlAccFuncHandler**)(void)
Definition of the Event handler type function pointer.

Enumerations

enum **IxErrHdlAccErrorEventType** {
 IX_ERRHDLACC_NPEA_ERROR,
 IX_ERRHDLACC_NPEB_ERROR,
 IX_ERRHDLACC_NPEC_ERROR,
 IX_ERRHDLACC_AQM_ERROR,
 IX_ERRHDLACC_NO_ERROR
}
Definition of the Soft–Error Event Types.

```
enum IxErrHdlAccNPEId {
    IX_ERRHDLACC_NPEA,
    IX_ERRHDLACC_NPEB,
    IX_ERRHDLACC_NPEC
}
```

Definition of the NPE ID.

```
enum IxErrHdlAccEnableEvent {
    IX_ERRHDLACC_EVT_DISABLE,
    IX_ERRHDLACC_EVT_ENABLE
}
```

Definition of the Soft-Error Event Enable/Disable.

Functions

PUBLIC
IX_STATUS ixErrHdlAccEnableConfigGet (UINT32 *configMask)
Gets the configuration word enable setup.

PUBLIC
IX_STATUS ixErrHdlAccEnableConfigSet (UINT32 configMask)
Configures the ixErrHdlAcc module's configuration, to enable or disable a maximum total of 32 Soft Error Events types. –Reentrant – no –ISR Callable – yes.

PUBLIC
IX_STATUS ixErrHdlAccNPEReset (**IxErrHdlAccNPEId** npelD)
Reset the NPE via the Expansion bus controller FUSE register. The API sets the FUSE Bit that resets the NPE. It waits for the NPE to reset and then, turns off the FUSE bit to re-enable the NPE.

PUBLIC
IX_STATUS ixErrHdlAccInit (void)
Initializes the ixErrHdlAcc component.

PUBLIC
IX_STATUS ixErrHdlAccUnload (void)
Unloads the ixErrHdlAccModule, destroying the semaphore object and killing all threads/tasks.

PUBLIC ixErrHdlAccErrorHandlerGet (**IxErrHdlAccErrorEventType** event,
IX_STATUS ixErrHdlAccFuncHandler *handler)
API to get the event handler API to be called within the interrupt error ISR or task level to initiate a soft-error handling of the error.

PUBLIC
IX_STATUS ixErrHdlAccStatusSet (UINT32 status)
Sets the current Error condition status results that indicates if there was an error in handling a soft-error.

PUBLIC
 IX_STATUS **ixErrHdlAccStatusGet** (UINT32 *status)
Gets the current Error condition status results that indicates if there was an error in handling a soft-error.

PUBLIC void **ixErrHdlAccStatisticsShow** (void)
Displays the Debug/Masurement statistics recorded by the module.

PUBLIC
 IX_STATUS **ixErrHdlAccStatisticsGet** (**IxErrHdlAccRecoveryStatistics** *statistics)
API to retrieve the statistics recorded by the module.

PUBLIC void **ixErrHdlAccStatisticsClear** (void)
Resets and Clears the Debug/Masurement statistics recorded by the module.

PUBLIC
 IX_STATUS **ixErrHdlAccCallbackRegister** (**IxErrHdlAccRecoveryDoneCallback** callback)
API to register a Completion done that is called after every completion of an error handling.

Detailed Description

The public API for the IXP400 Soft-Error Handler Driver (ixErrHdlAcc).

Define Documentation

```
#define IX_ERRHDLACC_AQM_SRAM_PARITY_ERROR_MASK_BIT
```

Definition of the AQM Error Mask Bit.

Definition at line **59** of file **IxErrHdlAcc.h**.

```
#define IX_ERRHDLACC_NPEA_ERROR_MASK_BIT
```

Definition of the NPE A Error Mask Bit.

Definition at line **41** of file **IxErrHdlAcc.h**.

```
#define IX_ERRHDLACC_NPEB_ERROR_MASK_BIT
```

Definition of the NPE B Error Mask Bit.

Definition at line **47** of file **IxErrHdlAcc.h**.

```
#define IX_ERRHDLACC_NPEC_ERROR_MASK_BIT
```

Definition of the NPE C Error Mask Bit.

Definition at line **53** of file **IxErrHdlAcc.h**.

Typedef Documentation

```
IxErrHdlAccFuncHandler
```

Definition of the Event handler type function pointer.

Definition at line **96** of file **IxErrHdlAcc.h**.

```
IxErrHdlAccRecoveryDoneCallback
```

Definition of the Recovery Done Call-back type Function pointer with IxErrHdlAccErrorEventType type as the argument.

Definition at line **89** of file **IxErrHdlAcc.h**.

Enumeration Type Documentation

```
enum IxErrHdlAccEnableEvent
```

Definition of the Soft-Error Event Enable/Disable.

Definition at line **78** of file **IxErrHdlAcc.h**.

```
enum IxErrHdlAccErrorEventType
```

Definition of the Soft-Error Event Types.

Definition at line **29** of file **IxErrHdlAcc.h**.

```
enum IxErrHdlAccNPEId
```

Definition of the NPE ID.

Definition at line **67** of file **IxErrHdlAcc.h**.

Function Documentation

IX_STATUS ixErrHdlAccCallbackRegister (**IxErrHdlAccRecoveryDoneCallback** *callback*)

API to register a Completion done that is called after every completion of an error handling.

- Reentrant – no
- ISR Callable – no

Precondition:

The ixErrHdlAcc module should have already been initialized prior to calling this API.

Parameters:

callback IxErrHdlAccRecoveryDoneCallback [in] Call-back function to be called by the module upon completion of a recovery task. See **IxErrHdlAccRecoveryDoneCallback**

Returns:

IX_STATUS
◊ IX_SUCCESS: Operation success
◊ IX_FAIL : An uninitialized ixErrHdlAcc module or a NULL pointer provided to the 1st parameter argument of the function.

IX_STATUS ixErrHdlAccEnableConfigGet (UINT32 * *configMask*)

Gets the configuration word enable setup.

Note:

This API gets the soft-error configuration setup in the module that was set by the call to the **ixErrHdlAccEnableConfigSet** API.

- Reentrant – no
- ISR Callable – yes

Precondition:

The ixErrHdlAcc module should have already been initialized prior to calling this API.

Parameters:

configMask UINT32* [in] Data UINT32 pointer to store the configuration Mask whereby, any bits set or clear indicates an enable or disable of a particular Error event type.

Returns:

IX_STATUS
◊ IX_SUCCESS: Operation success
◊ IX_FAIL : An uninitialized ixErrHdlAcc module or a NULL pointer provided to the 1st parameter argument of the function.

See also:

ixErrHdlAccEnableConfigSet

```
IX_STATUS ixErrHdlAccEnableConfigSet ( UINT32 configMask )
```

Configures the ixErrHdlAcc module's configuration, to enable or disable a maximum total of 32 Soft Error Events types. –Reentrant – no –ISR Callable – yes.

Note:

An example to enable NPE A , NPE B and NPE C Error handling.

```
ixErrHdlAccEnableConfigSet(IX_ERRHDLACC_NPEA_ERROR_MASK_BIT  
|IX_ERRHDLACC_NPEB_ERROR_MASK_BIT  
|IX_ERRHDLACC_NPEC_ERROR_MASK_BIT);
```

Precondition:

ixErrHdlAcc must be initialized by calling the ixErrHdlAccInit prior to using this API.

Parameters:

configMask UINT32 [in] – a 32 bit Configuration word where a bit N set will enable the event N a bit N clear will disable the event N N=0, 1, 2, ...31.

Returns:

IX_STATUS
 ◇ IX_SUCCESS: Operation success
 ◇ IX_FAIL : A fail if the module is not initialized.

See also:

ixErrHdlAccEnableConfigGet

```
IX_STATUS ixErrHdlAccErrorHandlerGet ( IxErrHdlAccErrorEventType event,  
                                         IxErrHdlAccFuncHandler * handler  
                                         )
```

API to get the event handler API to be called within the interrupt error ISR or task level to initiate a soft-error handling of the error.

Note:

For an NPE Error, the event handlers can be called to reset the NPE irrespective of whether there is an NPE parity error or an AHB error. This API can be used to restore the NPE in a need to need basis.

- Reentrant – no
- ISR Callable – yes

Precondition:

The ixErrHdlAcc module should have already been initialized prior to calling this API.

Parameters:

event IxErrHdlAccErrorEventType [in] An Event ID defined as: **IxErrHdlAccErrorEventType**
handler IxErrHdlAccFuncHandler* [in] A pointer to a Event Error handler defined as **IxErrHdlAccFuncHandler**

Returns:

IX_STATUS
 ◇ IX_SUCCESS: Operation success
 ◇ IX_FAIL : An uninitialized ixErrHdlAcc module or a NULL pointer provided to the 2nd parameter argument of the function or an invalid Event ID (1st Parameter)

IX_STATUS ixErrHdlAccInit (void)

Initializes the ixErrHdlAcc component.

- Reentrant – no
- ISR Callable – no

Precondition:

The ixErrHdlAcc module should not already been loaded or initialized.

Returns:

IX_STATUS
 ◇ IX_SUCCESS: Module has initialized or already initialized.
 ◇ IX_FAIL : Failure to create thread, create a semaphore object & initializing of the module which is already initialized.

See also:

ixErrHdlAccUnload

IX_STATUS ixErrHdlAccNPEReset (**IxErrHdlAccNPEId** *npeID*)

Reset the NPE via the Expansion bus controller FUSE register. The API sets the FUSE Bit that resets the NPE. It waits for the NPE to reset and then, turns off the FUSE bit to re-enable the NPE.

- Reentrant – yes
- ISR Callable – yes

Precondition:

npeID must be a valid NPE ID where, 0 – NPEA, 1 – NPEB & 2 – NPEC

Parameters:

npeID IxErrHdlAccNPEId [in] – NPE ID for NPEA, NPEB and NPEC. See **IxErrHdlAccNPEId**

Returns:

IX_STATUS

◊ IX_SUCCESS: Operation success

◊ IX_FAIL : Invalid NPEID, Failure to Reset the NPE due to time-out while waiting for the NPE to reset and for the NPE FUSE Bit to turn off.

```
void ixErrHdlAccStatisticsClear ( void )
```

Resets and Clears the Debug/Masurement statistics recorded by the module.

- Reentrant – no
- ISR Callable – no

Returns:

NONE

See also:

ixErrHdlAccStatisticsGet

ixErrHdlAccStatisticsShow

```
IX_STATUS ixErrHdlAccStatisticsGet ( IxErrHdlAccRecoveryStatistics * statistics )
```

API to retrieve the statistics recorded by the module.

Note:

See **IxErrHdlAccRecoveryStatistics** for details

- Reentrant – no
- ISR Callable – no

Precondition:

The ixErrHdlAcc module should have already been initialized prior to calling this API.

Parameters:

statistics **IxErrHdlAccRecoveryStatistics** [in]

Returns:

IX_STATUS

◊ IX_SUCCESS

◊ IX_FAIL : An uninitialized ixErrHdlAcc module or a NULL pointer provided to the 1st parameter argument of the function.

See also:

ixErrHdlAccStatisticsClear

ixErrHdlAccStatisticsShow

```
void ixErrHdlAccStatisticsShow ( void )
```

Displays the Debug/Measurement statistics recorded by the module.

- Reentrant – no
- ISR Callable – no

Returns:

NONE

See also:

ixErrHdlAccStatisticsClear

ixErrHdlAccStatisticsGet

```
IX_STATUS ixErrHdlAccStatusGet ( UINT32 * status )
```

Gets the current Error condition status results that indicates if there was an error in handling a soft-error.

Note:

Usage guide: This API can be used to get the Event Error WORD condition where, Any bit N set in the status WORD (32bit) shall indicate an error. Currently only bit N = 0, 1, 2 & 3 is valid.

Usage Example:

This example gets the current status and checks for NPE A Error.

```
ixErrHdlAccStatusGet(&status);  
if(status&IX_ERRHDLACC_NPEA_ERROR_MASK_BIT)  
{ < NPE A Error> }
```

- Reentrant – no
- ISR Callable – yes

Precondition:

The ixErrHdlAcc module should have already been initialized prior to calling this API.

Parameters:

status UINT32 [in] Pointer to a UINT32 (WORD) to write the current Event Status condition WORD

Returns:

IX_STATUS

◊ IX_SUCCESS: Operation success

◊ IX_FAIL : An uninitialized ixErrHdlAcc module or a NULL pointer provided to the 1st parameter.

See also:

ixErrHdlAccStatusSet

IX_STATUS ixErrHdlAccStatusSet (UINT32 *status*)

Sets the current Error condition status results that indicates if there was an error in handling a soft-error.

Warning:

This function must be used only in conditions whereby, the client performs it's own error handling in addition to the ones provided by the ixErrHdlAcc component which may result in recovery failure. This is particularly applicable for customized NPE firmware done by customers. The API then must be called to indicate an error in the hardware component impacted.

Note:

Usage guide: This API can be used to set the Event Error WORD condition where, any bit N set in the status WORD (32bit) shall indicate an error. Currently only bit N = 0, 1, 2 & 3 is valid.

An Example,

This enables NPE A and NPE C Error handling.

```
ixErrHdlAccStatusSet(IX_ERRHDLACC_NPEA_ERROR_MASK_BIT  
|IX_ERRHDLACC_NPEC_ERROR_MASK_BIT);
```

- Reentrant – no
- ISR Callable – yes

Precondition:

The ixErrHdlAcc module should have already been intialized prior to calling this API.

Parameters:

status UINT32 [in] UINT32 (WORD) to write the current Event Status condition WORD

Returns:

IX_STATUS

◊ IX_SUCCESS: Operation success

◊ IX_FAIL : An uninitialized ixErrHdlAcc module

See also:

ixErrHdlAccStatusGet

IX_STATUS ixErrHdlAccUnload (void)

Unloads the ixErrHdlAccModule, destroying the semaphore object and killing all threads/tasks.

- Reentrant – no
- ISR Callable – no

Precondition:

The ixErrHdlAcc module should have already been initialized prior to calling this API.

Returns:

IX_STATUS

◇ IX_SUCCESS : Module has unloaded or already unloaded.

◇ IX_FAIL : Failure to terminate thread, destroy a semaphore objects and to de-allocate any allocated memory.

See also:

ixErrHdlAccInit

Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API

ethAcc is a library that does provides access to the internal IXP4XX Product Line of Network Processors 10/100Bt Ethernet MACs.

Data Structures

- struct **IxEthAccMacAddr**
Definition of the IEEE 802.3 Ethernet MAC address structure.
- struct **IxEthAccNe**
Definition of service-specific informations.
- struct **IxEthAccNe**
Definition of service-specific informations.
- struct **IxEthAccNe**
Definition of service-specific informations.
- struct **IxEthEthObjStats**
This struct defines the statistics returned by this component.

Defines

- #define **ixEthAccUnload**
- #define **IX_ETH_ACC_NUMBER_OF_PORTS**
Definition of the number of ports.
- #define **IX_IEEE803_MAC_ADDRESS_SIZE**
Definition of the size of the MAC address.
- #define **IX_ETH_ACC_NUM_TX_PRIORITIES**
Definition of the number of transmit priorities.
- #define **IX_ETHACC_NE_PORT_UNKNOWN**
Contents of the field IX_ETHACC_NE_DESTPORTID when no destination port can be found by the NPE for this frame.
- #define **IX_ETHACC_NE_PADLENGTH**(mBufPtr)
The location of the number of padding bytes in the Mbuf header.
- #define **IX_ETHACC_NE_DESTMAC**(mBufPtr)
The location of the destination MAC address in the Mbuf header.
- #define **IX_ETHACC_NE_SOURCEMAC**(mBufPtr)

The location of the source MAC address in the Mbuf header.

```
#define IX_ETHACC_NE_VLANTCI(mBufPtr)  
    The VLAN Tag Control Information associated with this frame.  
  
#define IX_ETHACC_NE_SOURCEPORTID(mBufPtr)  
    The port where this frame came from.  
  
#define IX_ETHACC_NE_DESTPORTID(mBufPtr)  
    The destination port where this frame should be sent.  
  
#define IX_ETHACC_NE_QOS(mBufPtr)  
    QualityOfService class (QoS) for this received frame.  
  
#define IX_ETHACC_NE_FLAGS(mBufPtr)  
    Bit Mask of the different flags associated with a frame.  
  
#define IX_ETHACC_NE_BCASTMASK  
    This mask defines if a received frame is a broadcast frame.  
  
#define IX_ETHACC_NE_MCASTMASK  
    This mask defines if a received frame is a multicast frame.  
  
#define IX_ETHACC_NE_IPMASK  
    This mask defines if a received frame is a IP frame.  
  
#define IX_ETHACC_NE_IPV6MASK  
    This mask defines if a received frame is a IP frame.  
  
#define IX_ETHACC_NE_LINKMASK  
    This mask is the link layer protocol indicator.  
  
#define IX_ETHACC_NE_STMASK  
    This mask defines if a received frame is a Spanning Tree frame.  
  
#define IX_ETHACC_NE_FILTERMASK  
    This bit indicates whether a frame has been filtered by the Rx service.  
  
#define IX_ETHACC_NE_PORTOVERMASK  
    This mask defines the rule to transmit a frame.  
  
#define IX_ETHACC_NE_TAGMODEMASK  
    This mask defines the tagging rules to apply to a transmit frame.  
  
#define IX_ETHACC_NE_TAGOVERMASK  
    This mask defines the rule to transmit a frame.  
  
#define IX_ETHACC_NE_LOCALMACMASK  
    This mask defines the rule to receive a frame to local mac.  
  
#define IX_ETHACC_NE_VLANMASK
```

This mask defines if a received frame is VLAN tagged.

#define IX_ETHACC_NE_VLANENABLEMASK

This mask defines if a frame is a VLAN frame or not.

#define IX_ETHACC_NE_NEWSRCMASK

This mask defines if a received frame has been learned.

#define IX_ETHACC_RX_MBUF_MIN_SIZE

This defines the recommended minimum size of MBUF's submitted to the frame receive service.

#define IXP400_ETH_ACC_MII_MAX_ADDR

This defines the highest MII address of any attached PHYs.

#define IXP425_ETH_ACC_MII_MAX_ADDR

This defines the highest MII address of any attached PHYs.

#define ixEthRxPriorityPoll

*Following definition providing backward compatibility to **ixEthRxPriorityPoll()** function that will be deprecated in future release.*

#define ixEthRxMultiBufferPriorityPoll

*Following definition providing backward compatibility to **ixEthRxMultiBufferPriorityPoll()** function that will be deprecated in future release.*

#define IxEthAccTxSchedulerDiscipline

Deprecated definition for the port transmit scheduling discipline.

#define ixEthAccMiiPhyScan(phyPresent)

: deprecated API entry point. This definition ensures backward compatibility

#define ixEthAccMiiPhyConfig(phyAddr, speed100, fullDuplex, autonegotiate)

: deprecated API entry point. This definition ensures backward compatibility

#define ixEthAccMiiPhyReset(phyAddr)

: deprecated API entry point. This definition ensures backward compatibility

#define ixEthAccMiiLinkStatus(phyAddr, linkUp, speed100, fullDuplex, autoneg)

: deprecated API entry point. This definition ensures backward compatibility

#define ixEthAccMiiShow(phyAddr)

: deprecated API entry point. This definition ensures backward compatibility

Typedefs

typedef void(* IxEthAccPortTxDoneCallback)(UINT32 callbackTag, IX_OSAL_MBUF *buffer)

*Function prototype for Ethernet Tx Buffer Done callback. Registered via **ixEthAccTxBufferDoneCallbackRegister**.*

```
typedef void(* IxEthAccPortRxCallback )(UINT32 callbackTag, IX_OSAL_MBUF *buffer, UINT32 reserved)
```

Function prototype for Ethernet Frame Rx callback. Registered via ixEthAccPortRxCallbackRegister.

```
typedef void(* IxEthAccPortMultiBufferRxCallback )(UINT32 callbackTag, IX_OSAL_MBUF **buffer)
```

Function prototype for Ethernet Frame Rx callback. Registered via ixEthAccPortMultiBufferRxCallbackRegister.

Enumerations

```
enum IxEthAccStatus {
    IX_ETH_ACC_SUCCESS,
    IX_ETH_ACC_FAIL,
    IX_ETH_ACC_INVALID_PORT,
    IX_ETH_ACC_PORT_UNINITIALIZED,
    IX_ETH_ACC_MAC_UNINITIALIZED,
    IX_ETH_ACC_INVALID_ARG,
    IX_ETH_TX_Q_FULL,
    IX_ETH_ACC_NO_SUCH_ADDR
}
```

Definition of the Ethernet Access status.

```
enum IxEthAccPortId {
    IX_ETH_PORT_1,
    IX_ETH_PORT_2,
    IX_ETH_PORT_3
}
```

Definition of the IXP400 Mac Ethernet device.

```
enum IxEthAccTxPriority {
    IX_ETH_ACC_TX_PRIORITY_0,
    IX_ETH_ACC_TX_PRIORITY_1,
    IX_ETH_ACC_TX_PRIORITY_2,
    IX_ETH_ACC_TX_PRIORITY_3,
    IX_ETH_ACC_TX_PRIORITY_4,
    IX_ETH_ACC_TX_PRIORITY_5,
    IX_ETH_ACC_TX_PRIORITY_6,
    IX_ETH_ACC_TX_PRIORITY_7,
    IX_ETH_ACC_TX_DEFAULT_PRIORITY
}
```

Definition of the relative priority used to transmit a frame.

```
enum IxEthAccRxFrameType {
    IX_ETHACC_RX_LLCTYPE,
    IX_ETHACC_RX_ETHTYPE,
    IX_ETHACC_RX_STATTYPE,
}
```



```

IX_ETHACC_RX_APTYPE
}

```

Identify the type of a frame.

```

enum IxEthAccDuplexMode {
    IX_ETH_ACC_FULL_DUPLEX,
    IX_ETH_ACC_HALF_DUPLEX
}

```

Definition to provision the duplex mode of the MAC.

```

enum IxEthAccSchedulerDiscipline {
    FIFO_NO_PRIORITY,
    FIFO_PRIORITY
}

```

Definition for the port scheduling discipline.

Functions

PUBLIC

IxEthAccStatus **ixEthAccInit** (void)

Initializes the Intel (R) IXP400 Software Ethernet Access Service.

PUBLIC

IxEthAccStatus **ixEthAccUninit** (void)

Un-Initializes the Intel (R) IXP400 Software Ethernet Access Service.

PUBLIC

IxEthAccStatus **ixEthAccPortInit** (**IxEthAccPortId** portId)

Initializes an NPE/Ethernet MAC Port.

PUBLIC **ixEthAccPortTxFrameSubmit** (**IxEthAccPortId** portId, **IX_OSAL_MBUF** *buffer,
IxEthAccStatus **ixEthAccTxPriority** priority)

PUBLIC **ixEthAccPortTxDoneCallbackRegister** (**IxEthAccPortId** portId,
IxEthAccStatus **ixEthAccPortTxDoneCallback** txCallbackFn, **UINT32** callbackTag)

Register a callback function to allow the transmitted buffers to return to the user.

UINT32 **ixEthAccRxPriorityPoll** (**UINT32** reserved, **UINT32** maxQEntries)

UINT32 **ixEthAccRxMultiBufferPriorityPoll** (**UINT32** reserved, **UINT32** maxQEntries)

PUBLIC **ixEthAccPortRxCallbackRegister** (**IxEthAccPortId** portId, **IxEthAccPortRxCallback**
IxEthAccStatus rxCallbackFn, **UINT32** callbackTag)

Register a callback function to allow the reception of frames.

PUBLIC **ixEthAccPortMultiBufferRxCallbackRegister** (**IxEthAccPortId** portId,
IxEthAccStatus **ixEthAccPortMultiBufferRxCallback** rxCallbackFn, **UINT32** callbackTag)

Register a callback function to allow the reception of frames.

PUBLIC

IxEthAccStatus **ixEthAccPortRxFreeReplenish** (**IxEthAccPortId** portId, **IX_OSAL_MBUF** *buffer)

This function provides buffers for the Ethernet receive path.

PUBLIC

IxEthAccStatus ixEthAccPortEnable (IxEthAccPortId portId)
This enables an Ethernet port for both Tx and Rx.

PUBLIC

IxEthAccStatus ixEthAccPortDisable (IxEthAccPortId portId)
This disables an Ethernet port for both Tx and Rx.

PUBLIC

IxEthAccStatus ixEthAccPortEnabledQuery (IxEthAccPortId portId, BOOL *enabled)
Get the enabled state of a port.

PUBLIC

IxEthAccStatus ixEthAccPortPromiscuousModeClear (IxEthAccPortId portId)
Put the Ethernet MAC device in non-promiscuous mode.

PUBLIC

IxEthAccStatus ixEthAccPortPromiscuousModeSet (IxEthAccPortId portId)
Put the MAC device in promiscuous mode.

**PUBLIC IxEthAccPortUnicastMacAddressSet (IxEthAccPortId portId, IxEthAccMacAddr
IxEthAccStatus *macAddr)**
Configure unicast MAC address for a particular port.

**PUBLIC IxEthAccPortUnicastMacAddressGet (IxEthAccPortId portId, IxEthAccMacAddr
IxEthAccStatus *macAddr)**

**PUBLIC IxEthAccPortMulticastAddressJoin (IxEthAccPortId portId, IxEthAccMacAddr
IxEthAccStatus *macAddr)**

PUBLIC IxEthAccStatus ixEthAccPortMulticastAddressJoinAll (IxEthAccPortId portId)
Filter all frames with multicast dest.

**PUBLIC IxEthAccPortMulticastAddressLeave (IxEthAccPortId portId, IxEthAccMacAddr
IxEthAccStatus *macAddr)**

PUBLIC IxEthAccStatus ixEthAccPortMulticastAddressLeaveAll (IxEthAccPortId portId)
This function unconfigures the multicast filtering settings.

PUBLIC

IxEthAccStatus ixEthAccPortUnicastAddressShow (IxEthAccPortId portId)
Displays unicast MAC address.

PUBLIC void ixEthAccPortMulticastAddressShow (IxEthAccPortId portId)
Displays multicast MAC address.

PUBLIC

IxEthAccStatus ixEthAccPortDuplexModeSet (IxEthAccPortId portId, IxEthAccDuplexMode mode)
Set the duplex mode for the MAC.

PUBLIC
IxEthAccStatus **IxEthAccPortDuplexModeGet** (**IxEthAccPortId** portId, **IxEthAccDuplexMode** *mode)

Get the duplex mode for the MAC.

PUBLIC
IxEthAccStatus **IxEthAccPortTxFrameAppendPaddingEnable** (**IxEthAccPortId** portId)
Enable padding bytes to be appended to runt frames submitted to this port.

PUBLIC
IxEthAccStatus **IxEthAccPortTxFrameAppendPaddingDisable** (**IxEthAccPortId** portId)
Disable padding bytes to be appended to runt frames submitted to this port.

PUBLIC
IxEthAccStatus **IxEthAccPortTxFrameAppendFCSEnable** (**IxEthAccPortId** portId)
Enable the appending of Ethernet FCS to all frames submitted to this port.

PUBLIC
IxEthAccStatus **IxEthAccPortTxFrameAppendFCSDisable** (**IxEthAccPortId** portId)
Disable the appending of Ethernet FCS to all frames submitted to this port.

PUBLIC
IxEthAccStatus **IxEthAccPortRxFrameAppendFCSEnable** (**IxEthAccPortId** portId)
Forward frames with FCS included in the receive buffer.

PUBLIC
IxEthAccStatus **IxEthAccPortRxFrameAppendFCSDisable** (**IxEthAccPortId** portId)
Do not forward the FCS portion of the received Ethernet frame to the user. The FCS is striped from the receive buffer. The received frame length does not include the FCS size (4 bytes). Frame FCS validity checks are still carried out on all received frames.

PUBLIC
IxEthAccStatus **IxEthAccTxSchedulingDisciplineSet** (**IxEthAccPortId** portId, **IxEthAccSchedulerDiscipline** sched)
Set the port scheduling to one of IxEthAccSchedulerDiscipline.

PUBLIC
IxEthAccStatus **IxEthAccRxSchedulingDisciplineSet** (**IxEthAccSchedulerDiscipline** sched)
Set the Rx scheduling to one of IxEthAccSchedulerDiscipline.

PUBLIC
IxEthAccStatus **IxEthAccPortNpeLoopbackEnable** (**IxEthAccPortId** portId)

PUBLIC
IxEthAccStatus **IxEthAccPortNpeLoopbackDisable** (**IxEthAccPortId** portId)
Disable NPE loopback.

PUBLIC
IxEthAccStatus **IxEthAccPortTxEnable** (**IxEthAccPortId** portId)
Enable Tx on the port.

PUBLIC
IxEthAccStatus **IxEthAccPortTxDisable** (**IxEthAccPortId** portId)

Disable Tx on the port.

PUBLIC

IxEthAccStatus ixEthAccPortRxEnable (IxEthAccPortId portId)

Enable Rx on the port.

PUBLIC

IxEthAccStatus ixEthAccPortRxDisable (IxEthAccPortId portId)

Disable Rx on the port.

PUBLIC

IxEthAccStatus ixEthAccPortMacReset (IxEthAccPortId portId)

Reset MAC core on the port.

PUBLIC void **ixEthAccQMgrRxNotificationDisable (void)**

Disable queue interrupts for all Rx queues.

PUBLIC void **ixEthAccQMgrRxNotificationEnable (void)**

Enable queue interrupts for all Rx queues.

PUBLIC void **ixEthAccQMgrRxQEntryGet (UINT32 *numEntries)**

Get the total number of receive buffers in all rx queues.

PUBLIC

IxEthAccStatus ixEthAccStopRequest (void)

Request Ethernet access layer to stop Tx and Rx Services for all the Ethernet ports.

PUBLIC

IxEthAccStatus ixEthAccStartRequest (void)

Request Ethernet access layer to restart its currently stopped Tx and Rx Services for all the Ethernet ports.

PUBLIC BOOL **ixEthAccStopDoneCheck (void)**

Checks whether the Ethernet traffic service is stopped completely.

PUBLIC

IxEthAccStatus ixEthAccQMStatusUpdate (IxEthAccPortId portId)

To retrigger the update of queue condition (interrupt and status flag) in order to restore these states that are lost during soft-error handling. This ensures Eth-NPE to continue its services.

PUBLIC

IxEthAccStatus ixEthAccMibIIStatsGet (IxEthAccPortId portId, IxEthEthObjStats *retStats)

Returns the statistics maintained for a port.

PUBLIC

IxEthAccStatus ixEthAccMibIIStatsGetClear (IxEthAccPortId portId, IxEthEthObjStats *retStats)

Returns and clears the statistics maintained for a port.

PUBLIC

IxEthAccStatus ixEthAccMibIIStatsClear (IxEthAccPortId portId)

Clears the statistics maintained for a port.

PUBLIC

IxEthAccStatus **ixEthAccMacInit** (**IxEthAccPortId** portId)

Initializes the ethernet MAC settings.

PUBLIC

IxEthAccStatus **ixEthAccMacUninit** (**IxEthAccPortId** portId)

Un-Initializes the ethernet MAC settings.

PUBLIC

IxEthAccStatus **ixEthAccMacStateRestore** (**IxEthAccPortId** portId)

This function reconfigures the MAC Registers according to the settings in use prior to the occurrence of a soft-error in the NPE.

PUBLIC void **ixEthAccStatsShow** (**IxEthAccPortId** portId)

Displays a ports statistics on the standard io console using printf.

PUBLIC

IxEthAccStatus **ixEthAccMiiReadRtn** (UINT8 phyAddr, UINT8 phyReg, UINT16 *value)

Reads a 16 bit value from a PHY.

PUBLIC

IxEthAccStatus **ixEthAccMiiWriteRtn** (UINT8 phyAddr, UINT8 phyReg, UINT16 value)

Writes a 16 bit value to a PHY.

PUBLIC

IxEthAccStatus **ixEthAccMiiAccessTimeoutSet** (UINT32 timeout, UINT32 retryCount)

PUBLIC

IxEthAccStatus **ixEthAccMiiStatsShow** (UINT32 phyAddr)

Displays detailed information on a specified PHY.

Detailed Description

ethAcc is a library that does provides access to the internal IXP4XX Product Line of Network Processors 10/100Bt Ethernet MACs.

Define Documentation

```
#define IX_ETH_ACC_NUM_TX_PRIORITIES
```

Definition of the number of transmit priorities.

Definition at line **110** of file **IxEthAcc.h**.

```
#define IX_ETH_ACC_NUMBER_OF_PORTS
```

Definition of the number of ports.

Definition at line **78** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_BCASTMASK
```

This mask defines if a received frame is a broadcast frame.

This mask defines if a received frame is a broadcast frame. The BCAST flag is set when the destination MAC address of a frame is broadcast.

See also:

IX_ETHACC_NE_FLAGS

Definition at line **325** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_DESTMAC ( mBufPtr )
```

The location of the destination MAC address in the Mbuf header.

Definition at line **214** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_DESTPORTID ( mBufPtr )
```

The destination port where this frame should be sent.

The destination port where this frame should be sent.

- In the transmit direction, this field contains the destination port and is ignored unless *IX_ETHACC_NE_FLAG_DST* is set.
- In the receive direction, this field contains the port where the destination MAC addresses has been learned. If the destination MAC address is unknown, then this value is set to the reserved value *IX_ETHACC_NE_PORT_UNKNOWN*

Definition at line **273** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_FILTERMASK
```

This bit indicates whether a frame has been filtered by the Rx service.

This mask applies to *IX_ETHACC_NE_FLAGS*. Certain frames, which should normally be fully filtered by the NPE to due the destination MAC address being on the same segment as the Rx port are still forwarded

to the XScale (although the payload is invalid) in order to learn the MAC address of the transmitting station, if this is unknown. Normally EthAcc will filter and recycle these frames internally and no frames with the FILTER bit set will be received by the client.

See also:

IX_ETHACC_NE_FLAGS

Definition at line **432** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_FLAGS ( mBufPtr )
```

Bit Mask of the different flags associated with a frame.

The flags are the bit-oring combination of the following different fields :

- IP flag (Rx *IX_ETHACC_NE_IPMASK*)
- Spanning Tree flag (Rx *IX_ETHACC_NE_STMASK*)
- Link layer type (Rx and Tx *IX_ETHACC_NE_LINKMASK*)
- VLAN Tagged Frame (Rx *IX_ETHACC_NE_VLANMASK*)
- New source MAC address (Rx *IX_ETHACC_NE_NEWSRCMASK*)
- Multicast flag (Rx *IX_ETHACC_NE_MCASTMASK*)
- Broadcast flag (Rx *IX_ETHACC_NE_BCASTMASK*)
- Destination port flag (Tx *IX_ETHACC_NE_PORTMASK*)
- Tag/Untag Tx frame (Tx *IX_ETHACC_NE_TAGMODEMASK*)
- Overwrite destination port (Tx *IX_ETHACC_NE_PORTOVERMASK*)
- Filtered frame (Rx *IX_ETHACC_NE_STMASK*)
- VLAN Enabled (Rx and Tx *IX_ETHACC_NE_VLANENABLEMASK*)
- Local MAC (Rx *IX_ETHACC_NE_LOCALMACMASK*)

Definition at line **309** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_IPMASK
```

This mask defines if a received frame is a IP frame.

This mask applies to *IX_ETHACC_NE_FLAGS* and defines if a received frame is a IPv4 frame. The IP flag is set on Rx direction, depending on the frame contents. The flag is set when the length/type field of a received frame is 0x8000.

See also:

IX_ETHACC_NE_FLAGS

Definition at line **358** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_IPV6MASK
```

This mask defines if a received frame is a IP frame.

This mask applies to *IX_ETHACC_NE_FLAGS* and defines if a received frame is a IPv6 frame. The IP flag is set on Rx direction, depending on the frame contents. The flag is set when the length/type field of a received frame is 0x86DD.

See also:

IX_ETHACC_NE_FLAGS

Definition at line **375** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_LINKMASK
```

This mask is the link layer protocol indicator.

This mask applies to *IX_ETHACC_NE_FLAGS*. It reflects the state of a frame as it exits an NPE on the Rx path or enters an NPE on the Tx path. Its values are as follows:

- 0x00 – IEEE802.3 – 8802 (Rx) / IEEE802.3 – 8802 (Tx)
- 0x01 – IEEE802.3 – Ethernet (Rx) / IEEE802.3 – Ethernet (Tx)
- 0x02 – IEEE802.11 AP -> STA (Rx) / IEEE802.11 STA -> AP (Tx)
- 0x03 – IEEE802.11 AP -> AP (Rx) / IEEE802.11 AP->AP (Tx)

See also:

IX_ETHACC_NE_FLAGS

Definition at line **395** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_LOCALMACMASK
```

This mask defines the rule to receive a frame to local mac.

This mask defines the rule to receive a frame to local mac. When set, the default receive rules of a port are overridden. When not set, the default rules as set by **Intel (R) IXP400 Software Ethernet Database (IxEthDB) API** should apply.

See also:

IX_ETHACC_NE_FLAGS

IX_ETHACC_NE_LOCALMACMASK

Definition at line **506** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_MCASTMASK
```

This mask defines if a received frame is a multicast frame.

This mask defines if a received frame is a multicast frame. The MCAST flag is set when the destination MAC address of a frame is multicast.

See also:

IX_ETHACC_NE_FLAGS

Definition at line **341** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_NEWSRCMASK
```

This mask defines if a received frame has been learned.

This mask defines if the source MAC address of a frame is already known. If the bit is set, the source MAC address was unknown to the NPE at the time the frame was received.

See also:

IX_ETHACC_NE_FLAGS

Definition at line **562** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_PADLENGTH ( mBufPtr )
```

The location of the number of padding bytes in the Mbuf header.

Definition at line **204** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_PORT_UNKNOWN
```

Contents of the field *IX_ETHACC_NE_DESTPORTID* when no destination port can be found by the NPE for this frame.

Definition at line **194** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_PORTOVERMASK
```

This mask defines the rule to transmit a frame.

This mask defines the rule to transmit a frame. When set, a frame is transmitted to the destination port as set by the macro *IX_ETHACC_NE_DESTPORTID*. If not set, the destination port is searched using the destination MAC address.

Note:

This flag is meaningful only for multiport Network Engines.

See also:

IX_ETHACC_NE_FLAGS

IX_ETHACC_NE_DESTPORTID

Definition at line **452** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_QOS ( mBufPtr )
```

QualityOfService class (QoS) for this received frame.

Definition at line **283** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_SOURCEMAC ( mBufPtr )
```

The location of the source MAC address in the Mbuf header.

Definition at line **224** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_SOURCEPORTID ( mBufPtr )
```

The port where this frame came from.

The port where this frame came from. This field is set on receive with the port information. This field is ignored on Transmit path.

Definition at line **253** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_STMASK
```

This mask defines if a received frame is a Spanning Tree frame.

This mask applies to *IX_ETHACC_NE_FLAGS*. On rx direction, it defines if a received if frame is a Spanning Tree frame. Setting this fflag on transmit direction overrides the port settings regarding the VLAN options and

See also:

IX_ETHACC_NE_FLAGS

Definition at line **412** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_TAGMODEMASK
```

This mask defines the tagging rules to apply to a transmit frame.

This mask defines the tagging rules to apply to a transmit frame regardless of the default setting for a port. When used together with *IX_ETHACC_NE_TAGOVERMASK* and when set, the frame will be tagged prior to transmission. When not set, the frame will be untagged prior to transmission. This is accomplished irrespective of the Egress tagging rules, constituting a per-frame override.

See also:

IX_ETHACC_NE_FLAGS

IX_ETHACC_NE_TAGOVERMASK

Definition at line **472** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_TAGOVERMASK
```

This mask defines the rule to transmit a frame.

This mask defines the rule to transmit a frame. When set, the default transmit rules of a port are overridden. When not set, the default rules as set by **Intel (R) IXP400 Software Ethernet Database (IxEthDB) API** should apply.

See also:

IX_ETHACC_NE_FLAGS

IX_ETHACC_NE_TAGMODEMASK

Definition at line **489** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_VLANENABLEMASK
```

This mask defines if a frame is a VLAN frame or not.

When set, frames undergo normal VLAN processing on the Tx path (membership filtering, tagging, tag removal etc). If this flag is not set, the frame is considered to be a regular non-VLAN frame and no VLAN processing will be performed.

Note that VLAN-enabled NPE images will always set this flag in all Rx frames, and images which are not VLAN enabled will clear this flag for all received frames.

See also:

IX_ETHACC_NE_FLAGS

Definition at line **546** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_VLANMASK
```

This mask defines if a received frame is VLAN tagged.

This mask defines if a received frame is VLAN tagged. When set, the Rx frame is VLAN-tagged and the tag value is available thru *IX_ETHACC_NE_VLANID*. Note that when sending frames which are already tagged this flag should be set, to avoid inserting another VLAN tag.

See also:

IX_ETHACC_NE_FLAGS

IX_ETHACC_NE_VLANID

Definition at line **525** of file **IxEthAcc.h**.

```
#define IX_ETHACC_NE_VLANTCI ( mBufPtr )
```

The VLAN Tag Control Information associated with this frame.

The VLAN Tag Control Information associated with this frame. On Rx path, this field is extracted from the packet header. On Tx path, the value of this field is inserted in the frame when the port is configured to insert or replace vlan tags in the egress frames.

See also:

IX_ETHACC_NE_FLAGS

Definition at line **241** of file **IxEthAcc.h**.

```
#define IX_ETHACC_RX_MBUF_MIN_SIZE
```

This defines the recommended minimum size of MBUF's submitted to the frame receive service.

Definition at line **571** of file **IxEthAcc.h**.

```
#define IX_IEEE803_MAC_ADDRESS_SIZE
```

Definition of the size of the MAC address.

Definition at line **88** of file **IxEthAcc.h**.

```
#define ixEthAccMiiLinkStatus ( phyAddr,  
                                linkUp,  
                                speed100,  
                                fullDuplex,  
                                autoneg    )
```

: deprecated API entry point. This definition ensures backward compatibility

See **ixEthMiiLinkStatus**

Note:

this feature is board specific

Definition at line **2886** of file **IxEthAcc.h**.

```
#define ixEthAccMiiPhyConfig ( phyAddr,  
                                speed100,  
                                fullDuplex,  
                                autonegotiate )
```

: deprecated API entry point. This definition ensures backward compatibility

See **ixEthMiiPhyConfig**

Note:

this feature is board specific

Definition at line **2856** of file **IxEthAcc.h**.

```
#define ixEthAccMiiPhyReset ( phyAddr )
```

: deprecated API entry point. This definition ensures backward compatibility

See **ixEthMiiPhyReset**

Note:

this feature is board specific

Definition at line **2871** of file **IxEthAcc.h**.

```
#define ixEthAccMiiPhyScan ( phyPresent )
```

: deprecated API entry point. This definition ensures backward compatibility

See **ixEthMiiPhyScan**

Note:

this feature is board specific

Definition at line **2842** of file **IxEthAcc.h**.

```
#define ixEthAccMiiShow ( phyAddr )
```

: deprecated API entry point. This definition ensures backward compatibility

See **ixEthMiiPhyShow**

Note:

this feature is board specific

Definition at line **2903** of file **IxEthAcc.h**.

```
#define IxEthAccTxSchedulerDiscipline
```

Deprecated definition for the port transmit scheduling discipline.

Definition at line **1919** of file **IxEthAcc.h**.

```
ixEthRxMultiBufferPriorityPoll
```

Following definition providing backward compatibility to **ixEthRxMultiBufferPriorityPoll()** function that will be deprecated in future release.

Definition at line **976** of file **IxEthAcc.h**.

```
#define ixEthRxPriorityPoll
```

Following definition providing backward compatibility to **ixEthRxPriorityPoll()** function that will be deprecated in future release.

Definition at line **943** of file **IxEthAcc.h**.

```
#define IXP400_ETH_ACC_MII_MAX_ADDR
```

This defines the highest MII address of any attached PHYs.

The maximum number for PHY address is 31, add on for range checking.

Definition at line **581** of file **IxEthAcc.h**.

```
#define IXP425_ETH_ACC_MII_MAX_ADDR
```

This defines the highest MII address of any attached PHYs.

The maximum number for PHY address is 31, add on for range checking. This is maintained to provide backward compatibility. It will be deprecated in future release.

Definition at line **593** of file **IxEthAcc.h**.

Typedef Documentation

```
typedef void(* IxEthAccPortMultiBufferRxCallback)(UINT32 callbackTag, IX_OSAL_MBUF **buffer)
```

Function prototype for Ethernet Frame Rx callback. Registered via *ixEthAccPortMultiBufferRxCallbackRegister*.

It is the responsibility of the user function to free any MBUF's which it receives.

- Reentrant – yes , The user provided function should be reentrant.
- ISR Callable – yes , The user provided function must be callable from an ISR.
This function dispatches many frames to the user level via the provided function. The invocation shall be made for multiple frames dequeued from the Ethernet QM queue. The user is required to free any MBUF's supplied via this callback. In addition the registered callback must free up MBUF's from the receive free queue when the port is disabled
If called several times the latest callback shall be registered for a particular port.

Calling Context :

This callback is called in the context of the queue manager dispatch loop *ixQmgrDispatcherLoopRun* within the **IXP Queue Manager (qmgr) Public API** component. The calling context may be from interrupt or high priority thread. The decision is system specific.

Parameters:

callbackTag – This tag is that provided when the callback was registered for a particular MAC via *ixEthAccPortMultiBufferRxCallbackRegister*. It allows the same callback to be used for multiple MACs.

mbuf – Pointer to an array of Rx mbuf headers. Mbufs may be chained if the frame length is greater than the supplied mbuf length. The end of the array contains a zeroed entry (NULL pointer).

Returns:

void

Note:

The mbufs passed to this callback have the same structure than the buffers passed to *IxEthAccPortRxCallback* interfaz.

The usage of this callback is exclusive with the usage of *ixEthAccPortRxCallbackRegister* and *IxEthAccPortRxCallback*

See also:

ixEthAccPortMultiBufferRxCallbackRegister

IxEthAccPortMultiBufferRxCallback

ixEthAccPortRxCallbackRegister

IxEthAccPortRxCallback

Definition at line **932** of file **IxEthAcc.h**.

```
typedef void(* IxEthAccPortRxCallback)(UINT32 callbackTag, IX_OSAL_MBUF *buffer, UINT32 reserved)
```

Function prototype for Ethernet Frame Rx callback. Registered via *ixEthAccPortRxCallbackRegister*.

It is the responsibility of the user function to free any MBUF's which it receives.

- Reentrant – yes , The user provided function should be reentrant.
- ISR Callable – yes , The user provided function must be callable from an ISR.
This function dispatches frames to the user level via the provided function. The invocation shall be made for each frame dequeued from the Ethernet QM queue. The user is required to free any MBUF's supplied via this callback. In addition the registered callback must free up MBUF's from the receive free queue when the port is disabled
If called several times the latest callback shall be registered for a particular port.

Calling Context :

This callback is called in the context of the queue manager dispatch loop *ixQmgrgrDispatcherLoopRun* within the **IXP Queue Manager (qmgr) Public API** component. The calling context may be from interrupt or high priority thread. The decision is system specific.

Parameters:

callbackTag UINT32 [in] – This tag is that provided when the callback was registered for a particular MAC via *ixEthAccPortRxCallbackRegister*. It allows the same callback to be used for multiple MACs.

mbuf [in] – Pointer to the Rx mbuf header. Mbufs may be chained if the frame length is greater than the supplied mbuf length.

reserved [in] – deprecated parameter The information is passed thru the **IxEthAccNe** header destination port ID field (

See also:

IX_ETHACC_NE_DESTPORTID). For backward compatibility, the value is equal to **IX_ETH_DB_UNKNOWN_PORT** (0xff).

Returns:

void

Note:

Buffers may not be filled up to the length supplied in *ixEthAccPortRxFreeReplenish()*. The firmware fills them to the previous 64 bytes boundary. The user has to be aware that the length of the received mbufs may be smaller than the length of the supplied mbufs. The mbuf header contains the following modified field

- ◇ **IX_OSAL_MBUF_PKT_LEN** is set in the header of the first mbuf and indicates the total frame size
- ◇ **IX_OSAL_MBUF_MLEN** is set each mbuf header and indicates the payload length
- ◇ **IX_OSAL_MBUF_NEXT_BUFFER_IN_PKT_PTR** contains a pointer to the next mbuf, or NULL at the end of a chain.
- ◇ **IX_OSAL_MBUF_NEXT_PKT_IN_CHAIN_PTR** is modified. Its value is reset to NULL

◇ *IX_OSAL_MBUF_FLAGS* contains the bit 4 set for a broadcast packet and the bit 5 set for a multicast packet. Other bits are unmodified.

Definition at line **882** of file **IxEthAcc.h**.

```
typedef void(* IxEthAccPortTxDoneCallback)( UINT32 callbackTag, IX_OSAL_MBUF *buffer )
```

Function prototype for Ethernet Tx Buffer Done callback. Registered via *ixEthAccTxBufferDoneCallbackRegister*.

This function is called once the previously submitted buffer is no longer required by this service. It may be returned upon successful transmission of the frame or during the shutdown of the port prior to the transmission of a queued frame. The calling of this registered function is not a guarantee of successful transmission of the buffer.

- Reentrant – yes , The user provided function should be reentrant.
- ISR Callable – yes , The user provided function must be callable from an ISR.

Calling Context :

This callback is called in the context of the queue manager dispatch loop *ixQmgrgrDispatcherLoopRun* within the **IXP Queue Manager (qmgr) Public API** component. The calling context may be from interrupt or high priority thread. The decision is system specific.

Parameters:

callbackTag UINT32 [in] – This tag is that provided when the callback was registered for a particular MAC via *ixEthAccPortTxDoneCallbackRegister*. It allows the same callback to be used for multiple MACs.

mbuf [in] – Pointer to the Tx mbuf descriptor.

Returns:

void

Note:

The field *IX_OSAL_MBUF_NEXT_PKT_IN_CHAIN_PTR* is modified by the access layer and reset to NULL.

Definition at line **779** of file **IxEthAcc.h**.

Enumeration Type Documentation

```
enum IxEthAccDuplexMode
```

Definition to provision the duplex mode of the MAC.

Enumeration values:

IX_ETH_ACC_FULL_DUPLEX

Full duplex operation of the MAC.

IX_ETH_ACC_HALF_DUPLEX Half duplex operation of the MAC.

Definition at line **155** of file **IxEthAcc.h**.

enum IxEthAccPortId

Definition of the IXP400 Mac Ethernet device.

Enumeration values:

IX_ETH_PORT_1 Ethernet Port 1.

IX_ETH_PORT_2 Ethernet port 2.

IX_ETH_PORT_3 Ethernet port 3.

Definition at line **52** of file **IxEthAcc.h**.

enum IxEthAccRxFrameType

Identify the type of a frame.

See also:

IX_ETHACC_NE_FLAGS

IX_ETHACC_NE_LINKMASK

Enumeration values:

IX_ETHACC_RX_LLCTYPE 802.3 – 8802, with
LLC/SNAP

IX_ETHACC_RX_ETHTYPE 802.3 (Ethernet) without
LLC/SNAP

IX_ETHACC_RX_STATYPE 802.11, AP <=> STA

IX_ETHACC_RX_APTYPE 802.11, AP <=> AP

Definition at line **141** of file **IxEthAcc.h**.

enum IxEthAccSchedulerDiscipline

Definition for the port scheduling discipline.

Select the port scheduling discipline on receive and transmit path

- **FIFO : No Priority** : In this configuration all frames are processed in the access component in the strict order in which the component received them.

- **FIFO : Priority :** This shall be a very simple priority mechanism. Higher priority frames shall be forwarded before lower priority frames. There shall be no fairness mechanisms applied across different priorities. Higher priority frames could starve lower priority frames indefinitely.

Enumeration values:

FIFO_NO_PRIORITY frames submitted with no priority
FIFO_PRIORITY higher priority frames submitted before lower priority

Definition at line **1906** of file **IxEthAcc.h**.

```
enum IxEthAccStatus
```

Definition of the Ethernet Access status.

Enumeration values:

<i>IX_ETH_ACC_SUCCESS</i>	return success
<i>IX_ETH_ACC_FAIL</i>	return fail
<i>IX_ETH_ACC_INVALID_PORT</i>	return invalid port
<i>IX_ETH_ACC_PORT_UNINITIALIZED</i>	return uninitialized
<i>IX_ETH_ACC_MAC_UNINITIALIZED</i>	return MAC uninitialized
<i>IX_ETH_ACC_INVALID_ARG</i>	return invalid arg
<i>IX_ETH_TX_Q_FULL</i>	return tx queue is full
<i>IX_ETH_ACC_NO_SUCH_ADDR</i>	return no such address

Definition at line **35** of file **IxEthAcc.h**.

```
enum IxEthAccTxPriority
```

Definition of the relative priority used to transmit a frame.

Enumeration values:

<i>IX_ETH_ACC_TX_PRIORITY_0</i>	Lowest Priority submission.
<i>IX_ETH_ACC_TX_PRIORITY_1</i>	submission priority of 1 (0 is lowest)
<i>IX_ETH_ACC_TX_PRIORITY_2</i>	submission priority of 2 (0 is lowest)
<i>IX_ETH_ACC_TX_PRIORITY_3</i>	submission priority of 3 (0 is lowest)
<i>IX_ETH_ACC_TX_PRIORITY_4</i>	submission priority of 4 (0 is lowest)
<i>IX_ETH_ACC_TX_PRIORITY_5</i>	submission priority of 5 (0 is lowest)
<i>IX_ETH_ACC_TX_PRIORITY_6</i>	submission priority of 6 (0 is lowest)
<i>IX_ETH_ACC_TX_PRIORITY_7</i>	Highest priority submission.
<i>IX_ETH_ACC_TX_DEFAULT_PRIORITY</i>	By default send all packets with lowest priority.

Function Documentation

ixEthAccInit (void)

Initializes the Intel (R) IXP400 Software Ethernet Access Service.

- Reentrant – yes
- ISR Callable – no

This should be called once per module initialization. Second call to this function yields SUCCESS.

Precondition:

The NPE must first be downloaded with the required microcode which supports all required features.

Returns:

IxEthAccStatus

◇ *IX_ETH_ACC_SUCCESS* : Init Done successfully or already initialized

◇ *IX_ETH_ACC_FAIL* : Service has failed to initialize – EthDB, Dataplane, MII, MemInit, Mutex Init.

ixEthAccMacInit (**IxEthAccPortId** portId)

Initializes the ethernet MAC settings.

- Reentrant – no
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

◇ *IX_ETH_ACC_SUCCESS*

◇ *IX_ETH_ACC_INVALID_PORT* :
portId is invalid.

IxEthAccStatus ixEthAccMacStateRestore (**IxEthAccPortId** portId)

This function reconfigures the MAC Registers according to the settings in use prior to the occurrence of a soft-error in the NPE.

- Reentrant – no
- ISR Callable – no

Note:

The function is useful for error–handling module to handle soft–error in Ethernet NPE.

Precondition:

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

- ◊ *IX_ETH_ACC_SUCCESS* : MAC settings are reupdated
 - ◊ *IX_ETH_ACC_FAIL* : MAC settings are not reupdated
 - ◊ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 - ◊ *IX_ETH_ACC_PORT_UNINITIALIZED* : PORT is not initialized
 - ◊ *IX_ETH_ACC_MAC_UNINITIALIZED* : port MAC address is not initialized
-

ixEthAccMacUninit (IxEthAccPortId portId)

Un–Initializes the ethernet MAC settings.

- Reentrant – no
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

- ◊ *IX_ETH_ACC_SUCCESS*
 - ◊ *IX_ETH_ACC_INVALID_PORT* :
portId is invalid.
-

ixEthAccMibIIStatsClear (IxEthAccPortId portId)

Clears the statistics maintained for a port.

- Reentrant – yes
- ISR Callable – no

Precondition:

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_FAIL* : Invalid arguments.
 ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

```

ixEthAccMibIStatsGet ( IxEthAccPortId    portId,
                      IxEthEthObjStats * retStats
                      )

```

Returns the statistics maintained for a port.

- Reentrant – yes
- ISR Callable – no

Precondition:**Parameters:**

portId **IxEthAccPortId** [in]
retStats **IxEthEthObjStats** [out]

Note:

Please note the user is responsible for cache coherency of the retStat buffer. The data is actually populated via the NPE's. As such cache safe memory should be used in the retStats argument.

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_FAIL* : Invalid arguments.
 ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

```

ixEthAccMibIStatsGetClear ( IxEthAccPortId    portId,
                           IxEthEthObjStats * retStats
                           )

```

Returns and clears the statistics maintained for a port.

- Reentrant – yes
- ISR Callable – yes

Precondition:

Parameters:

portId **IxEthAccPortId** [in]
retStats **IxEthEthObjStats** [out]

Note:

Please note the user is responsible for cache coherency of the *retStats* buffer. The data is actually populated via the NPE's. As such cache safe memory should be used in the *retStats* argument.

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_FAIL* : invalid arguments.
 ◇ *IX_ETH_ACC_INVALID_PORT* : *portId* is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : *portId* is un-initialized

```
ixEthAccMiiReadRtn (  UINT8   phyAddr,
                      UINT8   phyReg,
                      UINT16 * value
                      )
```

Reads a 16 bit value from a PHY.

Reads a 16-bit word from a register of a MII-compliant PHY. Reading is performed through the MII management interface. This function returns when the read operation has successfully completed, or when a timeout has elapsed.

- Reentrant – no
- ISR Callable – no

Precondition:

The MAC on Ethernet Port 2 (NPE C) must be initialised, and generating the MDIO clock.

Parameters:

phyAddr **UINT8** [in] – the address of the Ethernet PHY (0–31)
phyReg **UINT8** [in] – the number of the MII register to read (0–31)
value **UINT16** [in] – the value read from the register

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_FAIL* : failed to read the register.

```
ixEthAccMiiStatsShow (  UINT32 phyAddr )
```

Displays detailed information on a specified PHY.

Displays the current values of the first eight MII registers for a PHY,

- Reentrant – no
- ISR Callable – no

Precondition:

The MAC on Ethernet Port 2 (NPE C) must be initialised, and generating the MDIO clock.

Parameters:

phyAddr UINT32 [in] – the address of the Ethernet PHY (0–31)

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_FAIL* : invalid arguments.

```
ixEthAccMiiWriteRtn (  UINT8  phyAddr,  
                          UINT8  phyReg,  
                          UINT16 value  
                      )
```

Writes a 16 bit value to a PHY.

Writes a 16-bit word from a register of a MII-compliant PHY. Writing is performed through the MII management interface. This function returns when the write operation has successfully completed, or when a timeout has elapsed.

- Reentrant – no
- ISR Callable – no

Precondition:

The MAC on Ethernet Port 2 (NPE C) must be initialised, and generating the MDIO clock.

Parameters:

phyAddr UINT8 [in] – the address of the Ethernet PHY (0–31)
phyReg UINT8 [in] – the number of the MII register to write (0–31)
value UINT16 [out] – the value to write to the register

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_FAIL* : failed to write register.

```
ixEthAccPortDisable ( IxEthAccPortId portId )
```


This disables an Ethernet port for both Tx and Rx.

Free MBufs are returned to the user via the registered callback when the port is disabled

- Reentrant – yes
- ISR Callable – no

Precondition:

The port must be enabled with *ixEthAccPortEnable*, otherwise this function has no effect

Parameters:

portId **IxEthAccPortId** [in] – Port id to act upon.

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is not initialized
 ◇ *IX_ETH_ACC_MAC_UNINITIALIZED* : port MAC address is not initialized

```
ixEthAccPortDuplexModeGet ( IxEthAccPortId      portId,  
                           IxEthAccDuplexMode * mode  
                           )
```

Get the duplex mode for the MAC.

return the duplex configuration of the IXP400 MAC.

Note:

The configuration should match that provisioned on the PHY. See *ixEthAccDuplexModeSet*

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in]
mode* **IxEthAccDuplexMode [out]

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

```

ixEthAccPortDuplexModeSet ( IxEthAccPortId      portId,
                           IxEthAccDuplexMode mode
                           )

```

Set the duplex mode for the MAC.

Configure the IXP400 MAC to either full or half duplex.

Note:

The configuration should match that provisioned on the PHY.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in]
mode **IxEthAccDuplexMode** [in]

Returns:

IxEthAccStatus
 ◇ **IX_ETH_ACC_SUCCESS**
 ◇ **IX_ETH_ACC_INVALID_PORT** : *portId* is invalid.
 ◇ **IX_ETH_ACC_PORT_UNINITIALIZED** : *portId* is un-initialized

```

ixEthAccPortEnable ( IxEthAccPortId portId )

```

This enables an Ethernet port for both Tx and Rx.

- Reentrant – yes
- ISR Callable – no

Precondition:

The port must first be initialized via *ixEthAccPortInit* and the MAC address must be set using *ixEthAccUnicastMacAddressSet* before enabling it. The rx and Tx Done callbacks registration via *ixEthAccPortTxDoneCallbackRegister* and *ixEthAccPortRxCallbackRegister* has to be done before enabling the traffic.

Parameters:

portId **IxEthAccPortId** [in] – Port id to act upon.

Returns:

IxEthAccStatus
 ◇ **IX_ETH_ACC_SUCCESS**
 ◇ **IX_ETH_ACC_INVALID_PORT** : *portId* is invalid.
 ◇ **IX_ETH_ACC_PORT_UNINITIALIZED** : *portId* is not initialized

◇ *IX_ETH_ACC_MAC_UNINITIALIZED* : port MAC address is not initialized

```
ixEthAccPortEnabledQuery ( IxEthAccPortId portId,  
                           BOOL *      enabled  
                           )
```

Get the enabled state of a port.

- Reentrant – yes
- ISR Callable – yes

Precondition:

The port must first be initialized via *ixEthAccPortInit*

Parameters:

portId **IxEthAccPortId** [in] – Port id to act upon.
enabled BOOL [out] – location to store the state of the port

Returns:

IxEthAccStatus
◇ *IX_ETH_ACC_SUCCESS*
◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid

```
ixEthAccPortInit ( IxEthAccPortId portId )
```

Initializes an NPE/Ethernet MAC Port.

The NPE/Ethernet port initialisation includes the following steps

- Initialize the NPE/Ethernet MAC hardware.
 - Verify NPE downloaded and operational.
 - The NPE shall be available for usage once this API returns.
 - Verify that the Ethernet port is present before initializing
-
- Reentrant – no
 - ISR Callable – no

This should be called once per mac device. The NPE/MAC shall be in disabled state after init.

Precondition:

The component must be initialized via *ixEthAccInit* The NPE must first be downloaded with the required microcode which supports all required features.

Dependant on Services: (Must be initialized before using this service may be initialized) ixNPEmh – NPE Message handling service. ixQmgr – Queue Manager component.

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

- ◇ *IX_ETH_ACC_SUCCESS*: if the ethernet port is not present, a warning is issued.
 - ◇ *IX_ETH_ACC_FAIL* : The NPE processor has failed to initialize.
 - ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
-

IxEthAccStatus ixEthAccPortMacReset (**IxEthAccPortId** *portId*)

Reset MAC core on the port.

This function will perform a MAC core reset (NPE Ethernet coprocessor). This function is inherently unsafe and the NPE recovery is not guaranteed after this function is called. The proper manner of performing port disable and enable (which will reset the MAC as well) is ixEthAccPortEnable/ixEthAccPortDisable.

This function is the recommended usage scenario for hardware failure recovery and should never be used for throttling traffic.

- Reentrant – yes
- ISR Callable – no

Precondition:

Note:

Calling ixEthAccPortDisable followed by ixEthAccPortEnable is guaranteed to restore correct Ethernet Tx/Rx operation.

Parameters:

portId **IxEthAccPortId** [in] : ID of the port

Returns:

IxEthAccStatus

- ◇ *IX_ETH_ACC_SUCCESS* : MAC core reset
 - ◇ *IX_ETH_ACC_FAIL* : Invalid port or Ethernet service not initialized
 - ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 - ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized
-

```

ixEthAccPortMultiBufferRxCallbackRegister ( IxEthAccPortId portId,
                                             IxEthAccPortMultiBufferRxCallback rxCallbackFn,
                                             UINT32 callbackTag
                                             )

```

Register a callback function to allow the reception of frames.

The registered callback function is called once a frame is received by this service. If many frames are already received, the function is called once.

If called several times the latest callback shall be registered for a particular port.

- Reentrant – yes
- ISR Callable – yes

Parameters:

portId **IxEthAccPortId** [in] – Register callback for a particular MAC device.
rxCallbackFn – *IxEthAccMultiBufferRxCallbackFn* – Function to be called when Ethernet frames are available.
callbackTag – This tag shall be provided to the callback function.

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized
 ◇ *IX_ETH_ACC_INVALID_ARG* : An argument other than portId is invalid.

See also:

ixEthAccPortMultiBufferRxCallbackRegister

IxEthAccPortMultiBufferRxCallback

ixEthAccPortRxCallbackRegister

IxEthAccPortRxCallback

```

ixEthAccPortMulticastAddressJoinAll ( IxEthAccPortId portId )

```

Filter all frames with multicast dest.

This function clears the MAC address table, and then sets the MAC to forward ALL multicast frames to the NPE. Specifically, it forwards all frames whose destination address has the LSB of the highest byte set (01:00:00:00:00:00). This bit is commonly referred to as the "multicast bit". Broadcast frames will still be forwarded.

Other functions modify the MAC filtering

- ***ixEthAccPortMulticastAddressJoinAll()*** – all multicast frames are forwarded to the application
- ***ixEthAccPortMulticastAddressLeaveAll()*** – rollback the effects of ***ixEthAccPortMulticastAddressJoinAll()***
- ***ixEthAccPortMulticastAddressLeave()*** – unprovision a new filtering address
- ***ixEthAccPortMulticastAddressJoin()*** – provision a new filtering address
- ***ixEthAccPortPromiscuousModeSet()*** – all frames are forwarded to the application regardless of the multicast address provisioned
- ***ixEthAccPortPromiscuousModeClear()*** – frames are forwarded to the application following the multicast address provisioned

In all cases, unicast and broadcast addresses are forwarded to the application.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in] – Ethernet port id.

Returns:

IxEthAccStatus
 ◇ ***IX_ETH_ACC_SUCCESS***
 ◇ ***IX_ETH_ACC_INVALID_PORT*** : *portId* is invalid.
 ◇ ***IX_ETH_ACC_PORT_UNINITIALIZED*** : *portId* is un–initialized

ixEthAccPortMulticastAddressLeaveAll (**IxEthAccPortId *portId*)**

This function unconfigures the multicast filtering settings.

This function first clears the MAC address table, and then sets the MAC as configured by the promiscuous mode current settings.

Other functions modify the MAC filtering

- ***ixEthAccPortMulticastAddressJoinAll()*** – all multicast frames are forwarded to the application
- ***ixEthAccPortMulticastAddressLeaveAll()*** – rollback the effects of ***ixEthAccPortMulticastAddressJoinAll()***
- ***ixEthAccPortMulticastAddressLeave()*** – unprovision a new filtering address
- ***ixEthAccPortMulticastAddressJoin()*** – provision a new filtering address
- ***ixEthAccPortPromiscuousModeSet()*** – all frames are forwarded to the application regardless of the multicast address provisioned
- ***ixEthAccPortPromiscuousModeClear()*** – frames are forwarded to the application following the multicast address provisioned

In all cases, unicast and broadcast addresses are forwarded to the application.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in] – Ethernet port id.

Returns:

IxEthAccStatus

◊ *IX_ETH_ACC_SUCCESS*

◊ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.

◊ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

ixEthAccPortMulticastAddressShow (**IxEthAccPortId** *portId*)

Displays multicast MAC address.

Displays multicast address which have been configured using *ixEthAccMulticastAddressJoin*

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in] – Ethernet port id.

Returns:

void

IxEthAccStatus **ixEthAccPortNpeLoopbackDisable** (**IxEthAccPortId** *portId*)

Disable NPE loopback.

This function is used to disable the NPE loopback if previously enabled using *ixEthAccNpeLoopbackEnable*.

This function is recommended for power-up diagnostic checks and should never be used under normal Ethernet traffic operations.

- Reentrant – yes
- ISR Callable – no

Precondition:

Note:

Calling *ixEthAccPortDisable* followed by *ixEthAccPortEnable* is guaranteed to restore correct Ethernet Tx/Rx operation.

Parameters:

portId **IxEthAccPortId** [in] : ID of the port

Returns:

IxEthAccStatus

- ◊ *IX_ETH_ACC_SUCCESS* : NPE loopback successfully disabled
 - ◊ *IX_ETH_ACC_FAIL* : Invalid port or Ethernet service not initialized
 - ◊ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 - ◊ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized
-

ixEthAccPortPromiscuousModeClear (**IxEthAccPortId** *portId*)

Put the Ethernet MAC device in non-promiscuous mode.

In non-promiscuous mode the MAC filters all frames other than destination MAC address which matches the following criteria:

- Unicast address provisioned via *ixEthAccUnicastMacAddressSet*
- All broadcast frames.
- Multicast addresses provisioned via *ixEthAccMulticastAddressJoin*

Other functions modify the MAC filtering

- *ixEthAccPortMulticastAddressJoinAll()* – all multicast frames are forwarded to the application
- *ixEthAccPortMulticastAddressLeaveAll()* – rollback the effects of *ixEthAccPortMulticastAddressJoinAll()*
- *ixEthAccPortMulticastAddressLeave()* – unprovision a new filtering address
- *ixEthAccPortMulticastAddressJoin()* – provision a new filtering address
- *ixEthAccPortPromiscuousModeSet()* – all frames are forwarded to the application regardless of the multicast address provisioned
- *ixEthAccPortPromiscuousModeClear()* – frames are forwarded to the application following the multicast address provisioned

In all cases, unicast and broadcast addresses are forwarded to the application.

- Reentrant – yes
- ISR Callable – no

See also:

ixEthAccPortPromiscuousModeSet

Parameters:

portId **IxEthAccPortId** [in] – Ethernet port id.

Returns:

IxEthAccStatus

- ◊ *IX_ETH_ACC_SUCCESS*
 - ◊ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 - ◊ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized
-


```
ixEthAccPortPromiscuousModeSet ( IxEthAccPortId portId )
```

Put the MAC device in promiscuous mode.

If the device is in promiscuous mode then all all received frames shall be forwarded to the NPE for processing.

Other functions modify the MAC filtering

- ***ixEthAccPortMulticastAddressJoinAll()*** – all multicast frames are forwarded to the application
- ***ixEthAccPortMulticastAddressLeaveAll()*** – rollback the effects of ***ixEthAccPortMulticastAddressJoinAll()***
- ***ixEthAccPortMulticastAddressLeave()*** – unprovision a new filtering address
- ***ixEthAccPortMulticastAddressJoin()*** – provision a new filtering address
- ***ixEthAccPortPromiscuousModeSet()*** – all frames are forwarded to the application regardless of the multicast address provisioned
- ***ixEthAccPortPromiscuousModeClear()*** – frames are forwarded to the application following the multicast address provisioned

In all cases, unicast and broadcast addresses are forwarded to the application.

- Reentrant – yes
- ISR Callable – no

See also:

ixEthAccPortPromiscuousModeClear

Parameters:

portId **IxEthAccPortId** [in] – Ethernet port id.

Returns:

IxEthAccStatus
 ◇ ***IX_ETH_ACC_SUCCESS***
 ◇ ***IX_ETH_ACC_INVALID_PORT*** : *portId* is invalid.
 ◇ ***IX_ETH_ACC_PORT_UNINITIALIZED*** : *portId* is un–initialized

```
ixEthAccPortRxCallbackRegister ( IxEthAccPortId          portId,
                                IxEthAccPortRxCallback rxCallbackFn,
                                UINT32                  callbackTag
                                )
```

Register a callback function to allow the reception of frames.

The registered callback function is called once a frame is received by this service.

If called several times the latest callback shall be registered for a particular port.

- Reentrant – yes

- ISR Callable – yes

Parameters:

portId **IxEthAccPortId** [in] – Register callback for a particular MAC device.
rxCallbackFn **IxEthAccPortRxCallback** [in] – Function to be called when Ethernet frames are available.
callbackTag UINT32 [in] – This tag shall be provided to the callback function.

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized
 ◇ *IX_ETH_ACC_INVALID_ARG* : An argument other than portId is invalid.

IxEthAccStatus ixEthAccPortRxDisable (**IxEthAccPortId** *portId*)

Disable Rx on the port.

This function can be used to disable Rx in the MAC core. Rx can be re-enabled, although this is not guaranteed, by performing a MAC core reset (*ixEthAccPortMacReset*) and calling ixEthAccPortRxEnable. Note that using this function is not recommended, except for shutting down Rx for emergency reasons. For proper port shutdown and re-enabling see ixEthAccPortEnable and ixEthAccPortDisable.

This function is the recommended usage scenario for emergency security shutdown and hardware failure recovery and should never be used for throttling traffic.

- Reentrant – yes
- ISR Callable – no

Precondition:

Note:

Calling ixEthAccPortDisable followed by ixEthAccPortEnable is guaranteed to restore correct Ethernet Tx/Rx operation.

Parameters:

portId : ID of the port

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS* : Rx successfully disabled
 ◇ *IX_ETH_ACC_FAIL* : Invalid port or Ethernet service not initialized
 ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

IxEthAccStatus ixEthAccPortRxEnable (**IxEthAccPortId** *portId*)

Enable Rx on the port.

This function is the complement of ixEthAccPortRxDisable and should be used only after Rx was disabled.

This function is the recommended usage scenario for emergency security shutdown and hardware failure recovery and should never be used for throttling traffic.

- Reentrant – yes
- ISR Callable – no

Note:

Calling ixEthAccPortDisable followed by ixEthAccPortEnable is guaranteed to restore correct Ethernet Tx/Rx operation.

Precondition:

Parameters:

portId **IxEthAccPortId** [in] : ID of the port

Returns:

IxEthAccStatus

- ◇ **IX_ETH_ACC_SUCCESS** : Rx successfully enabled
 - ◇ **IX_ETH_ACC_FAIL** : Invalid port or Ethernet service not initialized
 - ◇ **IX_ETH_ACC_INVALID_PORT** : portId is invalid.
 - ◇ **IX_ETH_ACC_PORT_UNINITIALIZED** : portId is un-initialized
-

ixEthAccPortRxFrameAppendFCSDisable (**IxEthAccPortId** *portId*)

Do not forward the FCS portion of the received Ethernet frame to the user. The FCS is striped from the receive buffer. The received frame length does not include the FCS size (4 bytes). Frame FCS validity checks are still carried out on all received frames.

This is the default behavior of the component. Do not change this behaviour while the port is enabled.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

- ◇ **IX_ETH_ACC_SUCCESS**
 - ◇ **IX_ETH_ACC_INVALID_PORT** : portId is invalid.
 - ◇ **IX_ETH_ACC_PORT_UNINITIALIZED** : portId is un-initialized
-

```
ixEthAccPortRxFramAppendFCSEnable ( IxEthAccPortId portId )
```

Forward frames with FCS included in the receive buffer.

The FCS is not striped from the receive buffer. The received frame length includes the FCS size (4 bytes). ie. A minimum sized ethernet frame shall have a length of 64bytes.

Frame FCS validity checks are still carried out on all received frames.

This is not the default behavior of the access component.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

◊ *IX_ETH_ACC_SUCCESS*

◊ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.

◊ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

```
ixEthAccPortRxFreeReplenish ( IxEthAccPortId portId,  
                             IX_OSAL_MBUF * buffer  
                             )
```

This function provides buffers for the Ethernet receive path.

This component does not have a buffer management mechanisms built in. All Rx buffers must be supplied to it via this interface.

- Reentrant – yes
- ISR Callable – yes

Parameters:

portId **IxEthAccPortId** [in] – Provide buffers only to specific Rx MAC.

buffer [in] – Provide an MBUF to the Ethernet receive mechanism. Buffers smaller than *IX_ETHNPE_ACC_RXFREE_BUFFER_LENGTH_MIN* is not allowed. Buffers smaller than *IX_ETHACC_RX_MBUF_MIN_SIZE* may result in poor performances and excessive buffer chaining. Buffers larger than this size may be suitable for jumbo frames. Chained packets are not supported and the field *IX_OSAL_MBUF_NEXT_PKT_IN_CHAIN_PTR* must be NULL.

Returns:

IxEthAccStatus

◊ *IX_ETH_ACC_SUCCESS*

◊ *IX_ETH_ACC_FAIL* : Not able to queue the buffer in the receive service.

- ◇ *IX_ETH_ACC_FAIL* : Buffer size is less than *IX_ETHNPE_ACC_RXFREE_BUFFER_LENGTH_MIN*
- ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
- ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

Note:

If the buffer replenish operation fails it is the responsibility of the user to free the buffer.

Sufficient buffers must be supplied to the component to maintain receive throughput and avoid rx buffer underflow conditions. To meet this goal, It is expected that the user preload the component with a sufficient number of buffers prior to enabling the NPE Ethernet receive path. The recommended minimum number of buffers is 8.

For maximum performances, the mbuf size should be greater than the maximum frame size (Ethernet header, payload and FCS) + 64. Supplying smaller mbufs to the service results in mbuf chaining and degraded performances. The recommended size is *IX_ETHACC_RX_MBUF_MIN_SIZE*, which is enough to take care of 802.3 frames and "baby jumbo" frames without chaining, and "jumbo" frame within chaining.

Buffers may not be filled up to their length. The firmware fills them up to the previous 64 bytes boundary. The user has to be aware that the length of the received mbufs may be smaller than the length of the supplied mbufs.

Warning:

This function checks the parameters if the NDEBUG flag is not defined. Turning on the argument checking (disabled by default) results in a lower EthAcc performance as this function is part of the data path.

IxEthAccStatus ixEthAccPortTxDisable (*IxEthAccPortId* portId)

Disable Tx on the port.

This function can be used to disable Tx in the MAC core. Tx can be re-enabled, although this is not guaranteed, by performing a MAC core reset (*ixEthAccPortMacReset*) and calling *ixEthAccPortTxEnable*. Note that using this function is not recommended, except for shutting down Tx for emergency reasons. For proper port shutdown and re-enabling see *ixEthAccPortEnable* and *ixEthAccPortDisable*.

This function is the recommended usage scenario for emergency security shutdown and hardware failure recovery and should never be used for throttling traffic.

- Reentrant – yes
- ISR Callable – no

Note:

Calling *ixEthAccPortDisable* followed by *ixEthAccPortEnable* is guaranteed to restore correct Ethernet Tx/Rx operation.

Precondition:

Parameters:

portId : ID of the port

Returns:

IxEthAccStatus

- ◇ *IX_ETH_ACC_SUCCESS* : Tx successfully disabled
 - ◇ *IX_ETH_ACC_FAIL* : Invalid port or Ethernet service not initialized
 - ◇ *IX_ETH_ACC_INVALID_PORT* : *portId* is invalid.
 - ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : *portId* is un-initialized
-

```

ixEthAccPortTxDoneCallbackRegister ( IxEthAccPortId           portId,
                                     IxEthAccPortTxDoneCallback txCallbackFn,
                                     UINT32                       callbackTag
                                     )

```

Register a callback function to allow the transmitted buffers to return to the user.

This function registers the transmit buffer done function callback for a particular port.

The registered callback function is called once the previously submitted buffer is no longer required by this service. It may be returned upon successful transmission of the frame or shutdown of port prior to submission. The calling of this registered function is not a guarantee of successful transmission of the buffer.

If called several times the latest callback shall be registered for a particular port.

- Reentrant – yes
- ISR Callable – yes

Precondition:

The port must be initialized via *ixEthAccPortInit*

Parameters:

portId **IxEthAccPortId** [in] – Register callback for a particular MAC device.
txCallbackFn **IxEthAccPortTxDoneCallback** [in] – Function to be called to return transmit buffers to the user.
callbackTag UINT32 [in] – This tag shall be provided to the callback function.

Returns:

IxEthAccStatus

- ◇ *IX_ETH_ACC_SUCCESS*
 - ◇ *IX_ETH_ACC_INVALID_PORT* : *portId* is invalid.
 - ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : *portId* is un-initialized
 - ◇ *IX_ETH_ACC_INVALID_ARG* : An argument other than *portId* is invalid.
-

```

IxEthAccStatus ixEthAccPortTxEnable ( IxEthAccPortId portId )

```

Enable Tx on the port.

This function is the complement of `ixEthAccPortTxDisable` and should be used only after Tx was disabled. A MAC core reset is required before this function is called (see `ixEthAccPortMacReset`).

This function is the recommended usage scenario for emergency security shutdown and hardware failure recovery and should never be used for throttling traffic.

- Reentrant – yes
- ISR Callable – no

Precondition:

Note:

Calling `ixEthAccPortDisable` followed by `ixEthAccPortEnable` is guaranteed to restore correct Ethernet Tx/Rx operation.

Parameters:

portId : ID of the port

Returns:

`IxEthAccStatus`

- ◇ `IX_ETH_ACC_SUCCESS` : Tx successfully enabled
 - ◇ `IX_ETH_ACC_FAIL` : Invalid port or Ethernet service not initialized
 - ◇ `IX_ETH_ACC_INVALID_PORT` : *portId* is invalid.
 - ◇ `IX_ETH_ACC_PORT_UNINITIALIZED` : *portId* is un-initialized
-

`ixEthAccPortTxFrameAppendFCSDisable (IxEthAccPortId portId)`

Disable the appending of Ethernet FCS to all frames submitted to this port.

When disabled, the Ethernet FCS is not added to the submitted frames. This is not the default behavior of the access component.

Note:

Since the FCS is not appended to the frame it is expected that the frame submitted to the component includes a valid FCS at the end of the data, although this will not be validated.

The component shall forward the frame to the Ethernet MAC WITHOUT modification.

Do not change this behaviour while the port is enabled.

Note:

Tx FCS append is not disabled while Tx padding is enabled.

- Reentrant – yes
- ISR Callable – no

See also:

ixEthAccPortTxFrameAppendPaddingEnable

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

◇ *IX_ETH_ACC_SUCCESS*

◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.

◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

ixEthAccPortTxFrameAppendFCSEnable (**IxEthAccPortId *portId*)**

Enable the appending of Ethernet FCS to all frames submitted to this port.

When enabled, the FCS is added to the submitted frames. This is the default behavior of the access component. Do not change this behaviour while the port is enabled.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

◇ *IX_ETH_ACC_SUCCESS*

◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.

◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

ixEthAccPortTxFrameAppendPaddingDisable (**IxEthAccPortId *portId*)**

Disable padding bytes to be appended to runt frames submitted to this port.

Disable padding bytes to be appended to runt frames submitted to this port. This is not the default behavior of the access component.

Warning:

Do not change this behaviour while the port is enabled.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

◊ *IX_ETH_ACC_SUCCESS*◊ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.◊ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

ixEthAccPortTxFrameAppendPaddingEnable (**IxEthAccPortId *portId*)**

Enable padding bytes to be appended to runt frames submitted to this port.

Enable up to 60 null-bytes padding bytes to be appended to runt frames submitted to this port. This is the default behavior of the access component.

Warning:

Do not change this behaviour while the port is enabled.

Note:

When Tx padding is enabled, Tx FCS generation is turned on

- Reentrant – yes
- ISR Callable – no

See also:

ixEthAccPortTxFrameAppendFCSDusable

Parameters:

portId **IxEthAccPortId** [in]

Returns:

IxEthAccStatus

◊ *IX_ETH_ACC_SUCCESS*◊ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.◊ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

ixEthAccPortUnicastAddressShow (**IxEthAccPortId *portId*)**

Displays unicast MAC address.

Displays unicast address which is configured using *ixEthAccUnicastMacAddressSet*. This function also displays the MAC filter used to filter multicast frames.

Other functions modify the MAC filtering

- *ixEthAccPortMulticastAddressJoinAll()* – all multicast frames are forwarded to the application
- *ixEthAccPortMulticastAddressLeaveAll()* – rollback the effects of *ixEthAccPortMulticastAddressJoinAll()*

- ***ixEthAccPortMulticastAddressLeave()*** – unprovision a new filtering address
- ***ixEthAccPortMulticastAddressJoin()*** – provision a new filtering address
- ***ixEthAccPortPromiscuousModeSet()*** – all frames are forwarded to the application regardless of the multicast address provisioned
- ***ixEthAccPortPromiscuousModeClear()*** – frames are forwarded to the application following the multicast address provisioned

In all cases, unicast and broadcast addresses are forwarded to the application.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in] – Ethernet port id.

Returns:

void

```
ixEthAccPortUnicastMacAddressSet ( IxEthAccPortId    portId,
                                   IxEthAccMacAddr * macAddr
                                   )
```

Configure unicast MAC address for a particular port.

- Reentrant – yes
- ISR Callable – no

Parameters:

portId **IxEthAccPortId** [in] – Ethernet port id.
macAddr* **IxEthAccMacAddr [in] – Ethernet Mac address.

Returns:

IxEthAccStatus
 ◇ ***IX_ETH_ACC_SUCCESS***
 ◇ ***IX_ETH_ACC_INVALID_PORT*** : *portId* is invalid.
 ◇ ***IX_ETH_ACC_PORT_UNINITIALIZED*** : *portId* is un-initialized

```
void ixEthAccQMgrRxNotificationDisable ( void )
```

Disable queue interrupts for all Rx queues.

This function will write to the QMgr interrupt enable register, clearing the bits associated with the receive queues. It will then write to the QMgr status interrupt to clear any already pending interrupts associated

with the receive queues. This means that no more interrupts can occur for these queues until the conditions are satisfied: the queues are completely drained, then the interrupt i enable register bits for the queues are re-enabled using **ixEthAccQMGrRxNotificationEnable()**.

- Reentrant – no
 - ISR Callable – yes
-

```
void ixEthAccQMGrRxNotificationEnable ( void )
```

Enable queue interrupts for all Rx queues.

This function will write to the QMgr interrupt enable register, adding the bits associated with the receive queues. After calling this function interrupts can occur for these queues given that the queues were properly drained prior to calling the function.

- Reentrant – no
 - ISR Callable – yes
-

```
IxEthAccStatus ixEthAccQMGrRxQEntryGet ( UINT32 * numEntries )
```

Get the total number of receive buffers in all rx queues.

This function will query QMgr to get each receive queue's number of entries and store the total in the UINT32 pointed to by the numEntries parameter.

- Reentrant – yes
- ISR Callable – yes

Precondition:

Parameters:

numEntries : pointer to UINT32 where the number of total entries can be written

```
IxEthAccStatus ixEthAccQMStatusUpdate ( IxEthAccPortId portId )
```

To retrigger the update of queue condition (interrupt and status flag) in order to restore these states that are lost during soft-error handling. This ensures Eth-NPE to continue its services.

- Reentrant – no
- ISR Callable – no

Note:

The function is useful for error-handling module to handle soft-error in Ethernet NPE.

It is expected that IRQ is disabled when this function is called.

Parameters:

portId **IxEthAccPortId** [in] : ID of the port

Returns:

IxEthAccStatus

- ◇ *IX_ETH_ACC_SUCCESS* : Queue conditions are retrigged
 - ◇ *IX_ETH_ACC_FAIL* : Queue conditions are not retrigged
 - ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 - ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : PORT is not initialized
-

ixEthAccRxSchedulingDisciplineSet (IxEthAccSchedulerDiscipline *sched*)

Set the Rx scheduling to one of *IxEthAccSchedulerDiscipline*.

The default behavior of the component is *FIFO_NO_PRIORITY*.

- Reentrant – yes
- ISR Callable – no

Precondition:

Parameters:

sched : *IxEthAccSchedulerDiscipline*

Returns:

IxEthAccStatus

- ◇ *IX_ETH_ACC_SUCCESS* : Set appropriate discipline.
 - ◇ *IX_ETH_ACC_FAIL* : Port is busy/priority scheduling not supported for A0.
 - ◇ *IX_ETH_ACC_INVALID_ARG* : Invalid/unsupported discipline.
-

IxEthAccStatus ixEthAccStartRequest (void)

Request Ethernet access layer to restart its currently stopped Tx and Rx Services for all the Ethernet ports.

Whenever this function is called, the internal counter is decremented by one (**ixEthAccStopRequest** increments this counter). If the counter becomes zero, this function sends an enable signal to QMgr dispatcher for it to proceed in serving the queues.

The internal counter is for synchronizing multiple requests to stop and resume Ethernet services.

- Reentrant – yes
- ISR Callable – no

Note:

The function is useful for error-handling module to handle soft-error in Ethernet NPE. User may use the APIs as follow:

- 1) Call **ixEthAccStopRequest** to stop Ethernet service.
- 2) Check that Ethernet service has been stoppoed with **ixEthAccStopDoneCheck**.
- 3) Proceed with soft-error recovery routine.
- 4) Call **ixEthAccStartRequest** to restart Ethernet service.

Returns:

IxEthAccStatus

- ◊ *IX_ETH_ACC_SUCCESS* : Service start request is posted successfully.
 - ◊ *IX_ETH_ACC_FAIL* : EthAcc service is not initialized.
-

ixEthAccStatsShow (IxEthAccPortId portId)

Displays a ports statistics on the standard io console using printf.

- Reentrant – no
- ISR Callable – no

Precondition:**Parameters:**

portId **IxEthAccPortId** [in]

Returns:

void

BOOL ixEthAccStopDoneCheck (void)

Checks whether the Ethernet traffic service is stopped completely.

- Reentrant – yes
- ISR Callable – no

Note:

The function is useful for error-handling module to handle soft-error in Ethernet NPE. User may use the APIs as follow:

- 1) Call **ixEthAccStopRequest** to stop Ethernet service.
- 2) Check that Ethernet service has been stoppoed with **ixEthAccStopDoneCheck**.
- 3) Proceed with soft-error recovery routine.
- 4) Call **ixEthAccStartRequest** to restart Ethernet service.

Returns:

BOOL

- ◊ *TRUE* : Ethernet Tx & Rx services for all ports are stopped

◇ *FALSE* : Ethernet Tx & Rx services for all ports are not stopped

IxEthAccStatus IxEthAccStopRequest (void)

Request Ethernet access layer to stop Tx and Rx Services for all the Ethernet ports.

This function maybe called multiple times e.g. NPE soft-errors in different NPEs. Whenever this function is called, an internal counter is incremented by one. The internal counter keep tracks on the number of "stop Ethernet-service" requested by user.

If it is the first request, a disable signal is sent to QMgr dispatcher function. On subsequent request, this function only increments the value of the counter without disabling QMgr dispatcher.

The internal counter is for synchronizing the possibility of multiple requests to stop and resume Ethernet services.

- Reentrant – yes
- ISR Callable – yes

Note:

The function is useful for error-handling module to handle soft-error in Ethernet NPE. User may use the APIs as follow:

- 1) Call **IxEthAccStopRequest** to stop Ethernet service.
- 2) Check that Ethernet service has been stoppoed with **IxEthAccStopDoneCheck**.
- 3) Proceed with soft-error recovery routine.
- 4) Call **IxEthAccStartRequest** to restart Ethernet service.

Returns:

IxEthAccStatus

◇ *IX_ETH_ACC_SUCCESS* : "Stop Ethernet-service" request is posted successfully.

◇ *IX_ETH_ACC_FAIL* : EthAcc service is not initialized.

```
IxEthAccTxSchedulingDisciplineSet ( IxEthAccPortId          portId,  
                                   IxEthAccSchedulerDiscipline sched  
                                   )
```

Set the port scheduling to one of *IxEthAccSchedulerDiscipline*.

The default behavior of the component is *FIFO_NO_PRIORITY*.

- Reentrant – yes
- ISR Callable – no

Precondition:

Parameters:

portId **IxEthAccPortId** [in]
sched **IxEthAccSchedulerDiscipline** [in]

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS* : Set appropriate discipline.
 ◇ *IX_ETH_ACC_INVALID_ARG* : Invalid/unsupported discipline.
 ◇ *IX_ETH_ACC_INVALID_PORT* : portId is invalid.
 ◇ *IX_ETH_ACC_PORT_UNINITIALIZED* : portId is un-initialized

ixEthAccUninit (void)

Un-Initializes the Intel (R) IXP400 Software Ethernet Access Service.

- Reentrant – no
- ISR Callable – no

This should be called once per module Un-initialization.

Returns:

IxEthAccStatus
 ◇ *IX_ETH_ACC_SUCCESS*
 ◇ *IX_ETH_ACC_FAIL* : Service has failed to Un-initialize.

Intel (R) IXP400 Software Ethernet Database (IxEthDB) API

ethDB is a library that does provides a MAC address database learning/filtering capability

Data Structures

struct **IX_OSAL_ATTRIBUTE_PACKED**
The IEEE 802.3 Ethernet MAC address structure.

struct **IxEthDBWiFiRecData**
The user wi-fi input parameters structure.

Defines

```
#define INLINE
#define IX_ETH_DB_PRIVATE
#define IX_ETH_DB_PUBLIC
#define IX_IEEE803_MAC_ADDRESS_SIZE
    The size of the MAC address.

#define IX_IEEE802_1Q_QOS_PRIORITY_COUNT
    Number of QoS priorities defined by IEEE802.1Q.

#define IX_ETH_DB_802_1Q_VLAN_MASK
    VLAN mask.

#define IX_ETH_DB_802_1Q_QOS_MASK
    QoS Mask.

#define IX_ETH_DB_802_1Q_MAX_VLAN_ID
    Maximum VLAN IDs.

#define IX_ETH_DB_SET_VLAN_ID(vlanTag, vlanID)
    returns the given 802.1Q tag with the VLAN ID field substituted with the given VLAN ID

#define IX_ETH_DB_GET_VLAN_ID(vlanTag)
    returns the VLAN ID from the given 802.1Q tag

#define IX_ETH_DB_GET_QOS_PRIORITY(vlanTag)
    gets the QoS priority from the given 802.1Q tag

#define IX_ETH_DB_SET_QOS_PRIORITY(vlanTag, priority)
    sets the QoS priority to the given 802.1Q tag
```



```

#define IX_ETH_DB_CHECK_VLAN_TAG(vlanTag)
    checks the VLAN ID of the given 802.1Q tag

#define IX_ETH_DB_CHECK_VLAN_ID(vlanId)
    checks the VLAN ID

#define IX_IEEE802_1Q_VLAN_TPID
    returns the VLAN TPID (0x8100)

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_COUNT_PROPERTY
    Property identifying number the supported number of traffic classes.

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_0_RX_QUEUE_PROPERTY
    Rx queue assigned to traffic class 0.

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_1_RX_QUEUE_PROPERTY
    Rx queue assigned to traffic class 1.

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_2_RX_QUEUE_PROPERTY
    Rx queue assigned to traffic class 2.

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_3_RX_QUEUE_PROPERTY
    Rx queue assigned to traffic class 3.

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_4_RX_QUEUE_PROPERTY
    Rx queue assigned to traffic class 4.

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_5_RX_QUEUE_PROPERTY
    Rx queue assigned to traffic class 5.

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_6_RX_QUEUE_PROPERTY
    Rx queue assigned to traffic class 6.

#define IX_ETH_DB_QOS_TRAFFIC_CLASS_7_RX_QUEUE_PROPERTY
    Rx queue assigned to traffic class 7.

#define IX_ETH_DB_QOS_QUEUE_CONFIGURATION_COMPLETE
    Queue configuration complete.

#define IX_ETH_DB_WIFI_MIN_PAD_SIZE
    Minimum pad size.

#define IX_ETH_DB_WIFI_MAX_PAD_SIZE
    Maximum pad size.

#define IX_ETH_DB_MAINTENANCE_TIME
    The ixEthDBDatabaseMaintenance must be called by the user at a frequency of  
IX_ETH_DB_MAINTENANCE_TIME.

#define IX_ETH_DB_LEARNING_ENTRY_AGE_TIME

```

The define specifies the filtering database age entry time. Static entries older than IX_ETH_DB_LEARNING_ENTRY_AGE_TIME +/- IX_ETH_DB_MAINTENANCE_TIME shall be removed.

Typedefs

```
typedef UINT32 IxEthDBVlanId
    VLAN ID type, valid range is 0..4094, 0 signifying no VLAN membership.

typedef UINT32 IxEthDBVlanTag
    802.1Q VLAN tag, contains 3 bits user priority, 1 bit CFI, 12 bits VLAN ID

typedef UINT32 IxEthDBPriority
    QoS priority/traffic class type, valid range is 0..7, 0 being the lowest.

typedef UINT8 IxEthDBPriorityTable [8]
    Priority mapping table; 0..7 QoS priorities used to index, table contains traffic
    classes.

typedef UINT8 IxEthDBVlanSet [512]
    A 4096 bit array used to map the complete VLAN ID range.

typedef UINT32 IxEthDBProperty
    Property ID type.

typedef UINT32 IxEthDBPortId
    Definition of an IXP400 port.

typedef UINT8 IxEthDBPortMap [32]
    Port dependency map definition.
```

Enumerations

```
enum IxEthDBStatus {
    IX_ETH_DB_SUCCESS,
    IX_ETH_DB_FAIL,
    IX_ETH_DB_INVALID_PORT,
    IX_ETH_DB_PORT_UNINITIALIZED,
    IX_ETH_DB_MAC_UNINITIALIZED,
    IX_ETH_DB_INVALID_ARG,
    IX_ETH_DB_NO_SUCH_ADDR,
    IX_ETH_DB_NOMEM,
    IX_ETH_DB_BUSY,
    IX_ETH_DB_END,
    IX_ETH_DB_INVALID_VLAN,
    IX_ETH_DB_INVALID_PRIORITY,
    IX_ETH_DB_NO_PERMISSION,
    IX_ETH_DB_FEATURE_UNAVAILABLE,
```

```

    IX_ETH_DB_INVALID_KEY,
    IX_ETH_DB_INVALID_RECORD_TYPE
}
Ethernet Database API return values.

enum IxEthDBFrameFilter {
    IX_ETH_DB_UNTAGGED_FRAMES,
    IX_ETH_DB_VLAN_TAGGED_FRAMES,
    IX_ETH_DB_PRIORITY_TAGGED_FRAMES,
    IX_ETH_DB_ACCEPT_ALL_FRAMES
}

enum IxEthDBTaggingAction {
    IX_ETH_DB_PASS_THROUGH,
    IX_ETH_DB_ADD_TAG,
    IX_ETH_DB_REMOVE_TAG,
    IX_ETH_DB_ENABLE_VLAN,
    IX_ETH_DB_DISABLE_VLAN
}

enum IxEthDBFirewallMode {
    IX_ETH_DB_FIREWALL_WHITE_LIST,
    IX_ETH_DB_FIREWALL_BLACK_LIST
}

enum IxEthDBRecordType {
    IX_ETH_DB_FILTERING_RECORD,
    IX_ETH_DB_FILTERING_VLAN_RECORD,
    IX_ETH_DB_WIFI_RECORD,
    IX_ETH_DB_FIREWALL_RECORD,
    IX_ETH_DB_GATEWAY_RECORD,
    IX_ETH_DB_MASK_RECORD,
    IX_ETH_DB_MAX_RECORD_TYPE_INDEX,
    IX_ETH_DB_NO_RECORD_TYPE,
    IX_ETH_DB_ALL_FILTERING_RECORDS,
    IX_ETH_DB_MASKED_FIREWALL_RECORD,
    IX_ETH_DB_ALL_RECORD_TYPES
}

enum IxEthDBFeature {
    IX_ETH_DB_LEARNING,
    IX_ETH_DB_FILTERING,
    IX_ETH_DB_VLAN_QOS,
    IX_ETH_DB_FIREWALL,
    IX_ETH_DB_SPANNING_TREE_PROTOCOL,
    IX_ETH_DB_WIFI_HEADER_CONVERSION,
    IX_ETH_DB_ADDRESS_MASKING
}

enum IxEthDBPropertyType {
    IX_ETH_DB_INTEGER_PROPERTY,
    IX_ETH_DB_STRING_PROPERTY,
    IX_ETH_DB_MAC_ADDR_PROPERTY,
    IX_ETH_DB_BOOL_PROPERTY
}

enum

```

```

IxEthDBWiFiRecordType {
    IX_ETH_DB_WIFI_AP_TO_STA,
    IX_ETH_DB_WIFI_AP_TO_AP,
    IX_ETH_DB_WIFI_TO_ETHER,
    IX_ETH_DB_WIFI_TO_LOCAL
}

```

The WI-FI record types enum.

```

enum IxEthDBWiFiVlanTag {
    IX_ETH_DB_WIFI_VLAN_NOTAG,
    IX_ETH_DB_WIFI_VLAN_TAG
}

```

The WI-FI VLAN tag/untag enum.

Functions

IX_ETH_DB_PUBLIC

IxEthDBStatus **ixEthDBInit** (void)

Initializes the Ethernet learning/filtering database.

IX_ETH_DB_PUBLIC

IxEthDBStatus **ixEthDBUnload** (void)

Stops and prepares the EthDB component for unloading.

IX_ETH_DB_PUBLIC

void **ixEthDBPortInit** (**IxEthDBPortId** portID)

Initializes a port.

IX_ETH_DB_PUBLIC

IxEthDBStatus **ixEthDBPortEnable** (**IxEthDBPortId** portID)

Enables a port.

IX_ETH_DB_PUBLIC

IxEthDBStatus **ixEthDBPortDisable** (**IxEthDBPortId** portID)

Disables processing on a port.

IX_ETH_DB_PUBLIC

IxEthDBStatus **ixEthDBPortAddressSet** (**IxEthDBPortId** portID, **IxEthDBMacAddr** *macAddr)

Sets the port MAC address.

IX_ETH_DB_PUBLIC **ixEthDBFilteringPortMaximumFrameSizeSet** (**IxEthDBPortId** portID, **UINT32**

IxEthDBStatus maximumFrameSize)

Set the maximum frame size supported on the given port ID.

IX_ETH_DB_PUBLIC **ixEthDBFilteringStaticEntryProvision** (**IxEthDBPortId** portID,

IxEthDBStatus **IxEthDBMacAddr** *macAddr)

Populate the Ethernet learning/filtering database with a static MAC address.

IX_ETH_DB_PUBLIC**ixEthDBFilteringDynamicEntryProvision** (**IxEthDBPortId** portID,
IxEthDBStatus IxEthDBMacAddr *macAddr)
Populate the Ethernet learning/filtering database with a dynamic MAC address.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBFilteringEntryDelete** (**IxEthDBMacAddr** *macAddr)
Removes a MAC address entry from the Ethernet learning/filtering database.

IX_ETH_DB_PUBLIC**ixEthDBFilteringPortSearch** (**IxEthDBPortId** portID, **IxEthDBMacAddr**
IxEthDBStatus *macAddr)
Search the Ethernet learning/filtering database for the given MAC address and port ID.

IX_ETH_DB_PUBLIC**ixEthDBFilteringDatabaseSearch** (**IxEthDBPortId** *portID, **IxEthDBMacAddr**
IxEthDBStatus *macAddr)
Search the Ethernet learning/filtering database for a MAC address and return the port ID.

IX_ETH_DB_PUBLIC**ixEthDBFilteringPortUpdatingSearch** (**IxEthDBPortId** *portID,
IxEthDBStatus IxEthDBMacAddr *macAddr)
Search the filtering database for a MAC address, return the port ID and reset the record age.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBPortAgingDisable** (**IxEthDBPortId** portID)
Disable the aging function for a specific port.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBPortAgingEnable** (**IxEthDBPortId** portID)
Enable the aging function for a specific port.

IX_ETH_DB_PUBLIC
void **ixEthDBDatabaseMaintenance** (void)
Performs a maintenance operation on the Ethernet learning/filtering database.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBEventProcessorPauseModeSet** (BOOL pauseEnable)
Pauses/resumes Ethernet DB event processor.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBFilteringDatabaseShow** (**IxEthDBPortId** portID)
This function displays the Mac Ethernet MAC address filtering tables.

IX_ETH_DB_PUBLIC
void **ixEthDBFilteringDatabaseShowAll** (void)
*Displays the MAC address recorded in the filtering database for all registered ports (see **IxEthDBPortDefs.h**), grouped by port ID.*

IX_ETH_DB_PUBLIC**ixEthDBFilteringDatabaseShowRecords** (**IxEthDBPortId** portID,
IxEthDBStatus **IxEthDBRecordType** recordFilter)

This function displays per port database records, given a record type filter.

IX_ETH_DB_PUBLICIxEthDBPortDependencyMapSet (IxEthDBPortId portID, IxEthDBPortMap IxEthDBStatus dependencyPortMap)

Sets the dependency port map for a port.

IX_ETH_DB_PUBLICIxEthDBPortDependencyMapGet (IxEthDBPortId portID, IxEthDBPortMap IxEthDBStatus dependencyPortMap)

Retrieves the dependency port map for a port.

IX_ETH_DB_PUBLIC

IxEthDBStatus ixEthDBPortVlanTagSet (IxEthDBPortId portID, IxEthDBVlanTag vlanTag)

Sets the default 802.1Q VLAN tag for a given port.

IX_ETH_DB_PUBLIC

IxEthDBStatus ixEthDBPortVlanTagGet (IxEthDBPortId portID, IxEthDBVlanTag *vlanTag)

Retrieves the default 802.1Q port VLAN tag for a given port (see also ixEthDBPortVlanTagSet).

IX_ETH_DB_PUBLIC

IxEthDBStatus ixEthDBVlanTagSet (IxEthDBMacAddr *macAddr, IxEthDBVlanTag vlanTag)

Sets the 802.1Q VLAN tag for a database record.

IX_ETH_DB_PUBLIC

IxEthDBStatus ixEthDBVlanTagGet (IxEthDBMacAddr *macAddr, IxEthDBVlanTag *vlanTag)

Retrieves the 802.1Q VLAN tag from a database record given the record MAC address.

IX_ETH_DB_PUBLICIxEthDBPortVlanMembershipAdd (IxEthDBPortId portID, IxEthDBVlanId IxEthDBStatus vlanID)

Adds a VLAN ID to a port's VLAN membership table.

IX_ETH_DB_PUBLICIxEthDBPortVlanMembershipRangeAdd (IxEthDBPortId portID, IxEthDBStatus IxEthDBVlanId vlanIDMin, IxEthDBVlanId vlanIDMax)

Adds a VLAN ID range to a port's VLAN membership table.

IX_ETH_DB_PUBLICIxEthDBPortVlanMembershipRemove (IxEthDBPortId portID, IxEthDBVlanId IxEthDBStatus vlanID)

Removes a VLAN ID from a port's VLAN membership table.

IX_ETH_DB_PUBLICIxEthDBPortVlanMembershipRangeRemove (IxEthDBPortId portID, IxEthDBStatus IxEthDBVlanId vlanIDMin, IxEthDBVlanId vlanIDMax)

Removes a VLAN ID range from a port's VLAN membership table.

IX_ETH_DB_PUBLICIxEthDBPortVlanMembershipSet (IxEthDBPortId portID, IxEthDBVlanSet IxEthDBStatus vlanSet)

Sets a port's VLAN membership table.

IX_ETH_DB_PUBLICIxEthDBPortVlanMembershipGet (IxEthDBPortId portID, IxEthDBVlanSet IxEthDBStatus vlanSet)

Retrieves a port's VLAN membership table.

**IX_ETH_DB_PUBLICIxEthDBAcceptableFrameTypeSet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBFrameFilter frameFilter)**

Sets a port's acceptable frame type filter.

**IX_ETH_DB_PUBLICIxEthDBAcceptableFrameTypeGet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBFrameFilter *frameFilter)**

Retrieves a port's acceptable frame type filter.

**IX_ETH_DB_PUBLICIxEthDBPriorityMappingTableSet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBPriorityTable priorityTable)**

Sets a port's priority mapping table.

**IX_ETH_DB_PUBLICIxEthDBPriorityMappingTableGet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBPriorityTable priorityTable)**

Retrieves a port's priority mapping table.

IX_ETH_DB_PUBLIC

IxEthDBStatus ixEthDBPriorityMappingTableUpdate (IxEthDBPortId portID)

*Reloads the last port priority mapping table set by the user. (see also
ixEthDBPriorityMappingTableSet).*

**IX_ETH_DB_PUBLICIxEthDBPriorityMappingClassSet (IxEthDBPortId portID, IxEthDBPriority
IxEthDBStatus userPriority, IxEthDBPriority trafficClass)**

*Sets one QoS/user priority => traffic class mapping in a port's priority mapping
table.*

**IX_ETH_DB_PUBLICIxEthDBPriorityMappingClassGet (IxEthDBPortId portID, IxEthDBPriority
IxEthDBStatus userPriority, IxEthDBPriority *trafficClass)**

*Retrieves one QoS/user priority => traffic class mapping in a port's priority mapping
table.*

**IX_ETH_DB_PUBLICIxEthDBEgressVlanEntryTaggingEnabledSet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBVlanId vlanID, BOOL enabled)**

Enables or disables Egress VLAN tagging for a port and a given VLAN.

**IX_ETH_DB_PUBLICIxEthDBEgressVlanEntryTaggingEnabledGet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBVlanId vlanID, BOOL *enabled)**

Retrieves the Egress VLAN tagging enabling status for a port and VLAN ID.

**IX_ETH_DB_PUBLICIxEthDBEgressVlanRangeTaggingEnabledSet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBVlanId vlanIDMin, IxEthDBVlanId vlanIDMax, BOOL enabled)**

Enables or disables Egress VLAN tagging for a port and given VLAN range.

**IX_ETH_DB_PUBLICIxEthDBEgressVlanTaggingEnabledSet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBVlanSet vlanSet)**

Sets the complete Egress VLAN tagging table for a port.

**IX_ETH_DB_PUBLICIxEthDBEgressVlanTaggingEnabledGet (IxEthDBPortId portID,
IxEthDBStatus IxEthDBVlanSet vlanSet)**

Retrieves the complete Egress VLAN tagging table from a port.

IX_ETH_DB_PUBLICIxEthDBIngressVlanTaggingEnabledSet (IxEthDBPortId portID, IxEthDBStatus IxEthDBTaggingAction taggingAction)

Sets the Ingress VLAN tagging behavior for a port.

IX_ETH_DB_PUBLICIxEthDBIngressVlanTaggingEnabledGet (IxEthDBPortId portID, IxEthDBStatus IxEthDBTaggingAction *taggingAction)

*Retrieves the Ingress VLAN tagging behavior from a port (see **ixEthDBIngressVlanTaggingEnabledSet**).*

IX_ETH_DB_PUBLIC

IxEthDBStatus ixEthDBVlanPortExtractionEnable (IxEthDBPortId portID, BOOL enable)

Enables or disables port ID extraction.

IX_ETH_DB_PUBLICIxEthDBFeatureCapabilityGet (IxEthDBPortId portID, IxEthDBFeature IxEthDBStatus *featureSet)

Retrieves the feature capability set for a port.

IX_ETH_DB_PUBLICIxEthDBFeatureEnable (IxEthDBPortId portID, IxEthDBFeature feature, BOOL IxEthDBStatus enabled)

Enables or disables one or more EthDB features.

IX_ETH_DB_PUBLICIxEthDBFeatureStatusGet (IxEthDBPortId portID, IxEthDBFeature feature, IxEthDBStatus BOOL *present, BOOL *enabled)

Retrieves the availability and status of a feature set.

IX_ETH_DB_PUBLICIxEthDBFeaturePropertyGet (IxEthDBPortId portID, IxEthDBFeature feature, IxEthDBStatus IxEthDBProperty property, IxEthDBPropertyType *type, void *value)

Retrieves the value of a feature property.

IX_ETH_DB_PUBLICIxEthDBFeaturePropertySet (IxEthDBPortId portID, IxEthDBFeature feature, IxEthDBStatus IxEthDBProperty property, void *value)

Sets the value of a feature property.

IX_ETH_DB_PUBLIC

IxEthDBStatus ixEthDBFeatureStatesRestore (IxEthDBPortId portId)

Restores the state of EthDB based on latest settings, following the occurrence of an NPE soft-error. State is restored by re-downloading tables for the enabled features (e.g. Header Conversion and Firewall) or sending configuration messages to NPE.

IX_ETH_DB_PUBLICIxEthDBDatabaseClear (IxEthDBPortId portID, IxEthDBRecordType IxEthDBStatus recordType)

Deletes a set of record types from the Ethernet Database.

IX_ETH_DB_PUBLICIxEthDBWiFiRecordEntryAdd (IxEthDBPortId portID, IxEthDBMacAddr IxEthDBStatus *macAddr, IxEthDBWiFiRecData *wifiRecData)

Adds "APMAC/BSSID/STATIONS" record to the database, for 802.3 => 802.11 frame header conversion.

IX_ETH_DB_PUBLIC**CxEthDBWiFiStationEntryAdd** (**IxEthDBPortId** portID, **IxEthDBMacAddr** **IxEthDBStatus** *macAddr)
Adds an "Access Point to Station" record to the database, for 802.3 => 802.11 frame header conversion.

IX_ETH_DB_PUBLIC**CxEthDBWiFiAccessPointEntryAdd** (**IxEthDBPortId** portID, **IxEthDBMacAddr** **IxEthDBStatus** *macAddr, **IxEthDBMacAddr** *gatewayMacAddr)
Adds an "Access Point to Access Point" record to the database.

IX_ETH_DB_PUBLIC**CxEthDBWiFiEntryRemove** (**IxEthDBPortId** portID, **IxEthDBMacAddr** **IxEthDBStatus** *macAddr)
Removes a WiFi station record.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBWiFiConversionTableDownload** (**IxEthDBPortId** portID)
Downloads the MAC address table for 802.3 => 802.11 frame header conversion to the NPE.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBWiFiFrameControlSet** (**IxEthDBPortId** portID, **UINT16** frameControl)
Sets the GlobalFrameControl field.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBWiFiDurationIDSet** (**IxEthDBPortId** portID, **UINT16** durationID)
Sets the GlobalDurationID field.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBWiFiBSSIDSet** (**IxEthDBPortId** portID, **IxEthDBMacAddr** *bssid)
Sets the BSSID field.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBSpanningTreeBlockingStateSet** (**IxEthDBPortId** portID, **BOOL** blocked)
Sets the STP blocked/unblocked state for a port.

IX_ETH_DB_PUBLIC**CxEthDBSpanningTreeBlockingStateGet** (**IxEthDBPortId** portID, **BOOL** **IxEthDBStatus** *blocked)
Retrieves the STP blocked/unblocked state for a port.

IX_ETH_DB_PUBLIC
IxEthDBStatus **ixEthDBFirewallModeSet** (**IxEthDBPortId** portID, **IxEthDBFirewallMode** mode)
Sets the firewall mode to use white or black listing.

IX_ETH_DB_PUBLIC**CxEthDBFirewallInvalidAddressFilterEnable** (**IxEthDBPortId** portID, **BOOL** **IxEthDBStatus** enable)
Enables or disables invalid MAC address filtering.

IX_ETH_DB_PUBLIC**CxEthDBFirewallEntryAdd** (**IxEthDBPortId** portID, **IxEthDBMacAddr** **IxEthDBStatus** *macAddr)
Adds a MAC address to the firewall address list.

IX_ETH_DB_PUBLICIxEthDBFirewallEntryRemove (**IxEthDBPortId** portID, IxEthDBMacAddr
IxEthDBStatus *macAddr)

Removes a MAC address from the firewall address list.

IX_ETH_DB_PUBLICIxEthDBFirewallMaskedEntryAdd (**IxEthDBPortId** portID, IxEthDBMacAddr
IxEthDBStatus *macAddr, IxEthDBMacAddr *addrMask)

Adds a MAC address + mask to the firewall address list.

IX_ETH_DB_PUBLICIxEthDBFirewallMaskedEntryRemove (**IxEthDBPortId** portID,
IxEthDBStatus IxEthDBMacAddr *macAddr, IxEthDBMacAddr *addrMask)

Removes a MAC address + mask from the firewall address list.

IX_ETH_DB_PUBLIC

IxEthDBStatus ixEthDBFirewallTableDownload (**IxEthDBPortId** portID)

Downloads the MAC firewall table to a port.

IX_ETH_DB_PUBLICIxEthDBUserFieldSet (**IxEthDBRecordType** recordType, IxEthDBMacAddr
IxEthDBStatus *macAddr, **IxEthDBPortId** portID, **IxEthDBVlanId** vlanID, void *field)

Adds a user-defined field to a database record.

IX_ETH_DB_PUBLICIxEthDBUserFieldGet (**IxEthDBRecordType** recordType, IxEthDBMacAddr
IxEthDBStatus *macAddr, **IxEthDBPortId** portId, **IxEthDBVlanId** vlanID, void **field)

Retrieves a user-defined field from a database record.

Detailed Description

ethDB is a library that does provides a MAC address database learning/filtering capability

Define Documentation

```
#define IX_ETH_DB_802_1Q_MAX_VLAN_ID
```

Maximum VLAN IDs.

Definition at line **85** of file **IxEthDB.h**.

```
#define IX_ETH_DB_802_1Q_QOS_MASK
```

QoS Mask.

Definition at line **83** of file **IxEthDB.h**.

```
#define IX_ETH_DB_802_1Q_VLAN_MASK
```

VLAN mask.

Definition at line **82** of file **IxEthDB.h**.

```
#define IX_ETH_DB_CHECK_VLAN_ID ( vlanId )
```

checks the VLAN ID

Definition at line **129** of file **IxEthDB.h**.

```
#define IX_ETH_DB_CHECK_VLAN_TAG ( vlanTag )
```

checks the VLAN ID of the given 802.1Q tag

Definition at line **123** of file **IxEthDB.h**.

```
#define IX_ETH_DB_GET_QOS_PRIORITY ( vlanTag )
```

gets the QOS priority from the given 802.1Q tag

Definition at line **111** of file **IxEthDB.h**.

```
#define IX_ETH_DB_GET_VLAN_ID ( vlanTag )
```

returns the VLAN ID from the given 802.1Q tag

Definition at line **105** of file **IxEthDB.h**.

```
#define IX_ETH_DB_LEARNING_ENTRY_AGE_TIME
```

The define specifies the filtering database age entry time. Static entries older than `IX_ETH_DB_LEARNING_ENTRY_AGE_TIME +/- IX_ETH_DB_MAINTENANCE_TIME` shall be removed.

Definition at line **644** of file **IxEthDB.h**.

```
#define IX_ETH_DB_MAINTENANCE_TIME
```

The **ixEthDBDatabaseMaintenance** must be called by the user at a frequency of `IX_ETH_DB_MAINTENANCE_TIME`.

Definition at line **633** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_QUEUE_CONFIGURATION_COMPLETE
```

Queue configuration complete.

Definition at line **222** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_0_RX_QUEUE_PROPERTY
```

Rx queue assigned to traffic class 0.

Definition at line **212** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_1_RX_QUEUE_PROPERTY
```

Rx queue assigned to traffic class 1.

Definition at line **213** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_2_RX_QUEUE_PROPERTY
```

Rx queue assigned to traffic class 2.

Definition at line **214** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_3_RX_QUEUE_PROPERTY
```

Rx queue assigned to traffic class 3.

Definition at line **215** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_4_RX_QUEUE_PROPERTY
```

Rx queue assigned to traffic class 4.

Definition at line **216** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_5_RX_QUEUE_PROPERTY
```

Rx queue assigned to traffic class 5.

Definition at line **217** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_6_RX_QUEUE_PROPERTY
```

Rx queue assigned to traffic class 6.

Definition at line **218** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_7_RX_QUEUE_PROPERTY
```

Rx queue assigned to traffic class 7.

Definition at line **219** of file **IxEthDB.h**.

```
#define IX_ETH_DB_QOS_TRAFFIC_CLASS_COUNT_PROPERTY
```

Property identifying number the supported number of traffic classes.

Definition at line **211** of file **IxEthDB.h**.

```
#define IX_ETH_DB_SET_QOS_PRIORITY ( vlanTag,  
                                   priority )
```

sets the QOS priority to the given 802.1Q tag

Definition at line **117** of file **IxEthDB.h**.

```
#define IX_ETH_DB_SET_VLAN_ID ( vlanTag,  
                                vlanID )
```

returns the given 802.1Q tag with the VLAN ID field substituted with the given VLAN ID

This macro is used to change the VLAN ID in a 802.1Q tag.

Example:

tag = **IX_ETH_DB_SET_VLAN_ID(tag, 32)**

inserts the VLAN ID "32" in the given tag.

Definition at line **99** of file **IxEthDB.h**.

```
#define IX_ETH_DB_WIFI_MAX_PAD_SIZE
```

Maximum pad size.

Definition at line **226** of file **IxEthDB.h**.

```
#define IX_ETH_DB_WIFI_MIN_PAD_SIZE
```

Minimum pad size.

Definition at line **225** of file **IxEthDB.h**.

```
#define IX_IEEE802_1Q_QOS_PRIORITY_COUNT
```

Number of QoS priorities defined by IEEE802.1Q.

Definition at line **41** of file **IxEthDB.h**.

```
#define IX_IEEE802_1Q_VLAN_TPID
```

returns the VLAN TPID (0x8100)

Definition at line **135** of file **IxEthDB.h**.

```
#define IX_IEEE803_MAC_ADDRESS_SIZE
```

The size of the MAC address.

Definition at line **35** of file **IxEthDB.h**.

Typedef Documentation

```
typedef UINT32 IxEthDBPortId
```

Definition of an IXP400 port.

Definition at line **290** of file **IxEthDB.h**.

```
typedef UINT8 IxEthDBPortMap[32]
```

Port dependency map definition.

Definition at line **297** of file **IxEthDB.h**.

```
typedef UINT32 IxEthDBPriority
```

QoS priority/traffic class type, valid range is 0..7, 0 being the lowest.

Definition at line **74** of file **IxEthDB.h**.

```
typedef UINT8 IxEthDBPriorityTable[8]
```

Priority mapping table; 0..7 QoS priorities used to index, table contains traffic classes.

Definition at line **77** of file **IxEthDB.h**.

```
typedef UINT32 IxEthDBProperty
```

Property ID type.

Definition at line **200** of file **IxEthDB.h**.

```
typedef UINT32 IxEthDBVlanId
```

VLAN ID type, valid range is 0..4094, 0 signifying no VLAN membership.

Definition at line **68** of file **IxEthDB.h**.

```
typedef UINT8 IxEthDBVlanSet[512]
```

A 4096 bit array used to map the complete VLAN ID range.

Definition at line **80** of file **IxEthDB.h**.

```
typedef UINT32 IxEthDBVlanTag
```

802.1Q VLAN tag, contains 3 bits user priority, 1 bit CFI, 12 bits VLAN ID

Definition at line **71** of file **IxEthDB.h**.

Enumeration Type Documentation

```
enum IxEthDBFeature
```

Enumeration values:

<i>IX_ETH_DB_LEARNING</i>	Learning feature; enables EthDB to learn MAC address (filtering) records, including 802.1Q enabled records.
<i>IX_ETH_DB_FILTERING</i>	Filtering feature; enables EthDB to communicate with the NPEs for downloading filtering information in the NPEs; depends on the learning feature.
<i>IX_ETH_DB_VLAN_QOS</i>	VLAN/QoS feature; enables EthDB to configure NPEs to operate in VLAN/QoS aware modes.
<i>IX_ETH_DB_FIREWALL</i>	Firewall feature; enables EthDB to configure NPEs to operate in firewall mode, using white/black address lists.
<i>IX_ETH_DB_SPANNING_TREE_PROTOCOL</i>	Spanning tree protocol feature; enables EthDB to configure the NPEs as STP nodes.
<i>IX_ETH_DB_WIFI_HEADER_CONVERSION</i>	WiFi 802.3 to 802.11 header conversion feature; enables EthDB to handle WiFi conversion data.
<i>IX_ETH_DB_ADDRESS_MASKING</i>	Masking of MAC addresses using an address mask.
	Currently only usable in conjunction with the <i>IX_ETH_DB_FIREWALL</i> feature

Definition at line **189** of file **IxEthDB.h**.

```
enum IxEthDBFirewallMode
```

Enumeration values:

<i>IX_ETH_DB_FIREWALL_WHITE_LIST</i>	Firewall operates in white-list mode (MAC address based admission).
<i>IX_ETH_DB_FIREWALL_BLACK_LIST</i>	Firewall operates in black-list mode (MAC address based blocking).

Definition at line **155** of file **IxEthDB.h**.

```
enum IxEthDBFrameFilter
```

Enumeration values:

<i>IX_ETH_DB_UNTAGGED_FRAMES</i>	Accepts untagged frames.
<i>IX_ETH_DB_VLAN_TAGGED_FRAMES</i>	Accepts tagged frames.
<i>IX_ETH_DB_PRIORITY_TAGGED_FRAMES</i>	Accepts tagged frames with VLAN ID set to 0 (no VLAN membership).
<i>IX_ETH_DB_ACCEPT_ALL_FRAMES</i>	Accepts all the frames.

Definition at line **137** of file **IxEthDB.h**.

enum IxEthDBPropertyType

Enumeration values:	
<i>IX_ETH_DB_INTEGER_PROPERTY</i>	4 byte unsigned integer type
<i>IX_ETH_DB_STRING_PROPERTY</i>	NULL-terminated string type of maximum 255 characters (including the terminator).
<i>IX_ETH_DB_MAC_ADDR_PROPERTY</i>	6 byte MAC address type
<i>IX_ETH_DB_BOOL_PROPERTY</i>	4 byte boolean type; can contain only TRUE and FALSE values

Definition at line **202** of file **IxEthDB.h**.

enum IxEthDBRecordType

Enumeration values:					
<i>IX_ETH_DB_FILTERING_RECORD</i>	Filtering record <table><tr><td>MAC address</td><td>static/dynamic type</td><td>age</td></tr></table>	MAC address	static/dynamic type	age	
MAC address	static/dynamic type	age			
<i>IX_ETH_DB_FILTERING_VLAN_RECORD</i>	VLAN-enabled filtering record <table><tr><td>MAC address</td><td>static/dynamic type</td><td>age</td><td>802.1Q tag</td></tr></table>	MAC address	static/dynamic type	age	802.1Q tag
MAC address	static/dynamic type	age	802.1Q tag		
<i>IX_ETH_DB_WIFI_RECORD</i>	WiFi header conversion record <table><tr><td>MAC address</td><td>optional gateway MAC address</td></tr></table>	MAC address	optional gateway MAC address		
MAC address	optional gateway MAC address				
<i>IX_ETH_DB_FIREWALL_RECORD</i>	Firewall record <table><tr><td>MAC address</td></tr></table>	MAC address			
MAC address					
<i>IX_ETH_DB_GATEWAY_RECORD</i>	<i>For internal use only</i>				
<i>IX_ETH_DB_MASK_RECORD</i>	<i>For internal use only</i>				
<i>IX_ETH_DB_MAX_RECORD_TYPE_INDEX</i>	<i>For internal use only</i>				
<i>IX_ETH_DB_NO_RECORD_TYPE</i>	None of the registered record types.				
<i>IX_ETH_DB_ALL_FILTERING_RECORDS</i>	All the filtering records.				
<i>IX_ETH_DB_MASKED_FIREWALL_RECORD</i>	Masked firewall records.				
<i>IX_ETH_DB_ALL_RECORD_TYPES</i>	All the record types registered within EthDB.				

Definition at line **161** of file **IxEthDB.h**.

enum IxEthDBStatus

Ethernet Database API return values.

Enumeration values:

<i>IX_ETH_DB_SUCCESS</i>	Success.
<i>IX_ETH_DB_FAIL</i>	Failure.
<i>IX_ETH_DB_INVALID_PORT</i>	Invalid port.
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	Port not initialized.
<i>IX_ETH_DB_MAC_UNINITIALIZED</i>	MAC not initialized.
<i>IX_ETH_DB_INVALID_ARG</i>	Invalid argument.
<i>IX_ETH_DB_NO_SUCH_ADDR</i>	Address not found for search or delete operations.
<i>IX_ETH_DB_NOMEM</i>	Learning database memory full.
<i>IX_ETH_DB_BUSY</i>	Learning database cannot complete operation, access temporarily blocked.
<i>IX_ETH_DB_END</i>	Database browser passed the end of the record set.
<i>IX_ETH_DB_INVALID_VLAN</i>	Invalid VLAN ID (valid range is 0..4094, 0 signifies no VLAN membership, used for priority tagged frames).
<i>IX_ETH_DB_INVALID_PRIORITY</i>	Invalid QoS priority/traffic class (valid range for QoS priority is 0..7, valid range for traffic class depends on run-time configuration).
<i>IX_ETH_DB_NO_PERMISSION</i>	No permission for attempted operation.
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Feature not available (or not enabled).
<i>IX_ETH_DB_INVALID_KEY</i>	Invalid search key.
<i>IX_ETH_DB_INVALID_RECORD_TYPE</i>	Invalid record type.

Definition at line **47** of file **IxEthDB.h**.

```
enum IxEthDBTaggingAction
```

Enumeration values:

<i>IX_ETH_DB_PASS_THROUGH</i>	Leave frame as-is.
<i>IX_ETH_DB_ADD_TAG</i>	Add default port VLAN tag.
<i>IX_ETH_DB_REMOVE_TAG</i>	Remove VLAN tag from frame.
<i>IX_ETH_DB_ENABLE_VLAN</i>	VLAN enable bit.
<i>IX_ETH_DB_DISABLE_VLAN</i>	VLAN disable bit.

Definition at line **146** of file **IxEthDB.h**.

```
enum IxEthDBWiFiRecordType
```

The WI-FI record types enum.

The type value should be any of the types

Enumeration values:

IX_ETH_DB_WIFI_AP_TO_STA Ap to Sta
record.
IX_ETH_DB_WIFI_AP_TO_AP Ap to Ap
record.
IX_ETH_DB_WIFI_TO_ETHER To Ether
record.
IX_ETH_DB_WIFI_TO_LOCAL To Local
record.

Definition at line **248** of file **IxEthDB.h**.

```
enum IxEthDBWiFiVlanTag
```

The WI-FI VLAN tag/untag enum.

The tag value should be either tag or untag

Enumeration values:

IX_ETH_DB_WIFI_VLAN_NOTAG Tag 802.11
frames.
IX_ETH_DB_WIFI_VLAN_TAG Untag
802.11
frames.

Definition at line **263** of file **IxEthDB.h**.

Function Documentation

```
IxEthDBStatus ixEthDBAcceptableFrameTypeGet ( IxEthDBPortId portID,  
                                                IxEthDBFrameFilter * frameFilter  
                                                )
```

Retrieves a port's acceptable frame type filter.

For a description of the acceptable frame types see **ixEthDBAcceptableFrameTypeSet**

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID to retrieve the acceptable frame type filter from
frameFilter **IxEthDBFrameFilter** [out] – location to store the acceptable frame type filter

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_PORT portID is not a valid port identifier

<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>frameFilter</i> pointer argument
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port

```
IxEthDBStatus ixEthDBAcceptableFrameTypeSet ( IxEthDBPortId    portID,
                                                IxEthDBFrameFilter frameFilter
                                                )
```

Sets a port's acceptable frame type filter.

The acceptable frame type is one (or a combination) of the following values:

- *IX_ETH_DB_ACCEPT_ALL_FRAMES* – accepts all the frames
- *IX_ETH_DB_UNTAGGED_FRAMES* – accepts untagged frames
- *IX_ETH_DB_VLAN_TAGGED_FRAMES* – accepts tagged frames
- *IX_ETH_DB_PRIORITY_TAGGED_FRAMES* – accepts tagged frames with VLAN ID set to 0 (no VLAN membership)

Except for using the exact values given above only the following combinations are valid:

- *IX_ETH_DB_UNTAGGED_FRAMES* | *IX_ETH_DB_VLAN_TAGGED_FRAMES*
- *IX_ETH_DB_UNTAGGED_FRAMES* | *IX_ETH_DB_PRIORITY_TAGGED_FRAMES*

Please note that *IX_ETH_DB_UNTAGGED_FRAMES* | *IX_ETH_DB_VLAN_TAGGED_FRAMES* is equivalent to *IX_ETH_DB_ACCEPT_ALL_FRAMES*.

- Reentrant – no
- ISR Callable – no

Note:

by default the acceptable frame type filter is set to *IX_ETH_DB_ACCEPT_ALL_FRAMES*

setting the acceptable frame type to *PRIORITY_TAGGED_FRAMES* is internally accomplished by changing the frame filter to *VLAN_TAGGED_FRAMES* and setting the VLAN membership list to include only VLAN ID 0; the membership list will need to be restored manually to an appropriate value if the acceptable frame type filter is changed back to *ACCEPT_ALL_FRAMES* or *VLAN_TAGGED_FRAMES*; failure to do so will filter all VLAN traffic bar frames tagged with VLAN ID 0

Parameters:

portID **IxEthDBPortId** [in] – port ID to set the acceptable frame type filter to
frameFilter **IxEthDBFrameFilter** [in] – acceptable frame type filter

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid frame type filter

IX_ETH_DB_FEATURE_UNAVAILABLE VLAN/QoS feature is not available or not enabled for the port
IX_FAIL unknown OS or NPE communication error

```
IxEthDBStatus ixEthDBDatabaseClear ( IxEthDBPortId portID,  

IxEthDBRecordType recordType  

)
```

Deletes a set of record types from the Ethernet Database.

This function deletes all the records of certain types (specified in the recordType filter) associated with a port. Additionally, the IX_ETH_DB_ALL_PORTS value can be used as port ID to indicate that the specified record types should be deleted for all the ports.

The record type filter can be an ORed combination of the following types:

Record types

- **IX_ETH_DB_FILTERING_RECORD**
Filtering record

MAC address	static/dynamic type	age
-------------	---------------------	-----

- **IX_ETH_DB_FILTERING_VLAN_RECORD**
VLAN-enabled filtering record

MAC address	static/dynamic type	age	802.1Q tag
-------------	---------------------	-----	------------

- **IX_ETH_DB_WIFI_RECORD**
WiFi header conversion record

MAC address	optional gateway MAC address
-------------	------------------------------

- **IX_ETH_DB_FIREWALL_RECORD**
Firewall record

MAC address

- **IX_ETH_DB_ALL_RECORD_TYPES**

Any combination of the above types is valid e.g.

(IX_ETH_DB_FILTERING_RECORD | IX_ETH_DB_FILTERING_VLAN_RECORD | IX_ETH_DB_FIREWALL_RECORD),

although some might be redundant (it is not an error to do so) e.g.

(IX_ETH_DB_FILTERING_RECORD | IX_ETH_DB_ALL_RECORD_TYPES)

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
recordType **IxEthDBRecordType** [in] – record type filter

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_PORT *portID* is not a valid port identifier
IX_ETH_DB_INVALID_ARG invalid *recordType* filter

Note:

If the record type filter contains any unrecognized value (hence the IX_ETH_DB_INVALID_ARG error value is returned) no actual records will be deleted.

```
void ixEthDBDatabaseMaintenance ( void )
```

Performs a maintenance operation on the Ethernet learning/filtering database.

In order to perform a database maintenance this function must be called every **IX_ETH_DB_MAINTENANCE_TIME** seconds. It should be called regardless of whether learning is enabled or not.

- Reentrant – no
- ISR Callable – no

Note:

this function call will be ignored if the learning feature is disabled

```
IxEthDBStatus ixEthDBEgressVlanEntryTaggingEnabledGet ( IxEthDBPortId portID,  
                                                         IxEthDBVlanId vlanID,  
                                                         BOOL * enabled  
                                                         )
```

Retrieves the Egress VLAN tagging enabling status for a port and VLAN ID.

Parameters:

portID [in] – ID of the port to extract the Egress VLAN ID tagging status from
vlanID VLAN [in] – ID whose tagging status is to be extracted
enabled [in] – user-specified location where the status is copied to; following the successful execution of this function the value will be TRUE if Egress VLAN tagging is enabled for the given port and VLAN ID, and FALSE otherwise

- Reentrant – no
- ISR Callable – no

See also:

ixEthDBEgressVlanEntryTaggingEnabledGet

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_VLAN</i>	invalid VLAN ID (out of range)
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>enabled</i> argument pointer
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port

```

IxEthDBStatus ixEthDBEgressVlanEntryTaggingEnabledSet ( IxEthDBPortId portID,
                                                         IxEthDBVlanId vlanID,
                                                         BOOL enabled
                                                         )

```

Enables or disables Egress VLAN tagging for a port and a given VLAN.

This function enables or disables Egress VLAN tagging for the given port and VLAN ID. If the VLAN tagging for a certain VLAN ID is enabled then all the frames to be transmitted on the given port tagged with the same VLAN ID will be transmitted in a tagged format. If tagging is not enabled for the given VLAN ID, the VLAN tag from the frames matching this VLAN ID will be removed (the frames will be untagged).

VLAN ID 4095 is reserved and should never be used with this function. VLAN ID 0 has the special meaning of "No VLAN membership" and it is used in this context to allow the port to send priority-tagged frames or not.

By default, no Egress VLAN tagging is enabled on any port.

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to enable or disable the VLAN ID Egress tagging on
vlanID **IxEthDBVlanId** [in] – VLAN ID to be matched against outgoing frames
enabled **BOOL** [in] – TRUE to enable Egress VLAN tagging on the port and given VLAN, and FALSE to disable Egress VLAN tagging

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_VLAN</i>	invalid VLAN ID (out of range)
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_FAIL</i>	unknown OS or NPE communication error

```

IxEthDBStatus ixEthDBEgressVlanRangeTaggingEnabledSet ( IxEthDBPortId portID,
                                                         IxEthDBVlanId vlanIDMin,
                                                         IxEthDBVlanId vlanIDMax,
                                                         BOOL enabled
                                                         )

```

Enables or disables Egress VLAN tagging for a port and given VLAN range.

This function is very similar to **ixEthDBEgressVlanEntryTaggingEnabledSet** with the difference that it can manipulate the Egress tagging status on multiple VLAN IDs, defined by a contiguous range. Note that both limits in the range are explicitly included in the execution of this function.

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to enable or disable the VLAN ID Egress tagging on

vlanIDMin **IxEthDBVlanId** [in] – start of the VLAN range to be matched against outgoing frames

vlanIDMax **IxEthDBVlanId** [in] – end of the VLAN range to be matched against outgoing frames

enabled **BOOL** [in] – TRUE to enable Egress VLAN tagging on the port and given VLAN range, and FALSE to disable Egress VLAN tagging

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_VLAN</i>	invalid VLAN ID (out of range), or do not constitute a range
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_ETH_DB_NO_PERMISSION</i>	attempted to explicitly remove the default port VLAN ID from the tagging table
<i>IX_FAIL</i>	unknown OS or NPE communication error

Note:

Specifically removing the default port VLAN ID from the Egress tagging table by setting both *vlanIDMin* and *vlanIDMax* to the VLAN ID portion of the PVID is not allowed by this function and will return *IX_ETH_DB_NO_PERMISSION*. However, this can be circumvented, should the user specifically desire this, by either using a larger range (*vlanIDMin* < *vlanIDMax*) or by using **ixEthDBEgressVlanEntryTaggingEnabledSet**.

```

IxEthDBStatus ixEthDBEgressVlanTaggingEnabledGet ( IxEthDBPortId portID,
                                                         IxEthDBVlanSet vlanSet
                                                         )

```


Retrieves the complete Egress VLAN tagging table from a port.

This function copies the 4096 bit table controlling the Egress VLAN tagging into a user specified area. Each bit in the array indicates whether tagging for the corresponding VLAN (the bit position in the array) is enabled (the bit is set) or not (the bit is unset).

Bit 4095 is reserved and should not be set (it will be ignored if set).

See also:

ixEthDBEgressVlanTaggingEnabledSet

Parameters:

<i>portID</i>	IxEthDBPortId [in] – ID of the port whose Egress VLAN tagging behavior is retrieved
<i>vlanSet</i>	IxEthDBVlanSet [out] – user location to copy the Egress tagging table into; should have room to store 4096 bits (512 bytes)

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>vlanSet</i> pointer
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port

```
IxEthDBStatus ixEthDBEgressVlanTaggingEnabledSet ( IxEthDBPortId portID,  
                                                    IxEthDBVlanSet vlanSet  
                                                    )
```

Sets the complete Egress VLAN tagging table for a port.

This function is used to set the VLAN tagging/untagging per VLAN ID for a given port covering the entire VLAN ID range (0..4094). The *vlanSet* parameter is a 4096 bit array, each bit indicating the Egress behavior for the corresponding VLAN ID. If a bit is set then outgoing frames with the corresponding VLAN ID will be transmitted with the VLAN tag, otherwise the frame will be transmitted without the VLAN tag.

Bit 0 has a special significance, indicating tagging or tag removal for priority-tagged frames.

Bit 4095 is reserved and should never be set (it will be ignored if set).

- Reentrant – no
- ISR Callable – no

Parameters:

<i>portID</i>	IxEthDBPortId [in] – ID of the port whose Egress VLAN tagging behavior is set
<i>vlanSet</i>	IxEthDBVlanSet [in] – 4096 bit array controlling per-VLAN tagging and untagging

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>vlanSet</i> pointer
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_FAIL</i>	unknown OS or NPE communication error

Warning:

This function will automatically add the default port VLAN ID to the Egress tagging table every time it is called. The user should manually call `ixEthDBEgressVlanEntryTaggingEnabledSet` to prevent tagging on the default port VLAN ID if the default behavior is not intended.

IxEthDBStatus `ixEthDBEventProcessorPauseModeSet (BOOL pauseEnable)`

Pauses/resumes Ethernet DB event processor.

This API is provided to pause/resume Ethernet DB event processor without the need to kill and recreate event processor thread.

- Reentrant – no
- ISR Callable – no

Parameters:

pauseEnable BOOL [in] – pause mode: TRUE/FALSE

Return values:

IX_ETH_DB_SUCCESS Changing the pause mode is successful.
IX_ETH_DB_FAIL Ethernet event processor is not started. So, changing the pause mode is unsuccessful.

IxEthDBStatus `ixEthDBFeatureCapabilityGet (IxEthDBPortId portID,
IxEthDBFeature * featureSet
)`

Retrieves the feature capability set for a port.

This function retrieves the feature capability set for a port or the common capabilities shared between all the ports, writing the feature capability set in a user specified location.

The feature capability set will consist of a set formed by OR-ing one or more of the following values:

- *IX_ETH_DB_LEARNING* – Learning feature; enables EthDB to learn MAC address (filtering) records, including 802.1Q enabled records
- *IX_ETH_DB_FILTERING* – Filtering feature; enables EthDB to communicate with the NPEs for downloading filtering information in the NPEs; depends on the learning feature
- *IX_ETH_DB_VLAN_QOS* – VLAN/QoS feature; enables EthDB to configure NPEs to operate in

VLAN/QoS aware modes

- **IX_ETH_DB_FIREWALL** – Firewall feature; enables EthDB to configure NPEs to operate in firewall mode, using white/black address lists
- **IX_ETH_DB_SPANNING_TREE_PROTOCOL** – Spanning tree protocol feature; enables EthDB to configure the NPEs as STP nodes
- **IX_ETH_DB_WIFI_HEADER_CONVERSION** – WiFi 802.3 to 802.11 header conversion feature; enables EthDB to handle WiFi conversion data

Note that EthDB provides only the LEARNING feature for non-NPE ports.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to retrieve the capability set for (use **IX_ETH_DB_ALL_PORTS** to retrieve the common capabilities shared between all the ports)

featureSet **IxEthDBFeature** [out] – location where the capability set will be written to

Return values:

IX_ETH_DB_SUCCESS	operation completed successfully
IX_ETH_DB_INVALID_PORT	<i>portID</i> is not a valid port identifier
IX_ETH_DB_PORT_UNINITIALIZED	port is not initialized
IX_ETH_DB_INVALID_ARG	invalid <i>featureSet</i> pointer

```
IxEthDBStatus ixEthDBFeatureEnable ( IxEthDBPortId portID,  
                                     IxEthDBFeature feature,  
                                     BOOL enabled  
                                     )
```

Enables or disables one or more EthDB features.

Selects one or more features (see **ixEthDBFeatureCapabilityGet** for a description of the supported features) to be enabled or disabled on the selected port (or all the ports).

Note that some features are mutually incompatible:

- **IX_ETH_DB_FILTERING** is incompatible with **IX_ETH_DB_WIFI_HEADER_CONVERSION**

Also note that some features require other features to be enabled:

- **IX_ETH_DB_FILTERING** requires **IX_ETH_DB_LEARNING**

This function will either enable the entire selected feature set for the selected port (or all the ports), in which case it will return **IX_ETH_DB_SUCCESS**, or in case of error it will not enable any feature at all and return an appropriate error message.

The following features are enabled by default (for ports with the respective capability), for compatibility reasons with previous versions of CSR:

- **IX_ETH_DB_LEARNING**
- **IX_ETH_DB_FILTERING**

All other features are disabled by default and require manual enabling using `ixEthDBFeatureEnable`.

Default settings for VLAN, QoS, Firewall and WiFi header conversion features:

VLAN

When the VLAN/QoS feature is enabled for a port for the first time the default VLAN behavior of the port is set to be as **permissive** (it will accept all the frames) and **non-interferential** (it will not change any frames) as possible:

- the port VLAN ID (VID) is set to 0
- the Ingress acceptable frame filter is set to accept all frames
- the VLAN port membership is set to the complete VLAN range (0 – 4094)
- the Ingress tagging mode is set to pass-through (will not change frames)
- the Egress tagging mode is to send tagged frames in the entire VLAN range (0 – 4094)

Note that further disabling and re-enabling the VLAN feature for a given port will not reset the port VLAN behavior to the settings listed above. Any VLAN settings made by the user are kept.

QoS

The following default priority mapping table will be used (as per IEEE 802.1Q and IEEE 802.1D):

QoS traffic classes

QoS priority	Default traffic class	Traffic type
0	2	Best effort, default class for unexpedited traffic
1	0	Background traffic
2	1	Spare bandwidth
3	3	Excellent effort
4	4	Controlled load
5	5	Video traffic
6	6	Voice traffic
7	7	Network control

Firewall

The port firewall is configured by default in black-list mode, and the firewall address table is empty. This means the firewall will not filter any frames until the feature is configured and the firewall table is downloaded to the NPE.

Spanning Tree

The port is set to STP unblocked mode, therefore it will accept all frames until re-configured.

WiFi header conversion

The WiFi header conversion database is empty, therefore no actual header conversion will take place until this feature is configured and the conversion table downloaded to the NPE.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to enable or disable the features on (use IX_ETH_DB_ALL_PORTS for all the ports)
feature **IxEthDBFeature** [in] – feature or feature set to enable or disable
enabled **BOOL** [in] – TRUE to enable the feature and FALSE to disable it

Note:

Certain features, from a functional point of view, cannot be disabled as such at NPE level; when such features are set to *disabled* using the EthDB API they will be configured in such a way to determine a behavior equivalent to the feature being disabled. As well as this, disabled features cannot be configured or accessed via the EthDB API (except for getting their status).

Return values:

IX_ETH_DB_SUCCESS	operation completed successfully
IX_ETH_DB_INVALID_PORT	portID is not a valid port identifier
IX_ETH_DB_PORT_UNINITIALIZED	port is not initialized
IX_ETH_DB_NO_PERMISSION	attempted to enable mutually exclusive features, or a feature that depends on another feature which is not present or enabled
IX_ETH_DB_FEATURE_UNAVAILABLE	at least one of the features selected is unavailable
IX_FAIL	unknown OS or NPE communication error

```

IxEthDBStatus ixEthDBFeaturePropertyGet ( IxEthDBPortId      portID,
                                             IxEthDBFeature      feature,
                                             IxEthDBProperty      property,
                                             IxEthDBPropertyType * type,
                                             void *                value
                                             )

```

Retrieves the value of a feature property.

The EthDB features usually contain feature-specific properties describing or controlling how the feature operates. W (e.g. the firewall operating mode) have their own API, secondary properties can be retrieved using this function.

Properties can be read-only or read-write. ixEthDBFeaturePropertyGet operates with both types of features.

Properties have types associated with them. A descriptor indicating the property type is returned in the *type* argument

The currently supported properties and their corresponding features are as follows:

Properties for IX_ETH_DB_VLAN_QOS

Property identifier	Property type
IX_ETH_DB_QOS_TRAFFIC_CLASS_COUNT_PROPERTY	IX_ETH_DB_INTEGER_PROPER

IX_ETH_DB_QOS_TRAFFIC_CLASS_0_RX_QUEUE_PROPERTY	IX_ETH_DB_INTEGER_PROPERTY
IX_ETH_DB_QOS_TRAFFIC_CLASS_1_RX_QUEUE_PROPERTY	IX_ETH_DB_INTEGER_PROPERTY
IX_ETH_DB_QOS_TRAFFIC_CLASS_2_RX_QUEUE_PROPERTY	IX_ETH_DB_INTEGER_PROPERTY
IX_ETH_DB_QOS_TRAFFIC_CLASS_3_RX_QUEUE_PROPERTY	IX_ETH_DB_INTEGER_PROPERTY
IX_ETH_DB_QOS_TRAFFIC_CLASS_4_RX_QUEUE_PROPERTY	IX_ETH_DB_INTEGER_PROPERTY
IX_ETH_DB_QOS_TRAFFIC_CLASS_5_RX_QUEUE_PROPERTY	IX_ETH_DB_INTEGER_PROPERTY
IX_ETH_DB_QOS_TRAFFIC_CLASS_6_RX_QUEUE_PROPERTY	IX_ETH_DB_INTEGER_PROPERTY
IX_ETH_DB_QOS_TRAFFIC_CLASS_7_RX_QUEUE_PROPERTY	IX_ETH_DB_INTEGER_PROPERTY

See also:

ixEthDBFeaturePropertySet

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
feature **IxEthDBFeature** [in] – EthDB feature for which the property is retrieved
property **IxEthDBProperty** [in] – property identifier
type **IxEthDBPropertyType** [out] – location where the property type will be stored

value void [out] – location where the property value will be stored

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_INVALID_ARG</i>	invalid property identifier, <i>type</i> or <i>value</i> pointer arguments
<i>IX_ETH_DB_FAIL</i>	incorrect property value or unknown error

```
IxEthDBStatus ixEthDBFeaturePropertySet ( IxEthDBPortId   portID,  
                                           IxEthDBFeature  feature,  
                                           IxEthDBProperty property,  
                                           void *           value  
                                           )
```

Sets the value of a feature property.

Unlike **ixEthDBFeaturePropertyGet**, this function operates only with read–write properties

The currently supported properties and their corresponding features are as follows:

- **IX_ETH_DB_QOS_QUEUE_CONFIGURATION_COMPLETE** (for **IX_ETH_DB_VLAN_QOS**): freezes the availability of traffic classes to the number of traffic classes currently in use

Note that this function creates deep copies of the property values; once the function is invoked the client can free or reuse the memory area containing the original property value.

Copy behavior for different property types is defined as follows:

- **IX_ETH_DB_INTEGER_PROPERTY** – 4 bytes are copied from the source location
- **IX_ETH_DB_STRING_PROPERTY** – the source string will be copied up to the NULL " string terminator, maximum of 255 characters
- **IX_ETH_DB_MAC_ADDR_PROPERTY** – 6 bytes are copied from the source location
- **IX_ETH_DB_BOOL_PROPERTY** – 4 bytes are copied from the source location; the only allowed values are TRUE (1L) and false (0L)

See also:

ixEthDBFeaturePropertySet

Warning:

IX_ETH_DB_QOS_QUEUE_CONFIGURATION_COMPLETE is provided for EthAcc internal use; do not attempt to set this property directly

Parameters:

<i>portID</i>	IxEthDBPortId [in] – ID of the port
<i>feature</i>	IxEthDBFeature [in] – EthDB feature for which the property is set
<i>property</i>	IxEthDBProperty [in] – property identifier
<i>value</i>	void [in] – location where the property value is to be copied from

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_INVALID_ARG</i>	invalid property identifier, <i>value</i> pointer, or invalid property value

IxEthDBStatus ixEthDBFeatureStatesRestore (**IxEthDBPortId** *portId*)

Restores the state of EthDB based on latest settings, following the occurrence of an NPE soft-error. State is restored by re-downloading tables for the enabled features (e.g. Header Conversion and Firewall) or sending configuration messages to NPE.

Parameters:

portId **IxEthDBPortId** [in] – ID of the port

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_FAIL</i>	operation fails
<i>IX_ETH_DB_INVALID_PORT</i>	portId is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized

Note:

The function is useful for error-handling module to handle soft-error in Ethernet NPE.

This API will not restore learning table in Ethernet NPE. As the mechanism, to restore the original learning table is not trivial, after soft-error is handled it is expected that Ethernet NPE to learn the new source address again.

IxEthDBStatus ixEthDBFeatureStatusGet (**IxEthDBPortId** *portId*,
IxEthDBFeature *feature*,
 BOOL * *present*,
 BOOL * *enabled*
)

Retrieves the availability and status of a feature set.

This function returns the availability and status for a feature set. Note that if more than one feature is selected (e.g. IX_ETH_DB_LEARNING | IX_ETH_DB_FILTERING) the "present" and "enabled" return values will be set to TRUE only if all the features in the feature set are present and enabled (not only some).

Parameters:

<i>portId</i>	IxEthDBPortId [in] – ID of the port
<i>feature</i>	IxEthDBFeature [in] – identifier of the feature to retrieve the status for
<i>present</i>	BOOL [out] – location where a boolean flag indicating whether this feature is present will be written to
<i>enabled</i>	BOOL [out] – location where a boolean flag indicating whether this feature is enabled will be written to

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	either <i>present</i> or <i>enabled</i> pointer argument is invalid

```
IxEthDBStatus ixEthDBFilteringDatabaseSearch ( IxEthDBPortId * portID,
                                                IxEthDBMacAddr * macAddr
                                                )
```

Search the Ethernet learning/filtering database for a MAC address and return the port ID.

Searches the database for a MAC address. The function returns the portID for the MAC address record, if found. If no match is found the function returns IX_ETH_DB_NO_SUCH_ADDR. The portID is only valid if the function finds a match.

- Reentrant – yes
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID the address belongs to (populated only on a successful search)

macAddr [in] – MAC address to search for

Return values:

IX_ETH_DB_SUCCESS the record exists in the database

IX_ETH_DB_NO_SUCH_ADDR the record was not found in the database

IX_ETH_DB_INVALID_ARG invalid macAddr or portID pointer argument(s)

```
IxEthDBStatus ixEthDBFilteringDatabaseShow ( IxEthDBPortId portID )
```

This function displays the Mac Ethernet MAC address filtering tables.

It displays the MAC address, port ID, entry type (dynamic/static), and age for the given port ID.

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID to display the MAC address entries

Return values:

IX_ETH_DB_SUCCESS operation completed successfully

IX_ETH_DB_INVALID_PORT portID is invalid

IX_ETH_DB_PORT_UNINITIALIZED port ID is not initialized

IX_ETH_DB_FAIL record browser failed due to an internal busy or lock condition

Note:

this function is deprecated and kept for compatibility reasons; use **ixEthDBFilteringDatabaseShowRecords** instead

See also:

ixEthDBFilteringDatabaseShowRecords

```
void ixEthDBFilteringDatabaseShowAll ( void )
```

Displays the MAC address recorded in the filtering database for all registered ports (see **IxEthDBPortDefs.h**), grouped by port ID.

* – Reentrant – no

- ISR Callable – no

Return values:

void

Note:

this function is deprecated and kept for compatibility reasons; use **ixEthDBFilteringDatabaseShowRecords** instead

See also:

ixEthDBFilteringDatabaseShowRecords

```
IxEthDBStatus ixEthDBFilteringDatabaseShowRecords ( IxEthDBPortId      portID,  
                                                    IxEthDBRecordType recordFilter  
                                                    )
```

This function displays per port database records, given a record type filter.

The supported record type filters are:

- **IX_ETH_DB_FILTERING_RECORD** – displays the non-VLAN filtering records (MAC address, age, static/dynamic)
- **IX_ETH_DB_FILTERING_VLAN_RECORD** – displays the VLAN filtering records (MAC address, age, static/dynamic, VLAN ID, CFI, QoS class)
- **IX_ETH_DB_FILTERING_RECORD | IX_ETH_DB_FILTERING_VLAN_RECORD** – displays the previous two types of records
- **IX_ETH_DB_WIFI_RECORD** – displays the WiFi header conversion records (MAC address, optional gateway MAC address) and WiFi header conversion parameters (BSSID, Duration/ID)
- **IX_ETH_DB_FIREWALL_RECORD** – displays the firewall MAC address table and firewall operating mode (white list/black list)
- **IX_ETH_DB_ALL_RECORD_TYPES** – displays all the record types
- **IX_ETH_DB_NO_RECORD_TYPE** – displays only the port status (no records are displayed)

Additionally, the status of each port will be displayed, containing the following information: type, capabilities, enabled status, aging enabled status, group membership and maximum frame size.

The port ID can either be an actual port or IX_ETH_DB_ALL_PORTS, in which case the requested information will be displayed for all the ports (grouped by port)

- Reentrant – no
- ISR Callable – no

Parameters:

portID ID of the port to display information on (use IX_ETH_DB_ALL_PORTS for all the ports)
recordFilter record type filter

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_PORT portID is invalid
IX_ETH_DB_PORT_UNINITIALIZED port ID is not initialized

```
IxEthDBStatus ixEthDBFilteringDynamicEntryProvision ( IxEthDBPortId portID,
                                                         IxEthDBMacAddr * macAddr
                                                         )
```

Populate the Ethernet learning/filtering database with a dynamic MAC address.

Populates the Ethernet learning/filtering database with a dynamic MAC address. This entry will be subject to normal aging function, if aging is enabled on its port. If there is an entry (static or dynamic) with the same MAC address on any port this entry will take precedence. Any other entry with the same MAC address will be removed.

- Reentrant – yes
- ISR Callable – yes

Parameters:

portID **IxEthDBPortId** [in] – port ID to add the dynamic address to
macAddr [in] – static MAC address to add

Return values:

IX_ETH_DB_SUCCESS the add was successful
IX_ETH_DB_FAIL failed to populate the database entry
IX_ETH_DB_BUSY failed due to a temporary busy condition (i.e. lack of CPU cycles), try again later
IX_ETH_DB_INVALID_PORT portID is invalid
IX_ETH_DB_PORT_UNINITIALIZED port is not initialized
IX_ETH_DB_INVALID_ARG invalid *macAddr* pointer argument
IX_ETH_DB_FEATURE_UNAVAILABLE learning feature is disabled

IxEthDBStatus ixEthDBFilteringEntryDelete (IxEthDBMacAddr * *macAddr*)

Removes a MAC address entry from the Ethernet learning/filtering database.

Parameters:

macAddr IxEthDBMacAddr [in] – MAC address to remove

- Reentrant – yes
- ISR Callable – no

Return values:

<i>IX_ETH_DB_SUCCESS</i>	the removal was successful
<i>IX_ETH_DB_NO_SUCH_ADDR</i>	failed to remove the address (not in the database)
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> pointer argument
<i>IX_ETH_DB_BUSY</i>	failed due to a temporary busy condition (i.e. lack of CPU cycles), try again later

IxEthDBStatus ixEthDBFilteringPortMaximumFrameSizeSet (**IxEthDBPortId** *portID*,
 UINT32 *maximumFrameSize*
)

Set the maximum frame size supported on the given port ID.

This functions set the maximum frame size supported on a specific port ID

- Reentrant – yes
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID to configure
maximumFrameSize UINT32 [in] – maximum frame size to configure

Return values:

<i>IX_ETH_DB_SUCCESS</i>	the port is configured
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	the port has not been initialized
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is invalid
<i>IX_ETH_DB_INVALID_ARG</i>	size parameter is out of range
<i>IX_ETH_DB_NO_PERMISSION</i>	selected port is not an Ethernet NPE
<i>IX_FAIL</i>	unknown OS or NPE communication error

Note:

This maximum frame size is used to filter the frames based on their destination addresses and the capabilities of the destination port. The maximum value that can be set for a NPE port is 16320. (IX_ETHNPE_ACC_FRAME_LENGTH_MAX)

```
IxEthDBStatus ixEthDBFilteringPortSearch ( IxEthDBPortId    portID,
                                           IxEthDBMacAddr * macAddr
                                           )
```

Search the Ethernet learning/filtering database for the given MAC address and port ID.

This functions searches the database for a specific port ID and MAC address. Both the port ID and the MAC address have to match in order for the record to be reported as found.

- Reentrant – yes
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID to search for
macAddr [in] – MAC address to search for

Return values:

<i>IX_ETH_DB_SUCCESS</i>	the record exists in the database
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> pointer argument
<i>IX_ETH_DB_NO_SUCH_ADDR</i>	the record was not found in the database
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is invalid
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port ID is not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	learning feature is disabled

```
IxEthDBStatus ixEthDBFilteringPortUpdatingSearch ( IxEthDBPortId * portID,
                                                    IxEthDBMacAddr * macAddr
                                                    )
```

Search the filtering database for a MAC address, return the port ID and reset the record age.

Searches the database for a MAC address. The function returns the *portID* for the MAC address record and resets the entry age to 0, if found. If no match is found the function returns *IX_ETH_DB_NO_SUCH_ADDR*. The *portID* is only valid if the function finds a match.

- Reentrant – yes
- ISR Callable – no

Return values:

<i>IX_ETH_DB_SUCCESS</i>	the MAC address was found
<i>IX_ETH_DB_NO_SUCH_ADDR</i>	the MAC address was not found
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> or <i>portID</i> pointer argument(s)

```
IxEthDBStatus ixEthDBFilteringStaticEntryProvision ( IxEthDBPortId    portID,
                                                       IxEthDBMacAddr * macAddr
                                                       )
```

Populate the Ethernet learning/filtering database with a static MAC address.

Populates the Ethernet learning/filtering database with a static MAC address. The entry will not be subject to aging. If there is an entry (static or dynamic) with the corresponding MAC address on any port this entry will take precedence. Any other entry with the same MAC address will be removed.

- Reentrant – yes
- ISR Callable – yes

Parameters:

portID **IxEthDBPortId** [in] – port ID to add the static address to
macAddr [in] – static MAC address to add

Return values:

<i>IX_ETH_DB_SUCCESS</i>	the add was successful
<i>IX_ETH_DB_FAIL</i>	failed to populate the database entry
<i>IX_ETH_DB_BUSY</i>	failed due to a temporary busy condition (i.e. lack of CPU cycles), try again later
<i>IX_ETH_DB_INVALID_PORT</i>	portID is invalid
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> pointer argument
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	learning feature is disabled

```
IxEthDBStatus ixEthDBFirewallEntryAdd ( IxEthDBPortId     portID,  
                                           IxEthDBMacAddr * macAddr  
                                           )
```

Adds a MAC address to the firewall address list.

Note that adding the same MAC address twice will not return an error but will not actually accomplish anything.

The firewall MAC address list has a limited number of entries; once the maximum number of entries has been reached this function will failed to add more addresses, returning *IX_ETH_DB_NOMEM*.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
macAddr [in] – MAC address to be added

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> pointer argument
<i>IX_ETH_DB_FAIL</i>	maximum number of records reached
<i>IX_ETH_DB_BUSY</i>	lock condition or transaction in progress, try again later
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Firewall feature not enabled

```
IxEthDBStatus ixEthDBFirewallEntryRemove ( IxEthDBPortId portID,
                                             IxEthDBMacAddr * macAddr
                                             )
```

Removes a MAC address from the firewall address list.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
macAddr [in] – MAC address to be removed

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> pointer argument
<i>IX_ETH_DB_NO_SUCH_ADDR</i>	address not found
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Firewall feature not enabled

```
ixEthDBFirewallInvalidAddressFilterEnable ( IxEthDBPortId portID,
                                             BOOL enable
                                             )
```

Enables or disables invalid MAC address filtering.

According to IEEE802 it is illegal for a source address to be a multicast or broadcast address. If this feature is enabled the NPE inspects the source MAC addresses of incoming frames and discards them if invalid addresses are detected.

By default this service is enabled, if the firewall feature is supported by the NPE image.

Parameters:

portID ID of the port
enable TRUE to enable invalid MAC address filtering and FALSE to disable it

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Firewall feature not enabled
<i>IX_ETH_DB_FAIL</i>	unknown OS or NPE communication error

```
IxEthDBStatus ixEthDBFirewallMaskedEntryAdd ( IxEthDBPortId    portID,
                                                IxEthDBMacAddr * macAddr,
                                                IxEthDBMacAddr * addrMask
                                                )
```

Adds a MAC address + mask to the firewall address list.

Note that adding the same MAC address twice will not return an error but will not actually accomplish anything.

The firewall MAC address list has a limited number of entries; once the maximum number of entries has been reached this function will failed to add more addresses, returning `IX_ETH_DB_NOMEM`.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
macAddr [in] – MAC address to be added
addrMask [in] – address mask to be added

Return values:

<code>IX_ETH_DB_SUCCESS</code>	operation completed successfully
<code>IX_ETH_DB_INVALID_PORT</code>	<i>portID</i> is not a valid port identifier
<code>IX_ETH_DB_PORT_UNINITIALIZED</code>	port not initialized
<code>IX_ETH_DB_INVALID_ARG</code>	invalid <i>macAddr</i> pointer argument
<code>IX_ETH_DB_FAIL</code>	maximum number of records reached
<code>IX_ETH_DB_BUSY</code>	lock condition or transaction in progress, try again later
<code>IX_ETH_DB_FEATURE_UNAVAILABLE</code>	Firewall feature not enabled

```
IxEthDBStatus ixEthDBFirewallMaskedEntryRemove ( IxEthDBPortId    portID,
                                                    IxEthDBMacAddr * macAddr,
                                                    IxEthDBMacAddr * addrMask
                                                    )
```

Removes a MAC address + mask from the firewall address list.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
macAddr [in] – MAC address to be removed
addrMask [in] – address mask to be added

Return values:

<code>IX_ETH_DB_SUCCESS</code>	operation completed successfully
<code>IX_ETH_DB_INVALID_PORT</code>	<i>portID</i> is not a valid port identifier
<code>IX_ETH_DB_PORT_UNINITIALIZED</code>	port not initialized
<code>IX_ETH_DB_INVALID_ARG</code>	invalid <i>macAddr</i> pointer argument
<code>IX_ETH_DB_NO_SUCH_ADDR</code>	address not found

IX_ETH_DB_FEATURE_UNAVAILABLE Firewall feature not enabled

```
IxEthDBStatus ixEthDBFirewallModeSet ( IxEthDBPortId portID,  
                                         IxEthDBFirewallMode mode  
                                         )
```

Sets the firewall mode to use white or black listing.

When enabled, the NPE MAC address based firewall support operates in two modes:

- white-list mode (MAC address based admission)
 - ◆ *mode* set to *IX_ETH_DB_FIREWALL_WHITE_LIST*
 - ◆ only packets originating from MAC addresses contained in the firewall address list are allowed on the Rx path
- black-list mode (MAC address based blocking)
 - ◆ *mode* set to *IX_ETH_DB_FIREWALL_BLACK_LIST*
 - ◆ packets originating from MAC addresses contained in the firewall address list are discarded

Parameters:

portID **IxEthDBPortId** [in] – ID of the port

mode **IxEthDBFirewallMode** [in] – firewall mode (*IX_ETH_DB_FIREWALL_WHITE_LIST* or *IX_ETH_DB_FIREWALL_BLACK_LIST*)

Note:

by default the firewall operates in black-list mode with an empty address list, hence it doesn't filter any packets

Return values:

IX_ETH_DB_SUCCESS operation completed successfully

IX_ETH_DB_INVALID_PORT portID is not a valid port identifier

IX_ETH_DB_PORT_UNINITIALIZED port not initialized

IX_ETH_DB_FEATURE_UNAVAILABLE Firewall feature not enabled

IX_ETH_DB_INVALID_ARGUMENT *mode* argument is not a valid firewall configuration mode

IX_ETH_DB_FAIL unknown OS or NPE communication error

```
IxEthDBStatus ixEthDBFirewallTableDownload ( IxEthDBPortId portID )
```

Downloads the MAC firewall table to a port.

Parameters:

portID ID of the port

Return values:

IX_ETH_DB_SUCCESS operation completed successfully

<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Firewall feature not enabled
<i>IX_ETH_DB_FAIL</i>	unknown OS or NPE communication error

```
IxEthDBStatus ixEthDBIngressVlanTaggingEnabledGet ( IxEthDBPortId      portID,
                                                    IxEthDBTaggingAction taggingAction
                                                    *
                                                    )
```

Retrieves the Ingress VLAN tagging behavior from a port (see **ixEthDBIngressVlanTaggingEnabledSet**).

Parameters:

portID **IxEthDBPortId** [in] – ID of the port whose Ingress VLAN tagging behavior is set
taggingAction **IxEthDBTaggingAction** [out] – location where the tagging behavior for the port is written to

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>taggingAction</i> pointer argument
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port

```
IxEthDBStatus ixEthDBIngressVlanTaggingEnabledSet ( IxEthDBPortId      portID,
                                                    IxEthDBTaggingAction taggingAction
                                                    )
```

Sets the Ingress VLAN tagging behavior for a port.

A port's Ingress tagging behavior is controlled by the *taggingAction* parameter, which can take one of the following values:

- **IX_ETH_DB_PASS_THROUGH** – leaves the frame unchanged (does not add or remove the VLAN tag)
- **IX_ETH_DB_ADD_TAG** – adds the VLAN tag if not present, using the default port VID
- **IX_ETH_DB_REMOVE_TAG** – removes the VLAN tag if present

Parameters:

portID **IxEthDBPortId** [in] – ID of the port whose Ingress VLAN tagging behavior is set
taggingAction **IxEthDBTaggingAction** [in] – tagging behavior for the port

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>taggingAction</i> argument
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_FAIL</i>	unknown OS or NPE communication error

IxEthDBStatus ixEthDBInit (void)

Initializes the Ethernet learning/filtering database.

Note:

calling this function multiple times does not constitute an error; redundant calls will be ignored, returning *IX_ETH_DB_SUCCESS*

Return values:

IX_ETH_DB_SUCCESS initialization was successful
IX_ETH_DB_FAIL initialization failed (OS error)

IxEthDBStatus ixEthDBPortAddressSet (**IxEthDBPortId** *portID*,
IxEthDBMacAddr * *macAddr*
)

Sets the port MAC address.

This function is to be called from the Ethernet Access component top-level ixEthDBUnicastAddressSet(). Event processing cannot be enabled for a port until its MAC address has been set.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port whose MAC address is set
macAddr [in] – port MAC address

Return values:

IX_ETH_DB_SUCCESS MAC address was set successfully
IX_ETH_DB_FAIL MAC address was not set due to a message handler failure
IX_ETH_DB_INVALID_PORT if the port is not an Ethernet NPE

See also:

IxEthDBPortDefs.h for port definitions

IxEthDBStatus ixEthDBPortAgingDisable (**IxEthDBPortId** *portID*)

Disable the aging function for a specific port.

Parameters:

portID **IxEthDBPortId** [in] – port ID to disable aging on

- Reentrant – yes
- ISR Callable – no

Return values:

<i>IX_ETH_DB_SUCCESS</i>	aging disabled successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is invalid
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port ID is not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	learning feature is disabled

IxEthDBStatus ixEthDBPortAgingEnable (**IxEthDBPortId** *portID*)

Enable the aging function for a specific port.

Enables the aging of dynamic MAC address entries stored in the learning/filtering database

Note:

The aging function relies on the **ixEthDBDatabaseMaintenance** being called with a period of **IX_ETH_DB_MAINTENANCE_TIME** seconds.

- Reentrant – yes
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID to enable aging on

Return values:

<i>IX_ETH_DB_SUCCESS</i>	aging enabled successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is invalid
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port ID is not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	learning feature is disabled

IxEthDBStatus ixEthDBPortDependencyMapGet (**IxEthDBPortId** *portID*,
IxEthDBPortMap *dependencyPortMap*)

Retrieves the dependency port map for a port.

Parameters:

portID ID of the port to set the dependency map to

dependencyPortMap location where the port dependency map is to be copied

This function will copy the port dependency map to a user specified location.

- Reentrant – no
- ISR Callable – no

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>dependencyPortMap</i> pointer
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Filtering is not available or not enabled for the port

```
IxEthDBStatus ixEthDBPortDependencyMapSet ( IxEthDBPortId portID,  
                                              IxEthDBPortMap dependencyPortMap  
                                              )
```

Sets the dependency port map for a port.

Parameters:

<i>portID</i>	ID of the port to set the dependency map to
<i>dependencyPortMap</i>	new dependency map (as bitmap, each bit set indicates a port being included)

This function is used to share filtering information between ports. By adding a port into another port's dependency map the target port filtering data will import the filtering data from the port it depends on. Any changes to filtering data for a port – such as adding, updating or removing records – will trigger updates in the filtering information for all the ports depending on on the updated port.

For example, if ports 2 and 3 are set in the port 0 dependency map the filtering information for port 0 will also include the filtering information from ports 2 and 3. Adding a record to port 2 will also trigger an update not only on port 2 but also on port 0.

The dependency map is a 256 bit array where each bit corresponds to a port corresponding to the bit offset (bit 0 – port 0, bit 1 – port 1 etc). Setting a bit to 1 indicates that the corresponding port is the port map. For example, a dependency port map of 0x14 consists in the ports with IDs 2 and 4. Note that the last bit (offset 255) is reserved and should never be set (it will be automatically cleared by the function).

By default, each port has a dependency port map consisting only of itself, i.e.

```
IxEthDBPortMap portMap;  
  
// clear all ports from port map  
memset(portMap, 0, sizeof (portMap));  
  
// include portID in port map  
portMap[portID / 8] = 1 << (portID % 8);
```

- Reentrant – no
- ISR Callable – no

Note:

Setting dependency maps is useful for NPE ports, which benefit from automatic updates of filtering information. Setting dependency maps for user-defined ports is not an error but will have no actual effect.

Including a port in its own dependency map is not compulsory, however note that in this case updating the port will not trigger an update on the port itself, which might not be the intended behavior

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>dependencyPortMap</i> pointer
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Filtering is not available or not enabled for the port

IxEthDBStatus **ixEthDBPortDisable** (**IxEthDBPortId** *portID*)

Disables processing on a port.

This function is called automatically from the Ethernet Access component **ixEthAccPortDisable()** routine for Ethernet NPE ports and should be manually called for any user-defined port (any port that is not one of the Ethernet NPEs).

Note:

Calling **ixEthAccPortDisable()** will disable the respective Ethernet NPE. After Ethernet NPEs are disabled they are stopped therefore when re-enabled they need to be reset, downloaded with microcode and started. For learning to restart working the user needs to call again **ixEthAccPortUnicastMacAddressSet** or **ixEthDBUnicastAddressSet** with the respective port MAC address. Residual MAC addresses learnt before the port was disabled are deleted as soon as the port is disabled. This only applies to dynamic (learnt) entries, static entries do not disappear when the port is disabled.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to disable processing on

Return values:

<i>IX_ETH_DB_SUCCESS</i>	if disabling is successful
<i>IX_ETH_DB_FAIL</i>	if the disabling was not successful due to a message handler error
<i>IX_ETH_DB_INVALID_PORT</i>	if portID is invalid

Note:

calling this function multiple times after the first time completed successfully does not constitute an error; redundant calls will be ignored and return **IX_ETH_DB_SUCCESS**

IxEthDBStatus ixEthDBPortEnable (**IxEthDBPortId** *portID*)

Enables a port.

This function is called automatically from the Ethernet Access component **ixEthAccPortEnable()** routine for Ethernet NPE ports and should be manually called for any user-defined port (any port that is not one of the Ethernet NPEs).

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to enable processing on

Return values:

<i>IX_ETH_DB_SUCCESS</i>	if enabling is successful
<i>IX_ETH_DB_FAIL</i>	if the enabling was not successful due to a message handler error
<i>IX_ETH_DB_MAC_UNINITIALIZED</i>	the MAC address of this port was not initialized (only for Ethernet NPEs)
<i>IX_ETH_DB_INVALID_PORT</i>	if <i>portID</i> is invalid

Precondition:

ixEthDBPortAddressSet needs to be called prior to enabling the port events for Ethernet NPEs

See also:

ixEthDBPortAddressSet

IxEthDBPortDefs.h for port definitions

Note:

calling this function multiple times does not constitute an error; redundant calls will be ignored

void ixEthDBPortInit (**IxEthDBPortId** *portID*)

Initializes a port.

This function is called automatically by the Ethernet Access **ixEthAccPortInit()** routine for Ethernet NPE ports and should be manually called for any user-defined port (any port that is not one of the two Ethernet NPEs).

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to be initialized

See also:

IxEthDBPortDefs.h for port definitions

Note:

calling this function multiple times does not constitute an error; redundant calls will be ignored

```
IxEthDBStatus ixEthDBPortVlanMembershipAdd ( IxEthDBPortId portID,
                                                IxEthDBVlanId vlanID
                                                )
```

Adds a VLAN ID to a port's VLAN membership table.

Adding a VLAN ID to a port's VLAN membership table will cause frames tagged with the specified VLAN ID to be accepted by the frame filter, if Ingress VLAN membership filtering is enabled.

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to add the VLAN ID membership to
vlanID **IxEthDBVlanId** [in] – VLAN ID to be added to the port membership table

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_VLAN</i>	vlanID is not a valid VLAN ID
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_FAIL</i>	unknown OS or NPE communication error

Note:

A port's default VLAN ID is always in its own membership table, hence there is no need to explicitly add it using this function (although it is not an error to do so)

```
IxEthDBStatus ixEthDBPortVlanMembershipGet ( IxEthDBPortId portID,
                                                IxEthDBVlanSet vlanSet
                                                )
```

Retrieves a port's VLAN membership table.

Retrieves the complete VLAN membership table from a port, containing all the possible 4096 VLAN IDs. The table format is an array containing 4096 bits (512 bytes), where each bit indicates whether the VLAN at that bit index is in the port's membership list (if set) or not (unset).

The bit at index 0, indicating VLAN ID 0, indicates no VLAN membership and therefore no other bit will be set if bit 0 is set.

The bit at index 4095 is reserved and will not be set (it will be ignored if set).

The bit referencing the same VLAN ID as the default port VLAN ID will always be set, as the membership list must contain at least the default port VLAN ID.

- Reentrant – no

- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID to retrieve the VLAN membership table from
vlanSet **IxEthDBVlanSet** [out] – pointer a location where the VLAN membership table will be written to

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_PORT portID is not a valid port identifier
IX_ETH_DB_PORT_UNINITIALIZED port is not initialized
IX_ETH_DB_INVALID_ARG invalid *vlanSet* pointer
IX_ETH_DB_FEATURE_UNAVAILABLE VLAN/QoS feature is not available or not enabled for the port

```
IxEthDBStatus ixEthDBPortVlanMembershipRangeAdd ( IxEthDBPortId portID,
                                                    IxEthDBVlanId vlanIDMin,
                                                    IxEthDBVlanId vlanIDMax
                                                    )
```

Adds a VLAN ID range to a port's VLAN membership table.

All the VLAN IDs in the specified range will be added to the port VLAN membership table, including the range start and end VLAN IDs. Tagged frames with VLAN IDs in the specified range will be accepted by the frame filter, if Ingress VLAN membership filtering is enabled.

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID to add the VLAN membership range into
vlanIDMin **IxEthDBVlanId** [in] – start of the VLAN ID range
vlanIDMax **IxEthDBVlanId** [in] – end of the VLAN ID range

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_PORT portID is not a valid port identifier
IX_ETH_DB_PORT_UNINITIALIZED port is not initialized
IX_ETH_DB_INVALID_VLAN the specified VLAN IDs are invalid or do not constitute a range
IX_ETH_DB_FEATURE_UNAVAILABLE VLAN/QoS feature is not available or not enabled for the port
IX_FAIL unknown OS or NPE communication error

Note:

Is is valid to use the same VLAN ID for both *vlanIDMin* and *vlanIDMax*, in which case this function will behave as **ixEthDBPortVlanMembershipAdd**

A port's default VLAN ID is always in its own membership table, hence there is no need to explicitly add it using this function (although it is not an error to do so)

```
IxEthDBStatus ixEthDBPortVlanMembershipRangeRemove ( IxEthDBPortId portID,
                                                         IxEthDBVlanId vlanIDMin,
                                                         IxEthDBVlanId vlanIDMax
                                                         )
```

Removes a VLAN ID range from a port's VLAN membership table.

All the VLAN IDs in the specified range will be removed from the port VLAN membership table, including the range start and end VLAN IDs. Tagged frames with VLAN IDs in the range will be discarded by the frame filter, if Ingress membership filtering is enabled.

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to remove the VLAN membership range from
vlanIDMin **IxEthDBVlanId** [in] – start of the VLAN ID range
vlanIDMax **IxEthDBVlanId** [in] – end of the VLAN ID range

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_VLAN</i>	the specified VLAN IDs are invalid or do not constitute a range
<i>IX_ETH_DB_NO_PERMISSION</i>	attempted to remove the default VLAN ID from the port membership table (both vlanIDMin and vlanIDMax were set to the default port VLAN ID)
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_FAIL</i>	unknown OS or NPE communication error

Note:

It is valid to use the same VLAN ID for both vlanIDMin and vlanIDMax, in which case function will behave as **ixEthDBPortVlanMembershipRemove**

If the given range overlaps the default port VLAN ID this function will remove all the VLAN IDs in the range except for the port VLAN ID from its own membership table. This situation will be silently dealt with (no error message will be returned) as long as the range contains more than one value (i.e. at least one other value, apart from the default port VLAN ID). If the function is called with the vlanIDMin and vlanIDMax parameters both set to the port default VLAN ID, the function will infer that an attempt was specifically made to remove the default port VLAN ID from the port membership table, in which case the return value will be *IX_ETH_DB_NO_PERMISSION*.

```
IxEthDBStatus ixEthDBPortVlanMembershipRemove ( IxEthDBPortId portID,
                                                    IxEthDBVlanId vlanID
                                                    )
```

Removes a VLAN ID from a port's VLAN membership table.

Frames tagged with a VLAN ID which is not in a port's VLAN membership table will be discarded by the frame filter, if Ingress membership filtering is enabled.

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to remove the VLAN ID membership from
vlanID **IxEthDBVlanId** [in] – VLAN ID to be removed from the port membership table

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_INVALID_VLAN</i>	vlanID is not a valid VLAN ID
<i>IX_ETH_DB_NO_PERMISSION</i>	attempted to remove the default VLAN ID from the port membership table (vlanID was set to the default port VLAN ID)
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_FAIL</i>	unknown OS or NPE communication error

Note:

A port's default VLAN ID cannot be removed from the port's membership table; attempting it will return *IX_ETH_DB_NO_PERMISSION*

```
IxEthDBStatus ixEthDBPortVlanMembershipSet ( IxEthDBPortId portID,
                                                IxEthDBVlanSet vlanSet
                                                )
```

Sets a port's VLAN membership table.

Sets a port's VLAN membership table from a complete VLAN table containing all the possible 4096 VLAN IDs. The table format is an array containing 4096 bits (512 bytes), where each bit indicates whether the VLAN at that bit index is in the port's membership list (if set) or not (unset).

The bit at index 0, indicating VLAN ID 0, indicates no VLAN membership and therefore no other bit must be set if bit 0 is set.

The bit at index 4095 is reserved and should never be set (it will be ignored if set).

The bit referencing the same VLAN ID as the default port VLAN ID should always be set, as the membership list must contain at least the default port VLAN ID.

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID to set the VLAN membership table to
vlanSet **IxEthDBVlanSet** [in] – pointer to the VLAN membership table

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>vlanSet</i> pointer
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_FAIL</i>	unknown OS or NPE communication error

```
IxEthDBStatus ixEthDBPortVlanTagGet ( IxEthDBPortId    portID,
                                         IxEthDBVlanTag * vlanTag
                                         )
```

Retrieves the default 802.1Q port VLAN tag for a given port (see also **ixEthDBPortVlanTagSet**).

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to retrieve the default VLAN tag from
vlanTag **IxEthDBVlanTag** [out] – location to write the default port 802.1Q VLAN tag to

- Reentrant – no
- ISR Callable – no

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>vlanTag</i> pointer
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port

```
IxEthDBStatus ixEthDBPortVlanTagSet ( IxEthDBPortId    portID,
                                         IxEthDBVlanTag vlanTag
                                         )
```

Sets the default 802.1Q VLAN tag for a given port.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port to set the default VLAN tag to
vlanTag **IxEthDBVlanTag** [in] – default 802.1Q VLAN tag

The tag format has 16 bits and it is defined in the IEEE802.1Q specification. This tag will be used for tagging untagged frames (if enabled) and classifying unexpedited traffic into an internal traffic class (using the user priority field).

802.1Q tag format

3 bits	1 bit	12 bits
user priority	CFI	VID

User Priority : Defines user priority, giving eight (2^3) priority levels. IEEE 802.1P defines the operation for these 3 user priority bits

CFI : Canonical Format Indicator is always set to zero for Ethernet switches. CFI is used for compatibility reason between Ethernet type network and Token Ring type network. If a frame received at an Ethernet port has a CFI set to 1, then that frame should not be forwarded as it is to an untagged port.

VID : VLAN ID is the identification of the VLAN, which is basically used by the standard 802.1Q. It has 12 bits and allow the id entification of 4096 (2^{12}) VLANs. Of the 4096 possible VIDs, a VID of 0 is used to identify priority frames and value 4095 (FFF) is reserved, so the maximum possible VLAN configurations are 4,094.

- Reentrant – no
- ISR Callable – no

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_ETH_DB_INVALID_VLAN</i>	<i>vlanTag</i> argument does not parse to a valid 802.1Q VLAN tag

Note:

a VLAN ID value of 0 indicates that the port is not part of any VLAN

the value of the canonical frame indicator (CFI) field is ignored, the field being used only in frame tagging operations

```
IxEthDBStatus ixEthDBPriorityMappingClassGet ( IxEthDBPortId    portID,
IxEthDBPriority    userPriority,
IxEthDBPriority * trafficClass
)
```

Retrieves one QoS/user priority => traffic class mapping in a port's priority mapping table.

This function retrieves the internal traffic class associated with a QoS (user) priority from a given port's priority mapping table. Use this function when not all the QoS priority mappings are required (see also **ixEthDBPriorityMappingTableGet**)

- Reentrant – no
- ISR Callable – no

Parameters:

<i>portID</i>	IxEthDBPortId [in] – ID of the port to set the mapping to
<i>userPriority</i>	IxEthDBPriority [in] – user (QoS) priority, between 0 and 7 (0 being the lowest)
<i>trafficClass</i>	IxEthDBPriority [out] – location to write the corresponding internal traffic class to

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_PRIORITY</i>	invalid userPriority value (out of range)
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>trafficClass</i> pointer argument

```
IxEthDBStatus ixEthDBPriorityMappingClassSet ( IxEthDBPortId portID,  
                                                IxEthDBPriority userPriority,  
                                                IxEthDBPriority trafficClass  
                                                )
```

Sets one QoS/user priority => traffic class mapping in a port's priority mapping table.

This function establishes a mapping between a user (QoS) priority and an internal traffic class. The mapping will be saved in the port's priority mapping table. Use this function when not all the QoS priorities need remapping (see also **ixEthDBPriorityMappingTableSet**)

- Reentrant – no
- ISR Callable – no

Parameters:

<i>portID</i>	IxEthDBPortId [in] – ID of the port to set the mapping to
<i>userPriority</i>	IxEthDBPriority [in] – user (QoS) priority, between 0 and 7 (0 being the lowest)
<i>trafficClass</i>	IxEthDBPriority [in] – internal traffic class, between 0 and 3 (0 being the lowest)

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
--------------------------	----------------------------------

<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_PRIORITY</i>	<i>userPriority</i> out of range or <i>trafficClass</i> is beyond the number of currently available traffic classes
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port
<i>IX_FAIL</i>	unknown OS or NPE communication error

```
IxEthDBStatus ixEthDBPriorityMappingTableGet ( IxEthDBPortId      portID,
                                                IxEthDBPriorityTable priorityTable
                                                )
```

Retrieves a port's priority mapping table.

The priority mapping table for the given port will be copied in the location specified by the caller using "priorityTable"

- Reentrant – no
- ISR Callable – no

Parameters:

portID **ID IxEthDBPortId** [in] – of the port to retrieve the priority mapping table from
priorityTable **IxEthDBPriorityTable** [out] – pointer to a user specified location where the table will be copied to

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid priorityTable pointer
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	VLAN/QoS feature is not available or not enabled for the port

```
IxEthDBStatus ixEthDBPriorityMappingTableSet ( IxEthDBPortId      portID,
                                                IxEthDBPriorityTable priorityTable
                                                )
```

Sets a port's priority mapping table.

The priority mapping table is an 8x2 table mapping a QoS (user) priority into an internal traffic class. There are 8 valid QoS priorities (0..7, 0 being the lowest) which can be mapped into one of the 8 available traffic classes (0..7, 0 being the lowest). If a custom priority mapping table is not specified using this function the following default priority table will be used (as per IEEE 802.1Q and IEEE 802.1D):

QoS traffic classes

QoS priority	Default traffic class	Traffic type
--------------	-----------------------	--------------

0	2	Best effort, default class for unexpedited traffic
1	0	Background traffic
2	1	Spare bandwidth
3	3	Excellent effort
4	4	Controlled load
5	5	Video traffic
6	6	Voice traffic
7	7	Network control

- Reentrant – no
- ISR Callable – no

Parameters:

portID **IxEthDBPortId** [in] – port ID of the port to set the priority mapping table to
priorityTable **IxEthDBPriorityTable** [in] – location of the user priority table

Note:

The provided table will be copied into internal data structures in EthDB and can be deallocated by the called after this function has completed its execution, if so desired

Warning:

The number of available traffic classes differs depending on the NPE images and queue configuration. Check **IxEthDBQoS.h** for up-to-date information on the availability of traffic classes. Note that specifying a traffic class in the priority map which exceeds the system availability will produce an **IX_ETH_DB_INVALID_PRIORITY** return error code and no priority will be remapped.

Return values:

IX_ETH_DB_SUCCESS	operation completed successfully
IX_ETH_DB_INVALID_PORT	portID is not a valid port identifier
IX_ETH_DB_PORT_UNINITIALIZED	port is not initialized
IX_ETH_DB_INVALID_ARG	invalid <i>priorityTable</i> pointer
IX_ETH_DB_INVALID_PRIORITY	at least one priority value exceeds the current number of available traffic classes
IX_ETH_DB_FEATURE_UNAVAILABLE	VLAN/QoS feature is not available or not enabled for the port
IX_FAIL	unknown OS or NPE communication error

IxEthDBStatus **ixEthDBPriorityMappingTableUpdate** (**IxEthDBPortId** *portID*)

Reloads the last port priority mapping table set by the user. (see also **ixEthDBPriorityMappingTableSet**).

Parameters:

portID **IxEthDBPortId** [in] – ID of the port

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_FAIL</i>	operatoin fails

Note:

The function is useful for error-handling module to handle soft-error in Ethernet NPE. As this function is needed in non VLAN/QoS case to reconfigure Ethernet Rx queue, it does not checks for VLAN/QoS feature is enabled.

```
IxEthDBStatus ixEthDBSpanningTreeBlockingStateGet ( IxEthDBPortId portID,  
                                                    BOOL * blocked  
                                                    )
```

Retrieves the STP blocked/unblocked state for a port.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
blocked **BOOL** * [in] – set to TRUE if the port is STP blocked, FALSE otherwise

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>blocked</i> pointer argument
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Spanning Tree Protocol feature not enabled

```
IxEthDBStatus ixEthDBSpanningTreeBlockingStateSet ( IxEthDBPortId portID,  
                                                    BOOL blocked  
                                                    )
```

Sets the STP blocked/unblocked state for a port.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
blocked **BOOL** [in] – TRUE to set the port as STP blocked, FALSE to set it as unblocked

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	Spanning Tree Protocol feature not enabled

IX_ETH_DB_FAIL

unknown OS or NPE communication
error

IxEthDBStatus ixEthDBUnload (void)

Stops and prepares the EthDB component for unloading.

Return values:

IX_ETH_DB_SUCCESS de-initialization was successful
IX_ETH_DB_BUSY de-initialization failed, ports must be disabled first
IX_ETH_DB_FAIL de-initialization failed (OS error)

```
IxEthDBStatus ixEthDBUserFieldGet ( IxEthDBRecordType recordType,  
                                     IxEthDBMacAddr * macAddr,  
                                     IxEthDBPortId portId,  
                                     IxEthDBVlanId vlanId,  
                                     void ** field  
                                     )
```

Retrieves a user-defined field from a database record.

The database record is identified using a combination of the given parameters, depending on the record type. All the record types require the record MAC address.

- *IX_ETH_DB_FILTERING_RECORD* requires only the MAC address
- *IX_ETH_DB_VLAN_FILTERING_RECORD* requires the MAC address and the VLAN ID
- *IX_ETH_DB_WIFI_RECORD* requires the MAC address and the portID
- *IX_ETH_DB_FIREWALL_RECORD* requires the MAC address and the portID

Please note that if a parameter is not required it is completely ignored (it does not undergo parameter checking).

If no user-defined field was registered with the specified record then **NULL** will be written at the location specified by *field*.

Parameters:

recordType type of record (can be *IX_ETH_DB_FILTERING_RECORD*,
IX_ETH_DB_FILTERING_VLAN_RECORD, *IX_ETH_DB_WIFI_RECORD* or
IX_ETH_DB_FIREWALL_RECORD)
portID ID of the port (required only for *WIFI* and *FIREWALL* records)
macAddr MAC address of the record
vlanID VLAN ID of the record (required only for *FILTERING_VLAN* records)
field location to write the user defined field into

Return values:

IX_ETH_DB_SUCCESS operation completed successfully

IX_ETH_DB_INVALID_PORT portID was required but it is not a valid port identifier
IX_ETH_DB_INVALID_ARG invalid *macAddr* or *field* pointer arguments
IX_ETH_DB_NO_SUCH_ADDR record not found

```

IxEthDBStatus ixEthDBUserFieldSet ( IxEthDBRecordType recordType,
                                     IxEthDBMacAddr * macAddr,
                                     IxEthDBPortId portID,
                                     IxEthDBVlanId vlanID,
                                     void * field
                                     )

```

Adds a user-defined field to a database record.

This function associates a user-defined field to a database record. The user-defined field is passed as a (*void **) parameter, hence it can be used for any purpose (such as identifying a structure). Retrieving the user-defined field from a record is done using **ixEthDBUserFieldGet**. Note that EthDB never uses the user-defined field for any internal operation and it is not aware of the significance of its contents. The field is only stored as a pointer.

The database record is identified using a combination of the given parameters, depending on the record type. All the record types require the record MAC address.

- **IX_ETH_DB_FILTERING_RECORD** requires only the MAC address
- **IX_ETH_DB_VLAN_FILTERING_RECORD** requires the MAC address and the VLAN ID
- **IX_ETH_DB_WIFI_RECORD** requires the MAC address and the portID
- **IX_ETH_DB_FIREWALL_RECORD** requires the MAC address and the portID

Please note that if a parameter is not required it is completely ignored (it does not undergo parameter checking). The user-defined field can be cleared using a **NULL** *field* parameter.

Parameters:

recordType **IxEthDBRecordType** [in] – type of record (can be
 IX_ETH_DB_FILTERING_RECORD,
 IX_ETH_DB_FILTERING_VLAN_RECORD, IX_ETH_DB_WIFI_RECORD or
 IX_ETH_DB_FIREWALL_RECORD)
portID **IxEthDBPortId** [in] – ID of the port (required only for WIFI and FIREWALL records)
macAddr * [in] – MAC address of the record
vlanID **IxEthDBVlanId** [in] – VLAN ID of the record (required only for FILTERING_VLAN
 records)
field void * [in] – user defined field

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_PORT portID was required but it is not a valid port identifier
IX_ETH_DB_INVALID_ARG invalid *macAddr* pointer argument
IX_ETH_DB_NO_SUCH_ADDR record not found

```
IxEthDBStatus ixEthDBVlanPortExtractionEnable ( IxEthDBPortId portID,
                                                    BOOL enable
                                                    )
```

Enables or disables port ID extraction.

This feature can be used in the situation when a multi-port device (e.g. a switch) is connected to an IXP4XX port and the device can provide incoming frame port identification by tagging the TPID field in the Ethernet frame. Enabling port extraction will instruct the NPE to copy the TPID field from the frame and place it in the *ixp_ne_src_port* of the *ixp_buf* header. In addition, the NPE restores the TPID field to 0.

If the frame is not tagged the NPE will fill the *ixp_ne_src_port* with the port ID of the MII interface the frame was received from.

The TPID field is the least significant byte of the type/length field, which is normally set to 0x8100 for 802.1Q-tagged frames.

This feature is disabled by default.

Parameters:

portID ID of the port to configure port ID extraction on
enable TRUE to enable port ID extraction and FALSE to disable it

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_PORT portID is not a valid port identifier
IX_ETH_DB_PORT_UNINITIALIZED port is not initialized
IX_ETH_DB_FEATURE_UNAVAILABLE VLAN/QoS feature is not available or not enabled for the port
IX_FAIL unknown OS or NPE communication error

```
ixEthDBVlanTagGet ( IxEthDBMacAddr * macAddr,
                    IxEthDBVlanTag * vlanTag
                    )
```

Retrieves the 802.1Q VLAN tag from a database record given the record MAC address.

Parameters:

macAddr MAC address
vlanTag location to write the record 802.1Q VLAN tag to

Note:

VLAN tags can be retrieved only from IX_ETH_DB_FILTERING_VLAN_RECORD type records

This function is used together with ixEthDBVlanTagSet to provide MAC-based VLAN classification support. Please note that the bridging application must contain specific code to make use of this feature (see **ixEthDBVlanTagSet**).

- Reentrant – no
- ISR Callable – no

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_ARG invalid *macAddr* or *vlanTag* pointer
IX_ETH_DB_NO_SUCH_ADDR a filtering record with the specified MAC address was not found

```
IxEthDBStatus ixEthDBVlanTagSet ( IxEthDBMacAddr * macAddr,
                                   IxEthDBVlanTag vlanTag
                                   )
```

Sets the 802.1Q VLAN tag for a database record.

Parameters:

macAddr MAC address
vlanTag 802.1Q VLAN tag

This function is used together with **ixEthDBVlanTagGet** to provide MAC-based VLAN classification support. Please note that the bridging application must contain specific code to make use of this feature (see below).

VLAN tags can be set only in *IX_ETH_DB_FILTERING_RECORD* or *IX_ETH_DB_FILTERING_VLAN_RECORD* type records. If to an *IX_ETH_DB_FILTERING_RECORD* type record is added a VLAN tag the record type is automatically changed to *IX_ETH_DB_FILTERING_VLAN_RECORD*. Once this has occurred the record type will never revert to a non-VLAN type (unless deleted and re-added).

Record types used for different purposes (such as *IX_ETH_DB_WIFI_RECORD*) will be ignored by this function.

After using this function to associate a VLAN ID with a MAC address the VLAN ID can be extracted knowing the MAC address using **ixEthDBVlanTagGet**. This mechanism can be used to implement MAC-based VLAN classification if a bridging application searches for the VLAN tag when receiving a frame based on the source MAC address (contained in the *ixp_ne_src_mac* field of the buffer header). If found in the database, the application can instruct the NPE to tag the frame by writing the VLAN tag in the *ixp_ne_vlan_tci* field of the buffer header. This way the NPE will inspect the Egress tagging rule associated with the given VLAN ID on the Tx port and tag the frame if Egress tagging on the VLAN is allowed. Additionally, Egress tagging can be forced by setting the *ixp_ne_tx_flags.tag_over* and *ixp_ne_tx_flags.tag_mode* flags in the buffer header.

- Reentrant – no
- ISR Callable – no

Note:

this function will **not** add a filtering record, it can only be used to update an existing one

Return values:

IX_ETH_DB_SUCCESS operation completed successfully

IX_ETH_DB_INVALID_ARG invalid *macAddr* pointer
IX_ETH_DB_NO_SUCH_ADDR a filtering record with the specified MAC address was not found
IX_ETH_DB_INVALID_VLAN *vlanTag* argument does not parse to a valid 802.1Q VLAN tag

```
IxEthDBStatus ixEthDBWiFiAccessPointEntryAdd ( IxEthDBPortId     portID,
                                                IxEthDBMacAddr * macAddr,
                                                IxEthDBMacAddr * gatewayMacAddr
                                                )
```

Adds an "Access Point to Access Point" record to the database.

See also:

ixEthDBWiFiStationEntryAdd

Note that adding the same MAC address twice will simply overwrite the previously defined gateway MAC address value in the same record, if the record was previously of the "Access Point to Access Point" type.

Re-adding a MAC address as "Access Point to Access Point", which was previously added as "Access Point to Station" will migrate the record type to "Access Point to Access Point" and record the gateway MAC address.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
macAddr [in] – MAC address to add
gatewayMacAddr [in] – MAC address of the gateway Access Point

Return values:

IX_ETH_DB_SUCCESS operation completed successfully
IX_ETH_DB_INVALID_PORT portID is not a valid port identifier
IX_ETH_DB_PORT_UNINITIALIZED port is not initialized
IX_ETH_DB_FEATURE_UNAVAILABLE WiFi feature not enabled
IX_ETH_DB_INVALID_ARG invalid *macAddr* or *gatewayMacAddr* or *bssid* pointer argument
IX_ETH_DB_FAIL maximum number of records reached
IX_ETH_DB_BUSY lock condition or transaction in progress, try again later

```
IxEthDBStatus ixEthDBWiFiBSSIDSet ( IxEthDBPortId     portID,
                                       IxEthDBMacAddr * bssid
                                       )
```

Sets the BSSID field.

The BSSID field is a 6-byte value which identifies the infrastructure of the service set managed by the Access Point having the IXP400 as its processor. The value is written in the *BSSID* field of the 802.11 frame header. The BSSID value is the MAC address of the Access Point.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
bssid [in] – pointer to 6 bytes containing the BSSID

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>bssid</i> pointer argument
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	WiFi feature not enabled
<i>IX_ETH_DB_FAIL</i>	unknown OS or NPE communication error

IxEthDBStatus ixEthDBWiFiConversionTableDownload (**IxEthDBPortId** *portID*)

Downloads the MAC address table for 802.3 => 802.11 frame header conversion to the NPE.

Note that the frame conversion MAC address table must be individually downloaded to each NPE for which the frame header conversion feature is enabled (i.e. it is not possible to specify *IX_ETH_DB_ALL_PORTS*).

Parameters:

portID **IxEthDBPortId** [in] – ID of the port

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	WiFi feature not enabled
<i>IX_ETH_DB_FAIL</i>	unknown OS or NPE communication error

IxEthDBStatus ixEthDBWiFiDurationIDSet (**IxEthDBPortId** *portID*,
 UINT16 *durationID*
)

Sets the GlobalDurationID field.

The GlobalDurationID field is a 2–byte value inserted in the *Duration/ID* field for all 802.3 to 802.11 frame header conversions

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
durationID UINT16 [in] – GlobalDurationID field

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	WiFi feature not enabled

IX_ETH_DB_FAIL

unknown OS or NPE communication error

```
IxEthDBStatus ixEthDBWiFiEntryRemove ( IxEthDBPortId    portID,  
                                         IxEthDBMacAddr * macAddr  
                                         )
```

Removes a WiFi station record.

This function removes both types of WiFi records ("Access Point to Station" and "Access Point to Access Point").

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
macAddr [in] – MAC address to remove

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port is not initialized
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> pointer argument
<i>IX_ETH_DB_NO_SUCH_ADDR</i>	specified address was not found in the database
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	WiFi feature not enabled
<i>IX_ETH_DB_BUSY</i>	lock condition or transaction in progress, try again later

```
IxEthDBStatus ixEthDBWiFiFrameControlSet ( IxEthDBPortId portID,  
                                             UINT16           frameControl  
                                             )
```

Sets the GlobalFrameControl field.

The GlobalFrameControl field is a 2-byte value inserted in the *Frame Control* field for all 802.3 to 802.11 frame header conversions

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
frameControl UINT16 [in] – GlobalFrameControl value

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	<i>portID</i> is not a valid port identifier
<i>IX_ETH_DB_PORT_UNINITIALIZED</i>	port not initialized
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	WiFi feature not enabled
<i>IX_ETH_DB_FAIL</i>	unknown OS or NPE communication error


```

IxEthDBStatus ixEthDBWiFiRecordEntryAdd ( IxEthDBPortId      portID,
                                             IxEthDBMacAddr *   macAddr,
                                             IxEthDBWiFiRecData * wifiRecData
                                             )

```

Adds "APMAC/BSSID/STATIONS" record to the database, for 802.3 => 802.11 frame header conversion.

Frame header conversion is controlled by the set of MAC addresses and bssids , for the backward compatibility the old APIs are still usable to add gateway MAC address and station entry **ixEthDBWiFiAccessPointEntryAdd** and **ixEthDBWiFiStationEntryAdd**. Conversion arguments are added using **ixEthDBWiFiFrameControlSet**, **ixEthDBWiFiDurationIDSet** and **ixEthDBWiFiRecordEntryAdd**.

Note that adding the same MAC address twice will not return an error (but will not accomplish anything either)

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
macAddr [in] – MAC address to add
wifiRecData pointer to the wifi specific data (flags, gw etc.)

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	WiFi feature not enabled
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> , <i>wifiRecData</i> , <i>recType</i> , <i>logPort</i> , <i>vlanFlag</i> or <i>padLen</i> arguments
<i>IX_ETH_DB_FAIL</i>	maximum number of records reached
<i>IX_ETH_DB_BUSY</i>	lock condition or transaction in progress, try again later

```

IxEthDBStatus ixEthDBWiFiStationEntryAdd ( IxEthDBPortId   portID,
                                             IxEthDBMacAddr * macAddr
                                             )

```

Adds an "Access Point to Station" record to the database, for 802.3 => 802.11 frame header conversion.

Frame header conversion is controlled by the set of MAC addresses added using **ixEthDBWiFiStationEntryAdd** and **ixEthDBWiFiAccessPointEntryAdd**. Conversion arguments are added using **ixEthDBWiFiFrameControlSet**, **ixEthDBWiFiDurationIDSet** and **ixEthDBWiFiBSSIDSet**.

Note that adding the same MAC address twice will not return an error (but will not accomplish anything either), while re-adding a record previously added as an "Access Point to Access Point" will migrate the record to the "Access Point to Station" type.

Parameters:

portID **IxEthDBPortId** [in] – ID of the port
macAddr [in] – MAC address to add

Return values:

<i>IX_ETH_DB_SUCCESS</i>	operation completed successfully
<i>IX_ETH_DB_INVALID_PORT</i>	portID is not a valid port identifier
<i>IX_ETH_DB_FEATURE_UNAVAILABLE</i>	WiFi feature not enabled
<i>IX_ETH_DB_INVALID_ARG</i>	invalid <i>macAddr</i> or <i>bssid</i> pointer argument
<i>IX_ETH_DB_FAIL</i>	maximum number of records reached
<i>IX_ETH_DB_BUSY</i>	lock condition or transaction in progress, try again later

Intel (R) IXP400 Software Ethernet Database Port Definitions (IxEthDBPortDefs)

IXP400 Public definition of the ports and port capabilities.

Data Structures

struct **IxEthDBPortDefinition**
Port Definition – a structure contains the Port type and capabilities.

Defines

```
#define IX_ETH_DB_NUMBER_OF_PORTS  
    number of supported ports  
  
#define IX_ETH_DB_UNKNOWN_PORT  
    definition of an unknown port  
  
#define IX_ETH_DB_ALL_PORTS  
    Special port ID indicating all the ports.  
  
#define IX_ETH_DB_PORTS_ASSERTION  
    catch invalid port definitions (<2) with a compile-time assertion  
    resulting in a duplicate case error.  
  
#define IX_ETH_DB_CHECK_PORT(portID)  
    safety checks to verify whether the port is invalid or uninitialized  
  
#define IX_ETH_DB_CHECK_PORT_ALL(portID)  
    safety checks to verify whether the port is invalid or uninitialized;  
    tolerates the use of IX_ETH_DB_ALL_PORTS  
  
#define IX_ETH_DB_QUEUE_UNAVAILABLE  
    alias to indicate a queue (traffic class) is not available  
  
#define IX_IEEE802_1Q_QOS_PRIORITY_COUNT  
    number of QoS priorities, according to IEEE 802.1Q  
  
#define IX_ETH_DB_NPE_A_FUNCTIONALITY_ID_INDEX  
    value used to index the NPE A functionality ID in the traffic class  
    definition table  
  
#define IX_ETH_DB_TRAFFIC_CLASS_COUNT_INDEX  
    value used to index the traffic class count in the traffic class definition  
    table
```

```
#define IX_ETH_DB_QUEUE_ASSIGNMENT_INDEX  
value used to index the queue assignment index in the traffic class  
definition table
```

Enumerations

```
enum IxEthDBPortType {  
    IX_ETH_GENERIC,  
    IX_ETH_NPE  
}  
Port types – currently only Ethernet NPEs are recognized as specific  
types All other (user-defined) ports must be specified as  
IX_ETH_GENERIC.
```

```
enum IxEthDBPortCapability {  
    IX_ETH_NO_CAPABILITIES,  
    IX_ETH_ENTRY_AGING  
}  
Port capabilities – used by ixEthAccDatabaseMaintenance to decide  
whether it should manually age entries or not depending on the port  
capabilities.
```

Variables

```
IxEthDBPortDefinition ixEthDBPortDefinitions [IX_ETH_DB_NUMBER_OF_PORTS]  
Port definitions structure, indexed on the port ID.
```

Detailed Description

IXP400 Public definition of the ports and port capabilities.

Define Documentation

```
#define IX_ETH_DB_ALL_PORTS
```

Special port ID indicating all the ports.

Note:

This port ID can be used only by a subset of the EthDB API; each function specifically mentions whether this is a valid parameter as the port ID

Definition at line **83** of file **IxEthDBPortDefs.h**.

```
#define IX_ETH_DB_CHECK_PORT ( portID )
```

safety checks to verify whether the port is invalid or uninitialized

Definition at line **96** of file **IxEthDBPortDefs.h**.

```
#define IX_ETH_DB_CHECK_PORT_ALL ( portID )
```

safety checks to verify whether the port is invalid or uninitialized; tolerates the use of IX_ETH_DB_ALL_PORTS

Definition at line **114** of file **IxEthDBPortDefs.h**.

```
#define IX_ETH_DB_NPE_A_FUNCTIONALITY_ID_INDEX
```

value used to index the NPE A functionality ID in the traffic class definition table

Definition at line **51** of file **IxEthDBQoS.h**.

```
#define IX_ETH_DB_NUMBER_OF_PORTS
```

number of supported ports

Definition at line **57** of file **IxEthDBPortDefs.h**.

```
#define IX_ETH_DB_PORTS_ASSERTION
```

catch invalid port definitions (<2) with a compile-time assertion resulting in a duplicate case error.

Definition at line **90** of file **IxEthDBPortDefs.h**.

```
#define IX_ETH_DB_QUEUE_ASSIGNMENT_INDEX
```

value used to index the queue assignment index in the traffic class definition table

Definition at line **61** of file **IxEthDBQoS.h**.

```
#define IX_ETH_DB_QUEUE_UNAVAILABLE
```

alias to indicate a queue (traffic class) is not available

Definition at line **25** of file **IxEthDBQoS.h**.

```
#define IX_ETH_DB_TRAFFIC_CLASS_COUNT_INDEX
```

value used to index the traffic class count in the traffic class definition table

Definition at line **56** of file **IxEthDBQoS.h**.

```
#define IX_ETH_DB_UNKNOWN_PORT
```

definition of an unknown port

Definition at line **75** of file **IxEthDBPortDefs.h**.

```
#define IX_IEEE802_1Q_QOS_PRIORITY_COUNT
```

number of QoS priorities, according to IEEE 802.1Q

Definition at line **32** of file **IxEthDBQoS.h**.

Enumeration Type Documentation

```
enum IxEthDBPortCapability
```

Port capabilities – used by ixEthAccDatabaseMaintenance to decide whether it should manually age entries or not depending on the port capabilities.

Ethernet NPEs have aging capabilities, meaning that they will age the entries automatically (by themselves).

Enumeration values:

<i>IX_ETH_NO_CAPABILITIES</i>	no aging capabilities
<i>IX_ETH_ENTRY_AGING</i>	aging capabilities present

Definition at line **37** of file **IxEthDBPortDefs.h**.

```
enum IxEthDBPortType
```

Port types – currently only Ethernet NPEs are recognized as specific types All other (user-defined) ports must be specified as IX_ETH_GENERIC.

Enumeration values:

<i>IX_ETH_GENERIC</i>	generic ethernet port
<i>IX_ETH_NPE</i>	specific Ethernet NPE

Definition at line **25** of file **IxEthDBPortDefs.h**.

Variable Documentation

IxEthDBPortDefinition ixEthDBPortDefinitions[IX_ETH_DB_NUMBER_OF_PORTS]

Port definitions structure, indexed on the port ID.

Warning:

Ports 0 and 1 are used by the Ethernet access component therefore it is essential to be left untouched. Port 2 can be Ethernet Port or WAN port. Port 3 here (WAN) is given as an example port. The NPE firmware also assumes the NPE B to be the port 0, NPE C to be the port 1, and NPE A to be port 2.

Note:

that only 32 ports (0..31) are supported by EthDB

Definition at line **69** of file **IxEthDBPortDefs.h**.

Intel (R) IXP400 Software Ethernet Phy Access (IxEthMii) API

ethMii is a library that does provides access to the Ethernet PHYs

Functions

PUBLIC
IX_STATUS ixEthMiiPhyScan (BOOL phyPresent[], UINT32 maxPhyCount)
Scan the MDIO bus for PHYs This function scans PHY addresses 0 through 31, and sets phyPresent[n] to TRUE if a phy is discovered at address n.

PUBLIC
ixEthMiiPhyConfig (UINT32 phyAddr, BOOL speed100, BOOL fullDuplex, BOOL IX_STATUS autonegotiate)
Configure a PHY Configure a PHY's speed, duplex and autonegotiation status.

PUBLIC
IX_STATUS ixEthMiiPhyLoopbackEnable (UINT32 phyAddr)
Enable PHY Loopback in a specific Eth MII port.

PUBLIC
IX_STATUS ixEthMiiPhyLoopbackDisable (UINT32 phyAddr)
Disable PHY Loopback in a specific Eth MII port.

PUBLIC
IX_STATUS ixEthMiiPhyReset (UINT32 phyAddr)
Reset a PHY Reset a PHY.

PUBLIC
ixEthMiiLinkStatus (UINT32 phyAddr, BOOL *linkUp, BOOL *speed100, BOOL IX_STATUS *fullDuplex, BOOL *autoneg)
Retrieve the current status of a PHY Retrieve the link, speed, duplex and autonegotiation status of a PHY.

PUBLIC
IX_STATUS ixEthMiiPhyShow (UINT32 phyAddr)
Display information on a specified PHY Display link status, speed, duplex and Auto Negotiation status.

Detailed Description

ethMii is a library that does provides access to the Ethernet PHYs

Function Documentation

```
ixEthMiiLinkStatus ( UINT32 phyAddr,  
                     BOOL * linkUp,  
                     BOOL * speed100,  
                     BOOL * fullDuplex,  
                     BOOL * autoneg  
                     )
```

Retrieve the current status of a PHY Retrieve the link, speed, duplex and autonegotiation status of a PHY.

* – Reentrant – no

- ISR Callable – no

Precondition:

The MAC on Ethernet Port 2 (NPE C) must be initialised, and generating the MDIO clock.

Parameters:

phyAddr UINT32 [in] – the address of the Ethernet PHY (0–31)
linkUp BOOL [out] – set to TRUE if the link is up
speed100 BOOL [out] – set to TRUE indicates 100Mbit/s, FALSE indicates 10Mbit/s
fullDuplex BOOL [out] – set to TRUE indicates Full Duplex, FALSE indicates Half Duplex
autoneg BOOL [out] – set to TRUE indicates autonegotiation is enabled, FALSE indicates autonegotiation is disabled

Returns:

IX_STATUS
 ◇ IX_SUCCESS
 ◇ IX_FAIL : invalid arguments.

```
ixEthMiiPhyConfig ( UINT32 phyAddr,  
                    BOOL speed100,  
                    BOOL fullDuplex,  
                    BOOL autonegotiate  
                    )
```

Configure a PHY Configure a PHY's speed, duplex and autonegotiation status.

* – Reentrant – no

- ISR Callable – no

Precondition:

The MAC on Ethernet Port 2 (NPE C) must be initialised, and generating the MDIO clock.

Parameters:

phyAddr UINT32 [in]
speed100 BOOL [in] – set to TRUE for 100Mbit/s operation, FALSE for 10Mbit/s
fullDuplex BOOL [in] – set to TRUE for Full Duplex, FALSE for Half Duplex
autonegotiate BOOL [in] – set to TRUE to enable autonegotiation

Returns:

IX_STATUS
 ◇ IX_SUCCESS
 ◇ IX_FAIL : invalid arguments.

ixEthMiiPhyLoopbackDisable (UINT32 *phyAddr*)

Disable PHY Loopback in a specific Eth MII port.

* – Reentrant – no

- ISR Callable – no

Parameters:

phyAddr UINT32 [in] – the address of the Ethernet PHY (0–31)

Returns:

IX_STATUS
 ◇ IX_SUCCESS
 ◇ IX_FAIL : invalid arguments.

ixEthMiiPhyLoopbackEnable (UINT32 *phyAddr*)

Enable PHY Loopback in a specific Eth MII port.

Note:

When PHY Loopback is enabled, frames sent out to the PHY from the IXP400 will be looped back to the IXP400. They will not be transmitted out on the wire.

- Reentrant – no
- ISR Callable – no

Parameters:

phyAddr UINT32 [in] – the address of the Ethernet PHY (0–31)

Returns:

IX_STATUS

◇ IX_SUCCESS
◇ IX_FAIL : invalid arguments.

`ixEthMiiPhyReset (UINT32 phyAddr)`

Reset a PHY Reset a PHY.

* – Reentrant – no

• ISR Callable – no

Precondition:

The MAC on Ethernet Port 2 (NPE C) must be initialised, and generating the MDIO clock.

Parameters:

phyAddr UINT32 [in] – the address of the Ethernet PHY (0–31)

Returns:

IX_STATUS
◇ IX_SUCCESS
◇ IX_FAIL : invalid arguments.

`ixEthMiiPhyScan (BOOL phyPresent[],
 UINT32 maxPhyCount
)`

Scan the MDIO bus for PHYs This function scans PHY addresses 0 through 31, and sets *phyPresent*[n] to TRUE if a phy is discovered at address n.

* – Reentrant – no

• ISR Callable – no

Precondition:

The MAC on Ethernet Port 2 (NPE C) must be initialised, and generating the MDIO clock.

Parameters:

phyPresent BOOL [in] – boolean array of IXP400_ETH_ACC_MII_MAX_ADDR entries
maxPhyCount UINT32 [in] – number of PHYs to search for (the scan will stop when the indicated number of PHYs is found).

Returns:

IX_STATUS
◇ IX_ETH_ACC_SUCCESS
◇ IX_ETH_ACC_FAIL : invalid arguments.

`ixEthMiiPhyShow (UINT32 phyAddr)`

Display information on a specified PHY Display link status, speed, duplex and Auto Negotiation status.

* – Reentrant – no

- ISR Callable – no

Precondition:

The MAC on Ethernet Port 2 (NPE C) must be initialised, and generating the MDIO clock.

Parameters:

phyAddr UINT32 [in] – the address of the Ethernet PHY (0–31)

Returns:

IX_STATUS
 ◇ IX_SUCCESS
 ◇ IX_FAIL : invalid arguments.

Intel(R) IXP Software Feature Control (featureCtrl) Public API

The Public API for the IXP Feature Control.

Modules

Software Configuration for featureCtrl
Component

This section describes software configuration in access component.

Defines

```
#define IX_FEATURE_CTRL_COMPONENT_DISABLED  
Hardware Component is disabled/unavailable. Return status by  
ixFeatureCtrlComponentCheck().
```

```
#define IX_FEATURE_CTRL_COMPONENT_ENABLED  
Hardware Component is available. Return status by  
ixFeatureCtrlComponentCheck().
```

```
#define IX_FEATURE_CTRL_SILICON_TYPE_A0  
This is the value of A0 Silicon in product ID.
```

```
#define IX_FEATURE_CTRL_SILICON_TYPE_B0  
This is the value of B0 Silicon in product ID.
```

```
#define IX_FEATURE_CTRL_SILICON_STEPPING_MASK  
This is the mask of silicon stepping in product ID.
```

```
#define IX_FEATURE_CTRL_DEVICE_TYPE_MASK  
This is the mask of silicon stepping in product ID.
```

```
#define IX_FEATURE_CTRL_DEVICE_TYPE_OFFSET  
This is the mask of silicon stepping in product ID.
```

```
#define IX_FEATURE_CTRL_XSCALE_FREQ_533  
This is the value of 533MHz Intel XScale(R) Processor in product ID.
```

```
#define IX_FEATURE_CTRL_XSCALE_FREQ_400  
This is the value of 400MHz Intel XScale(R) Processor in product ID.
```

```
#define IX_FEATURE_CTRL_XSCALE_FREQ_266  
This is the value of 266MHz Intel XScale(R) Processor in product ID.
```

```

#define IX_FEATURE_CTRL_XSCALE_FREQ_MASK
    This is the mask of Intel XScale(R) Processor in product ID.

#define IX_FEATURECTRL_REG_UTOPIA_32PHY
    Maximum UTOPIA PHY available is 32.

#define IX_FEATURECTRL_REG_UTOPIA_16PHY
    Maximum UTOPIA PHY available is 16.

#define IX_FEATURECTRL_REG_UTOPIA_8PHY
    Maximum UTOPIA PHY available to is 8.

#define IX_FEATURECTRL_REG_UTOPIA_4PHY
    Maximum UTOPIA PHY available to is 4.

#define IX_FEATURECTRL_REG_XSCALE_533FREQ
    Maximum frequency available to Intel (R) IXP46X Product Line of Network Processors is 533 MHz.

#define IX_FEATURECTRL_REG_XSCALE_667FREQ
    Maximum frequency available to Intel (R) IXP46X Product Line of Network Processors is 667 MHz.

#define IX_FEATURECTRL_REG_XSCALE_400FREQ
    Maximum frequency available to Intel (R) IXP46X Product Line of Network Processors is 400 MHz.

#define IX_FEATURECTRL_REG_XSCALE_266FREQ
    Maximum frequency available to Intel (R) IXP46X Product Line of Network Processors is 266 MHz.

#define IX_FEATURECTRL_COMPONENT_NOT_AVAILABLE
    Component selected is not available for device.

#define IX_FEATURECTRL_COMPONENT_ALWAYS_AVAILABLE
    Component selected is not available for device.

```

Typedefs

```

typedef UINT32 IxFeatureCtrlReg
    Feature Control Register that contains hardware components' availability information.

typedef UINT32 IxFeatureCtrlProductId
    Product ID of Silicon that contains Silicon Stepping and Maximum Intel XScale(R) Processor Frequency information.

```

Functions

IxFeatureCtrlDeviceId IxFeatureCtrlDeviceRead (void)

This function gets the type of device that the software is currently running on.

IxFeatureCtrlBuildDevice IxFeatureCtrlSoftwareBuildGet (void)

This function refers to the value set by the compiler flag to determine the type of device the software is built for.

PUBLIC

IxFeatureCtrlReg IxFeatureCtrlHwCapabilityRead (void)

This function reads out the hardware capability of a silicon type as defined in feature control register. This value is different from that returned by IxFeatureCtrlRead() because this function returns the actual hardware component availability.

PUBLIC IX_STATUS **IxFeatureCtrlComponentCheck** (IxFeatureCtrlComponentType componentType)

This function will check the availability of hardware component specified as componentType value.

PUBLIC

IxFeatureCtrlProductId IxFeatureCtrlProductIdRead (void)

This function will return the device product ID.

PUBLIC IX_STATUS **IxFeatureCtrlSwConfigurationCheck** (IxFeatureCtrlSwConfig swConfigType)

This function checks whether the specified software configuration is enabled or disabled.

PUBLIC void **IxFeatureCtrlSwConfigurationWrite** (IxFeatureCtrlSwConfig swConfigType, BOOL enabled)

This function enable/disable the specified software configuration.

PUBLIC void **IxFeatureCtrlSwVersionShow** (void)

This function shows the current software release information for the device.

Detailed Description

The Public API for the IXP Feature Control.

Define Documentation

```
#define IX_FEATURE_CTRL_COMPONENT_DISABLED
```

Hardware Component is disabled/unavailable. Return status by **IxFeatureCtrlComponentCheck()**.

Definition at line **221** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_COMPONENT_ENABLED
```

Hardware Component is available. Return status by **ixFeatureCtrlComponentCheck()**.

Definition at line **231** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_DEVICE_TYPE_MASK
```

This is the mask of silicon stepping in product ID.

Definition at line **301** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_DEVICE_TYPE_OFFSET
```

This is the mask of silicon stepping in product ID.

Definition at line **313** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_SILICON_STEPPING_MASK
```

This is the mask of silicon stepping in product ID.

Definition at line **292** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_SILICON_TYPE_A0
```

This is the value of A0 Silicon in product ID.

Definition at line **274** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_SILICON_TYPE_B0
```

This is the value of B0 Silicon in product ID.

Definition at line **283** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_XSCALE_FREQ_266
```

This is the value of 266MHz Intel XScale(R) Processor in product ID.

Definition at line **343** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_XSCALE_FREQ_400
```

This is the value of 400MHz Intel XScale(R) Processor in product ID.

Definition at line **334** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_XSCALE_FREQ_533
```

This is the value of 533MHz Intel XScale(R) Processor in product ID.

Definition at line **325** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_XSCALE_FREQ_MASK
```

This is the mask of Intel XScale(R) Processor in product ID.

Definition at line **352** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_COMPONENT_ALWAYS_AVAILABLE
```

Component selected is not available for device.

Definition at line **507** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_COMPONENT_NOT_AVAILABLE
```

Component selected is not available for device.

Definition at line **497** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_REG_UTOPIA_16PHY
```

Maximum UTOPIA PHY available is 16.

Definition at line **372** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_REG_UTOPIA_32PHY
```

Maximum UTOPIA PHY available is 32.

Definition at line **362** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_REG_UTOPIA_4PHY
```

Maximum UTOPIA PHY available to is 4.

Definition at line **392** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_REG_UTOPIA_8PHY
```

Maximum UTOPIA PHY available to is 8.

Definition at line **382** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_REG_XSCALE_266FREQ
```

Maximum frequency available to Intel (R) IXP46X Product Line of Network Processors is 266 MHz.

Definition at line **436** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_REG_XSCALE_400FREQ
```

Maximum frequency available to Intel (R) IXP46X Product Line of Network Processors is 400 MHz.

Definition at line **425** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_REG_XSCALE_533FREQ
```

Maximum frequency available to Intel (R) IXP46X Product Line of Network Processors is 533 MHz.

Definition at line **403** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURECTRL_REG_XSCALE_667FREQ
```

Maximum frequency available to Intel (R) IXP46X Product Line of Network Processors is 667 MHz.

Definition at line **414** of file **IxFeatureCtrl.h**.

Typedef Documentation

```
IxFeatureCtrlProductId
```

Product ID of Silicon that contains Silicon Stepping and Maximum Intel XScale(R) Processor Frequency information.

Definition at line **898** of file **IxFeatureCtrl.h**.

IxFeatureCtrlReg

Feature Control Register that contains hardware components' availability information.

Definition at line **888** of file **IxFeatureCtrl.h**.

Function Documentation

IX_STATUS ixFeatureCtrlComponentCheck (**IxFeatureCtrlComponentType** *componentType*)

This function will check the availability of hardware component specified as *componentType* value.

Usage Example:

- if(IX_FEATURE_CTRL_COMPONENT_DISABLED != ixFeatureCtrlComponentCheck(IX_FEATURECTRL_NPEA))
- if(IX_FEATURE_CTRL_COMPONENT_ENABLED == ixFeatureCtrlComponentCheck(IX_FEATURECTRL_NPEB))

This function is typically called during component initialization time.

Parameters:

componentType **IxFeatureCtrlComponentType** [in] – the type of a component as defined above as IX_FEATURECTRL_XXX

Returns:

- ◇ IX_FEATURE_CTRL_COMPONENT_ENABLED if component is available
- ◇ IX_FEATURE_CTRL_COMPONENT_DISABLED if component is unavailable

IxFeatureDeviceId ixFeatureCtrlDeviceRead (void)

This function gets the type of device that the software is currently running on.

This function reads the feature Ctrl register specifically to obtain the device id. The definitions of the available IDs are as above.

Returns:

- ◇ IxFeatureCtrlDeviceId – the type of device currently running

IxFeatureCtrlReg ixFeatureCtrlHwCapabilityRead (void)

This function reads out the hardware capability of a silicon type as defined in feature control register. This value is different from that returned by `ixFeatureCtrlRead()` because this function returns the actual hardware component availability.

The bit location of each hardware component is defined above. A value of '1' in bit means the hardware component is not available. A value of '0' means the hardware component is available.

Returns:

◇ `IxFeatureCtrlReg` – the hardware capability of the device.

Warning:

◇ This function must not be called when the device is running as the result is undefined.

`IxFeatureCtrlProductId` `ixFeatureCtrlProductIdRead (void)`

This function will return the device product ID.

Returns:

◇ `IxFeatureCtrlProductId` – the value of product ID.

`IxFeatureCtrlBuildDevice` `ixFeatureCtrlSoftwareBuildGet (void)`

This function refers to the value set by the compiler flag to determine the type of device the software is built for.

`IX_STATUS` `ixFeatureCtrlSwConfigurationCheck (IxFeatureCtrlSwConfig swConfigType)`

This function checks whether the specified software configuration is enabled or disabled.

Usage Example:

- `if(IX_FEATURE_CTRL_SWCONFIG_DISABLED != ixFeatureCtrlSwConfigurationCheck(IX_FEATURECTRL_ETH_LEARNING))`
- `if(IX_FEATURE_CTRL_SWCONFIG_ENABLED == ixFeatureCtrlSwConfigurationCheck(IX_FEATURECTRL_ETH_LEARNING))`

This function is typically called during access component initialization time.

Parameters:

swConfigType **Software Configuration for featureCtrl Component** [in] – the type of a software configuration defined in `IxFeatureCtrlSwConfig` enumeration.

Returns:

◇ `IX_FEATURE_CTRL_SWCONFIG_ENABLED` if software configuration is enabled.
◇ `IX_FEATURE_CTRL_SWCONFIG_DISABLED` if software configuration is disabled.

```
void ixFeatureCtrlSwConfigurationWrite ( IxFeatureCtrlSwConfig swConfigType,
                                         BOOL enabled
                                         )
```

This function enable/disable the specified software configuration.

Usage Example:

- ixFeatureCtrlSwConfigurationWrite(IX_FEATURECTRL_ETH_LEARNING, TRUE) is used to enable Ethernet Learning Feature
- ixFeatureCtrlSwConfigurationWrite(IX_FEATURECTRL_ETH_LEARNING, FALSE) is used to disable Ethernet Learning Feature

Parameters:

swConfigType IxFeatureCtrlSwConfig [in] – the type of a software configuration defined in IxFeatureCtrlSwConfig enumeration.

enabled **BOOL** [in] – To enable(TRUE) / disable (FALSE) the specified software configuration.

Returns:

none

```
void ixFeatureCtrlSwVersionShow ( void )
```

This function shows the current software release information for the device.

Returns:

none

Software Configuration for featureCtrl Component

[Intel(R) IXP Software Feature Control (featureCtrl) Public API]

This section describes software configuration in access component.

Defines

#define IX_FEATURE_CTRL_SWCONFIG_DISABLED
Software configuration is disabled.

#define IX_FEATURE_CTRL_SWCONFIG_ENABLED
Software configuration is enabled.

Enumerations

enum IxFeatureCtrlBuildDevice {
 IX_FEATURE_CTRL_SW_BUILD_IXP42X,
 IX_FEATURE_CTRL_SW_BUILD_IXP46X,
 IX_FEATURE_CTRL_SW_BUILD_MAX
}
Indicates software build type.

enum IxFeatureCtrlSwConfig {
 IX_FEATURECTRL_ETH_LEARNING,
 IX_FEATURECTRL_ORIGB0_DISPATCHER,
 IX_FEATURECTRL_SWCONFIG_MAX
}
Enumeration for software configuration in access components.

enum IxFeatureCtrlComponentType {
 IX_FEATURECTRL_RCOMP,
 IX_FEATURECTRL_USB,
 IX_FEATURECTRL_HASH,
 IX_FEATURECTRL_AES,
 IX_FEATURECTRL_DES,
 IX_FEATURECTRL_HDLC,
 IX_FEATURECTRL_AAL,
 IX_FEATURECTRL_HSS,
 IX_FEATURECTRL_UTOPIA,
 IX_FEATURECTRL_ETH0,
 IX_FEATURECTRL_ETH1,
 IX_FEATURECTRL_NPEA,
 IX_FEATURECTRL_NPEB,
 IX_FEATURECTRL_NPEC,
 IX_FEATURECTRL_PCI,
 IX_FEATURECTRL_ECC_TIMESYNC,
}

```

IX_FEATURECTRL_UTOPIA_PHY_LIMIT,
IX_FEATURECTRL_UTOPIA_PHY_LIMIT_BIT2,
IX_FEATURECTRL_USB_HOST_CONTROLLER,
IX_FEATURECTRL_NPEA_ETH,
IX_FEATURECTRL_NPEB_ETH,
IX_FEATURECTRL_RSA,
IX_FEATURECTRL_XSCALE_MAX_FREQ,
IX_FEATURECTRL_XSCALE_MAX_FREQ_BIT2,
IX_FEATURECTRL_MAX_COMPONENTS
}

```

Enumeration for components availavble.

```

enum IxFeatureCtrlDeviceId {
    IX_FEATURE_CTRL_DEVICE_TYPE_IXP42X,
    IX_FEATURE_CTRL_DEVICE_TYPE_IXP46X,
    IX_FEATURE_CTRL_DEVICE_TYPE_MAX
}

```

Enumeration for device type.

Detailed Description

This section describes software configuration in access component.

The configuration can be changed at run–time. **ixFeatureCtrlSwConfigurationCheck()** will be used across applicable access layer components to check the configuration. **ixFeatureCtrlSwConfigurationWrite()** is used to write the software configuration.

Note:

All software configurations are default to be enabled.

Define Documentation

```
#define IX_FEATURE_CTRL_SWCONFIG_DISABLED
```

Software configuration is disabled.

Definition at line **531** of file **IxFeatureCtrl.h**.

```
#define IX_FEATURE_CTRL_SWCONFIG_ENABLED
```

Software configuration is enabled.

Definition at line **541** of file **IxFeatureCtrl.h**.

Enumeration Type Documentation

enum IxFeatureCtrlBuildDevice

Indicates software build type.

Enumeration values:

<i>IX_FEATURE_CTRL_SW_BUILD_IXP42X</i>	Build type is IXP42X.
<i>IX_FEATURE_CTRL_SW_BUILD_IXP46X</i>	Build type is IXP46X.
<i>IX_FEATURE_CTRL_SW_BUILD_MAX</i>	Max build types.

Definition at line **555** of file **IxFeatureCtrl.h**.

enum IxFeatureCtrlComponentType

Enumeration for components availavble.

Enumeration values:

<i>IX_FEATURECTRL_RCOMP</i>	bit location for RComp Circuitry
<i>IX_FEATURECTRL_USB</i>	bit location for USB Controller
<i>IX_FEATURECTRL_HASH</i>	bit location for Hashing Coprocessor
<i>IX_FEATURECTRL_AES</i>	bit location for AES Coprocessor
<i>IX_FEATURECTRL_DES</i>	bit location for DES Coprocessor
<i>IX_FEATURECTRL_HDLC</i>	bit location for HDLC Coprocessor
<i>IX_FEATURECTRL_AAL</i>	bit location for AAL Coprocessor
<i>IX_FEATURECTRL_HSS</i>	bit location for HSS Coprocessor
<i>IX_FEATURECTRL_UTOPIA</i>	bit location for UTOPIA Coprocessor
<i>IX_FEATURECTRL_ETH0</i>	bit location for Ethernet 0 Coprocessor
<i>IX_FEATURECTRL_ETH1</i>	bit location for Ethernet 1 Coprocessor
<i>IX_FEATURECTRL_NPEA</i>	bit location for NPE A
<i>IX_FEATURECTRL_NPEB</i>	bit location for NPE B
<i>IX_FEATURECTRL_NPEC</i>	bit location for NPE C
<i>IX_FEATURECTRL_PCI</i>	bit location for PCI Controller
<i>IX_FEATURECTRL_ECC_TIMESYNC</i>	bit location for TimeSync Coprocessor
<i>IX_FEATURECTRL_UTOPIA_PHY_LIMIT</i>	bit location for Utopia PHY Limit Status
<i>IX_FEATURECTRL_UTOPIA_PHY_LIMIT_BIT2</i>	2nd bit of PHY limit status
<i>IX_FEATURECTRL_USB_HOST_CONTROLLER</i>	bit location for USB host controller
<i>IX_FEATURECTRL_NPEA_ETH</i>	bit location for NPE–A Ethernet Disable
<i>IX_FEATURECTRL_NPEB_ETH</i>	bit location for NPE–B Ethernet 1–3 Coprocessors Disable
<i>IX_FEATURECTRL_RSA</i>	bit location for RSA Crypto block Coprocessors Disable

<i>IX_FEATURECTRL_XSCALE_MAX_FREQ</i>	bit location for Intel XScale(R) Processor max frequency
<i>IX_FEATURECTRL_XSCALE_MAX_FREQ_BIT2</i>	2nd xscale max freq bit NOT TO BE USED

Definition at line **642** of file **IxFeatureCtrl.h**.

```
enum IxFeatureCtrlDeviceId
```

Enumeration for device type.

Warning:

This enum is closely related to the npe image. Its format should comply with formats used in the npe image ImageID. This is indicated by the first nibble of the image ID. This should also be in sync with the with what is defined in CP15. Current available formats are

Enumeration values:

<i>IX_FEATURE_CTRL_DEVICE_TYPE_IXP42X</i>	Device type is IXP42X.
<i>IX_FEATURE_CTRL_DEVICE_TYPE_IXP46X</i>	Device type is IXP46X.
<i>IX_FEATURE_CTRL_DEVICE_TYPE_MAX</i>	Max devices.

Definition at line **861** of file **IxFeatureCtrl.h**.

```
enum IxFeatureCtrlSwConfig
```

Enumeration for software configuration in access components.

Entry for new run-time software configuration should be added here.

Enumeration values:

<i>IX_FEATURECTRL_ETH_LEARNING</i>	EthDB Learning Feature.
<i>IX_FEATURECTRL_ORIGB0_DISPATCHER</i>	IXP42X B0 Silicon and IXP46X processor dispatcher without livelock prevention functionality Feature.
<i>IX_FEATURECTRL_SWCONFIG_MAX</i>	Maximum boudary for IxFeatureCtrlSwConfig.

Definition at line **574** of file **IxFeatureCtrl.h**.

Intel (R) IXP400 Software HSS Access (IxHssAcc) API

The public API for the IXP400 HssAccess component.

Data Structures

- struct **IxHssAccConfigParams**
Structure containing HSS configuration parameters.
- struct **IxHssAccHdlcMode**
This structure contains 56Kbps, HDLC-mode configuration parameters.
- struct **IxHssAccPktHdlcFraming**
This structure contains information required by the NPE to configure the HDLC co-processor.
- struct **IxHssAccPortConfig**
Structure containing HSS port configuration parameters.

Defines

- #define **IX_HSSACC_TSLOTS_PER_HSS_PORT**
The max number of TDM timeslots supported per HSS port – 4E1's = 32x4 = 128.
- #define **IX_HSSACC_CHAN_TSLOTSWITCH_NUM_GCT_ENTRY_MAX**
The max number of entries supported per gain control table for a timeslot switching voice channel.
- #define **IX_HSSACC_CHAN_TSLOTSWITCH_NUM_CHAN_MIN**
The minimum number of TDM timeslots that must be setup as channelised timeslots before timeslot switching service can be enabled. This is to maximize NPE resource utilization in order to guarantee high voice quality and minimum latency. Client can choose to ignore the unwanted channelised timeslots.
- #define **IX_HSSACC_CHAN_TSLOTSWITCH_NUM_BYPASS_MAX**
The max number of timeslot switching (bypass) channels supported per HSS port at any one time. In current release, only HSS port 0 supports this feature.
- #define **IX_HSSACC_CHAN_TSLOTSWITCH_NUM_HSS_PORT_MAX**
The max number of HSS ports that support timeslot switching (bypass) feature. In current release, only HSS port 0 supports this feature.
- #define **IX_HSSACC_PARAM_ERR**
HssAccess function return value for a parameter error.

```

#define IX_HSSACC_RESOURCE_ERR
    HssAccess function return value for a resource error.

#define IX_HSSACC_PKT_DISCONNECTING
    Indicates that a disconnect call is progressing and will disconnect soon.

#define IX_HSSACC_Q_WRITE_OVERFLOW
    Indicates that an attempt to Tx or to replenish an RxFree Q failed due to Q overflow.

#define IX_HSSACC_NO_ERROR
    HSS port no error present.

#define IX_HSSACC_TX_FRM_SYNC_ERR
    HSS port TX Frame Sync error.

#define IX_HSSACC_TX_OVER_RUN_ERR
    HSS port TX over-run error.

#define IX_HSSACC_CHANNELISED_SW_TX_ERR
    NPE software error in channelised TX.

#define IX_HSSACC_PACKETISED_SW_TX_ERR
    NPE software error in packetised TX.

#define IX_HSSACC_RX_FRM_SYNC_ERR
    HSS port RX Frame Sync error.

#define IX_HSSACC_RX_OVER_RUN_ERR
    HSS port RX over-run error.

#define IX_HSSACC_CHANNELISED_SW_RX_ERR
    NPE software error in channelised RX.

#define IX_HSSACC_PACKETISED_SW_RX_ERR
    NPE software error in packetised TX.

#define IX_HSSACC_PKT_MIN_RX_MBUF_SIZE
    Minimum size of the Rx mbuf in bytes which the client must supply to the component.

```

Typedefs

```

typedef
UINT32 IxHssAccPktUserId
    The client supplied value which will be supplied as a parameter with a given callback.

typedef
void(* IxHssAccLastErrorCallback )(unsigned lastHssError, unsigned servicePort)
    Prototype of the clients function to accept notification of the last error.

```

```
typedef IxHssAccPktRxCallback )(IX_OSAL_MBUF *buffer, unsigned numHssErrs,
void(* IxHssAccPktStatus pktStatus, IxHssAccPktUserId rxUserId)
```

Prototype of the clients function to accept notification of packetised rx.

```
typedef
```

```
void(* IxHssAccPktRxFreeLowCallback )(IxHssAccPktUserId rxFreeLowUserId)
```

Prototype of the clients function to accept notification of requirement of more Rx Free buffers.

```
typedef IxHssAccPktTxDoneCallback )(IX_OSAL_MBUF *buffer, unsigned numHssErrs,
```

```
void(* IxHssAccPktStatus pktStatus, IxHssAccPktUserId txDoneUserId)
```

Prototype of the clients function to accept notification of completion with Tx buffers.

```
typedef IxHssAccChanRxCallback )(IxHssAccHssPort hssPortId, unsigned rxOffset, unsigned
```

```
void(* txOffset, unsigned numHssErrs)
```

Prototype of the clients function to accept notification of channelised rx.

Enumerations

```
enum IxHssAccHssPort {
    IX_HSSACC_HSS_PORT_0,
    IX_HSSACC_HSS_PORT_1,
    IX_HSSACC_HSS_PORT_MAX
}
```

The HSS port ID – There are two identical ports (0–1).

```
enum IxHssAccHdlcPort {
    IX_HSSACC_HDLC_PORT_0,
    IX_HSSACC_HDLC_PORT_1,
    IX_HSSACC_HDLC_PORT_2,
    IX_HSSACC_HDLC_PORT_3,
    IX_HSSACC_HDLC_PORT_MAX
}
```

The HDLC port ID – There are four identical HDLC ports (0–3) per HSS port and they correspond to the 4 E1/T1 trunks.

```
enum IxHssAccTdmSlotUsage {
    IX_HSSACC_TDM_MAP_UNASSIGNED,
    IX_HSSACC_TDM_MAP_HDLC,
    IX_HSSACC_TDM_MAP_VOICE56K,
    IX_HSSACC_TDM_MAP_VOICE64K,
    IX_HSSACC_TDM_MAP_MAX
}
```

The HSS TDM stream timeslot assignment types.

```
enum IxHssAccFrmSyncType {
    IX_HSSACC_FRM_SYNC_ACTIVE_LOW,
    IX_HSSACC_FRM_SYNC_ACTIVE_HIGH,
    IX_HSSACC_FRM_SYNC_FALLINGEDGE,
    IX_HSSACC_FRM_SYNC_RISINGEDGE,
```

```

    IX_HSSACC_FRM_SYNC_TYPE_MAX
}

```

The HSS frame sync pulse type.

```

enum IxHssAccFrmSyncEnable {
    IX_HSSACC_FRM_SYNC_INPUT,
    IX_HSSACC_FRM_SYNC_INVALID_VALUE,
    IX_HSSACC_FRM_SYNC_OUTPUT_FALLING,
    IX_HSSACC_FRM_SYNC_OUTPUT_RISING,
    IX_HSSACC_FRM_SYNC_ENABLE_MAX
}

```

The IxHssAccFrmSyncEnable determines how the frame sync pulse is used.

```

enum IxHssAccClkEdge {
    IX_HSSACC_CLK_EDGE_FALLING,
    IX_HSSACC_CLK_EDGE_RISING,
    IX_HSSACC_CLK_EDGE_MAX
}

```

IxHssAccClkEdge is used to determine the clk edge to use for framing and data.

```

enum IxHssAccClkDir {
    IX_HSSACC_SYNC_CLK_DIR_INPUT,
    IX_HSSACC_SYNC_CLK_DIR_OUTPUT,
    IX_HSSACC_SYNC_CLK_DIR_MAX
}

```

The HSS clock direction.

```

enum IxHssAccFrmPulseUsage {
    IX_HSSACC_FRM_PULSE_ENABLED,
    IX_HSSACC_FRM_PULSE_DISABLED,
    IX_HSSACC_FRM_PULSE_MAX
}

```

The HSS frame pulse usage.

```

enum IxHssAccDataRate {
    IX_HSSACC_CLK_RATE,
    IX_HSSACC_HALF_CLK_RATE,
    IX_HSSACC_DATA_RATE_MAX
}

```

The HSS Data rate in relation to the clock.

```

enum IxHssAccDataPolarity {
    IX_HSSACC_DATA_POLARITY_SAME,
    IX_HSSACC_DATA_POLARITY_INVERT,
    IX_HSSACC_DATA_POLARITY_MAX
}

```

The HSS data polarity type.

```

enum IxHssAccBitEndian {
    IX_HSSACC_LSB_ENDIAN,
    IX_HSSACC_MSB_ENDIAN,
}

```

```

    IX_HSSACC_ENDIAN_MAX
}
HSS Data endianness.

enum IxHssAccDrainMode {
    IX_HSSACC_TX_PINS_NORMAL,
    IX_HSSACC_TX_PINS_OPEN_DRAIN,
    IX_HSSACC_TX_PINS_MAX
}
Tx pin open drain mode.

enum IxHssAccSOFTType {
    IX_HSSACC_SOF_FBIT,
    IX_HSSACC_SOF_DATA,
    IX_HSSACC_SOF_MAX
}
HSS start of frame types.

enum IxHssAccDataEnable {
    IX_HSSACC_DE_TRI_STATE,
    IX_HSSACC_DE_DATA,
    IX_HSSACC_DE_MAX
}
IxHssAccDataEnable is used to determine whether or not to drive the data pins.

enum IxHssAccTxSigType {
    IX_HSSACC_TXSIG_LOW,
    IX_HSSACC_TXSIG_HIGH,
    IX_HSSACC_TXSIG_HIGH_IMP,
    IX_HSSACC_TXSIG_MAX
}
IxHssAccTxSigType is used to determine how to drive the data pins.

enum IxHssAccFbType {
    IX_HSSACC_FB_FIFO,
    IX_HSSACC_FB_HIGH_IMP,
    IX_HSSACC_FB_MAX
}
IxHssAccFbType determines how to drive the Fbit.

enum IxHssAcc56kEndianness {
    IX_HSSACC_56KE_BIT_7_UNUSED,
    IX_HSSACC_56KE_BIT_0_UNUSED,
    IX_HSSACC_56KE_MAX
}
56k data endianness when using the 56k type

enum IxHssAcc56kSel {
    IX_HSSACC_56KS_32_8_DATA,
    IX_HSSACC_56KS_56K_DATA,
    IX_HSSACC_56KS_MAX
}

```

```

}
56k data transmission type when using the 56k type

```

```

enum IxHssAccClkSpeed {
    IX_HSSACC_CLK_SPEED_512KHZ,
    IX_HSSACC_CLK_SPEED_1536KHZ,
    IX_HSSACC_CLK_SPEED_1544KHZ,
    IX_HSSACC_CLK_SPEED_2048KHZ,
    IX_HSSACC_CLK_SPEED_4096KHZ,
    IX_HSSACC_CLK_SPEED_8192KHZ,
    IX_HSSACC_CLK_SPEED_MAX
}
IxHssAccClkSpeed represents the HSS clock speeds available.

```

```

enum IxHssAccPktStatus {
    IX_HSSACC_PKT_OK,
    IX_HSSACC_STOP_SHUTDOWN_ERROR,
    IX_HSSACC_HDLC_ALN_ERROR,
    IX_HSSACC_HDLC_FCS_ERROR,
    IX_HSSACC_RXFREE_Q_EMPTY_ERROR,
    IX_HSSACC_HDLC_MAX_FRAME_SIZE_EXCEEDED,
    IX_HSSACC_HDLC_ABORT_ERROR,
    IX_HSSACC_DISCONNECT_IN_PROGRESS
}
Indicates the status of packets passed to the client.

```

```

enum IxHssAccPktCrcType {
    IX_HSSACC_PKT_16_BIT_CRC,
    IX_HSSACC_PKT_32_BIT_CRC
}
HDLC CRC type.

```

```

enum IxHssAccPktHdlcIdleType {
    IX_HSSACC_HDLC_IDLE_ONES,
    IX_HSSACC_HDLC_IDLE_FLAGS
}
HDLC idle transmission type.

```

Functions

PUBLIC
IX_STATUS IxHssAccPortInit (**IxHssAccHssPort** hssPortId, **IxHssAccConfigParams** *configParams, **IX_STATUS IxHssAccTdmSlotUsage** *tdmMap, **IxHssAccLastErrorCallback** lastHssErrorCallback)
Initialise a HSS port. No channelised or packetised connections should exist in the HssAccess layer while this interface is being called.

PUBLIC
IX_STATUS ixHssAccLastErrorRetrievalInitiate (**IxHssAccHssPort** hssPortId)
Initiate the retrieval of the last HSS error. The HSS port should be configured before attempting to call this interface.

PUBLIC
IX_STATUS ixHssAccInit (void)
This function is responsible for initialising resources for use by the packetised and channelised clients. It should be called after HSS NPE image has been downloaded into NPE–A and before any other HssAccess interface is called. No other HssAccPacketised interface should be called while this interface is being processed.

PUBLIC
IX_STATUS ixHssAccUninit (void)
This function is responsible for un-initialize of resources for use by the packetised and channelised clients. It internally calls the uninitialize functions of sub components. This function should be the last function to be called before exiting HssAcc component.

PUBLIC ixHssAccPktPortConnect (**IxHssAccHssPort** hssPortId, **IxHssAccHdlcPort** hdlcPortId, **IX_STATUS** BOOL hdlcFraming, **IxHssAccHdlcMode** hdlcMode, **BOOL** hdlcBitInvert, unsigned blockSizeInWords, **UINT32** rawIdleBlockPattern, **IxHssAccPktHdlcFraming** hdlcTxFraming, **IxHssAccPktHdlcFraming** hdlcRxFraming, unsigned frmFlagStart, **IxHssAccPktRxCallback** rxCallback, **IxHssAccPktUserId** rxUserId, **IxHssAccPktRxFreeLowCallback** rxFreeLowCallback, **IxHssAccPktUserId** rxFreeLowUserId, **IxHssAccPktTxDoneCallback** txDoneCallback, **IxHssAccPktUserId** txDoneUserId)
This function is responsible for connecting a client to one of the 4 available HDLC ports. The HSS port should be configured before attempting a connect. No other HssAccPacketised interface should be called while this connect is being processed.

PUBLIC
IX_STATUS ixHssAccPktPortEnable (**IxHssAccHssPort** hssPortId, **IxHssAccHdlcPort** hdlcPortId)
This function is responsible for enabling a packetised service for the specified HSS/HDLC port combination. It enables the RX flow. The client must have already connected to a packetised service and is responsible for ensuring an adequate amount of RX mbufs have been supplied to the access component before enabling the packetised service. This function must be called on a given port before any call to ixHssAccPktPortTx on the same port. No other HssAccPacketised interface should be called while this interface is being processed.

PUBLIC
IX_STATUS ixHssAccPktPortDisable (**IxHssAccHssPort** hssPortId, **IxHssAccHdlcPort** hdlcPortId)
This function is responsible for disabling a packetised service for the specified HSS/HDLC port combination. It disables the RX flow. The client must have already connected to and enabled a packetised service for the specified HDLC port. This disable interface can be called before a disconnect, but is not required to.

PUBLIC
IX_STATUS ixHssAccPktPortDisconnect (**IxHssAccHssPort** hssPortId, **IxHssAccHdlcPort** hdlcPortId)
This function is responsible for disconnecting a client from one of the 4 available HDLC ports. It is not required that the Rx Flow has been disabled before calling this function. If the RX Flow has not been disabled, the disconnect will disable it before proceeding with the disconnect. No other HssAccPacketised interface should be called while this interface is being processed.

PUBLIC**ixHssAccPktPortIsDisconnectComplete** (**IxHssAccHssPort** hssPortId, **IxHssAccHdlcPort** hdlcPortId)
BOOL hdlcPortId)

This function is called to check if a given HSS/HDLC port combination is in a connected state or not. This function may be called at any time to determine a ports state. No other HssAccPacketised interface should be called while this interface is being processed.

PUBLIC**ixHssAccPktPortRxFreeReplenish** (**IxHssAccHssPort** hssPortId, **IxHssAccHdlcPort** hdlcPortId, **IX_STATUS** hdlcPortId, **IX_OSAL_MBUF** *buffer)

Function which the client calls at regular intervals to provide mbufs to the access component for RX. A connection should exist for the specified hssPortId/hdlcPortId combination before attempting to call this interface. Also, the connection should not be in a disconnecting state.

PUBLIC**ixHssAccPktPortTx** (**IxHssAccHssPort** hssPortId, **IxHssAccHdlcPort** hdlcPortId, **IX_STATUS** **IX_OSAL_MBUF** *buffer)

Function which the client calls when it wants to transmit packetised data. An enabled connection should exist on the specified hssPortId/hdlcPortId combination before attempting to call this interface. No other HssAccPacketised interface should be called while this interface is being processed.

PUBLIC**ixHssAccChanConnect** (**IxHssAccHssPort** hssPortId, unsigned bytesPerTSTrigger, **UINT8** **IX_STATUS** *rxCircular, unsigned numRxBytesPerTS, **UINT32** *txPtrList, unsigned numTxPtrLists, unsigned numTxBytesPerBlk, **IxHssAccChanRxCallback** rxCallback)

This function allows the client to connect to the Tx/Rx NPE Channelised Service. There can only be one client per HSS port. The client is responsible for ensuring that the HSS port is configured appropriately before its connect request. No other HssAccChannelised interface should be called while this interface is being processed.

PUBLIC
IX_STATUS **ixHssAccChanPortEnable** (**IxHssAccHssPort** hssPortId)

This function is responsible for enabling a channelised service for the specified HSS port. It enables the NPE RX flow. The client must have already connected to a channelised service before enabling the channelised service. No other HssAccChannelised interface should be called while this interface is being processed.

PUBLIC
IX_STATUS **ixHssAccChanPortDisable** (**IxHssAccHssPort** hssPortId)

This function is responsible for disabling a channelised service for the specified HSS port. It disables the NPE RX flow. The client must have already connected to and enabled a channelised service for the specified HSS port. This disable interface can be called before a disconnect, but is not required to. No other HssAccChannelised interface should be called while this interface is being processed.

PUBLIC
IX_STATUS **ixHssAccChanDisconnect** (**IxHssAccHssPort** hssPortId)

This function allows the client to Disconnect from a channelised service. If the NPE RX Flow has not been disabled, the disconnect will disable it before proceeding with other disconnect functionality. No other HssAccChannelised interface should be called while this interface is being processed.

PUBLIC**ixHssAccChanStatusQuery** (**IxHssAccHssPort** hssPortId, **BOOL** *dataRecvd, unsigned **IX_STATUS** *rxOffset, unsigned *txOffset, unsigned *numHssErrs)

This function is called by the client to query whether or not channelised data has been received. If there is, hssChanAcc will return the details in the output parameters. An enabled connection should exist on the specified hssPortId before attempting to call this interface. No other HssAccChannelised interface should be called while this interface is being processed.

PUBLIC IxHssAccChanTslotSwitchEnable (IxHssAccHssPort hssPortId, UINT32 srcTimeslot, IX_STATUS UINT32 destTimeslot, UINT32 *tsSwitchHandle)

This function is responsible for enabling timeslot switching (bypass) channel between two voice channels for the specified HSS port. The voice channels must have already been configured as channelised timeslot for the specified HSS port. In current release, only up to two timeslot switching channels can be enabled at any one time. In order to minimize bypass delay and ensure better voice quality, this function requires at least 8 TDM timeslots on the specified HSS port to be setup as channelised timeslots. In timeslot switching mode, data received on srcTimeslot is transmitted onto a partner timeslot (i.e. destTimeslot) at NPE level. A copy of the received data on srcTimeslot is also sent to client via HssAccess component. No other HssAccChannelised interface should be called while this interface is being processed.

PUBLIC IX_STATUS IxHssAccChanTslotSwitchDisable (IxHssAccHssPort hssPortId, UINT32 tsSwitchHandle)

This function is responsible for disabling timeslot switching (bypass) channel, that is associated with tsSwitchHandle, for the specified HSS port. The bypass channel to be disabled must have already been enabled for the specified HSS port. No other HssAccChannelised interface should be called while this interface is being processed.

PUBLIC IxHssAccChanTslotSwitchGctDownload (IxHssAccHssPort hssPortId, UINT8 IX_STATUS *gainCtrlTable, UINT32 tsSwitchHandle)

This function is responsible for downloading a gain control table (256 bytes) to NPE for the specified timeslot switching (bypass) channel, associated with tsSwitchHandle, on the specified HSS port. The bypass voice channel must have already been enabled for the specified HSS port before this API can be called to download the gain control table to NPE. No other HssAccChannelised interface should be called while this interface is being processed.

PUBLIC void IxHssAccShow (void)

This function will display the current state of the IxHssAcc component. The output is sent to stdout.

PUBLIC void IxHssAccStatsInit (void)

This function will reset the IxHssAcc statistics.

Detailed Description

The public API for the IXP400 HssAccess component.

IxHssAcc is the access layer to the HSS packetised and channelised services

Design Notes

- When a packet-pipe is configured for 56Kbps RAW mode, byte alignment of the transmitted data is not preserved. All raw data that is transmitted will be received in proper order by the receiver, but the first bit of the packet may be seen at any offset within a byte; all subsequent bytes will have the same offset for the duration of the packet. The same offset also applies to all subsequent packets received on the packet-pipe too. (Similar results will occur for data received from remote end.) While this behavior will also occur for 56Kbps HDLC mode, the HDLC encoding/decoding will preserve the original byte alignment at the receiver end.

56Kbps Packetised Service Bandwidth Limitation

- IxHssAcc supports 56Kbps packetised service at a maximum aggregate rate for all HSS ports/HDLC channels of 12.288Mbps[1] in each direction, i.e. it supports 56Kbps packetised service on up to 8 T1 trunks. It does not support 56Kbps packetised service on 8 E1 trunks (i.e. 4 trunks per HSS port) unless those trunks are running 'fractional E1' with maximum aggregate rate of 12.288 Mbps in each direction.

[1] $12.288\text{Mbps} = 1.536\text{Mbp} * 8 \text{ T1}$

Define Documentation

```
#define IX_HSSACC_CHAN_TSLOTSWITCH_NUM_BYPASS_MAX
```

The max number of timeslot switching (bypass) channels supported per HSS port at any one time. In current release, only HSS port 0 supports this feature.

Definition at line **94** of file **IxHssAcc.h**.

```
#define IX_HSSACC_CHAN_TSLOTSWITCH_NUM_CHAN_MIN
```

The minimum number of TDM timeslots that must be setup as channelised timeslots before timeslot switching service can be enabled. This is to maximize NPE resource utilization in order to guarantee high voice quality and minimum latency. Client can choose to ignore the unwanted channelised timeslots.

Definition at line **85** of file **IxHssAcc.h**.

```
#define IX_HSSACC_CHAN_TSLOTSWITCH_NUM_GCT_ENTRY_MAX
```

The max number of entries supported per gain control table for a timeslot switching voice channel.

Definition at line **74** of file **IxHssAcc.h**.

```
#define IX_HSSACC_CHAN_TSLOTSWITCH_NUM_HSS_PORT_MAX
```

The max number of HSS ports that support timeslot switching (bypass) feature. In current release, only HSS port 0 supports this feature.

Definition at line **102** of file **IxHssAcc.h**.

```
#define IX_HSSACC_CHANNELISED_SW_RX_ERR
```

NPE software error in channelised RX.

Definition at line **196** of file **IxHssAcc.h**.

```
#define IX_HSSACC_CHANNELISED_SW_TX_ERR
```

NPE software error in channelised TX.

Definition at line **168** of file **IxHssAcc.h**.

```
#define IX_HSSACC_NO_ERROR
```

HSS port no error present.

Definition at line **147** of file **IxHssAcc.h**.

```
#define IX_HSSACC_PACKETISED_SW_RX_ERR
```

NPE software error in packetised TX.

Definition at line **203** of file **IxHssAcc.h**.

```
#define IX_HSSACC_PACKETISED_SW_TX_ERR
```

NPE software error in packetised TX.

Definition at line **175** of file **IxHssAcc.h**.

```
#define IX_HSSACC_PARAM_ERR
```

HssAccess function return value for a parameter error.

Definition at line **114** of file **IxHssAcc.h**.

```
#define IX_HSSACC_PKT_DISCONNECTING
```

Indicates that a disconnect call is progressing and will disconnect soon.

Definition at line **129** of file **IxHssAcc.h**.

```
#define IX_HSSACC_PKT_MIN_RX_MBUF_SIZE
```

Minimum size of the Rx mbuf in bytes which the client must supply to the component.

Definition at line **215** of file **IxHssAcc.h**.

```
#define IX_HSSACC_Q_WRITE_OVERFLOW
```

Indicates that an attempt to Tx or to replenish an RxFree Q failed due to Q overflow.

Definition at line **137** of file **IxHssAcc.h**.

```
#define IX_HSSACC_RESOURCE_ERR
```

HssAccess function return value for a resource error.

Definition at line **121** of file **IxHssAcc.h**.

```
#define IX_HSSACC_RX_FRM_SYNC_ERR
```

HSS port RX Frame Sync error.

Definition at line **182** of file **IxHssAcc.h**.

```
#define IX_HSSACC_RX_OVER_RUN_ERR
```

HSS port RX over-run error.

Definition at line **189** of file **IxHssAcc.h**.

```
#define IX_HSSACC_TSLOTS_PER_HSS_PORT
```

The max number of TDM timeslots supported per HSS port – $4E1's = 32 \times 4 = 128$.

Definition at line **66** of file **IxHssAcc.h**.

```
#define IX_HSSACC_TX_FRM_SYNC_ERR
```

HSS port TX Frame Sync error.

Definition at line **154** of file **IxHssAcc.h**.

```
#define IX_HSSACC_TX_OVER_RUN_ERR
```

HSS port TX over-run error.

Definition at line **161** of file **IxHssAcc.h**.

Typedef Documentation

IxHssAccChanRxCallback

Prototype of the clients function to accept notification of channelised rx.

This callback, if defined by the client in the connect, will get called in the context of an IRQ. The IRQ will be triggered when the hssSyncQMQ is not empty. The queued entry will be dequeued and this function will be executed.

Parameters:

<i>hssPortId</i>	IxHssAccHssPort – The HSS port Id. There are two identical ports (0–1).
<i>txOffset</i>	unsigned [in] – an offset indicating from where within the txPtrList the NPE is currently transmitting from.
<i>rxOffset</i>	unsigned [in] – an offset indicating where within the receive buffers the NPE has just written the received data to.
<i>numHssErrs</i>	unsigned [in] – This is the number of hssErrors the Npe has received

Returns:

void

Definition at line **732** of file **IxHssAcc.h**.

IxHssAccLastErrorCallback

Prototype of the clients function to accept notification of the last error.

This function is registered through the config. The client will initiate the last error retrieval. The HssAccess component will send a message to the NPE through the NPE Message Handler. When a response to the read is received, the NPE Message Handler will callback the HssAccess component which will execute this function in the same IxNpeMh context. The client will be passed the last error and the related service port (packetised 0–3, channelised 0)

Parameters:

<i>lastHssError</i>	unsigned [in] – The last Hss error registered that has been registered.
<i>servicePort</i>	unsigned [in] – This is the service port number. (packetised 0–3, channelised 0)

Returns:

void

Definition at line **641** of file **IxHssAcc.h**.

IxHssAccPktRxCallback

Prototype of the clients function to accept notification of packetised rx.

This function is registered through the ixHssAccPktPortConnect. hssPktAcc will pass received data in the form of mbufs to the client. The mbuf passed back to the client could contain a chain of buffers, depending on the packet size received.

Parameters:

**buffer* [in] – This is the mbuf which contains the payload received.
numHssErrs unsigned [in] – This is the number of hssErrors the Npe has received
pktStatus **IxHssAccPktStatus** [in] – This is the status of the mbuf that has been received.
rxUserId **IxHssAccPktUserId** [in] – This is the client supplied value passed in at ixHssAccPktPortConnect time which is now returned to the client.

Returns:

void

Definition at line **665** of file **IxHssAcc.h**.

IxHssAccPktRxFreeLowCallback

Prototype of the clients function to accept notification of requirement of more Rx Free buffers.

The client can choose to register a callback of this type when calling a connecting. This function is registered through the ixHssAccPktPortConnect. If defined, the access layer will provide the trigger for this callback. The callback will be responsible for supplying mbufs to the access layer for use on the receive path from the HSS using ixHssPktAccFreeBufReplenish.

Returns:

void

Definition at line **684** of file **IxHssAcc.h**.

IxHssAccPktTxDoneCallback

Prototype of the clients function to accept notification of completion with Tx buffers.

This function is registered through the ixHssAccPktPortConnect. It enables the hssPktAcc to pass buffers back to the client when transmission is complete.

Parameters:

**buffer* [in] – This is the mbuf which contained the payload that was for Tx.
numHssErrs unsigned [in] – This is the number of hssErrors the Npe has received
pktStatus **IxHssAccPktStatus** [in] – This is the status of the mbuf that has been transmitted.
txDoneUserId **IxHssAccPktUserId** [in] – This is the client supplied value passed in at
 ixHssAccPktPortConnect time which is now returned to the client.

Returns:

void

Definition at line **706** of file **IxHssAcc.h**.

UINT32 IxHssAccPktUserId

The client supplied value which will be supplied as a parameter with a given callback.

This value will be passed into the ixHssAccPktPortConnect function once each with given callbacks. This value will then be passed back to the client as one of the parameters to each of these callbacks, when these callbacks are called.

Definition at line **618** of file **IxHssAcc.h**.

Enumeration Type Documentation

enum IxHssAcc56kEndianness

56k data endianness when using the 56k type

Enumeration values:

IX_HSSACC_56KE_BIT_7_UNUSED High bit is
 unused.
IX_HSSACC_56KE_BIT_0_UNUSED Low bit is
 unused.
IX_HSSACC_56KE_MAX Delimiter for
 error checks.

Definition at line **437** of file **IxHssAcc.h**.

enum IxHssAcc56kSel

56k data transmission type when using the 56k type

Enumeration values:

IX_HSSACC_56KS_32_8_DATA 32/8 bit data
IX_HSSACC_56KS_56K_DATA 56K data
IX_HSSACC_56KS_MAX Delimiter for

error checks.

Definition at line **449** of file **IxHssAcc.h**.

```
enum IxHssAccBitEndian
```

HSS Data endianness.

Enumeration values:

IX_HSSACC_LSB_ENDIAN TX/RX Least Significant Bit first.
IX_HSSACC_MSB_ENDIAN TX/RX Most Significant Bit first.
IX_HSSACC_ENDIAN_MAX Delimiter for the purposes of error checks.

Definition at line **360** of file **IxHssAcc.h**.

```
enum IxHssAccClkDir
```

The HSS clock direction.

Enumeration values:

IX_HSSACC_SYNC_CLK_DIR_INPUT Clock is an input.
IX_HSSACC_SYNC_CLK_DIR_OUTPUT Clock is an output.
IX_HSSACC_SYNC_CLK_DIR_MAX Delimiter for error checks.

Definition at line **310** of file **IxHssAcc.h**.

```
enum IxHssAccClkEdge
```

IxHssAccClkEdge is used to determine the clk edge to use for framing and data.

Enumeration values:

IX_HSSACC_CLK_EDGE_FALLING Clock sampled off a falling edge.
IX_HSSACC_CLK_EDGE_RISING Clock sampled off a rising edge.
IX_HSSACC_CLK_EDGE_MAX Delimiter for error checks.

Definition at line **298** of file **IxHssAcc.h**.

```
enum IxHssAccClkSpeed
```

IxHssAccClkSpeed represents the HSS clock speeds available.

Enumeration values:

<i>IX_HSSACC_CLK_SPEED_512KHZ</i>	512KHz
<i>IX_HSSACC_CLK_SPEED_1536KHZ</i>	1.536MHz
<i>IX_HSSACC_CLK_SPEED_1544KHZ</i>	1.544MHz
<i>IX_HSSACC_CLK_SPEED_2048KHZ</i>	2.048MHz
<i>IX_HSSACC_CLK_SPEED_4096KHZ</i>	4.096MHz
<i>IX_HSSACC_CLK_SPEED_8192KHZ</i>	8.192MHz
<i>IX_HSSACC_CLK_SPEED_MAX</i>	Delimiter for error checking.

Definition at line **462** of file **IxHssAcc.h**.

```
enum IxHssAccDataEnable
```

IxHssAccDataEnable is used to determine whether or not to drive the data pins.

Enumeration values:

<i>IX_HSSACC_DE_TRI_STATE</i>	TRI-State the data pins.
<i>IX_HSSACC_DE_DATA</i>	Push data out the data pins.
<i>IX_HSSACC_DE_MAX</i>	Delimiter for error checks.

Definition at line **398** of file **IxHssAcc.h**.

```
enum IxHssAccDataPolarity
```

The HSS data polarity type.

Enumeration values:

<i>IX_HSSACC_DATA_POLARITY_SAME</i>	Don't invert data between NPE and HSS FIFOs.
<i>IX_HSSACC_DATA_POLARITY_INVERT</i>	Invert data between NPE and HSS FIFOs.
<i>IX_HSSACC_DATA_POLARITY_MAX</i>	Delimiter for error checks.

Definition at line **346** of file **IxHssAcc.h**.

```
enum IxHssAccDataRate
```

The HSS Data rate in relation to the clock.

Enumeration values:

<i>IX_HSSACC_CLK_RATE</i>	Data rate is at the configured clk speed.
<i>IX_HSSACC_HALF_CLK_RATE</i>	

Data rate is half the configured clk speed.

IX_HSSACC_DATA_RATE_MAX Delimiter for error checks.

Definition at line **334** of file **IxHssAcc.h**.

enum IxHssAccDrainMode

Tx pin open drain mode.

Enumeration values:

<i>IX_HSSACC_TX_PINS_NORMAL</i>	Normal mode.
<i>IX_HSSACC_TX_PINS_OPEN_DRAIN</i>	Open Drain mode.
<i>IX_HSSACC_TX_PINS_MAX</i>	Delimiter for error checks.

Definition at line **373** of file **IxHssAcc.h**.

enum IxHssAccFbType

IxHssAccFbType determines how to drive the Fbit.

Warning:

This will only be used for T1 @ 1.544MHz

Enumeration values:

<i>IX_HSSACC_FB_FIFO</i>	Fbit is dictated in FIFO.
<i>IX_HSSACC_FB_HIGH_IMP</i>	Fbit is high impedance.
<i>IX_HSSACC_FB_MAX</i>	Delimiter for error checks.

Definition at line **425** of file **IxHssAcc.h**.

enum IxHssAccFrmPulseUsage

The HSS frame pulse usage.

Enumeration values:

<i>IX_HSSACC_FRM_PULSE_ENABLED</i>	Generate/Receive frame pulses.
<i>IX_HSSACC_FRM_PULSE_DISABLED</i>	Disregard frame pulses.

<i>IX_HSSACC_FRM_PULSE_MAX</i>	Delimiter for error checks.
--------------------------------	-----------------------------

Definition at line **322** of file **IxHssAcc.h**.

```
enum IxHssAccFrmSyncEnable
```

The IxHssAccFrmSyncEnable determines how the frame sync pulse is used.

Enumeration values:

<i>IX_HSSACC_FRM_SYNC_INPUT</i>	Frame sync is sampled as an input.
<i>IX_HSSACC_FRM_SYNC_INVALID_VALUE</i>	1 is not used
<i>IX_HSSACC_FRM_SYNC_OUTPUT_FALLING</i>	Frame sync is an output generated off a falling clock edge.
<i>IX_HSSACC_FRM_SYNC_OUTPUT_RISING</i>	Frame sync is an output generated off a rising clock edge.
<i>IX_HSSACC_FRM_SYNC_ENABLE_MAX</i>	Delimiter for error checks.

Definition at line **281** of file **IxHssAcc.h**.

```
enum IxHssAccFrmSyncType
```

The HSS frame sync pulse type.

Enumeration values:

<i>IX_HSSACC_FRM_SYNC_ACTIVE_LOW</i>	Frame sync is sampled low.
<i>IX_HSSACC_FRM_SYNC_ACTIVE_HIGH</i>	sampled high
<i>IX_HSSACC_FRM_SYNC_FALLINGEDGE</i>	sampled on a falling edge
<i>IX_HSSACC_FRM_SYNC_RISINGEDGE</i>	sampled on a rising edge
<i>IX_HSSACC_FRM_SYNC_TYPE_MAX</i>	Delimiter for error checks.

Definition at line **267** of file **IxHssAcc.h**.

```
enum IxHssAccHdlcPort
```

The HDLC port ID – There are four identical HDLC ports (0–3) per HSS port and they correspond to the 4 E1/T1 trunks.

Enumeration values:

<i>IX_HSSACC_HDLC_PORT_0</i>	HDLC Port 0.
<i>IX_HSSACC_HDLC_PORT_1</i>	HDLC Port 1.
<i>IX_HSSACC_HDLC_PORT_2</i>	HDLC Port 2.

IX_HSSACC_HDLC_PORT_3 HDLC Port 3.
IX_HSSACC_HDLC_PORT_MAX Delimiter for error checks.

Definition at line **239** of file **IxHssAcc.h**.

enum IxHssAccHssPort

The HSS port ID – There are two identical ports (0–1).

Enumeration values:

IX_HSSACC_HSS_PORT_0 HSS Port 0.
IX_HSSACC_HSS_PORT_1 HSS Port 1.
IX_HSSACC_HSS_PORT_MAX Delimiter for error checks.

Definition at line **226** of file **IxHssAcc.h**.

enum IxHssAccPktCrcType

HDLC CRC type.

Enumeration values:

IX_HSSACC_PKT_16_BIT_CRC 16 bit CRC is being used
IX_HSSACC_PKT_32_BIT_CRC 32 bit CRC is being used

Definition at line **502** of file **IxHssAcc.h**.

enum IxHssAccPktHdlcIdleType

HDLC idle transmission type.

Enumeration values:

IX_HSSACC_HDLC_IDLE_ONES idle tx/rx will be a succession of ones
IX_HSSACC_HDLC_IDLE_FLAGS idle tx/rx will be repeated flags

Definition at line **513** of file **IxHssAcc.h**.

enum IxHssAccPktStatus

Indicates the status of packets passed to the client.

Enumeration values:

<i>IX_HSSACC_PKT_OK</i>	Error free.
<i>IX_HSSACC_STOP_SHUTDOWN_ERROR</i>	Errored due to stop or shutdown occurrence.
<i>IX_HSSACC_HDLC_ALN_ERROR</i>	HDLC alignment error.
<i>IX_HSSACC_HDLC_FCS_ERROR</i>	HDLC Frame Check Sum error.
<i>IX_HSSACC_RXFREE_Q_EMPTY_ERROR</i>	RxFree Q became empty while receiving this packet.
<i>IX_HSSACC_HDLC_MAX_FRAME_SIZE_EXCEEDED</i>	HDLC frame size received is greater than max specified at connect.
<i>IX_HSSACC_HDLC_ABORT_ERROR</i>	HDLC frame received is invalid due to an abort sequence received.
<i>IX_HSSACC_DISCONNECT_IN_PROGRESS</i>	Packet returned because a disconnect is in progress.

Definition at line **478** of file **IxHssAcc.h**.

```
enum IxHssAccSOFType
```

HSS start of frame types.

Enumeration values:

<i>IX_HSSACC_SOF_FBIT</i>	Framing bit transmitted and expected on rx.
<i>IX_HSSACC_SOF_DATA</i>	Framing bit not transmitted nor expected on rx.
<i>IX_HSSACC_SOF_MAX</i>	Delimiter for error checks.

Definition at line **385** of file **IxHssAcc.h**.

```
enum IxHssAccTdmSlotUsage
```

The HSS TDM stream timeslot assignment types.

Enumeration values:

<i>IX_HSSACC_TDMMAP_UNASSIGNED</i>	Unassigned.
<i>IX_HSSACC_TDMMAP_HDLC</i>	HDLC – packetised.
<i>IX_HSSACC_TDMMAP_VOICE56K</i>	Voice56K – channelised.
<i>IX_HSSACC_TDMMAP_VOICE64K</i>	Voice64K – channelised.
<i>IX_HSSACC_TDMMAP_MAX</i>	Delimiter for error checks.

Definition at line **253** of file **IxHssAcc.h**.

```
enum IxHssAccTxSigType
```

IxHssAccTxSigType is used to determine how to drive the data pins.

Enumeration values:

<i>IX_HSSACC_TXSIG_LOW</i>	Drive the data pins low.
<i>IX_HSSACC_TXSIG_HIGH</i>	Drive the data pins high.
<i>IX_HSSACC_TXSIG_HIGH_IMP</i>	Drive the data pins with high impedance.
<i>IX_HSSACC_TXSIG_MAX</i>	Delimiter for error checks.

Definition at line **410** of file **IxHssAcc.h**.

Function Documentation

```
IX_STATUS ixHssAccChanConnect ( IxHssAccHssPort          hssPortId,
                                unsigned                    bytesPerTSTrigger,
                                UINT8 *                     rxCircular,
                                unsigned                    numRxBytesPerTS,
                                UINT32 *                   txPtrList,
                                unsigned                    numTxPtrLists,
                                unsigned                    numTxBytesPerBlk,
                                IxHssAccChanRxCallback rxCallback
                                )
```

This function allows the client to connect to the Tx/Rx NPE Channelised Service. There can only be one client per HSS port. The client is responsible for ensuring that the HSS port is configured appropriately before its connect request. No other HssAccChannelised interface should be called while this interface is being processed.

Parameters:

<i>hssPortId</i>	IxHssAccHssPort [in] – The HSS port Id. There are two identical ports (0–1).
<i>bytesPerTSTrigger</i>	unsigned [in] – The NPE will trigger the access component after bytesPerTSTrigger have been received for all trunk timeslots. This figure is a multiple of 8 e.g. 8 for 1ms trigger, 16 for 2ms trigger.
<i>*rxCircular</i>	UINT8 [in] – A pointer to memory allocated by the client to be filled by data received. The buffer at this address is part of a pool of buffers to be accessed in a circular fashion. This address will be written to by the NPE. Therefore, it needs to be a physical address.
<i>numRxBytesPerTS</i>	unsigned [in] – The number of bytes allocated per timeslot within the receive memory. This figure will depend on the latency of the system. It needs to be deep enough for data to be read by the client before the NPE re–writes over that memory e.g. if the client samples at a rate of 40bytes per timeslot, numRxBytesPerTS may need to be 40bytes * 3. This would give the client 3 * 5ms of time before received data is over–written.

<i>*txPtrList</i>	UINT32 [in] – The address of an area of contiguous memory allocated by the client to be populated with pointers to data for transmission. Each pointer list contains a pointer per active channel. The txPtrs will point to data to be transmitted by the NPE. Therefore, they must point to physical addresses.
<i>numTxPtrLists</i>	unsigned [in] – The number of pointer lists in txPtrList. This figure is dependent on jitter.
<i>numTxBytesPerBlk</i>	unsigned [in] – The size of the Tx data, in bytes, that each pointer within the PtrList points to.
<i>rxCallback</i>	IxHssAccChanRxCallback [in] – A client function pointer to be called back to handle the actual tx/rx of channelised data. If this is not NULL, an ISR will call this function. If this pointer is NULL, it implies that the client will use a polling mechanism to detect when the tx and rx of channelised data is to occur. The client will use hssChanAccStatus for this.

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

IX_STATUS ixHssAccChanDisconnect (**IxHssAccHssPort** *hssPortId*)

This function allows the client to Disconnect from a channelised service. If the NPE RX Flow has not been disabled, the disconnect will disable it before proceeding with other disconnect functionality. No other HssAccChannelised interface should be called while this interface is being processed.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

IX_STATUS ixHssAccChanPortDisable (**IxHssAccHssPort** *hssPortId*)

This function is responsible for disabling a channelised service for the specified HSS port. It disables the NPE RX flow. The client must have already connected to and enabled a channelised service for the specified HSS port. This disable interface can be called before a disconnect, but is not required to. No other HssAccChannelised interface should be called while this interface is being processed.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

IX_STATUS ixHssAccChanPortEnable (**IxHssAccHssPort** *hssPortId*)

This function is responsible for enabling a channelised service for the specified HSS port. It enables the NPE RX flow. The client must have already connected to a channelised service before enabling the channelised service. No other HssAccChannelised interface should be called while this interface is being processed.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

IX_STATUS ixHssAccChanStatusQuery (**IxHssAccHssPort** *hssPortId*,
 BOOL * *dataRecvd*,
 unsigned * *rxOffset*,
 unsigned * *txOffset*,
 unsigned * *numHssErrs*
)

This function is called by the client to query whether or not channelised data has been received. If there is, hssChanAcc will return the details in the output parameters. An enabled connection should exist on the specified hssPortId before attempting to call this interface. No other HssAccChannelised interface should be called while this interface is being processed.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).
**dataRecvd* BOOL [out] – This BOOL indicates to the client whether or not the access component has read any data for the client. If FALSE, the other output parameters will not have been written to.
**rxOffset* unsigned [out] – An offset to indicate to the client where within the receive buffers the NPE has just written the received data to.
**txOffset* unsigned [out] – An offset to indicate to the client from where within the txPtrList the NPE is currently transmitting from
**numHssErrs* unsigned [out] – The total number of HSS port errors since initial port configuration

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully

◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

```
IX_STATUS ixHssAccChanTslotSwitchDisable ( IxHssAccHssPort hssPortId,  
                                           UINT32             tsSwitchHandle  
                                           )
```

This function is responsible for disabling timeslot switching (bypass) channel, that is associated with tsSwitchHandle, for the specified HSS port. The bypass channel to be disabled must have already been enabled for the specified HSS port. No other HssAccChannelised interface should be called while this interface is being processed.

Parameters:

IxHssAccHssPort hssPortId (in) – The HSS port Id. There are two identical ports (0–1). Only port 0 will be supported.
UINT32 tsSwitchHandle (in) – The handle that hooks to the bypass channel. This handle is the parameter returned to client by ixHssAccChanTslotSwitchEnable during timeslot switching channel enabling operation.

Returns:

◇ IX_SUCCESS The function executed successfully
◇ IX_FAIL The function did not execute successfully
◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

```
IX_STATUS ixHssAccChanTslotSwitchEnable ( IxHssAccHssPort hssPortId,  
                                           UINT32             srcTimeslot,  
                                           UINT32             destTimeslot,  
                                           UINT32 *           tsSwitchHandle  
                                           )
```

This function is responsible for enabling timeslot switching (bypass) channel between two voice channels for the specified HSS port. The voice channels must have already been configured as channelised timeslot for the specified HSS port. In current release, only up to two timeslot switching channels can be enabled at any one time. In order to minimize bypass delay and ensure better voice quality, this function requires at least 8 TDM timeslots on the specified HSS port to be setup as channelised timeslots. In timeslot switching mode, data received on srcTimeslot is transmitted onto a partner timeslot (i.e. destTimeslot) at NPE level. A copy of the received data on srcTimeslot is also sent to client via HssAccess component. No other HssAccChannelised interface should be called while this interface is being processed.

Parameters:

IxHssAccHssPort hssPortId (in) – The HSS port Id. There are two identical ports (0–1). Only port 0 will be supported.
UINT32 srcTimeslot (in) – The voice channel Id whose its receive side will be used in the bypass (0–127).
UINT32 destTimeslot (in) – The voice channel Id whose its transmit side will be used in the bypass (0–127).
UINT32

*tsSwitchHandle (out) – The handle returned to client, that hooks to the bypass channel established between srcTimeslot and destTimeslot. This handle will be the mean by which client disables or downloads gain control table to NPE for the bypass channel that associates with this handle. Client must ignore the value returned through this handle if bypass channel fails to setup.

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

```
IX_STATUS ixHssAccChanTslotSwitchGctDownload ( IxHssAccHssPort hssPortId,
                                                UINT8 *      gainCtrlTable,
                                                UINT32      tsSwitchHandle
                                                )
```

This function is responsible for downloading a gain control table (256 bytes) to NPE for the specified timeslot switching (bypass) channel, associated with tsSwitchHandle, on the specified HSS port. The bypass voice channel must have already been enabled for the specified HSS port before this API can be called to download the gain control table to NPE. No other HssAccChannelised interface should be called while this interface is being processed.

Parameters:

- IxHssAccHssPort* hssPortId (in) – The HSS port Id. There are two identical ports (0–1). Only port 0 will be supported.
- UINT8* *gainCtrlTable (in) – A pointer to an array of size IX_HSSACC_ENTRIES_PER_GAIN_CTRL_TABLE, defining each entry for a gain control table for the specified bypass voice channel.
- UINT32* tsSwitchHandle (in) – The handle that hooks to the bypass channel. This handle is the parameter returned to client by ixHssAccChanTslotSwitchEnable during timeslot switching channel enabling operation.

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

```
IX_STATUS ixHssAccInit ( void )
```

This function is responsible for initialising resources for use by the packetised and channelised clients. It should be called after HSS NPE image has been downloaded into NPE–A and before any other HssAccess interface is called. No other HssAccPacketised interface should be called while this interface is being processed.

Returns:

- ◇ IX_SUCCESS The function executed successfully

- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_RESOURCE_ERR The function did not execute successfully due to a resource error

IX_STATUS ixHssAccLastErrorRetrievalInitiate (**IxHssAccHssPort** *hssPortId*)

Initiate the retrieval of the last HSS error. The HSS port should be configured before attempting to call this interface.

Parameters:

hssPortId **IxHssAccHssPort** [in] – the HSS port ID

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

```

ixHssAccPktPortConnect ( IxHssAccHssPort          hssPortId,
                        IxHssAccHdlcPort          hdlcPortId,
                        BOOL                          hdlcFraming,
                        IxHssAccHdlcMode          hdlcMode,
                        BOOL                          hdlcBitInvert,
                        unsigned                       blockSizeInWords,
                        UINT32                        rawIdleBlockPattern,
                        IxHssAccPktHdlcFraming      hdlcTxFraming,
                        IxHssAccPktHdlcFraming      hdlcRxFraming,
                        unsigned                       frmFlagStart,
                        IxHssAccPktRxCallback       rxCallback,
                        IxHssAccPktUserId          rxUserId,
                        IxHssAccPktRxFreeLowCallback rxFreeLowCallback,
                        IxHssAccPktUserId          rxFreeLowUserId,
                        IxHssAccPktTxDoneCallback   txDoneCallback,
                        IxHssAccPktUserId          txDoneUserId
                        )

```

This function is responsible for connecting a client to one of the 4 available HDLC ports. The HSS port should be configured before attempting a connect. No other HssAccPacketised interface should be called while this connect is being processed.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).

hdlcPortId **IxHssAccHdlcPort** [in] – This is the number of the HDLC port and it corresponds to the physical E1/T1 trunk i.e. 0, 1, 2, 3

hdlcFraming BOOL [in] – This value determines whether the service will use HDLC data or the debug, raw data type i.e. no HDLC processing

hdlcMode

	IxHssAccHdlcMode [in] – This structure contains 56Kbps, HDLC–mode configuration parameters
<i>hdlcBitInvert</i>	BOOL [in] – This value determines whether bit inversion will occur between HDLC and HSS co–processors i.e. post–HDLC processing for transmit and pre–HDLC processing for receive, for the specified HDLC Termination Point
<i>blockSizeInWords</i>	unsigned [in] – The max tx/rx block size
<i>rawIdleBlockPattern</i>	UINT32 [in] – Tx idle pattern in raw mode
<i>hdlcTxFraming</i>	IxHssAccPktHdlcFraming [in] – This structure contains the following information required by the NPE to configure the HDLC co–processor for TX
<i>hdlcRxFraming</i>	IxHssAccPktHdlcFraming [in] – This structure contains the following information required by the NPE to configure the HDLC co–processor for RX
<i>frmFlagStart</i>	unsigned – Number of flags to precede to transmitted flags (0–2).
<i>rxCallback</i>	IxHssAccPktRxCallback [in] – Pointer to the clients packet receive function.
<i>rxUserId</i>	IxHssAccPktUserId [in] – The client supplied rx value to be passed back as an argument to the supplied rxCallback
<i>rxFreeLowCallback</i>	IxHssAccPktRxFreeLowCallback [in] – Pointer to the clients Rx free buffer request function. If NULL, assume client will trigger independently.
<i>rxFreeLowUserId</i>	IxHssAccPktUserId [in] – The client supplied RxFreeLow value to be passed back as an argument to the supplied rxFreeLowCallback
<i>txDoneCallback</i>	IxHssAccPktTxDoneCallback [in] – Pointer to the clients Tx done callback function
<i>txDoneUserId</i>	IxHssAccPktUserId [in] – The client supplied txDone value to be passed back as an argument to the supplied txDoneCallback

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error
- ◇ IX_HSSACC_RESOURCE_ERR The function did not execute successfully due to a resource error

```

IX_STATUS ixHssAccPktPortDisable ( IxHssAccHssPort  hssPortId,
                                   IxHssAccHdlcPort hdlcPortId
                                   )

```

This function is responsible for disabling a packetised service for the specified HSS/HDLC port combination. It disables the RX flow. The client must have already connected to and enabled a packetised service for the specified HDLC port. This disable interface can be called before a disconnect, but is not required to.

Parameters:

- hssPortId* **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).
- hdlcPortId* **IxHssAccHdlcPort** [in] – The port id (0,1,2,3) to disable the service on.

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully

◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

```
IX_STATUS ixHssAccPktPortDisconnect ( IxHssAccHssPort  hssPortId,  
                                       IxHssAccHdlcPort hdlcPortId  
                                       )
```

This function is responsible for disconnecting a client from one of the 4 available HDLC ports. It is not required that the Rx Flow has been disabled before calling this function. If the RX Flow has not been disabled, the disconnect will disable it before proceeding with the disconnect. No other HssAccPacketised interface should be called while this interface is being processed.

Parameters:

<i>hssPortId</i>	IxHssAccHssPort [in] – The HSS port Id. There are two identical ports (0–1).
<i>hdlcPortId</i>	IxHssAccHdlcPort [in] – This is the number of the HDLC port to disconnect and it corresponds to the physical E1/T1 trunk i.e. 0, 1, 2, 3

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PKT_DISCONNECTING The function has initiated the disconnecting procedure but it has not completed yet.

```
IX_STATUS ixHssAccPktPortEnable ( IxHssAccHssPort  hssPortId,  
                                   IxHssAccHdlcPort hdlcPortId  
                                   )
```

This function is responsible for enabling a packetised service for the specified HSS/HDLC port combination. It enables the RX flow. The client must have already connected to a packetised service and is responsible for ensuring an adequate amount of RX mbufs have been supplied to the access component before enabling the packetised service. This function must be called on a given port before any call to ixHssAccPktPortTx on the same port. No other HssAccPacketised interface should be called while this interface is being processed.

Parameters:

<i>hssPortId</i>	IxHssAccHssPort [in] – The HSS port Id. There are two identical ports (0–1).
<i>hdlcPortId</i>	IxHssAccHdlcPort [in] – The port id (0,1,2,3) to enable the service on.

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

```

BOOL ixHssAccPktPortIsDisconnectComplete ( IxHssAccHssPort  hssPortId,
                                             IxHssAccHdlcPort hdlcPortId
                                             )

```

This function is called to check if a given HSS/HDLC port combination is in a connected state or not. This function may be called at any time to determine a ports state. No other HssAccPacketised interface should be called while this interface is being processed.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).
hdlcPortId **IxHssAccHdlcPort** [in] – This is the number of the HDLC port to disconnect and it corresponds to the physical E1/T1 trunk i.e. 0, 1, 2, 3

Returns:

- ◇ TRUE The state of this HSS/HDLC port combination is disconnected, so if a disconnect was called, it is now completed.
- ◇ FALSE The state of this HSS/HDLC port combination is connected, so if a disconnect was called, it is not yet completed.

```

IX_STATUS ixHssAccPktPortRxFreeReplenish ( IxHssAccHssPort  hssPortId,
                                             IxHssAccHdlcPort hdlcPortId,
                                             IX_OSAL_MBUF * buffer
                                             )

```

Function which the client calls at regular intervals to provide mbufs to the access component for RX. A connection should exist for the specified hssPortId/hdlcPortId combination before attempting to call this interface. Also, the connection should not be in a disconnecting state.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).
hdlcPortId **IxHssAccHdlcPort** [in] – This is the number of the HDLC port and it corresponds to the physical E1/T1 trunk i.e. 0, 1, 2, 3
**buffer* [in] – A pointer to a free mbuf to filled with payload.

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully
- ◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error
- ◇ IX_HSSACC_RESOURCE_ERR The function did not execute successfully due to a resource error
- ◇ IX_HSSACC_Q_WRITE_OVERFLOW The function did not succeed due to a Q overflow

```

IX_STATUS ixHssAccPktPortTx ( IxHssAccHssPort  hssPortId,
                              IxHssAccHdlcPort hdlcPortId,
                              IX_OSAL_MBUF * buffer
                              )

```

Function which the client calls when it wants to transmit packetised data. An enabled connection should exist on the specified `hssPortId/hdlcPortId` combination before attempting to call this interface. No other `HssAccPacketised` interface should be called while this interface is being processed.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).
hdlcPortId **IxHssAccHdlcPort** [in] – This is the number of the HDLC port and it corresponds to the physical E1/T1 trunk i.e. 0, 1, 2, 3
**buffer* [in] – A pointer to a chain of mbufs which the client has filled with the payload

Returns:

- ◇ **IX_SUCCESS** The function executed successfully
- ◇ **IX_FAIL** The function did not execute successfully
- ◇ **IX_HSSACC_PARAM_ERR** The function did not execute successfully due to a parameter error
- ◇ **IX_HSSACC_RESOURCE_ERR** The function did not execute successfully due to a resource error. See note.
- ◇ **IX_HSSACC_Q_WRITE_OVERFLOW** The function did not succeed due to a Q overflow

Note:

IX_HSSACC_RESOURCE_ERR is returned when a free descriptor cannot be obtained to send the chain of mbufs to the NPE. This is a normal scenario. `HssAcc` has a pool of descriptors and this error means that they are currently all in use. The recommended approach to this is to retry until a descriptor becomes free and the packet is successfully transmitted. Alternatively, the user could wait until the next `IxHssAccPktTxDoneCallback` callback is triggered, and then retry, as it is this event that causes a transmit descriptor to be freed.

```
IX_STATUS ixHssAccPortInit ( IxHssAccHssPort          hssPortId,
                             IxHssAccConfigParams *   configParams,
                             IxHssAccTdmSlotUsage *   tdmMap,
                             IxHssAccLastErrorCallback lastHssErrorCallback
                             )
```

Initialise a HSS port. No channelised or packetised connections should exist in the `HssAccess` layer while this interface is being called.

Parameters:

hssPortId **IxHssAccHssPort** [in] – The HSS port Id. There are two identical ports (0–1).
configParams* **IxHssAccConfigParams [in] – A pointer to the HSS configuration structure
tdmMap* **IxHssAccTdmSlotUsage [in] – A pointer to an array of size **IX_HSSACC_TSLOTS_PER_HSS_PORT**, defining the slot usage over the HSS port
lastHssErrorCallback **IxHssAccLastErrorCallback** [in] – Client callback to report last error

Returns:

- ◇ **IX_SUCCESS** The function executed successfully
- ◇ **IX_FAIL** The function did not execute successfully

◇ IX_HSSACC_PARAM_ERR The function did not execute successfully due to a parameter error

```
void ixHssAccShow ( void )
```

This function will display the current state of the IxHssAcc component. The output is sent to stdout.

Returns:

void

```
void ixHssAccStatsInit ( void )
```

This function will reset the IxHssAcc statistics.

Returns:

void

```
IX_STATUS ixHssAccUninit ( void )
```

This function is responsible for un-initialize of resources for use by the packetised and channelised clients. It internally calls the uninitialized functions of sub components. This function should be the last function to be called before exiting HssAcc component.

Returns:

- ◇ IX_SUCCESS The function executed successfully
- ◇ IX_FAIL The function did not execute successfully

Intel (R) IXP400 Software I2C Driver(IxI2cDrv) API

IXP400 I2C Driver Public API.

Data Structures

struct **IxI2cInitVars**

contains all the variables required to initialize the I2C unit

struct **IxI2cStatsCounters**

contains results of counters and their overflow

Defines

#define **IX_I2C_US_POLL_FOR_XFER_STATUS**

The interval of micro/mili seconds the Intel (R) IXP4XX Product Line of Network Processors will wait before it polls for status from the ixI2cIntrXferStatus; Every 20us is 1 byte @ 400Kbps and 4 bytes @ 100Kbps. This is dependent on delay type selected through the API ixI2cDrvDelayTypeSelect.

#define **IX_I2C_NUM_OF_TRIES_TO_CALL_CALLBACK_FUNC**

The number of tries that will be attempted to call a callback function if the callback does not or is unable to resolve the issue it is called to resolve.

#define **IX_I2C_NUM_TO_POLL_IDBR_RX_FULL**

Number of tries slave will poll the IDBR Rx full bit before it gives up.

#define **IX_I2C_NUM_TO_POLL_IDBR_TX_EMPTY**

Number of tries slave will poll the IDBR Tx empty bit before it gives up.

Typedefs

typedef void(* **IxI2cMasterReadCallbackP**)(IxI2cMasterStatus, IxI2cXferMode, char *, UINT32)

The pointer to the function that will be called when the master has completed its receive. The parameter that is passed will provide the status of the read (success, arb loss, or bus error), the transfer mode (normal or repeated start, the buffer pointer and number of bytes transferred.

typedef void(* **IxI2cMasterWriteCallbackP**)(IxI2cMasterStatus, IxI2cXferMode, char *, UINT32)

The pointer to the function that will be called when the master has completed its transmit. The parameter that is passed will provide the status of the write (success, arb loss, or buss error), the transfer mode (normal or repeated start), the buffer pointer and number of bytes transferred.

typedef void(* **IxI2cSlaveReadCallbackP**)(IX_I2C_STATUS, char *, UINT32, UINT32)

The pointer to the function that will be called when a slave address detected in interrupt mode for a read. The parameters that is passed will provide the read status, buffer pointer, buffer size, and the bytes received. When a start of a read is initiated there will be no buffer allocated and this callback will be called to request for a buffer. While receiving, if the buffer gets filled, this callback will be called to request for a new buffer while sending the filled buffer's pointer and size, and data size received. When the receive is complete, this callback will be called to process the data and free the memory by passing the buffer's pointer and size, and data size received.

```
typedef void(* IxI2cSlaveWriteCallbackP )(IX_I2C_STATUS, char *, UINT32, UINT32)
```

The pointer to the function that will be called when a slave address detected in interrupt mode for a write. The parameters that is passed will provide the write status, buffer pointer, buffer size, and the bytes received. When a start of a write is initiated there will be no buffer allocated and this callback will be called to request for a buffer and to fill it with data. While transmitting, if the data in the buffer empties, this callback will be called to request for more data to be filled in the same or new buffer. When the transmit is complete, this callback will be called to free the memory or other actions to be taken.

```
typedef void(* IxI2cGenCallCallbackP )(IX_I2C_STATUS, char *, UINT32, UINT32)
```

The pointer to the function that will be called when a general call detected in interrupt mode for a read. The parameters that is passed will provide the read status, buffer pointer, buffer size, and the bytes received. When a start of a read is initiated there will be no buffer allocated and this callback will be called to request for a buffer. While receiving, if the buffer gets filled, this callback will be called to request for a new buffer while sending the filled buffer's pointer and size, and data size received. When the receive is complete, this callback will be called to process the data and free the memory by passing the buffer's pointer and size, and data size received.

Enumerations

```
enum IxI2cMasterStatus {
    IX_I2C_MASTER_XFER_COMPLETE,
    IX_I2C_MASTER_XFER_BUS_ERROR,
    IX_I2C_MASTER_XFER_ARB_LOSS
}
```

The master status – transfer complete, bus error or arbitration loss.

```
enum IX_I2C_STATUS {
    IX_I2C_SUCCESS,
    IX_I2C_FAIL,
    IX_I2C_NOT_SUPPORTED,
    IX_I2C_NULL_POINTER,
    IX_I2C_INVALID_SPEED_MODE_ENUM_VALUE,
    IX_I2C_INVALID_FLOW_MODE_ENUM_VALUE,
    IX_I2C_SLAVE_ADDR_CB_MISSING,
    IX_I2C_GEN_CALL_CB_MISSING,
    IX_I2C_INVALID_SLAVE_ADDR,
    IX_I2C_INT_BIND_FAIL,
    IX_I2C_INT_UNBIND_FAIL,
}
```

```

IX_I2C_NOT_INIT,
IX_I2C_MASTER_BUS_BUSY,
IX_I2C_MASTER_ARB_LOSS,
IX_I2C_MASTER_XFER_ERROR,
IX_I2C_MASTER_BUS_ERROR,
IX_I2C_MASTER_NO_BUFFER,
IX_I2C_MASTER_INVALID_XFER_MODE,
IX_I2C_SLAVE_ADDR_NOT_DETECTED,
IX_I2C_GEN_CALL_ADDR_DETECTED,
IX_I2C_SLAVE_READ_DETECTED,
IX_I2C_SLAVE_WRITE_DETECTED,
IX_I2C_SLAVE_NO_BUFFER,
IX_I2C_DATA_SIZE_ZERO,
IX_I2C_SLAVE_WRITE_BUFFER_EMPTY,
IX_I2C_SLAVE_WRITE_ERROR,
IX_I2C_SLAVE_OR_GEN_READ_BUFFER_FULL,
IX_I2C_SLAVE_OR_GEN_READ_ERROR
}

```

The status that can be returned in a I2C driver initialization.

```

enum IxI2cSpeedMode {
    IX_I2C_NORMAL_MODE,
    IX_I2C_FAST_MODE
}

```

Type of speed modes supported by the I2C hardware.

```

enum IxI2cXferMode {
    IX_I2C_NORMAL,
    IX_I2C_REPEATED_START
}

```

Used for indicating it is a repeated start or normal transfer.

```

enum IxI2cFlowMode {
    IX_I2C_POLL_MODE,
    IX_I2C_INTERRUPT_MODE
}

```

Used for indicating it is a poll or interrupt mode.

```

enum IxI2cDelayMode {
    IX_I2C_LOOP_DELAY,
    IX_I2C_SCHED_DELAY
}

```

Used for selecting looping delay or OS scheduler delay.

Functions

```

PUBLIC
IX_I2C_STATUS ixI2cDrvInit (IxI2cInitVars *InitVarsSelected)

```

Initializes the I2C Driver.

PUBLIC

IX_I2C_STATUS ixI2cDrvUninit (void)
Disables the I2C hardware.

PUBLIC

IX_I2C_STATUS ixI2cDrvSlaveAddrSet (UINT8 SlaveAddrSet)
Sets the I2C Slave Address.

PUBLIC

IX_I2C_STATUS ixI2cDrvBusScan (void)
scans the I2C bus for slave devices

PUBLIC **ixI2cDrvWriteTransfer** (UINT8 SlaveAddr, char *bufP, UINT32 dataSize,
IX_I2C_STATUS IxI2cXferMode XferModeSelect)
PUBLIC **ixI2cDrvReadTransfer** (UINT8 SlaveAddr, char *bufP, UINT32 dataSize,
IX_I2C_STATUS IxI2cXferMode XferModeSelect)
Initiates a transfer to receive bytes of data from a slave device through the I2C bus.

PUBLIC

IX_I2C_STATUS ixI2cDrvSlaveAddrAndGenCallDetectedCheck (void)
Checks the I2C Status Register to determine if a slave address is detected.

PUBLIC **ixI2cDrvSlaveOrGenDataReceive** (char *bufP, const UINT32 bufSize, UINT32
IX_I2C_STATUS *dataSizeRcvd)
Performs the slave receive or general call receive data transfer.

PUBLIC **ixI2cDrvSlaveDataTransmit** (char *bufP, const UINT32 dataSize, UINT32
IX_I2C_STATUS *dataSizeXmtd)
Performs the slave write data transfer.

PUBLIC void **ixI2cDrvSlaveOrGenCallBufReplenish** (char *bufP, UINT32 bufSize)
Replenishes the buffer which stores buffer info for both slave and general call.

PUBLIC

IX_I2C_STATUS ixI2cDrvStatsGet (**IxI2cStatsCounters** *I2cStats)
Returns the I2C Statistics through the pointer passed in.

PUBLIC void **ixI2cDrvStatsReset** (void)
Reset I2C statistics counters.

PUBLIC

IX_I2C_STATUS ixI2cDrvShow (void)
Displays the I2C status register and the statistics counter.

PUBLIC void **ixI2cDrvDelayTypeSelect** (**IxI2cDelayMode** delayTypeSelect)
Sets the delay type of either looping delay or OS scheduler delay according to the argument provided.

Detailed Description

IXP400 I2C Driver Public API.

Define Documentation

```
#define IX_I2C_NUM_OF_TRIES_TO_CALL_CALLBACK_FUNC
```

The number of tries that will be attempted to call a callback function if the callback does not or is unable to resolve the issue it is called to resolve.

Definition at line **44** of file **IxI2cDrv.h**.

```
#define IX_I2C_NUM_TO_POLL_IDBR_RX_FULL
```

Number of tries slave will poll the IDBR Rx full bit before it gives up.

Definition at line **52** of file **IxI2cDrv.h**.

```
#define IX_I2C_NUM_TO_POLL_IDBR_TX_EMPTY
```

Number of tries slave will poll the IDBR Tx empty bit before it gives up.

Definition at line **59** of file **IxI2cDrv.h**.

```
#define IX_I2C_US_POLL_FOR_XFER_STATUS
```

The interval of micro/mili seconds the Intel (R) IXP4XX Product Line of Network Processors will wait before it polls for status from the ixI2cIntrXferStatus; Every 20us is 1 byte @ 400Kbps and 4 bytes @ 100Kbps. This is dependent on delay type selected through the API ixI2cDrvDelayTypeSelect.

Definition at line **36** of file **IxI2cDrv.h**.

Typedef Documentation

```
typedef void(* IxI2cGenCallCallbackP)(IX_I2C_STATUS, char*, UINT32, UINT32)
```

The pointer to the function that will be called when a general call detected in interrupt mode for a read. The parameters that is passed will provide the read status, buffer pointer, buffer size, and the bytes received. When a start of a read is initiated there will be no buffer allocated and this callback will be called to request

for a buffer. While receiving, if the buffer gets filled, this callback will be called to request for a new buffer while sending the filled buffer's pointer and size, and data size received. When the receive is complete, this callback will be called to process the data and free the memory by passing the buffer's pointer and size, and data size received.

Definition at line **242** of file **IxI2cDrv.h**.

```
typedef void(* IxI2cMasterReadCallbackP)(IxI2cMasterStatus, IxI2cXferMode, char*, UINT32)
```

The pointer to the function that will be called when the master has completed its receive. The parameter that is passed will provide the status of the read (success, arb loss, or bus error), the transfer mode (normal or repeated start), the buffer pointer and number of bytes transferred.

Definition at line **180** of file **IxI2cDrv.h**.

```
typedef void(* IxI2cMasterWriteCallbackP)(IxI2cMasterStatus, IxI2cXferMode, char*, UINT32)
```

The pointer to the function that will be called when the master has completed its transmit. The parameter that is passed will provide the status of the write (success, arb loss, or bus error), the transfer mode (normal or repeated start), the buffer pointer and number of bytes transferred.

Definition at line **191** of file **IxI2cDrv.h**.

```
typedef void(* IxI2cSlaveReadCallbackP)(IX_I2C_STATUS, char*, UINT32, UINT32)
```

The pointer to the function that will be called when a slave address detected in interrupt mode for a read. The parameters that is passed will provide the read status, buffer pointer, buffer size, and the bytes received. When a start of a read is initiated there will be no buffer allocated and this callback will be called to request for a buffer. While receiving, if the buffer gets filled, this callback will be called to request for a new buffer while sending the filled buffer's pointer and size, and data size received. When the receive is complete, this callback will be called to process the data and free the memory by passing the buffer's pointer and size, and data size received.

Definition at line **208** of file **IxI2cDrv.h**.

```
typedef void(* IxI2cSlaveWriteCallbackP)(IX_I2C_STATUS, char*, UINT32, UINT32)
```

The pointer to the function that will be called when a slave address detected in interrupt mode for a write. The parameters that is passed will provide the write status, buffer pointer, buffer size, and the bytes received. When a start of a write is initiated there will be no buffer allocated and this callback will be called to request for a buffer and to fill it with data. While transmitting, if the data in the buffer empties, this callback will be called to request for more data to be filled in the same or new buffer. When the transmit is complete, this callback will be called to free the memory or other actions to be taken.

Definition at line **225** of file **IxI2cDrv.h**.

Enumeration Type Documentation

enum IX_I2C_STATUS

The status that can be returned in a I2C driver initialization.

Enumeration values:

<i>IX_I2C_SUCCESS</i>	Success status.
<i>IX_I2C_FAIL</i>	Fail status.
<i>IX_I2C_NOT_SUPPORTED</i>	hardware does not have dedicated I2C hardware
<i>IX_I2C_NULL_POINTER</i>	parameter passed in is NULL
<i>IX_I2C_INVALID_SPEED_MODE_ENUM_VALUE</i>	speed mode selected is invalid
<i>IX_I2C_INVALID_FLOW_MODE_ENUM_VALUE</i>	flow mode selected is invalid
<i>IX_I2C_SLAVE_ADDR_CB_MISSING</i>	slave callback is NULL
<i>IX_I2C_GEN_CALL_CB_MISSING</i>	general callback is NULL
<i>IX_I2C_INVALID_SLAVE_ADDR</i>	invalid slave address specified
<i>IX_I2C_INT_BIND_FAIL</i>	interrupt bind fail
<i>IX_I2C_INT_UNBIND_FAIL</i>	interrupt unbind fail
<i>IX_I2C_NOT_INIT</i>	I2C is not initialized yet.
<i>IX_I2C_MASTER_BUS_BUSY</i>	master detected a I2C bus busy
<i>IX_I2C_MASTER_ARB_LOSS</i>	master experienced arbitration loss
<i>IX_I2C_MASTER_XFER_ERROR</i>	master experienced a transfer error
<i>IX_I2C_MASTER_BUS_ERROR</i>	master detected a I2C bus error
<i>IX_I2C_MASTER_NO_BUFFER</i>	no buffer provided for master transfer
<i>IX_I2C_MASTER_INVALID_XFER_MODE</i>	xfer mode selected is invalid
<i>IX_I2C_SLAVE_ADDR_NOT_DETECTED</i>	polled slave addr not detected
<i>IX_I2C_GEN_CALL_ADDR_DETECTED</i>	polling detected general call
<i>IX_I2C_SLAVE_READ_DETECTED</i>	polling detected slave read request
<i>IX_I2C_SLAVE_WRITE_DETECTED</i>	polling detected slave

<i>IX_I2C_SLAVE_NO_BUFFER</i>	write request no buffer provided for slave transfers
<i>IX_I2C_DATA_SIZE_ZERO</i>	data size transfer is zero – invalid
<i>IX_I2C_SLAVE_WRITE_BUFFER_EMPTY</i>	slave buffer is used till empty
<i>IX_I2C_SLAVE_WRITE_ERROR</i>	slave write experienced an error
<i>IX_I2C_SLAVE_OR_GEN_READ_BUFFER_FULL</i>	slave buffer is filled up
<i>IX_I2C_SLAVE_OR_GEN_READ_ERROR</i>	slave read experienced an error

Definition at line **87** of file **IxI2cDrv.h**.

enum IxI2cDelayMode

Used for selecting looping delay or OS scheduler delay.

Enumeration values:

IX_I2C_LOOP_DELAY delay in microseconds
IX_I2C_SCHED_DELAY delay in milliseconds

Definition at line **165** of file **IxI2cDrv.h**.

enum IxI2cFlowMode

Used for indicating it is a poll or interrupt mode.

Definition at line **152** of file **IxI2cDrv.h**.

enum IxI2cMasterStatus

The master status – transfer complete, bus error or arbitration loss.

Definition at line **72** of file **IxI2cDrv.h**.

enum IxI2cSpeedMode

Type of speed modes supported by the I2C hardware.

Definition at line **126** of file **IxI2cDrv.h**.

enum IxI2cXferMode

Used for indicating it is a repeated start or normal transfer.

Definition at line **139** of file **IxI2cDrv.h**.

Function Documentation

ixI2cDrvBusScan (void)

scans the I2C bus for slave devices

Parameters:

- None

Global Data :

- None.

This API will prompt all slave addresses for a reply except its own

Returns:

- ◇ IX_I2C_SUCCESS – found at least one slave device
- ◇ IX_I2C_FAIL – Fail to find even one slave device
- ◇ IX_I2C_BUS_BUSY – The I2C bus is busy (held by another I2C master)
- ◇ IX_I2C_ARB_LOSS – The I2C bus was loss to another I2C master
- ◇ IX_I2C_NOT_INIT – I2C not init yet.

- Reentrant : yes
- ISR Callable : yes

ixI2cDrvDelayTypeSelect (**IxI2cDelayMode** *delayTypeSelect*)

Sets the delay type of either looping delay or OS scheduler delay according to the argument provided.

Parameters:

- "IxI2cDelayMode [in] delayTypeSelect" – the I2C delay type selected

Global Data :

- None.

This API will set the delay type used by the I2C Driver to either looping delay or OS scheduler delay.

Returns:

◇ None

- Reentrant : yes
- ISR Callable : no

```
ixI2cDrvInit ( IxI2cInitVars * InitVarsSelected )
```

Initializes the I2C Driver.

Parameters:

IxI2cInitVars [in] **InitVarsSelected* – struct containing required variables for initialization

Global Data :

- None.

This API will check if the hardware supports this I2C driver and the validity of the parameters passed in. It will continue to process the parameters passed in by setting the speed of the I2C unit (100kbps or 400kbps), setting the flow to either interrupt or poll mode, setting the address of the I2C unit, enabling/disabling the respond to General Calls, enabling/disabling the respond to Slave Address and SCL line driving. If it is interrupt mode, then it will register the callback routines for master, slavetransfer and general call receive.

Returns:

- ◇ IX_I2C_SUCCESS – Successfully initialize and enable the I2C hardware.
- ◇ IX_I2C_NOT_SUPPORTED – The hardware does not support or have a dedicated I2C unit to support this driver
- ◇ IX_I2C_NULL_POINTER – The parameter passed in is a NULL pointed
- ◇ IX_I2C_INVALID_SPEED_MODE_ENUM_VALUE – The speed mode selected in the *InitVarsSelected* is invalid
- ◇ IX_I2C_INVALID_FLOW_MODE_ENUM_VALUE – The flow mode selected in the *InitVarsSelected* is invalid
- ◇ IX_I2C_INVALID_SLAVE_ADDR – The address 0x0 is reserved for general call.
- ◇ IX_I2C_SLAVE_ADDR_CB_MISSING – interrupt mode is selected but slave address callback pointer is NULL
- ◇ IX_I2C_GEN_CALL_CB_MISSING – interrupt mode is selected but general call callback pointer is NULL
- ◇ IX_I2C_INT_BIND_FAIL – The ISR for the I2C failed to bind
- ◇ IX_I2C_INT_UNBIND_FAIL – The ISR for the I2C failed to unbind

- Reentrant : yes
- ISR Callable : yes

```
ixI2cDrvReadTransfer ( UINT8           SlaveAddr,  
                      char *           bufP,  
                      UINT32          dataSize,  
                      IxI2cXferMode XferModeSelect  
                      )
```

Initiates a transfer to receive bytes of data from a slave device through the I2C bus.

Parameters:

<i>UINT8 [in] SlaveAddr</i>	– The slave address to request data from.
<i>char [out] *bufP</i>	– The pointer to the buffer to store the requested data.
<i>UINT32 [in] dataSize</i>	– The number of bytes requested.
<i>IxI2cXferMode [in]</i>	– the transfer mode selected, either repeated start (ends w/o stop) or
<i>XferModeSelect</i>	normal (start and stop)

Global Data :

- None.

This API will try to obtain master control of the I2C bus and receive the number of bytes, specified by *dataSize*, from the user specified address into the receive buffer. It will use either interrupt or poll mode depending on the mode selected.

If in interrupt mode and *IxI2cMasterReadCallbackP* is not NULL, the driver will initiate the transfer and return immediately. The function pointed to by *IxI2cMasterReadCallbackP* will be called in the interrupt service handlers when the operation is complete.

If in interrupt mode and *IxI2cMasterReadCallbackP* is NULL, then the driver will wait for the operation to complete, and then return.

And if the repeated start transfer mode is selected, then it will not send a stop signal at the end of all the transfers. *NOTE*: If repeated start transfer mode is selected, it has to end with a normal mode transfer mode else the bus will continue to be held by the Intel (R) IXP4XX Product Line of Network Processors.

Returns:

- ◇ IX_I2C_SUCCESS – Successfully read slave data
- ◇ IX_I2C_MASTER_BUS_BUSY – The I2C bus is busy (held by another I2C master)
- ◇ IX_I2C_MASTER_ARB_LOSS – The I2C bus was loss to another I2C master
- ◇ IX_I2C_MASTER_XFER_ERROR – There was a bus error during transfer
- ◇ IX_I2C_MASTER_BUS_ERROR – There was a bus error during transfer
- ◇ IX_I2C_MASTER_NO_BUFFER – buffer pointer is NULL
- ◇ IX_I2C_MASTER_INVALID_XFER_MODE – Xfer mode selected is invalid
- ◇ IX_I2C_INVALID_SLAVE_ADDR – invalid slave address (zero) specified
- ◇ IX_I2C_DATA_SIZE_ZERO – *dataSize* passed in is zero, which is invalid
- ◇ IX_I2C_NOT_INIT – I2C not init yet.

- Reentrant : no
- ISR Callable : no

`ixI2cDrvShow (void)`

Displays the I2C status register and the statistics counter.

Parameters:

- None

Global Data :

- None.

This API will display the I2C Status register and is useful if any error occurs. It displays the detection of bus error, slave address, general call, address, IDBR receive full, IDBR transmit empty, arbitration loss, slave STOP signal, I2C bus busy, unit busy, ack/nack, read/write mode, and delay type selected. It will also call the ixI2cDrvGetStats and then display the statistics counter.

Returns:

- ◇ IX_I2C_SUCCESS – successfully displayed statistics and status register
- ◇ IX_I2C_NOT_INIT – I2C not init yet.

- Reentrant : yes
- ISR Callable : no

```
ixI2cDrvSlaveAddrAndGenCallDetectedCheck ( void )
```

Checks the I2C Status Register to determine if a slave address is detected.

Parameters:

- None

Global Data :

- None.

This API is used in polled mode to determine if the I2C unit is requested for a slave or general call transfer. If it is requested for a slave transfer then it will determine if it is a general call (read only), read, or write transfer requested.

Returns:

- ◇ IX_I2C_SLAVE_ADDR_NOT_DETECTED – The I2C unit is not requested for slave transfer
- ◇ IX_I2C_GEN_CALL_ADDR_DETECTED – The I2C unit is not requested for slave transfer but for general call
- ◇ IX_I2C_SLAVE_READ_DETECTED – The I2C unit is requested for a read
- ◇ IX_I2C_SLAVE_WRITE_DETECTED – The I2C unit is requested for a write
- ◇ IX_I2C_NOT_INIT – I2C not init yet.

- Reentrant : no
- ISR Callable : no

```
ixI2cDrvSlaveAddrSet ( UINT8 SlaveAddrSet )
```

Sets the I2C Slave Address.

Parameters:

UINT8 [in] SlaveAddrSet – Slave Address to be inserted into ISAR

Global Data :

- None.

This API will insert the SlaveAddrSet into the ISAR.

Returns:

- ◇ IX_I2C_SUCCESS – successfully set the slave addr
- ◇ IX_I2C_INVALID_SLAVE_ADDR – invalid slave address (zero) specified
- ◇ IX_I2C_NOT_INIT – I2C not init yet.

- Reentrant : yes
- ISR Callable : yes

```
ixI2cDrvSlaveDataTransmit ( char *      bufP,  
                           const UINT32 dataSize,  
                           UINT32 *    dataSizeXmtd  
                           )
```

Performs the slave write data transfer.

Parameters:

char [in] – the pointer to the buffer for data to be transmitted "const UINT32 [in] bufSize" – the
**bufP* buffer size allocated "UINT32 [in] *dataSizeRcvd" – the length of data trasnmited in
bytes

Global Data :

- None.

This API is only used in polled mode to perform the slave transmit data. It will continuously transmit the data from bufP until complete or until bufP is empty in which it will return IX_I2C_SLAVE_WRITE_BUFFER_EMPTY. If in interrupt mode, the callback will be used.

Returns:

- ◇ IX_I2C_SUCCESS – The I2C driver transferred the data successfully.
- ◇ IX_I2C_SLAVE_WRITE_BUFFER_EMPTY – The I2C driver needs more data to transmit.
- ◇ IX_I2C_SLAVE_WRITE_ERROR –The I2C driver didn't manage to detect the IDBR Tx empty bit or the slave stop bit.
- ◇ IX_I2C_DATA_SIZE_ZERO – dataSize passed in is zero, which is invalid
- ◇ IX_I2C_SLAVE_NO_BUFFER – buffer pointer is NULL
- ◇ IX_I2C_NULL_POINTER – dataSizeXmtd is NULL
- ◇ IX_I2C_NOT_INIT – I2C not init yet.

- Reentrant : no

- ISR Callable : no

```
ixI2cDrvSlaveOrGenCallBufReplenish ( char *   bufP,
                                     UINT32 bufSize
                                     )
```

Replenishes the buffer which stores buffer info for both slave and general call.

Parameters:

*char [in] *bufP* – pointer to the buffer allocated "UINT32 [in] bufSize" – size of the buffer

Global Data :

- None.

This API is only used in interrupt mode for replenishing the same buffer that is used by both slave and general call by updating the buffer info with new info and clearing previous offsets set by previous transfers.

Returns:

◇ None

- Reentrant : no
- ISR Callable : no

```
ixI2cDrvSlaveOrGenDataReceive ( char *           bufP,
                                const UINT32 bufSize,
                                UINT32 *      dataSizeRcvd
                                )
```

Performs the slave receive or general call receive data transfer.

Parameters:

*char [in] *bufP* – the pointer to the buffer to store data "const UINT32 [in] bufSize" – the buffer size allocated "UINT32 [in] *dataSizeRcvd" – the length of data received in bytes

Global Data :

- None.

This API is only used in polled mode to perform the slave read or general call receive data. It will continuously store the data received into bufP until complete or until bufP is full in which it will return IX_I2C_SLAVE_OR_GEN_READ_BUFFER_FULL. If in interrupt mode, the callback will be used.

Returns:

- ◇ IX_I2C_SUCCESS – The I2C driver transferred the data successfully.
- ◇ IX_I2C_SLAVE_OR_GEN_READ_BUFFER_FULL – The I2C driver has ran out of space to store the received data.

- ◇ IX_I2C_SLAVE_OR_GEN_READ_ERROR – The I2C driver didn't manage to detect the IDBR Rx Full bit
- ◇ IX_I2C_DATA_SIZE_ZERO – bufSize passed in is zero, which is invalid
- ◇ IX_I2C_SLAVE_NO_BUFFER – buffer pointer is NULL
- ◇ IX_I2C_NULL_POINTER – dataSizeRcvd is NULL
- ◇ IX_I2C_NOT_INIT – I2C not init yet.

- Reentrant : no
- ISR Callable : no

```
ixI2cDrvStatsGet ( IxI2cStatsCounters * I2cStats )
```

Returns the I2C Statistics through the pointer passed in.

Parameters:

- "IxI2cStatsCounters [out] *I2cStats" – I2C statistics counter will be read and written to the location pointed by this pointer.

Global Data :

- None.

This API will return the statistics counters of the I2C driver.

Returns:

- ◇ IX_I2C_NULL_POINTER – pointer passed in is NULL
- ◇ IX_I2C_SUCCESS – successfully obtained I2C statistics

- Reentrant : yes
- ISR Callable : no

```
ixI2cDrvStatsReset ( void )
```

Reset I2C statistics counters.

Parameters:

- None

Global Data :

- None.

This API will reset the statistics counters of the I2C driver.

Returns:

- ◇ None

- Reentrant : yes

- ISR Callable : no

```
ixI2cDrvUninit ( void )
```

Disables the I2C hardware.

Parameters:

- None

Global Data :

- None.

This API will disable the I2C hardware, unbind interrupt, and unmap memory.

Returns:

- ◊ IX_I2C_SUCCESS – successfully un-initialized I2C
- ◊ IX_I2C_INT_UNBIND_FAIL – failed to unbind the I2C interrupt
- ◊ IX_I2C_NOT_INIT – I2C not init yet.

- Reentrant : yes
- ISR Callable : yes

```
ixI2cDrvWriteTransfer (  UINT8      SlaveAddr,
                        char *      bufP,
                        UINT32      dataSize,
                        IxI2cXferMode XferModeSelect
                        )
```

Parameters:

- | | |
|--|--|
| <i>UINT8 [in] SlaveAddr</i> | – The slave address to request data from. |
| <i>char [in] *bufP</i> | – The pointer to the data to be transmitted. |
| <i>UINT32 [in] dataSize</i> | – The number of bytes requested. |
| <i>IxI2cXferMode [in] XferModeSelect</i> | – the transfer mode selected, either repeated start (ends w/o stop) or normal (start and stop) |

Global Data :

- None.

This API will try to obtain master control of the I2C bus and transmit the number of bytes, specified by *dataSize*, to the user specified slave address from the buffer pointer. It will use either interrupt or poll mode depending on the method selected.

If in interrupt mode and *IxI2cMasterWriteCallbackP* is not NULL, the driver will initiate the transfer and return immediately. The function pointed to by *IxI2cMasterWriteCallbackP* will be called in the interrupt

service handlers when the operation is complete.

If in interrupt mode and `IxI2cMasterWriteCallbackP` is `NULL`, then the driver will wait for the operation to complete, and then return.

And if the repeated start transfer mode is selected, then it will not send a stop signal at the end of all the transfers. *NOTE*: If repeated start transfer mode is selected, it has to end with a normal mode transfer mode else the bus will continue to be held by the Intel (R) IXP4XX Product Line of Network Processors.

Returns:

- ◇ `IX_I2C_SUCCESS` – Successfully wrote data to slave.
- ◇ `IX_I2C_MASTER_BUS_BUSY` – The I2C bus is busy (held by another I2C master)
- ◇ `IX_I2C_MASTER_ARB_LOSS` – The I2C bus was lost to another I2C master
- ◇ `IX_I2C_MASTER_XFER_ERROR` – There was a transfer error
- ◇ `IX_I2C_MASTER_BUS_ERROR` – There was a bus error during transfer
- ◇ `IX_I2C_MASTER_NO_BUFFER` – buffer pointer is `NULL`
- ◇ `IX_I2C_MASTER_INVALID_XFER_MODE` – Xfer mode selected is invalid
- ◇ `IX_I2C_DATA_SIZE_ZERO` – `dataSize` passed in is zero, which is invalid
- ◇ `IX_I2C_NOT_INIT` – I2C not init yet.

- Reentrant : no
- ISR Callable : no

Intel (R) IXP NPE–Downloader (IxnpeDI) API

The Public API for the IXP NPE Downloader.

Modules

Intel (R) IXP

Image ID

Definition

*Definition of Image ID to be passed to **ixNpeDIInitAndStart()** or **ixNpeDICustomImageNpeInitAndStart()** as input of type **UINT32** which has the following fields format:.*

Defines

#define **IX_NPEDL_PARAM_ERR**

NpeDI function return value for a parameter error.

#define **IX_NPEDL_RESOURCE_ERR**

NpeDI function return value for a resource error.

#define **IX_NPEDL_CRITICAL_NPE_ERR**

NpeDI function return value for a Critical NPE error occurring during download. Assume NPE is left in unstable condition if this value is returned or NPE is hang / halt.

#define **IX_NPEDL_CRITICAL_MICROCODE_ERR**

NpeDI function return value for a Critical Microcode error discovered during download. Assume NPE is left in unstable condition if this value is returned.

#define **IX_NPEDL_DEVICE_ERR**

NpeDI function return value when image being downloaded is not meant for the device in use.

Functions

PUBLIC

IX_STATUS **ixNpeDIInitAndStart** (UINT32 imageId)

Stop, reset, download microcode (firmware) and finally start NPE.

PUBLIC

IX_STATUS **ixNpeDICustomImageNpeInitAndStart** (UINT32 *imageLibrary, UINT32 imageId)

Stop, reset, download microcode (firmware) and finally start NPE.

PUBLIC

IX_STATUS **ixNpeDILoadedImageFunctionalityGet** (IxnpeDI npeId, UINT8 *functionalityId)

Gets the functionality of the image last loaded on a particular NPE.

PUBLIC
IX_STATUS **ixNpeDI NpeStopAndReset** (IxNpeDI NpeId npeId)
Stops and Resets an NPE.

PUBLIC
IX_STATUS **ixNpeDI NpeExecutionStart** (IxNpeDI NpeId npeId)
Starts code execution on a NPE.

PUBLIC
IX_STATUS **ixNpeDI NpeExecutionStop** (IxNpeDI NpeId npeId)
Stops code execution on a NPE.

PUBLIC
IX_STATUS **ixNpeDI Unload** (void)
This function will uninitialise the IxNpeDI component.

PUBLIC void **ixNpeDI StatsShow** (void)
This function will display run–time statistics from the IxNpeDI component.

PUBLIC void **ixNpeDI StatsReset** (void)
This function will reset the statistics of the IxNpeDI component.

PUBLIC
UINT32 **ixNpeDI DataMemRead** (UINT32 npeId, UINT32 dataMemAddress)
This function will read 1 WORD from the DMEM of the NPE.

PUBLIC
IX_STATUS **ixNpeDI LoadedImageGet** (IxNpeDI NpeId npeId, IxNpeDI ImageId *imageIdPtr)
Gets the Id of the image currently loaded on a particular NPE.

Detailed Description

The Public API for the IXP NPE Downloader.

Define Documentation

```
#define IX_NPEDL_CRITICAL_MICROCODE_ERR
```

NpeDI function return value for a Critical Microcode error discovered during download. Assume NPE is left in unstable condition if this value is returned.

Definition at line **65** of file **IxNpeDI.h**.

```
#define IX_NPEDL_CRITICAL_NPE_ERR
```

NpeDI function return value for a Critical NPE error occurring during download. Assume NPE is left in unstable condition if this value is returned or NPE is hang / halt.

Definition at line **56** of file **IxNpeDI.h**.

```
#define IX_NPEDL_DEVICE_ERR
```

NpeDI function return value when image being downloaded is not meant for the device in use.

Definition at line **73** of file **IxNpeDI.h**.

```
#define IX_NPEDL_PARAM_ERR
```

NpeDI function return value for a parameter error.

Definition at line **40** of file **IxNpeDI.h**.

```
#define IX_NPEDL_RESOURCE_ERR
```

NpeDI function return value for a resource error.

Definition at line **47** of file **IxNpeDI.h**.

Function Documentation

```
PUBLIC IX_STATUS ixNpeDICustomImageNpeInitAndStart ( UINT32 * imageLibrary,  
                                                    UINT32 imageId  
                                                    )
```

Stop, reset, download microcode (firmware) and finally start NPE.

Parameters:

imageId UINT32 [in] – Id of the microcode image to download.

This function locates the image specified by the *imageId* parameter from the specified microcode image library which is pointed to by the *imageLibrary* parameter. It then stops and resets the NPE, loads the firmware image onto the NPE, and then restarts the NPE.

This is a facility for users who wish to use an image from an external library of NPE firmware images. To use a standard image from the built-in library, see **ixNpeDINpeInitAndStart** instead.

Note:

A list of valid image IDs is included in this header file. See #defines with prefix IX_NPEDL_NPEIMAGE_...

Precondition:

- ◇ The Client is responsible for ensuring mutual access to the NPE.
- ◇ The image library supplied must be in the correct format for use by the NPE Downloader (IxNpeDI) component. Details of the library format are contained in the Functional Specification document for IxNpeDI.

Postcondition:

- ◇ The NPE Instruction Pipeline will be cleared if State Information has been downloaded.
- ◇ If the download fails with a critical error, the NPE may be left in an usable state.

Returns:

- ◇ IX_SUCCESS if the download was successful;
- ◇ IX_NPEDL_PARAM_ERR if a parameter error occurred
- ◇ IX_NPEDL_CRITICAL_NPE_ERR if a critical NPE error occurred during download
- ◇ IX_NPEDL_CRITICAL_MICROCODE_ERR if a critical microcode error occurred during download
- ◇ IX_NPEDL_DEVICE_ERR if the image being loaded is not meant for the device currently running.

```
UINT32 ixNpeDIDataMemRead ( UINT32 npelId,
                             UINT32 dataMemAddress
                           )
```

This function will read 1 WORD from the DMEM of the NPE.

Parameters:

<i>npelId</i>	IxNpeDINpelId [in] – Id of the target NPE
<i>dataMemAddress</i>	UINT32 [in] – DMEM Address

Returns:

DMEM Memory contents value in WORD size

```
PUBLIC IX_STATUS ixNpeDILoadedImageFunctionalityGet ( IxNpeDINpelId npelId,
                                                       UINT8 * functionalityId
                                                     )
```

Gets the functionality of the image last loaded on a particular NPE.

Parameters:

<i>npelId</i>	IxNpeDINpelId [in] – Id of the target NPE.
<i>functionalityId</i>	UINT8* [out] – the functionality ID of the image last loaded on the NPE.

This function retrieves the functionality ID of the image most recently downloaded successfully to the specified NPE. If the NPE does not contain a valid image, this function returns a FAIL status.

Warning:

This function is not intended for general use, as a knowledge of how to interpret the functionality ID is required. As such, this function should only be used by other Access Layer components of the IXP Software Release.

Precondition:

Postcondition:

Returns:

- ◇ IX_SUCCESS if the operation was successful
- ◇ IX_NPEDL_PARAM_ERR if a parameter error occurred
- ◇ IX_FAIL if the NPE does not have a valid image loaded

```
PUBLIC IX_STATUS ixNpeDILoadedImageGet ( IxNpeDINpeId    npelId,  
                                         IxNpeDIImageId * imageIdPtr  
                                         )
```

Gets the Id of the image currently loaded on a particular NPE.

Parameters:

npelId **IxNpeDINpeId** [in] – Id of the target NPE.
imageIdPtr **IxNpeDIImageId*** [out] – Pointer to the where the image id should be stored.

If an image of microcode was previously downloaded successfully to the NPE by NPE Downloader, this function returns in *imageIdPtr* the image Id of that image loaded on the NPE.

Precondition:

- ◇ The Client has allocated memory to the *imageIdPtr* pointer.

Postcondition:

Returns:

- ◇ IX_SUCCESS if the operation was successful
- ◇ IX_NPEDL_PARAM_ERR if a parameter error occurred
- ◇ IX_FAIL if the NPE doesn't currently have a image loaded

```
PUBLIC IX_STATUS ixNpeDINpeExecutionStart ( IxNpeDINpeId npelId )
```

Starts code execution on a NPE.

Parameters:

npelId **IxNpeDINpeId** [in] – Id of the target NPE

Starts execution of code on a particular NPE. A client would typically use this after a download to NPE is performed, to start/restart code execution on the NPE.

Note:

It is no longer necessary to call this function after downloading a new image to the NPE. It is left on the API only to allow greater control of NPE execution if required. Where appropriate, use **ixNpeDlNpeInitAndStart** or **ixNpeDlCustomImageNpeInitAndStart** instead.

Precondition:

- ◇ The Client is responsible for ensuring mutual access to the NPE.
- ◇ Note that this function does not set the NPE's Next Program Counter (NextPC), so it should be set beforehand if required by downloading appropriate State Information (using **ixNpeDlNpeInitAndStart()**).

Postcondition:

Returns:

- ◇ IX_SUCCESS if the operation was successful
- ◇ IX_NPEDL_PARAM_ERR if a parameter error occurred
- ◇ IX_FAIL otherwise

```
PUBLIC IX_STATUS ixNpeDlNpeExecutionStop ( IxNpeDlNpeId npelId )
```

Stops code execution on a NPE.

Parameters:

npelId **IxNpeDlNpeId** [in] – Id of the target NPE

Stops execution of code on a particular NPE. This would typically be used by a client before a download to NPE is performed, to stop code execution on an NPE, unless **ixNpeDlNpeStopAndReset()** is used instead. Unlike **ixNpeDlNpeStopAndReset()**, this function only halts the NPE and leaves all registers and settings intact. This is useful, for example, between stages of a multi-stage download, to stop the NPE prior to downloading the next image while leaving the current state of the NPE intact..

Precondition:

- ◇ The Client is responsible for ensuring mutual access to the NPE.

Postcondition:

Returns:

- ◇ IX_SUCCESS if the operation was successful
- ◇ IX_NPEDL_PARAM_ERR if a parameter error occurred
- ◇ IX_FAIL otherwise

```
PUBLIC IX_STATUS ixNpeDlNpeInitAndStart ( UINT32 imageId )
```

Stop, reset, download microcode (firmware) and finally start NPE.

Parameters:

imageId UINT32 [in] – Id of the microcode image to download.

This function locates the image specified by the *imageId* parameter from the default microcode image library which is included internally by this component. It then stops and resets the NPE, loads the firmware image onto the NPE, and then restarts the NPE.

Note:

A list of valid image IDs is included in this header file. See #defines with prefix IX_NPEDL_NPEIMAGE_...

Precondition:

◇ The Client is responsible for ensuring mutual access to the NPE.

Postcondition:

◇ The NPE Instruction Pipeline will be cleared if State Information has been downloaded.
 ◇ If the download fails with a critical error, the NPE may be left in an unusable state.

Returns:

◇ IX_SUCCESS if the download was successful;
 ◇ IX_NPEDL_PARAM_ERR if a parameter error occurred
 ◇ IX_NPEDL_CRITICAL_NPE_ERR if a critical NPE error occurred during download
 ◇ IX_NPEDL_CRITICAL_MICROCODE_ERR if a critical microcode error occurred during download
 ◇ IX_NPEDL_DEVICE_ERR if the image being loaded is not meant for the device currently running.

```
PUBLIC IX_STATUS ixNpeDlNpeStopAndReset ( IxNpeDlNpeId npeId )
```

Stops and Resets an NPE.

Parameters:

npeId **IxNpeDlNpeId** [in] – Id of the target NPE.

This function performs a soft NPE reset by writing reset values to particular NPE registers. Note that this does not reset NPE co-processors. This implicitly stops NPE code execution before resetting the NPE.

Note:

It is no longer necessary to call this function before downloading a new image to the NPE. It is left on the API only to allow greater control of NPE execution if required. Where appropriate, use **ixNpeDlNpeInitAndStart** or **ixNpeDlCustomImageNpeInitAndStart** instead.

Precondition:

◇ The Client is responsible for ensuring mutual access to the NPE.

Postcondition:**Returns:**

◇ IX_SUCCESS if the operation was successful

- ◇ IX_NPEDL_PARAM_ERR if a parameter error occurred
- ◇ IX_FAIL otherwise
- ◇ IX_NPEDL_CRITICAL_NPE_ERR failed to reset NPE due to timeout error. Timeout error could happen if NPE hang

```
PUBLIC void ixNpeDIStatsReset ( void )
```

This function will reset the statistics of the IxNpeDI component.

Returns:

none

```
PUBLIC void ixNpeDIStatsShow ( void )
```

This function will display run-time statistics from the IxNpeDI component.

Returns:

none

```
PUBLIC IX_STATUS ixNpeDIUnload ( void )
```

This function will uninitialise the IxNpeDI component.

This function will uninitialise the IxNpeDI component. It should only be called once, and only if the IxNpeDI component has already been initialised by calling any of the following functions:

- **ixNpeDINpeInitAndStart**
- **ixNpeDICustomImageNpeInitAndStart**

If possible, this function should be called before a soft reboot or unloading a kernel module to perform any clean up operations required for IxNpeDI.

The following actions will be performed by this function:

- Unmapping of any kernel memory mapped by IxNpeDI

Returns:

- ◇ IX_SUCCESS if the operation was successful
- ◇ IX_FAIL otherwise

Intel (R) IXP Image ID Definition

[Intel (R) IXP NPE–Downloader (IxnpeDI) API]

Definition of Image ID to be passed to **ixNpeDIInitAndStart()** or **ixNpeDICustomImageNpeInitAndStart()** as input of type UINT32 which has the following fields format..

Data Structures

```
struct IxnpeDIImageId  
    Image Id to identify each image contained in an image library.
```

Defines

```
#define IX_NPEDL_NPEIMAGE_FIELD_MASK  
    Mask for NPE Image ID's Field.  
  
#define IX_NPEDL_NPEIMAGE_NPEID_MASK  
    Mask for NPE Image NPE ID's Field.  
  
#define IX_NPEDL_NPEIMAGE_DEVICEID_MASK  
    Mask for NPE Image Device ID's Field.  
  
#define IX_NPEIMAGEID_FUNCTIONID_OFFSET  
    NPE Image function ID's offset (16bits).  
  
#define IX_FUNCTIONID_FROM_NPEIMAGEID_GET(imageId)  
    Macro to extract Functionality ID field from Image ID.
```

Typedefs

```
typedef  
UINT8 IxnpeDIFunctionalityId  
    Used to make up Functionality ID field of Image Id.  
  
typedef  
UINT8 IxnpeDIMajor  
    Used to make up Major Release field of Image Id.  
  
typedef  
UINT8 IxnpeDIMinor  
    Used to make up Minor Revision field of Image Id.  
  
typedef  
UINT8 IxnpeDIDeviceId
```

Used to make up Device Id field of Image Id.

Enumerations

```
enum IxNpeDlNpeId {  
    IX_NPEDL_NPEID_NPEA,  
    IX_NPEDL_NPEID_NPEB,  
    IX_NPEDL_NPEID_NPEC,  
    IX_NPEDL_NPEID_MAX  
}  
NpeId numbers to identify the system's NPEs.
```

```
enum IxNpePortId {  
    IX_NPEB_PORT,  
    IX_NPEC_PORT,  
    IX_NPEA_PORT  
}  
NPE Port ID numbers to identify NPE A, B or C This will be removed once updates have been  
made to ethDB.
```

Detailed Description

Definition of Image ID to be passed to **ixNpeDlNpeInitAndStart()** or **ixNpeDlCustomImageNpeInitAndStart()** as input of type UINT32 which has the following fields format:.

The following is the structure of the Image ID. The first row shows the fields; the second shows the bit locations.

Device ID	NPE ID	Functionality ID	Major Release Number	Minor Release Number
31	27	23	15	7

Field [Bit Location] – Purpose

-
- Device ID [31 – 28] – Specifies the type of device the image is to be downloaded to
 - NPE ID [27 – 24] – Specifies the NPE the image is to be downloaded to
 - Functionality ID [23 – 16] – Specifies the functionality of the image
 - Major Release Number [15 – 8] – Specifies the major version number of the image
 - Minor Release Number [7 – 0] – Specifies the minor version number of the image

Define Documentation

```
#define IX_FUNCTIONID_FROM_NPEIMAGEID_GET ( imageId )
```

Macro to extract Functionality ID field from Image ID.

Definition at line **164** of file **IxNpeDl.h**.

```
#define IX_NPEDL_NPEIMAGE_DEVICEID_MASK
```

Mask for NPE Image Device ID's Field.

Definition at line **149** of file **IxNpeDl.h**.

```
#define IX_NPEDL_NPEIMAGE_FIELD_MASK
```

Mask for NPE Image ID's Field.

Definition at line **133** of file **IxNpeDl.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEID_MASK
```

Mask for NPE Image NPE ID's Field.

Definition at line **141** of file **IxNpeDl.h**.

```
#define IX_NPEIMAGEID_FUNCTIONID_OFFSET
```

NPE Image function ID's offset (16bits).

Definition at line **157** of file **IxNpeDl.h**.

Typedef Documentation

```
IxNpeDIDeviceId
```

Used to make up Device Id field of Image Id.

See **ixNpeDIInitAndStart** for more information.

Definition at line **201** of file **IxNpeDl.h**.

```
IxNpeDIFunctionalityId
```

Used to make up Functionality ID field of Image Id.

See **ixNpeDlNpeInitAndStart** for more information.

Definition at line **177** of file **IxNpeDl.h**.

IxNpeDlMajor

Used to make up Major Release field of Image Id.

See **ixNpeDlNpeInitAndStart** for more information.

Definition at line **185** of file **IxNpeDl.h**.

IxNpeDlMinor

Used to make up Minor Revision field of Image Id.

See **ixNpeDlNpeInitAndStart** for more information.

Definition at line **193** of file **IxNpeDl.h**.

Enumeration Type Documentation

enum IxNpeDlNpeId

NpeId numbers to identify the system's NPEs.

Enumeration values:

IX_NPEDL_NPEID_NPEA Identifies NPE
A.

IX_NPEDL_NPEID_NPEB Identifies NPE
B.

IX_NPEDL_NPEID_NPEC Identifies NPE
C.

IX_NPEDL_NPEID_MAX Total Number
of NPEs.

Definition at line **224** of file **IxNpeDl.h**.

enum IxNpePortId

NPE Port ID numbers to identify NPE A, B or C This will be removed once updates have been made to ethDB.

Enumeration values:

<i>IX_NPEB_PORT</i>	Identifies NPE B.
<i>IX_NPEC_PORT</i>	Identifies NPE C.
<i>IX_NPEA_PORT</i>	Identifies NPE A.

Definition at line **236** of file **IxNpeDl.h**.

Intel (R) IXP Software NPE Message Handler (IxNpeMh) API

The public API for the IXP NPE Message Handler component.

Data Structures

struct **IxNpeMhMessage**
The 2–word message structure to send to and receive from the NPEs.

Defines

```
#define IX_NPEMH_MIN_MESSAGE_ID  
    minimum valid message ID  
  
#define IX_NPEMH_MAX_MESSAGE_ID  
    maximum valid message ID  
  
#define IX_NPEMH_SEND_RETRIES_DEFAULT  
    default msg send retries  
  
#define IX_NPEMH_CRITICAL_NPE_ERR  
    NpeMH function return value for a Critical NPE error occurring during  
    sending/receiving message. Assume NPE hang / halt if this value is  
    returned.
```

Typedefs

```
typedef UINT32 IxNpeMhMessageId  
    message ID  
  
typedef void(* IxNpeMhCallback )(IxNpeMhNpeId, IxNpeMhMessage)  
    This prototype shows the format of a message callback function.
```

Enumerations

```
enum IxNpeMhNpeId {  
    IX_NPEMH_NPEID_NPEA,  
    IX_NPEMH_NPEID_NPEB,  
    IX_NPEMH_NPEID_NPEC,  
    IX_NPEMH_NUM_NPES  
}
```


The ID of a particular NPE.

```
enum IxNpeMhNpeInterrupts {  
    IX_NPEMH_NPEINTERRUPTS_NO,  
    IX_NPEMH_NPEINTERRUPTS_YES  
}
```

Indicator specifying whether or not NPE interrupts should drive receiving of messages from the NPEs.

Functions

PUBLIC IX_STATUS IxNpeMhInitialize (IxNpeMhNpeInterrupts npeInterrupts)

This function will initialise the IxNpeMh component.

PUBLIC IX_STATUS IxNpeMhUnload (void)

This function will uninitialise the IxNpeMh component.

PUBLIC IX_STATUS IxNpeMhUnsolicitedCallbackRegister (IxNpeMhNpeId npeId, IxNpeMhMessageId messageId, IxNpeMhCallback unsolicitedCallback)

This function will register an unsolicited callback for a particular NPE and message ID.

PUBLIC IX_STATUS IxNpeMhUnsolicitedCallbackForRangeRegister (IxNpeMhNpeId npeId, IxNpeMhMessageId minMessageId, IxNpeMhMessageId maxMessageId, IxNpeMhCallback unsolicitedCallback)

This function will register an unsolicited callback for a particular NPE and range of message IDs.

PUBLIC IX_STATUS IxNpeMhMessageSend (IxNpeMhNpeId npeId, IxNpeMhMessage message, UINT32 maxSendRetries)

This function will send a message to a particular NPE.

PUBLIC IX_STATUS IxNpeMhMessageWithResponseSend (IxNpeMhNpeId npeId, IxNpeMhMessage message, IxNpeMhMessageId solicitedMessageId, IxNpeMhCallback solicitedCallback, UINT32 maxSendRetries)

*This function is equivalent to the **IxNpeMhMessageSend()** function, but must be used when the message being sent will solicited a response.*

PUBLIC IX_STATUS IxNpeMhMessagesReceive (IxNpeMhNpeId npeId)

This function will receive messages from a particular NPE and pass each message to the client via a solicited callback (for solicited messages) or an unsolicited callback (for unsolicited messages).

PUBLIC IX_STATUS IxNpeMhShow (IxNpeMhNpeId npeId)

This function will display the current state of the IxNpeMh component.

PUBLIC IX_STATUS IxNpeMhShowReset (IxNpeMhNpeId npeId)

This function will reset the current state of the IxNpeMh component.

IX_STATUS **ixNpeMhConfigStateRestore** (IxNpeMhNpeId npeId)

This function will restore the Interrupt Configuration setting.

Detailed Description

The public API for the IXP NPE Message Handler component.

Define Documentation

```
#define IX_NPEMH_CRITICAL_NPE_ERR
```

NpeMH function return value for a Critical NPE error occuring during sending/receiving message. Assume NPE hang / halt if this value is returned.

Definition at line **44** of file **IxNpeMh.h**.

```
#define IX_NPEMH_MAX_MESSAGE_ID
```

maximum valid message ID

Definition at line **32** of file **IxNpeMh.h**.

```
#define IX_NPEMH_MIN_MESSAGE_ID
```

minimum valid message ID

Definition at line **31** of file **IxNpeMh.h**.

```
#define IX_NPEMH_SEND_RETRIES_DEFAULT
```

default msg send retries

Definition at line **34** of file **IxNpeMh.h**.

Typedef Documentation

```
IxNpeMhCallback
```

This prototype shows the format of a message callback function.

This prototype shows the format of a message callback function. The message callback will be passed the message to be handled and will also be told from which NPE the message was received. The message callback will either be registered by **ixNpeMhUnsolicitedCallbackRegister()** or passed as a parameter to **ixNpeMhMessageWithResponseSend()**. It will be called from within an ISR triggered by the NPE's "outFIFO not empty" interrupt (see **ixNpeMhInitialize()**). The parameters passed are the ID of the NPE that the message was received from, and the message to be handled.

Re-entrancy: This function is only a prototype, and will be implemented by the client. It does not need to be re-entrant.

Definition at line **118** of file **IxNpeMh.h**.

```
typedef UINT32 IxNpeMhMessageId
```

message ID

Definition at line **99** of file **IxNpeMh.h**.

Enumeration Type Documentation

```
enum IxNpeMhNpeId
```

The ID of a particular NPE.

Enumeration values:

<i>IX_NPEMH_NPEID_NPEA</i>	Identifies NPE A.
<i>IX_NPEMH_NPEID_NPEB</i>	Identifies NPE B.
<i>IX_NPEMH_NPEID_NPEC</i>	Identifies NPE C.
<i>IX_NPEMH_NUM_NPES</i>	Number of NPEs.

Definition at line **66** of file **IxNpeMh.h**.

```
enum IxNpeMhNpeInterrupts
```

Indicator specifying whether or not NPE interrupts should drive receiving of messages from the NPEs.

Enumeration values:

<i>IX_NPEMH_NPEINTERRUPTS_NO</i>	Don't use NPE interrupts.
<i>IX_NPEMH_NPEINTERRUPTS_YES</i>	Do use NPE interrupts.

Function Documentation

IX_STATUS ixNpeMhConfigStateRestore (**IxNpeMhNpeId** *npeId*)

This function will restore the Interrupt Configuration setting.

Note:

This API restores the Interrupt Enabling configuration for the OUTFIFO of the NPE used if the ixNPEMH is set to an interrupt mode during initialization. This API must be called once the NPE is reset which may occur during an NPE error.

◊ Re-entrant : No

◊ ISR Callable : Yes

Parameters:

npeId **IxNpeMhNpeId** [in] – The ID of the NPE to restore the configuration

Returns:

The function returns a status indicating success or failure.

IX_STATUS ixNpeMhInitialize (**IxNpeMhNpeInterrupts** *npeInterrupts*)

This function will initialise the IxNpeMh component.

Parameters:

npeInterrupts **IxNpeMhNpeInterrupts** [in] – This parameter dictates whether or not the IxNpeMh component will service NPE "outFIFO not empty" interrupts to trigger receiving and processing of messages from the NPEs. If not then the client must use **ixNpeMhMessagesReceive()** to control message receiving and processing.

This function will initialise the IxNpeMh component. It should only be called once, prior to using the IxNpeMh component. The following actions will be performed by this function:

1. Initialization of internal data structures (e.g. solicited and unsolicited callback tables).
2. Configuration of the interface with the NPEs (e.g. enabling of NPE "outFIFO not empty" interrupts).
3. Registration of ISRs that will receive and handle messages when the NPEs' "outFIFO not empty" interrupts fire (if *npeInterrupts* equals **IX_NPEMH_NPEINTERRUPTS_YES**).

Returns:

The function returns a status indicating success or failure.

IX_STATUS ixNpeMhMessageSend (**IxNpeMhNpeId** *npeId*,
IxNpeMhMessage *message*,
UINT32 *maxSendRetries*)

)

This function will send a message to a particular NPE.

Parameters:

npeId **IxNpeMhNpeId** [in] – The ID of the NPE to send the message to.
message **IxNpeMhMessage** [in] – The message to send.
maxSendRetries **UINT32** [in] – Max num. of retries to perform if the NPE's inFIFO is full.

This function will send a message to a particular NPE. It will be the client's responsibility to ensure that the message is properly formed. The return status will signify to the client if the message was successfully sent or not.

If the message is sent to the NPE then this function will return a status of success. Note that this will only mean the message has been placed in the NPE's inFIFO. There will be no way of knowing that the NPE has actually read the message, but once in the incoming message queue it will be safe to assume that the NPE will process it.

The inFIFO may fill up sometimes if the Xscale is sending messages faster than the NPE can handle them. This forces us to retry attempts to send the message until the NPE services the inFIFO. The client should specify a ceiling value for the number of retries suitable to their needs.

IX_NPEMH_SEND_RETRIES_DEFAULT can be used as a default value for the *maxSendRetries* parameter for this function. Each retry exceeding this default number will incur a blocking delay of 1 microsecond, to avoid consuming too much AHB bus bandwidth while performing retries.

Note this function **must** only be used for messages, that do not solicit responses. If the message being sent will solicit a response then the **ixNpeMhMessageWithResponseSend()** function **must** be used to ensure that the response is correctly handled.

This function will return timeout status if NPE hang / halt while sending message. The timeout error is not related to the *maxSendRetries* as mentioned above. The timeout error will only occur if the first word of the message has been sent to NPE (not exceeding *maxSendRetries* when sending 1st message word), but the second word of the message can't be written to NPE's inFIFO due to NPE hang / halt after maximum waiting time (**IX_NPE_MH_MAX_NUM_OF_RETRIES**).

Re-entrancy: This function will be callable from any thread at any time. IxOsal will be used for any necessary resource protection.

Returns:

The function returns a status indicating success, failure or timeout.

```
IX_STATUS ixNpeMhMessagesReceive ( IxNpeMhNpeId npeId )
```

This function will receive messages from a particular NPE and pass each message to the client via a solicited callback (for solicited messages) or an unsolicited callback (for unsolicited messages).

Parameters:

npeId **IxNpeMhNpeId** [in] – The ID of the NPE to receive and process messages from.

This function will receive messages from a particular NPE and pass each message to the client via a solicited callback (for solicited messages) or an unsolicited callback (for unsolicited messages).

If the **IxNpeMh** component is initialised to service NPE "outFIFO not empty" interrupts (see **ixNpeMhInitialize()**) then there is no need to call this function. This function is only provided as an alternative mechanism to control the receiving and processing of messages from the NPEs.

This function will return timeout status if NPE hang / halt while receiving message. The timeout error will only occur if this function has read the first word of the message and can't read second word of the message from NPE's outFIFO after maximum retries (**IX_NPE_MH_MAX_NUM_OF_RETRIES**).

Note this function cannot be called from within an ISR as it will use resource protection mechanisms.

Re-entrancy: This function will be callable from any thread at any time. **IxOsal** will be used for any necessary resource protection.

Returns:

The function returns a status indicating success, failure or timeout.

```

IX_STATUS ixNpeMhMessageWithResponseSend ( IxNpeMhNpeId      npelId,
                                           IxNpeMhMessage    message,
                                           IxNpeMhMessageId solicitedMessageId,
                                           IxNpeMhCallback    solicitedCallback,
                                           UINT32              maxSendRetries
                                           )

```

This function is equivalent to the **ixNpeMhMessageSend()** function, but must be used when the message being sent will solicited a response.

Parameters:

<i>npelId</i>	IxNpeMhNpeId [in] – The ID of the NPE to send the message to.
<i>message</i>	IxNpeMhMessage [in] – The message to send.
<i>solicitedMessageId</i>	IxNpeMhMessageId [in] – The ID of the solicited response message.
<i>solicitedCallback</i>	IxNpeMhCallback [in] – The function to use to pass the response message back to the client. A value of NULL will cause the response message to be discarded.
<i>maxSendRetries</i>	UINT32 [in] – Max num. of retries to perform if the NPE's inFIFO is full.

This function is equivalent to the **ixNpeMhMessageSend()** function, but must be used when the message being sent will solicited a response.

The client must specify the ID of the solicited response message to allow the response to be recognised when it is received. The client must also specify a callback function to handle the received response. The **IxNpeMh** component will not offer the facility to send a message to a NPE and receive a response within the same context.

Note if the client is not interested in the response, specifying a NULL callback will cause the response message to be discarded.

The solicited callback will be stored and called some time later from an ISR that will be triggered by the NPE's "outFIFO not empty" interrupt (see **ixNpeMhInitialize()**) to handle the response message corresponding to the message sent. Response messages will be handled in the order they are received.

The inFIFO may fill up sometimes if the Xscale is sending messages faster than the NPE can handle them. This forces us to retry attempts to send the message until the NPE services the inFIFO. The client should specify a ceiling value for the number of retries suitable to their needs.

IX_NPEMH_SEND_RETRIES_DEFAULT can be used as a default value for the *maxSendRetries* parameter for this function. Each retry exceeding this default number will incur a blocking delay of 1 microsecond, to avoid consuming too much AHB bus bandwidth while performing retries.

This function will return timeout status if NPE hang / halt while sending message. The timeout error is not related to the *maxSendRetries* as mentioned above. The timeout error will only occur if the first word of the message has been sent to NPE (not exceeding *maxSendRetries* when sending 1st message word), but the second word of the message can't be written to NPE's inFIFO due to NPE hang / halt after maximum waiting time (**IX_NPE_MH_MAX_NUM_OF_RETRIES**).

Re-entrancy: This function will be callable from any thread at any time. IxOsal will be used for any necessary resource protection.

Returns:

The function returns a status indicating success or failure.

```
IX_STATUS ixNpeMhShow ( IxNpeMhNpeId npeId )
```

This function will display the current state of the IxNpeMh component.

Re-entrancy: This function will be callable from any thread at any time. However, no resource protection will be used so as not to impact system performance. As this function is only reading statistical information then this is acceptable.

Parameters:

npeId **IxNpeMhNpeId** [in] – The ID of the NPE to display state information for.

Returns:

The function returns a status indicating success or failure.

```
IX_STATUS ixNpeMhShowReset ( IxNpeMhNpeId npeId )
```

This function will reset the current state of the IxNpeMh component.

Re-entrancy: This function will be callable from any thread at any time. However, no resource protection will be used so as not to impact system performance. As this function is only writing statistical information then this is acceptable.

Parameters:

npeId **IxNpeMhNpeId** [in] – The ID of the NPE to reset state information for.

Returns:

The function returns a status indicating success or failure.

```
IX_STATUS ixNpeMhUnload ( void )
```

This function will uninitialise the IxNpeMh component.

This function will uninitialise the IxNpeMh component. It should only be called once, and only if the IxNpeMh component has already been initialised. No other IxNpeMh API functions should be called until **ixNpeMhInitialize** is called again. If possible, this function should be called before a soft reboot or unloading a kernel module to perform any clean up operations required for IxNpeMh.

The following actions will be performed by this function:

1. Unmapping of kernel memory mapped by the function **ixNpeMhInitialize**.

Returns:

The function returns a status indicating success or failure.

```
IX_STATUS ixNpeMhUnsolicitedCallbackForRangeRegister ( IxNpeMhNpeId      npeId,
                                                         IxNpeMhMessageId minMessageId,
                                                         IxNpeMhMessageId maxMessageId,
                                                         IxNpeMhCallback  unsolicitedCallback
                                                         )
```

This function will register an unsolicited callback for a particular NPE and range of message IDs.

Parameters:

<i>npeId</i>	IxNpeMhNpeId [in] – The ID of the NPE whose messages the unsolicited callback will handle.
<i>minMessageId</i>	IxNpeMhMessageId [in] – The minimum message ID in the range of message IDs the unsolicited callback will handle.
<i>maxMessageId</i>	IxNpeMhMessageId [in] – The maximum message ID in the range of message IDs the unsolicited callback will handle.
<i>unsolicitedCallback</i>	IxNpeMhCallback [in] – The unsolicited callback function. A value of NULL will deregister any previously registered callback(s) for this NPE and range of message IDs.

This function will register an unsolicited callback for a particular NPE and range of message IDs. It is a convenience function that is effectively the same as calling **ixNpeMhUnsolicitedCallbackRegister()** for each ID in the specified range. See **ixNpeMhUnsolicitedCallbackRegister()** for more information.

Re-entrancy: This function will be callable from any thread at any time. IxOsal will be used for any necessary resource protection.

Returns:

The function returns a status indicating success or failure.


```

IX_STATUS ixNpeMhUnsolicitedCallbackRegister ( IxNpeMhNpeId      npeId,
                                              IxNpeMhMessageId messageId,
                                              IxNpeMhCallback   unsolicitedCallback
                                              )

```

This function will register an unsolicited callback for a particular NPE and message ID.

Parameters:

npeId **IxNpeMhNpeId** [in] – The ID of the NPE whose messages the unsolicited callback will handle.

messageId **IxNpeMhMessageId** [in] – The ID of the messages the unsolicited callback will handle.

unsolicitedCallback **IxNpeMhCallback** [in] – The unsolicited callback function. A value of NULL will deregister any previously registered callback for this NPE and message ID.

This function will register an unsolicited message callback for a particular NPE and message ID.

If an unsolicited callback is already registered for the specified NPE and message ID then the callback will be overwritten. Only one client will be responsible for handling a particular message ID associated with a NPE. Registering a NULL unsolicited callback will deregister any previously registered callback.

The callback function will be called from an ISR that will be triggered by the NPE's "outFIFO not empty" interrupt (see **ixNpeMhInitialize()**) to handle any unsolicited messages of the specific message ID received from the NPE. Unsolicited messages will be handled in the order they are received.

If no unsolicited callback can be found for a received message then it is assumed that the message is solicited.

If more than one client may be interested in a particular unsolicited message then the suggested strategy is to register a callback for the message that can itself distribute the message to multiple clients as necessary.

See also **ixNpeMhUnsolicitedCallbackForRangeRegister()**.

Re-entrancy: This function will be callable from any thread at any time. IxOsal will be used for any necessary resource protection.

Returns:

The function returns a status indicating success or failure.

IXP400 NPE Microcode Image Library

Library containing a set of NPE firmware images, for use with NPE Downloader s/w component.

Defines

#define IX_NPE_IMAGE_INCLUDE

Wrap the following Image identifiers with "#if IX_NPE_IMAGE_INCLUDE ... #endif" to include the image in the library.

#define IX_NPE_IMAGE_OMIT

Wrap the following Image identifiers with "#if IX_NPE_IMAGE_OMIT ... #endif" to OMIT the image from the library.

#define IX_NPEDL_NPEIMAGE_NPEA_ATM_MPHY_12_PORT

NPE Image Id for NPE-A with ATM-Only feature. It supports AAL5, AAL0 and OAM for UTOPIA MPHY, 12 logical ports, 32 VCs. It also has Fast Path support.

#define IX_NPEDL_NPEIMAGE_NPEA_HSS0

NPE Image Id for NPE-A with HSS-0 Only feature. It supports 32 channelized and 4 packetized.

#define IX_NPEDL_NPEIMAGE_NPEA_HSS0_ATM_SPHY_1_PORT

NPE Image Id for NPE-A with HSS-0 and ATM feature. For HSS, it supports 16/32 channelized and 4/0 packetized. For ATM, it supports AAL5, AAL0 and OAM for UTOPIA SPHY, 1 logical port, 32 VCs. It also has Fast Path support.

#define IX_NPEDL_NPEIMAGE_NPEA_HSS0_ATM_MPHY_1_PORT

NPE Image Id for NPE-A with HSS-0 and ATM feature. For HSS, it supports 16/32 channelized and 4/0 packetized. For ATM, it supports AAL5, AAL0 and OAM for UTOPIA MPHY, 1 logical port, 32 VCs. It also has Fast Path support.

#define IX_NPEDL_NPEIMAGE_NPEA_DMA

NPE Image Id for NPE-A with DMA-Only feature.

#define IX_NPEDL_NPEIMAGE_NPEA_HSS_2_PORT

NPE Image Id for NPE-A with HSS-0 and HSS-1 feature. Each HSS port supports 32 channelized and 4 packetized.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH

NPE Image Id for NPE-A with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH_LEARN_FILTER_SPAN_FIREWALL

NPE Image Id for NPE-A with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH_LEARN_FILTER_SPAN_FIREWALL_VLAN_QOS

NPE Image Id for NPE-A with Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL, VLAN_QOS.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH_SPAN_FIREWALL_VLAN_QOS_HDR_CONV

NPE Image Id for NPE-A with Ethernet Rx/Tx which includes: SPANNING_TREE, FIREWALL, VLAN_QOS, HDR_CONV.

HEADER_CONVERSION.

#define IX_NPEDL_NPEIMAGE_NPEA_HSS_TSLOT_SWITCH

NPE Image Id for NPE–A with HSS–0 and timeslot switching feature. It supports 32 channelized and 4 packed HSS–0 as well.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH_LEARN_FILTER_SPAN_MASK_FIREWALL_VLAN_QOS

NPE Image Id for NPE–A with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, EXTENDED MIBII.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH_SPAN_VLAN_QOS_HDR_CONV_EXTMIB

NPE Image Id for NPE–A with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH_SPAN_MASK_FIREWALL_VLAN_QOS_HDR_CONV_EXTMIB

NPE Image Id for NPE–A with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH_MACFILTERLEARN_HSSCHAN_COEXIST

NPE Image Id for NPE–A with HSS–0 and Ethernet (with MAC filter/learn) feature.

#define IX_NPEDL_NPEIMAGE_NPEA_ETH_HDRCONV_HSSCHAN_COEXIST

NPE Image Id for NPE–A with HSS–0 and Ethernet (with header conversion) feature.

#define IX_NPEDL_NPEIMAGE_NPEA_HSS0_ATM_MPHY_4_PORT

NPE Image Id for NPE–A with ATM MPHY 4 Ports and HSS Channelized Service (with HSS Bypass) feature.

#define IX_NPEDL_NPEIMAGE_NPEB_ETH

NPE Image Id for NPE–B with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

#define IX_NPEDL_NPEIMAGE_NPEB_ETH_LEARN_FILTER_SPAN_FIREWALL

NPE Image Id for NPE–B with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

#define IX_NPEDL_NPEIMAGE_NPEB_ETH_LEARN_FILTER_SPAN_FIREWALL_VLAN_QOS

NPE Image Id for NPE–B with Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL, VLAN_QOS.

#define IX_NPEDL_NPEIMAGE_NPEB_ETH_SPAN_FIREWALL_VLAN_QOS_HDR_CONV

NPE Image Id for NPE–B with Ethernet Rx/Tx which includes: SPANNING_TREE, FIREWALL, VLAN_QOS, HEADER_CONVERSION.

#define IX_NPEDL_NPEIMAGE_NPEB_DMA

NPE Image Id for NPE–B with DMA–Only feature.

#define IX_NPEDL_NPEIMAGE_NPEB_ETH_LEARN_FILTER_SPAN_MASK_FIREWALL_VLAN_QOS

NPE Image Id for NPE–B with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, EXTENDED MIBII.

#define IX_NPEDL_NPEIMAGE_NPEB_ETH_SPAN_VLAN_QOS_HDR_CONV_EXTMIB

NPE Image Id for NPE–B with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

#define IX_NPEDL_NPEIMAGE_NPEB_ETH_SPAN_MASK_FIREWALL_VLAN_QOS_HDR_CONV_EXT
NPE Image Id for NPE–B with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, MASK_BASED_FL
VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

#define IX_NPEDL_NPEIMAGE_NPEC_ETH
NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING,
SPANNING_TREE, FIREWALL.

#define IX_NPEDL_NPEIMAGE_NPEC_ETH_LEARN_FILTER_SPAN_FIREWALL
NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING,
SPANNING_TREE, FIREWALL.

#define IX_NPEDL_NPEIMAGE_NPEC_ETH_LEARN_FILTER_SPAN_FIREWALL_VLAN_QOS
NPE Image Id for NPE–C with Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING,
SPANNING_TREE, FIREWALL, VLAN_QOS.

#define IX_NPEDL_NPEIMAGE_NPEC_ETH_SPAN_FIREWALL_VLAN_QOS_HDR_CONV
NPE Image Id for NPE–C with Ethernet Rx/Tx which includes: SPANNING_TREE, FIREWALL, VLAN_QOS
HEADER_CONVERSION.

#define IX_NPEDL_NPEIMAGE_NPEC_DMA
NPE Image Id for NPE–C with DMA–Only feature.

#define IX_NPEDL_NPEIMAGE_NPEC_ETH_LEARN_FILTER_SPAN_MASK_FIREWALL_VLAN_QOS
NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING,
SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, EXTENDED MIBII.

#define IX_NPEDL_NPEIMAGE_NPEC_ETH_SPAN_VLAN_QOS_HDR_CONV_EXTMIB
NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, VLAN_QOS,
HEADER_CONVERSION, EXTENDED MIBII.

#define IX_NPEDL_NPEIMAGE_NPEC_ETH_SPAN_MASK_FIREWALL_VLAN_QOS_HDR_CONV_EXT
NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, MASK_BASED_FL
VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

#define IX_NPE_MICROCODE_AVAILABLE_VERSIONS_COUNT

Detailed Description

Library containing a set of NPE firmware images, for use with NPE Downloader s/w component.

Define Documentation

```
#define IX_NPE_IMAGE_INCLUDE
```

Wrap the following Image identifiers with "#if IX_NPE_IMAGE_INCLUDE ... #endif" to include the image in the library.

Definition at line **29** of file **IxNpeMicrocode.h**.

```
#define IX_NPE_IMAGE_OMIT
```

Wrap the following Image identifiers with "#if IX_NPE_IMAGE_OMIT ... #endif" to OMIT the image from the library.

Definition at line **36** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_ATM_MPHY_12_PORT
```

NPE Image Id for NPE–A with ATM–Only feature. It supports AAL5, AAL0 and OAM for UTOPIA MPHY, 12 logical ports, 32 VCs. It also has Fast Path support.

Definition at line **45** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_DMA
```

NPE Image Id for NPE–A with DMA–Only feature.

Definition at line **81** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_ETH
```

NPE Image Id for NPE–A with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

Definition at line **99** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_ETH_HDRCONV_HSSCHAN_COEXIST
```

NPE Image Id for NPE–A with HSS–0 and Ethernet (with header conversion) feature.

Definition at line **180** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_ETH_LEARN_FILTER_SPAN_FIREWALL
```

NPE Image Id for NPE–A with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

Definition at line **108** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_ETH_LEARN_FILTER_SPAN_FIREWALL_VLAN_QOS
```

NPE Image Id for NPE-A with Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL, VLAN_QOS.

Definition at line **117** of file **IxNpeMicrocode.h**.

```
#define  
IX_NPEDL_NPEIMAGE_NPEA_ETH_LEARN_FILTER_SPAN_MASK_FIREWALL_VLAN_QOS_EXTMIB
```

NPE Image Id for NPE-A with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, EXTENDED MIBII.

Definition at line **144** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_ETH_MACFILTERLEARN_HSSCHAN_COEXIST
```

NPE Image Id for NPE-A with HSS-0 and Ethernet (with MAC filter/learn) feature.

Definition at line **171** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_ETH_SPAN_FIREWALL_VLAN_QOS_HDR_CONV
```

NPE Image Id for NPE-A with Ethernet Rx/Tx which includes: SPANNING_TREE, FIREWALL, VLAN_QOS, HEADER_CONVERSION.

Definition at line **126** of file **IxNpeMicrocode.h**.

```
#define  
IX_NPEDL_NPEIMAGE_NPEA_ETH_SPAN_MASK_FIREWALL_VLAN_QOS_HDR_CONV_EXTMIB
```

NPE Image Id for NPE-A with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

Definition at line **162** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_ETH_SPAN_VLAN_QOS_HDR_CONV_EXTMIB
```

NPE Image Id for NPE-A with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

Definition at line **153** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_HSS0
```

NPE Image Id for NPE–A with HSS–0 Only feature. It supports 32 channelized and 4 packetized.

Definition at line **54** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_HSS0_ATM_MPHY_1_PORT
```

NPE Image Id for NPE–A with HSS–0 and ATM feature. For HSS, it supports 16/32 channelized and 4/0 packetized. For ATM, it supports AAL5, AAL0 and OAM for UTOPIA MPHY, 1 logical port, 32 VCs. It also has Fast Path support.

Definition at line **72** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_HSS0_ATM_MPHY_4_PORT
```

NPE Image Id for NPE–A with ATM MPHY 4 Ports and HSS Channelized Service (with HSS Bypass) feature.

Definition at line **189** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_HSS0_ATM_SPHY_1_PORT
```

NPE Image Id for NPE–A with HSS–0 and ATM feature. For HSS, it supports 16/32 channelized and 4/0 packetized. For ATM, it supports AAL5, AAL0 and OAM for UTOPIA SPHY, 1 logical port, 32 VCs. It also has Fast Path support.

Definition at line **63** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_HSS_2_PORT
```

NPE Image Id for NPE–A with HSS–0 and HSS–1 feature. Each HSS port supports 32 channelized and 4 packetized.

Definition at line **90** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEA_HSS_TSLOT_SWITCH
```

NPE Image Id for NPE–A with HSS–0 and timeslot switching feature. It supports 32 channelized and 4 packetized on HSS–0 as well.

Definition at line **135** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEB_DMA
```

NPE Image Id for NPE-B with DMA-Only feature.

Definition at line **234** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEB_ETH
```

NPE Image Id for NPE-B with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

Definition at line **198** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEB_ETH_LEARN_FILTER_SPAN_FIREWALL
```

NPE Image Id for NPE-B with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

Definition at line **207** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEB_ETH_LEARN_FILTER_SPAN_FIREWALL_VLAN_QOS
```

NPE Image Id for NPE-B with Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL, VLAN_QOS.

Definition at line **216** of file **IxNpeMicrocode.h**.

```
#define  
IX_NPEDL_NPEIMAGE_NPEB_ETH_LEARN_FILTER_SPAN_MASK_FIREWALL_VLAN_QOS_EXTMIB
```

NPE Image Id for NPE-B with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, EXTENDED MIBII.

Definition at line **243** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEB_ETH_SPAN_FIREWALL_VLAN_QOS_HDR_CONV
```

NPE Image Id for NPE-B with Ethernet Rx/Tx which includes: SPANNING_TREE, FIREWALL, VLAN_QOS, HEADER_CONVERSION.

Definition at line **225** of file **IxNpeMicrocode.h**.

```
#define  
IX_NPEDL_NPEIMAGE_NPEB_ETH_SPAN_MASK_FIREWALL_VLAN_QOS_HDR_CONV_EXTMIB
```

NPE Image Id for NPE–B with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

Definition at line **261** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEB_ETH_SPAN_VLAN_QOS_HDR_CONV_EXTMIB
```

NPE Image Id for NPE–B with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

Definition at line **252** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEC_DMA
```

NPE Image Id for NPE–C with DMA–Only feature.

Definition at line **306** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEC_ETH
```

NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

Definition at line **270** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEC_ETH_LEARN_FILTER_SPAN_FIREWALL
```

NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL.

Definition at line **279** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEC_ETH_LEARN_FILTER_SPAN_FIREWALL_VLAN_QOS
```

NPE Image Id for NPE–C with Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, FIREWALL, VLAN_QOS.

Definition at line **288** of file **IxNpeMicrocode.h**.

```
#define
```

```
IX_NPEDL_NPEIMAGE_NPEC_ETH_LEARN_FILTER_SPAN_MASK_FIREWALL_VLAN_QOS_EXTMIB
```

NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: MAC_FILTERING, MAC_LEARNING, SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, EXTENDED MIBII.

Definition at line **315** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEC_ETH_SPAN_FIREWALL_VLAN_QOS_HDR_CONV
```

NPE Image Id for NPE–C with Ethernet Rx/Tx which includes: SPANNING_TREE, FIREWALL, VLAN_QOS, HEADER_CONVERSION.

Definition at line **297** of file **IxNpeMicrocode.h**.

```
#define
```

```
IX_NPEDL_NPEIMAGE_NPEC_ETH_SPAN_MASK_FIREWALL_VLAN_QOS_HDR_CONV_EXTMIB
```

NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, MASK_BASED_FIREWALL, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

Definition at line **333** of file **IxNpeMicrocode.h**.

```
#define IX_NPEDL_NPEIMAGE_NPEC_ETH_SPAN_VLAN_QOS_HDR_CONV_EXTMIB
```

NPE Image Id for NPE–C with Basic Ethernet Rx/Tx which includes: SPANNING_TREE, VLAN_QOS, HEADER_CONVERSION, EXTENDED MIBII.

Definition at line **324** of file **IxNpeMicrocode.h**.

Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API

The public API for the Parity Error Notifier.

Data Structures

struct **IxParityENAccAHBErrorTransaction**

The Master and Slave on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

struct **IxParityENAccAHBErrorTransaction**

The Master and Slave on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

struct **IxParityENAccAHBErrorTransaction**

The Master and Slave on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

struct **IxParityENAccEbcConfig**

Expansion Bus Controller parity detection is to be enabled or disabled.

struct **IxParityENAccEbcConfig**

Expansion Bus Controller parity detection is to be enabled or disabled.

struct **IxParityENAccEbcConfig**

Expansion Bus Controller parity detection is to be enabled or disabled.

struct **IxParityENAccEbcParityErrorStats**

Expansion Bus Controller parity error statistics.

struct **IxParityENAccEbcParityErrorStats**

Expansion Bus Controller parity error statistics.

struct **IxParityENAccEbcParityErrorStats**

Expansion Bus Controller parity error statistics.

struct **IxParityENAccHWParityConfig**

Parity error configuration of the Hardware Blocks.

struct **IxParityENAccHWParityConfig**

Parity error configuration of the Hardware Blocks.

struct **IxParityENAccHWParityConfig**

Parity error configuration of the Hardware Blocks.

struct **IxParityENAccMcuConfig**

MCU pairty detection is to be enabled/disabled.

struct **IxParityENAccMcuConfig**
MCU pairty detection is to be enabled/disabled.

struct **IxParityENAccMcuConfig**
MCU pairty detection is to be enabled/disabled.

struct **IxParityENAccMcuParityErrorStats**
DDR Memory Control Unit parity error statistics.

struct **IxParityENAccMcuParityErrorStats**
DDR Memory Control Unit parity error statistics.

struct **IxParityENAccMcuParityErrorStats**
DDR Memory Control Unit parity error statistics.

struct **IxParityENAccNpeConfig**
NPE parity detection is to be enabled/disabled.

struct **IxParityENAccNpeConfig**
NPE parity detection is to be enabled/disabled.

struct **IxParityENAccNpeConfig**
NPE parity detection is to be enabled/disabled.

struct **IxParityENAccNpeParityErrorStats**
NPE parity error statistics.

struct **IxParityENAccNpeParityErrorStats**
NPE parity error statistics.

struct **IxParityENAccNpeParityErrorStats**
NPE parity error statistics.

struct **IxParityENAccParityErrorContextMessage**
Parity Error Context Message.

struct **IxParityENAccParityErrorContextMessage**
Parity Error Context Message.

struct **IxParityENAccParityErrorContextMessage**
Parity Error Context Message.

struct **IxParityENAccParityErrorStats**
Parity Error Statistics for the all the hardware blocks.

struct **IxParityENAccParityErrorStats**
Parity Error Statistics for the all the hardware blocks.

struct **IxParityENAccParityErrorStats**

Parity Error Statistics for the all the hardware blocks.

```
struct IxParityENAccPbcConfig  
    PCI Bus Controller parity detection is to be enabled or disabled.  
  
struct IxParityENAccPbcConfig  
    PCI Bus Controller parity detection is to be enabled or disabled.  
  
struct IxParityENAccPbcConfig  
    PCI Bus Controller parity detection is to be enabled or disabled.  
  
struct IxParityENAccPbcParityErrorStats  
    PCI Bus Controller parity error statistics.  
  
struct IxParityENAccPbcParityErrorStats  
    PCI Bus Controller parity error statistics.  
  
struct IxParityENAccPbcParityErrorStats  
    PCI Bus Controller parity error statistics.
```

Typedefs

```
typedef UINT32 IxParityENAccParityErrorAddress  
    The memory location which has parity error.  
  
typedef UINT32 IxParityENAccParityErrorData  
    The data read from the memory location which has parity error.  
  
typedef void(* IxParityENAccCallback )(void)  
    This prototype shows the format of a callback function.
```

Enumerations

```
enum IxParityENAccStatus {  
    IX_PARITYENACC_SUCCESS,  
    IX_PARITYENACC_INVALID_PARAMETERS,  
    IX_PARITYENACC_NOT_INITIALISED,  
    IX_PARITYENACC_ALREADY_INITIALISED,  
    IX_PARITYENACC_OPERATION_FAILED,  
    IX_PARITYENACC_NO_PARITY  
}  
    The status as returned from the API.  
  
enum IxParityENAccParityType {  
    IX_PARITYENACC_EVEN_PARITY,  
    IX_PARITYENACC_ODD_PARITY  
}
```

Odd or Even Parity Type.

```
enum IxParityENAccConfigOption {  
    IX_PARITYENACC_DISABLE,  
    IX_PARITYENACC_ENABLE  
}
```

The parity error enable/disable configuration option.

```
enum IxParityENAccParityErrorSource {  
    IX_PARITYENACC_NPE_A_IMEM,  
    IX_PARITYENACC_NPE_A_DMEM,  
    IX_PARITYENACC_NPE_A_EXT,  
    IX_PARITYENACC_NPE_B_IMEM,  
    IX_PARITYENACC_NPE_B_DMEM,  
    IX_PARITYENACC_NPE_B_EXT,  
    IX_PARITYENACC_NPE_C_IMEM,  
    IX_PARITYENACC_NPE_C_DMEM,  
    IX_PARITYENACC_NPE_C_EXT,  
    IX_PARITYENACC_SWCP,  
    IX_PARITYENACC_AQM,  
    IX_PARITYENACC_MCU_SBIT,  
    IX_PARITYENACC_MCU_MBIT,  
    IX_PARITYENACC_MCU_OVERFLOW,  
    IX_PARITYENACC_PBC_INITIATOR,  
    IX_PARITYENACC_PBC_TARGET,  
    IX_PARITYENACC_EBC_CS,  
    IX_PARITYENACC_EBC_EXTMST  
}
```

The source of the parity error notification.

```
enum IxParityENAccParityErrorAccess {  
    IX_PARITYENACC_READ,  
    IX_PARITYENACC_WRITE  
}
```

The type of access resulting in parity error.

```
enum IxParityENAccParityErrorRequester {  
    IX_PARITYENACC_MPI,  
    IX_PARITYENACC_AHB_BUS  
}
```

The requester interface through which the SDRAM memory access resulted in the parity error.

```
enum IxParityENAccAHBErrorMaster {  
    IX_PARITYENACC_AHBN_MST_NPE_A,  
    IX_PARITYENACC_AHBN_MST_NPE_B,  
    IX_PARITYENACC_AHBN_MST_NPE_C,  
    IX_PARITYENACC_AHBS_MST_XSCALE,  
    IX_PARITYENACC_AHBS_MST_PBC,  
    IX_PARITYENACC_AHBS_MST_EBC,  
    IX_PARITYENACC_AHBS_MST_AHB_BRIDGE,  
}
```

```
IX_PARITYENACC_AHBS_MST_USBH
}
```

The Master on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

```
enum IxParityENAccAHBErrorSlave {
    IX_PARITYENACC_AHBN_SLV_MCU,
    IX_PARITYENACC_AHBN_SLV_AHB_BRIDGE,
    IX_PARITYENACC_AHBS_SLV_MCU,
    IX_PARITYENACC_AHBS_SLV_APB_BRIDGE,
    IX_PARITYENACC_AHBS_SLV_AQM,
    IX_PARITYENACC_AHBS_SLV_RSA,
    IX_PARITYENACC_AHBS_SLV_PBC,
    IX_PARITYENACC_AHBS_SLV_EBC,
    IX_PARITYENACC_AHBS_SLV_USBH
}
```

The Slave on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

Functions

PUBLIC

IxParityENAccStatus IxParityENAccInit (void)

This function will initialise the IxParityENAcc component.

PUBLIC**IxParityENAccCallbackRegister** (IxParityENAccCallback

IxParityENAccStatus parityErrNfyCallBack)

This function will register a new callback with IxParityENAcc component. It can also reregister a new callback replacing the old callback.

PUBLIC**IxParityENAccParityDetectionConfigure** (const

IxParityENAccStatus IxParityENAccHWParityConfig *hwParityConfig)

This interface allows the client application to enable the parity error detection on the underlying hardware block.

PUBLIC**IxParityENAccParityDetectionQuery** (IxParityENAccHWParityConfig *const

IxParityENAccStatus hwParityConfig)

This interface allows the client application to determine the status of the parity error detection on the specified hardware blocks.

PUBLIC**IxParityENAccParityErrorContextGet**

IxParityENAccStatus (IxParityENAccParityErrorMessage *const pecMessage)

This interface allows the client application to determine the status of the parity error context on hardware block for which the current parity error interrupt triggered.

PUBLIC**IxParityENAccParityErrorInterruptClear** (const

IxParityENAccStatus IxParityENAccParityErrorMessage *pecMessage)

This interface helps the client application to clear off the interrupt condition on the hardware block identified in the parity error context message. Please refer to the

table below as the operation varies depending on the interrupt source.

PUBLIC
IxParityENAccStatsGet (**IxParityENAccParityErrorStats** *const
IxParityENAccStatus ixParityErrorStats)
This interface allows the client application to retrieve parity error statistics for all the hardware blocks.

PUBLIC
IxParityENAccStatus **IxParityENAccStatsShow** (void)
This interface allows the client application to print all the parity error statistics.

PUBLIC
IxParityENAccStatus **IxParityENAccStatsReset** (void)
This interface allows the client application to reset all the parity error statistics.

PUBLIC
IxParityENAccStatus **IxParityENAccParityNPEConfigReUpdate** (UINT32 npeID)
This interface allows the client to restore and update the NPE Error enabling configuration.

PUBLIC
IxParityENAccNPEParityErrorCheck (UINT32 npeID,
IxParityENAccStatus **IxParityENAccParityErrorMessage** *const pecMessage)
This interface allows the client to check for any NPE Error status.

Detailed Description

The public API for the Parity Error Notifier.

Typedef Documentation

IxParityENAccCallback

This prototype shows the format of a callback function.

The callback will be used to notify the parity error to the client application. The callback will be registered by **IxParityENAccCallbackRegister**.

It will be called from an ISR when a parity error is detected and thus needs to follow the interrupt callable function conventions.

Definition at line **418** of file **IxParityENAcc.h**.

IxParityENAccParityErrorAddress

The memory location which has parity error.

Definition at line **290** of file **IxParityENAcc.h**.

IxParityENAccParityErrorData

The data read from the memory location which has parity error.

Definition at line **299** of file **IxParityENAcc.h**.

Enumeration Type Documentation

enum IxParityENAccAHBErrorMaster

The Master on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

Enumeration values:

<i>IX_PARITYENACC_AHBN_MST_NPE_A</i>	NPE – A.
<i>IX_PARITYENACC_AHBN_MST_NPE_B</i>	NPE – B.
<i>IX_PARITYENACC_AHBN_MST_NPE_C</i>	NPE – C.
<i>IX_PARITYENACC_AHBS_MST_XSCALE</i>	Intel XScale(R) Processor Bus Interface Unit.
<i>IX_PARITYENACC_AHBS_MST_PBC</i>	PCI Bus Controller.
<i>IX_PARITYENACC_AHBS_MST_EBC</i>	Expansion Bus Controller.
<i>IX_PARITYENACC_AHBS_MST_AHB_BRIDGE</i>	AHB Bridge.
<i>IX_PARITYENACC_AHBS_MST_USBH</i>	USB Host Controller.

Definition at line **323** of file **IxParityENAcc.h**.

enum IxParityENAccAHBErrorSlave

The Slave on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

Enumeration values:

<i>IX_PARITYENACC_AHBN_SLV_MCU</i>	Memory Control Unit.
<i>IX_PARITYENACC_AHBN_SLV_AHB_BRIDGE</i>	AHB Bridge.
<i>IX_PARITYENACC_AHBS_SLV_MCU</i>	Intel XScale(R) Processor Bus Interface Unit.
<i>IX_PARITYENACC_AHBS_SLV_APB_BRIDGE</i>	APB Bridge.
<i>IX_PARITYENACC_AHBS_SLV_AQM</i>	AQM.
<i>IX_PARITYENACC_AHBS_SLV_RSA</i>	RSA (Crypto Bus).
<i>IX_PARITYENACC_AHBS_SLV_PBC</i>	PCI Bus Controller.
<i>IX_PARITYENACC_AHBS_SLV_EBC</i>	Expansion Bus Controller.
<i>IX_PARITYENACC_AHBS_SLV_USBH</i>	USB Host Controller.

Definition at line **343** of file **IxParityENAcc.h**.

enum IxParityENAccConfigOption

The parity error enable/disable configuration option.

Enumeration values:

IX_PARITYENACC_DISABLE Disable parity error detection.

IX_PARITYENACC_ENABLE Enable parity error detection.

Definition at line **69** of file **IxParityENAcc.h**.

enum IxParityENAccParityErrorAccess

The type of access resulting in parity error.

Enumeration values:

IX_PARITYENACC_READ Read Access.

IX_PARITYENACC_WRITE Write Access.

Definition at line **277** of file **IxParityENAcc.h**.

enum IxParityENAccParityErrorRequester

The requester interface through which the SDRAM memory access resulted in the parity error.

Enumeration values:

IX_PARITYENACC_MPI Direct Memory Port Interface.

IX_PARITYENACC_AHB_BUS South or North AHB Bus.

Definition at line **309** of file **IxParityENAcc.h**.

enum IxParityENAccParityErrorSource

The source of the parity error notification.

Enumeration values:

IX_PARITYENACC_NPE_A_IMEM NPE A – Instruction memory.

IX_PARITYENACC_NPE_A_DMEN NPE A – Data memory.

IX_PARITYENACC_NPE_A_EXT NPE A – External Entity.

IX_PARITYENACC_NPE_B_IMEM NPE B – Instruction memory.

IX_PARITYENACC_NPE_B_DMEN NPE B – Data memory.

IX_PARITYENACC_NPE_B_EXT NPE B – External Entity.

<i>IX_PARITYENACC_NPE_C_IMEM</i>	NPE C – Instruction memory.
<i>IX_PARITYENACC_NPE_C_DMEM</i>	NPE C – Data memory.
<i>IX_PARITYENACC_NPE_C_EXT</i>	NPE C – External Entity.
<i>IX_PARITYENACC_SWCP</i>	SWCP.
<i>IX_PARITYENACC_AQM</i>	AQM.
<i>IX_PARITYENACC_MCU_SBIT</i>	DDR Memory Controller Unit – Single bit parity.
<i>IX_PARITYENACC_MCU_MBIT</i>	DDR Memory Controller Unit – Multi bit parity.
<i>IX_PARITYENACC_MCU_OVERFLOW</i>	DDR Memory Controller Unit – Parity errors in excess of two.
<i>IX_PARITYENACC_PBC_INITIATOR</i>	PCI Bus Controller as Initiator.
<i>IX_PARITYENACC_PBC_TARGET</i>	PCI Bus Controller as Target.
<i>IX_PARITYENACC_EBC_CS</i>	Expansion Bus Controller – Chip Select.
<i>IX_PARITYENACC_EBC_EXTMST</i>	Expansion Bus Controller – External Master.

Definition at line **248** of file **IxParityENAcc.h**.

```
enum IxParityENAccParityType
```

Odd or Even Parity Type.

Enumeration values:

<i>IX_PARITYENACC_EVEN_PARITY</i>	Even Parity.
<i>IX_PARITYENACC_ODD_PARITY</i>	Odd Parity.

Definition at line **56** of file **IxParityENAcc.h**.

```
enum IxParityENAccStatus
```

The status as returned from the API.

Enumeration values:

<i>IX_PARITYENACC_SUCCESS</i>	The request is successful.
<i>IX_PARITYENACC_INVALID_PARAMETERS</i>	Invalid or NULL parameters passed.
<i>IX_PARITYENACC_NOT_INITIALISED</i>	Access layer has not been initialised before accessing the APIs.
<i>IX_PARITYENACC_ALREADY_INITIALISED</i>	Access layer has already been initialised.
<i>IX_PARITYENACC_OPERATION_FAILED</i>	Operation did not succeed due to hardware failure.
<i>IX_PARITYENACC_NO_PARITY</i>	No parity condition exists or has already been cleared.

Definition at line **39** of file **IxParityENAcc.h**.

Function Documentation

IxParityENAccStatus (**IxParityENAccCallback** *parityErrNfyCallBack*)
ixParityENAccCallbackRegister

This function will register a new callback with IxParityENAcc component. It can also reregister a new callback replacing the old callback.

Parameters:

parityErrNfyCallBack [in] – This parameter will specify the call-back function supplied by the client application.

This interface registers the user application supplied call-back handler with the parity error handling access component after the init.

The callback function will be called from an ISR that will be triggered by the parity error in the IXP400 silicon.

The following actions will be performed by this function:

1. Check for the prior initialisation of the module before registering or re-registering of the callback.
Check for parity error detection disabled before re-registration of the callback.
- Re-entrant : No
 - ISR Callable : No

Returns:

- ◇ **IX_PARITYENACC_SUCCESS** – The parameters check passed and the registration is successful.
- ◇ **IX_PARITYENACC_INVALID_PARAMETERS** – Request failed due to NULL parameter passed.
- ◇ **IX_PARITYENACC_OPERATION_FAILED** – The request failed because the parity error detection not yet disabled.
- ◇ **IX_PARITYENACC_NOT_INITIALISED** – The operation requested prior to the initialisation of the access layer.

IxParityENAccStatus **ixParityENAccInit** (void)

This function will initialise the IxParityENAcc component.

This function will initialise the IxParityENAcc component. It should only be called once, prior to using the IxParityENAcc component.

1. It initialises the internal data structures, registers the ISR that will be triggered when a parity error occurs in the supported Intel (R) IXP4XX Product Line of Network processors.
- Re-entrant : No
 - ISR Callable : No

Returns:

- ◇ IX_PARITYENACC_SUCCESS – Initialization is successful
- ◇ IX_PARITYENACC_ALREADY_INITIALISED – The access layer has already been initialized
- ◇ IX_PARITYENACC_OPERATION_FAILED – The request failed because the operation didn't succeed on the hardware. Refer to error trace/log for details.

```

IxParityENAccStatus ( UINT32 npeID,
IxParityENAccNPEParityErrorCheck IxParityENAccParityErrorMessage
                                *const pecMessage
                                )

```

This interface allows the client to check for any NPE Error status.

- Re-entrant : No
- ISR Callable : Yes

Parameters:

npeID UINT32 [in] NPE ID, NPE–A (0) , NPE–B (1) and NPE–C (2)
pecMessage **IxParityENAccParityErrorMessage** [out]

Returns:

- IX_PARITYENACC_SUCCESS– Existence of an NPE Parity Error
- IX_PARITYENACC_INVALID_PARAMETERS–The request failed due to NULL parameter is passed
- IX_PARITYENACC_OPERATION_FAILED – The request failed because the operation didn't succeed on the hardware.
- IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.
- IX_PARITYENACC_NO_PARITY – No parity condition exists or has already been cleared

```

IxParityENAccStatus ( const hwParityConfig )
IxParityENAccParityDetectionConfigure IxParityENAccHWParityConfig *

```

This interface allows the client application to enable the parity error detection on the underlying hardware block.

Parameters:

hwParityConfig [in] – Hardware blocks for which the parity error detection is to be enabled or disabled.

The client application allocates and provides the reference to the buffer.

It will also verify whether the specific hardware block is functional or not.

NOTE: Failure in enabling or disabling of one or more components result in trace message but still returns IX_PARITYENACC_SUCCESS. Refer to the function **IxParityENAccParityDetectionQuery** on how to verify the failures while enabling/disabling parity error detection.

It shall be invoked after the Init and CallbackRegister functions but before any other function of the IxParityENAcc layer.

- Re-entrant : No
- ISR Callable : No

Returns:

- ◇ IX_PARITYENACC_SUCCESS – The parameters check passed and the request to enable/disable is successful.
- ◇ IX_PARITYENACC_INVALID_PARAMETERS–The request failed due to NULL parameter supplied.
- ◇ IX_PARITYENACC_OPERATION_FAILED – The request failed because the operation didn't succeed on the hardware.
- ◇ IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.

IxParityENAccStatus	(IxParityENAccHWParityConfig <i>hwParityConfig</i>)
ixParityENAccParityDetectionQuery	*const

This interface allows the client application to determine the status of the parity error detection on the specified hardware blocks.

Parameters:

hwParityConfig [out] – Hardware blocks whose parity error detection has been enabled or disabled.

The client application allocates and provides the reference to the buffer.

This interface can be used immediately after the interface **ixParityENAccParityDetectionConfigure** to see on which of the hardware blocks the parity error detection has either been enabled or disabled based on the client application request.

- Re-entrant : No
- ISR Callable : No

Returns:

- ◇ IX_PARITYENACC_SUCCESS – The parameters check passed and the request to query on whether the hardware parity error detection is enabled or disabled is successful.
- ◇ IX_PARITYENACC_INVALID_PARAMETERS–The request failed due to NULL parameter or invalid values supplied.
- ◇ IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.

IxParityENAccStatus	(IxParityENAccParityErrorMessage <i>pecMessage</i>)
ixParityENAccParityErrorContextGet	*const

This interface allows the client application to determine the status of the parity error context on hardware block for which the current parity error interrupt triggered.

Parameters:

pecMessage [out] – The parity error context information of the parity interrupt currently being process.

The client application allocates and provides the reference to the buffer.

Refer to the data structure **IxParityENAccParityErrorContextMessage** for details.

The routine will will fetch the parity error context in the following priority, if multiple parity errors observed.

```

0 - MCU (Multi-bit and single-bit in that order)
1 - NPE-A
2 - NPE-B
3 - NPE-C
4 - SWCP
5 - QM
6 - PCI
7 - EXP

```

NOTE: The information provided in the **IxParityENAccAHBErrorTransaction** may be of help for the client application to decide on the course of action to take. This info is taken from the Performance Monitoring Unit register which records most recent error observed on the AHB bus. This information might have been overwritten by some other error by the time it is retrieved.

- Re-entrant : No
- ISR Callable : Yes

Returns:

- ◇ IX_PARITYENACC_SUCCESS–The parameters check passed and the request to get the parity error context information is successful.
- ◇ IX_PARITYENACC_INVALID_PARAMETERS–The request failed due to NULL parameter is passed
- ◇ IX_PARITYENACC_OPERATION_FAILED – The request failed because the operation didn't succeed on the hardware.
- ◇ IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.
- ◇ IX_PARITYENACC_NO_PARITY – No parity condition exists or has already been cleared

IxParityENAccStatus	(const	<i>pecMessage</i>)
ixParityENAccParityErrorInterruptClear	IxParityENAccParityErrorContextMessage	
	*	

This interface helps the client application to clear off the interrupt condition on the hardware block identified in the parity error context message. Please refer to the table below as the operation varies depending on the interrupt source.

Parameters:

pecMessage [in] – The parity error context information of the hardware block whose parity error interrupt condition is to disabled.

The client application allocates and provides the reference to the buffer.

 Following actions will be taken during the interrupt clear for respective hardware blocks.

Parity Source -----	Actions taken during Interrupt clear -----
NPE-A	<p>Interrupt will be masked off at the interrupt controller so that it will not trigger continuously.</p> <p>Client application has to take appropriate action and re-configure the parity error detection subsequently. The client application will not be notified of further interrupts, until the re-configuration is done using ixParityENAccParityDetectionConfigure.</p>
NPE-B	<p>Interrupt will be masked off at the interrupt controller so that it will not trigger continuously.</p> <p>Client application has to take appropriate action and re-configure the parity error detection subsequently. The client application will not be notified of further interrupts, until the re-configuration is done using ixParityENAccParityDetectionConfigure.</p>
NPE-C	<p>Interrupt will be masked off at the interrupt controller</p> <p>Client application has to take appropriate action and re-configure the parity error detection subsequently. The client application will not be notified of further interrupts, until the re-configuration is done using ixParityENAccParityDetectionConfigure.</p>
SWCP	<p>Interrupt will be masked off at the interrupt controller.</p> <p>Client application has to take appropriate action and re-configure the parity error detection subsequently. The client application will not be notified of further interrupts, until the re-configuration is done using ixParityENAccParityDetectionConfigure.</p>
AQM	<p>Interrupt will be masked off at the interrupt controller.</p> <p>Client application has to take appropriate action and re-configure the parity error detection subsequently. The client application will not be notified of further interrupts, until the re-configuration is done using ixParityENAccParityDetectionConfigure.</p>
MCU	<p>Parity interrupt condition is cleared at the SDRAM MCU for the following:</p> <ol style="list-style-type: none"> 1. Single-bit 2. Multi-bit 3. Overflow condition i.e., more than two parity conditions occurred <p>Note that single-parity errors do not result in data abort and not all data aborts caused by multi-bit parity error.</p>
PCI	<p>Interrupt condition is cleared at the PCI bus controller.</p>
EXP	<p>Parity interrupt condition is cleared at the expansion bus controller for the following:</p> <ol style="list-style-type: none"> 1. External master initiated Inbound write 2. Internal master (IXP400) initiated Outbound read

- Re-entrant : No
- ISR Callable : No

Returns:

- ◇ IX_PARITYENACC_SUCCESS–The parameters check passed and the request to clear the parity error interrupt condition is successful.
- ◇ IX_PARITYENACC_INVALID_PARAMETERS–The request failed due to NULL parameters have been passed or contents have been supplied with invalid values.
- ◇ IX_PARITYENACC_OPERATION_FAILED – The request failed because the operation didn't succeed on the hardware.
- ◇ IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.

IxParityENAccStatus ixParityENAccParityNPEConfigReUpdate (UINT32 *npeID*)

This interface allows the client to restore and update the NPE Error enabling configuration.

- Re-entrant : No
- ISR Callable : No

Parameters:

npeID – [in] NPE ID, NPE-A (0) , NPE-B (1) and NPE-C (2)

Returns:

- IX_PARITYENACC_SUCCESS – The request to Restore/Re-update the parity error control enable bits in the NPE is a success.
- IX_PARITYENACC_OPERATION_FAILED – The request failed because the operation didn't succeed on the hardware.
- IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.

IxParityENAccStatus	(IxParityENAccParityErrorStats	<i>ixParityErrorStats</i>)
ixParityENAccStatsGet	*const	

This interface allows the client application to retrieve parity error statistics for all the hardware blocks.

Parameters:

ixParityErrorStats – [out] The statistics for all the hardware blocks.

The client application allocates and provides the reference to the buffer.

- Re-entrant : No
- ISR Callable : Yes

Returns:

- ◇ IX_PARITYENACC_SUCCESS–The parameters check passed and the request to retrieve parity error statistics for the hardware block is successful.

- ◇ IX_PARITYENACC_INVALID_PARAMETERS – The request failed due to a NULL parameter passed.
- ◇ IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.

IxParityENAccStatus ixParityENAccStatsReset (void)

This interface allows the client application to reset all the parity error statistics.

- Re-entrant : No
- ISR Callable : No

Returns:

- ◇ IX_PARITYENACC_SUCCESS – The request to reset the parity error statistics is successful.
- ◇ IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.

IxParityENAccStatus ixParityENAccStatsShow (void)

This interface allows the client application to print all the parity error statistics.

- Re-entrant : No
- ISR Callable : No

Returns:

- ◇ IX_PARITYENACC_SUCCESS – The request to show the parity error statistics is successful.
- ◇ IX_PARITYENACC_NOT_INITIALISED – The operation requested prior to the initialisation of the access layer.

Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API

IXP400 Performance Profiling Utility component Public API.

- NOTE: Xcycle measurement is not supported in Linux*.

Data Structures

struct **IxPerfProfAccBusPmuResults**
Results obtained from running the Bus Pmu component. The results are obtained when the get functions is called.

struct **IxPerfProfAccXcycleResults**
Results obtained from Xcycle run.

struct **IxPerfProfAccXscalePmuEvtCnt**
contains results of a counter

struct **IxPerfProfAccXscalePmuResults**
contains results of counters and their overflow

struct **IxPerfProfAccXscalePmuSamplePcProfile**
contains summary of samples taken

Defines

#define **IX_PERFPROF_ACC_XSCALE_PMU_MAX_PROFILE_SAMPLES**
This is the maximum number of profiling samples allowed, which can be modified according to user's discretion.

#define **IX_PERFPROF_ACC_BUS_PMU_MAX_PECS**
This is the maximum number of Programmable Event Counters available. This is a hardware specific and fixed value. Do not change.

#define **IX_PERFPROF_ACC_XCYCLE_MAX_NUM_OF_MEASUREMENTS**
Max number of measurement allowed. This constant is used when creating storage array for Xcycle. When run in continuous mode, Xcycle will wrap around and re-use buffer.

#define **IX_PERFPROF_ACC_XSCALE_PMU_SYMBOL_ACCURACY**
Level of accuracy required for matching the PC Address to symbol address. This is used when the Intel XScale(R) Processor PMU time/event sampling functions get the PC address and search for the corresponding symbol address.

#define **IX_PERFPROF_ACC_LOG**(level, device, str, a, b, c, d, e, f)

Enumerations

```
enum IxPerfProfAccBusPmuEventCounters1 {  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEA_GRANT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEB_GRANT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEC_GRANT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_BUS_IDLE_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEA_REQ_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEB_REQ_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEC_REQ_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_GSKT_GRANT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_ABB_GRANT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_PCI_GRANT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_APB_GRANT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_GSKT_REQ_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_ABB_REQ_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_PCI_REQ_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_APB_REQ_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_0_HIT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_1_HIT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_2_HIT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_3_HIT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_4_MISS_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_5_MISS_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_6_MISS_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_7_MISS_SELECT  
}
```

Type of bus pmu events supported on PEC 1.

```
enum IxPerfProfAccBusPmuEventCounters2 {  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEA_XFER_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEB_XFER_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEC_XFER_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_BUS_WRITE_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEA_OWN_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEB_OWN_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEC_OWN_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_GSKT_XFER_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_ABB_XFER_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_PCI_XFER_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_APB_XFER_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_GSKT_OWN_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_ABB_OWN_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_PCI_OWN_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_APB_OWN_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_1_HIT_SELECT,  
    IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_2_HIT_SELECT,  
}
```

```

IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_3_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_4_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_5_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_6_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_7_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_0_MISS_SELECT
}

```

Type of bus pmu events supported on PEC 2.

```

enum IxPerfProfAccBusPmuEventCounters3 {
    IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEA_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEB_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEC_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_BUS_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEA_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEB_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEC_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_GSKT_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_ABB_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_PCI_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_APB_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_GSKT_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_ABB_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_PCI_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_APB_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_2_HIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_3_HIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_4_HIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_5_HIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_6_MISS_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_7_MISS_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_0_MISS_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_1_MISS_SELECT
}

```

Type of bus pmu events supported on PEC 3.

```

enum IxPerfProfAccBusPmuEventCounters4 {
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_PCI_SPLIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_EXP_SPLIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_APB_GRANT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_APB_XFER_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_GSKT_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_ABB_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_PCI_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_APB_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_ABB_SPLIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_NPEA_REQ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_NPEA_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_NPEB_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_NPEC_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_3_HIT_SELECT,

```

```

IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_4_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_5_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_6_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_7_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_0_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_1_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_2_MISS_SELECT

```

```

}

```

Type of bus pmu events supported on PEC 4.

```

enum IxPerfProfAccBusPmuEventCounters5 {
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_GRANT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_XFER_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_EXP_SPLIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_REQ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_OWN_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_BUS_IDLE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_GRANT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_XFER_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_REQ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_OWN_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_4_HIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_5_HIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_6_HIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_7_HIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_0_MISS_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_1_MISS_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_2_MISS_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_3_MISS_SELECT
}

```

Type of bus pmu events supported on PEC 5.

```

enum IxPerfProfAccBusPmuEventCounters6 {
    IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_GRANT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_XFER_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_SPLIT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_REQ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_OWN_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_BUS_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_GRANT_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_XFER_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_REQ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_OWN_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEB_WRITE_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_READ_SELECT,

```

```

IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_5_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_6_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_7_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_0_HIT_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_1_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_2_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_3_MISS_SELECT,
IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_4_MISS_SELECT
}

```

Type of bus pmu events supported on PEC 6.

```

enum IxPerfProfAccBusPmuEventCounters7 {
    IX_PERFPROF_ACC_BUS_PMU_PEC7_SOUTH_APB_RETRY_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC7_SOUTH_APB_REQ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC7_SOUTH_APB_OWN_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC7_SOUTH_BUS_READ_SELECT,
    IX_PERFPROF_ACC_BUS_PMU_PEC7_CYCLE_COUNT_SELECT
}

```

Type of bus pmu events supported on PEC 7.

```

enum IxPerfProfAccXscalePmuEvent {
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_CACHE_MISS,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_CACHE_INSTRUCTION,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_STALL,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_INST_TLB_MISS,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_DATA_TLB_MISS,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_BRANCH_EXEC,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_BRANCH_MISPREDICT,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_INST_EXEC,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_FULL_EVERYCYCLE,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_ONCE,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_DATA_CACHE_ACCESS,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_DATA_CACHE_MISS,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_DATA_CACHE_WRITEBACK,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_SW_CHANGE_PC,
    IX_PERFPROF_ACC_XSCALE_PMU_EVENT_MAX
}

```

Type of Intel XScale (R) Processor PMU events supported.

```

enum IxPerfProfAccStatus {
    IX_PERFPROF_ACC_STATUS_SUCCESS,
    IX_PERFPROF_ACC_STATUS_FAIL,
    IX_PERFPROF_ACC_STATUS_ANOTHER_UTIL_IN_PROGRESS,
    IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_IN_PROGRESS,
    IX_PERFPROF_ACC_STATUS_XCYCLE_NO_BASELINE,
    IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_REQUEST_OUT_OF_RANGE,
    IX_PERFPROF_ACC_STATUS_XCYCLE_PRIORITY_SET_FAIL,
    IX_PERFPROF_ACC_STATUS_XCYCLE_THREAD_CREATE_FAIL,
    IX_PERFPROF_ACC_STATUS_XCYCLE_PRIORITY_RESTORE_FAIL,
    IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_NOT_RUNNING,
    IX_PERFPROF_ACC_STATUS_XSCALE_PMU_NUM_INVALID,
}

```

```

IX_PERFPROF_ACC_STATUS_XSCALE_PMU_EVENT_INVALID,
IX_PERFPROF_ACC_STATUS_XSCALE_PMU_START_NOT_CALLED,
IX_PERFPROF_ACC_STATUS_BUS_PMU_MODE_ERROR,
IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC1_ERROR,
IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC2_ERROR,
IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC3_ERROR,
IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC4_ERROR,
IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC5_ERROR,
IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC6_ERROR,
IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC7_ERROR,
IX_PERFPROF_ACC_STATUS_BUS_PMU_START_NOT_CALLED,
IX_PERFPROF_ACC_STATUS_COMPONENT_NOT_SUPPORTED
}

```

Invalid Status Definitions.

```

enum IxPerfProfAccBusPmuMode {
    IX_PERFPROF_ACC_BUS_PMU_MODE_HALT,
    IX_PERFPROF_ACC_BUS_PMU_MODE_SOUTH,
    IX_PERFPROF_ACC_BUS_PMU_MODE_NORTH,
    IX_PERFPROF_ACC_BUS_PMU_MODE_SDRAM
}

```

State selection of counters.

Functions

PUBLIC**IxPerfProfAccXscalePmuEventCountStart** (BOOL clkCntDiv, UINT32 numEvents, **IxPerfProfAccStatus** **IxPerfProfAccXscalePmuEvent** pmuEvent1, **IxPerfProfAccXscalePmuEvent** pmuEvent2, **IxPerfProfAccXscalePmuEvent** pmuEvent3, **IxPerfProfAccXscalePmuEvent** pmuEvent4)
This API will start the clock and event counting.

PUBLIC**IxPerfProfAccXscalePmuEventCountStop** (**IxPerfProfAccXscalePmuResults** **IxPerfProfAccStatus** *eventCountStopResults)
This API will stop the clock and event counting.

PUBLIC
IxPerfProfAccStatus **ixPerfProfAccXscalePmuTimeSampStart** (UINT32 samplingRate, BOOL clkCntDiv)
Starts the time based sampling.

PUBLIC**IxPerfProfAccXscalePmuTimeSampStop** (**IxPerfProfAccXscalePmuEvtCnt** *clkCount, **IxPerfProfAccStatus** **IxPerfProfAccXscalePmuSamplePcProfile** *timeProfile)
Stops the time based sampling.

PUBLIC**IxPerfProfAccXscalePmuEventSampStart** (UINT32 numEvents, **IxPerfProfAccXscalePmuEvent** pmuEvent1, UINT32 eventRate1, **IxPerfProfAccXscalePmuEvent** pmuEvent2, UINT32 eventRate2, **IxPerfProfAccXscalePmuEvent** pmuEvent3, UINT32 eventRate3, **IxPerfProfAccXscalePmuEvent** pmuEvent4, UINT32 eventRate4)
Starts the event based sampling.

PUBLIC **ixPerfProfAccXscalePmuEventSampStop** (**ixPerfProfAccXscalePmuSamplePcProfile** **ixPerfProfAccStatus** *eventProfile1, **ixPerfProfAccXscalePmuSamplePcProfile** *eventProfile2, **ixPerfProfAccXscalePmuSamplePcProfile** *eventProfile3, **ixPerfProfAccXscalePmuSamplePcProfile** *eventProfile4)
Stops the event based sampling.

PUBLIC **void ixPerfProfAccXscalePmuResultsGet** (**ixPerfProfAccXscalePmuResults** *results)
Reads the current value of the counters and their overflow.

PUBLIC **ixPerfProfAccBusPmuStart** (**ixPerfProfAccBusPmuMode** mode, **ixPerfProfAccStatus** **ixPerfProfAccBusPmuEventCounters1** pecEvent1, **ixPerfProfAccBusPmuEventCounters2** pecEvent2, **ixPerfProfAccBusPmuEventCounters3** pecEvent3, **ixPerfProfAccBusPmuEventCounters4** pecEvent4, **ixPerfProfAccBusPmuEventCounters5** pecEvent5, **ixPerfProfAccBusPmuEventCounters6** pecEvent6, **ixPerfProfAccBusPmuEventCounters7** pecEvent7)
Initializes all the counters and selects events to be monitored.

PUBLIC
ixPerfProfAccStatus ixPerfProfAccBusPmuStop (void)
Stops all counters.

PUBLIC **void ixPerfProfAccBusPmuResultsGet** (**ixPerfProfAccBusPmuResults** *BusPmuResults)
Gets values of all counters.

PUBLIC **void ixPerfProfAccBusPmuPMSRGet** (UINT32 *pmsrValue)
Get values of PMSR.

PUBLIC
ixPerfProfAccStatus ixPerfProfAccXcycleBaselineRun (UINT32 *numBaselineCycle)
Perform baseline for Xcycle.

PUBLIC
ixPerfProfAccStatus ixPerfProfAccXcycleStart (UINT32 numMeasurementsRequested)
Start the measurement.

PUBLIC
ixPerfProfAccStatus ixPerfProfAccXcycleStop (void)
Stop the Xcycle measurement.

PUBLIC
ixPerfProfAccStatus ixPerfProfAccXcycleResultsGet (**ixPerfProfAccXcycleResults** *xcycleResult)
Get the results of Xcycle measurement.

PUBLIC **BOOL ixPerfProfAccXcycleInProgress** (void)
Check if Xcycle is running.

int ixPerfProfAccXscalePmuTimeSampCreateProcFile (char *buf, char **start, off_t offset, int
 int *eof, void *data)
int ixPerfProfAccXscalePmuEventSampCreateProcFile (char *buf, char **start, off_t offset, int
 int *eof, void *data)

Detailed Description

IXP400 Performance Profiling Utility component Public API.

- NOTE: Xcycle measurement is not supported in Linux*.

Define Documentation

```
#define IX_PERFPROF_ACC_BUS_PMU_MAX_PPCS
```

This is the maximum number of Programmable Event Counters available. This is a hardware specific and fixed value. Do not change.

Definition at line **49** of file **IxPerfProfAcc.h**.

```
#define IX_PERFPROF_ACC_LOG ( level,  
                             device,  
                             str,  
                             a,  
                             b,  
                             c,  
                             d,  
                             e,  
                             f      )
```

Mechanism for logging a formatted message for the PerfProfAcc component.

Parameters:

<i>level</i>	UINT32 [in] – trace level
<i>device</i>	UINT32 [in] – output device
<i>str</i>	char* [in] – format string, similar to printf().
<i>a</i>	UINT32 [in] – first argument to display
<i>b</i>	UINT32 [in] – second argument to display
<i>c</i>	UINT32 [in] – third argument to display
<i>d</i>	UINT32 [in] – fourth argument to display
<i>e</i>	UINT32 [in] – fifth argument to display
<i>f</i>	UINT32 [in] – sixth argument to display

Returns:

none

Definition at line **95** of file **IxPerfProfAcc.h**.

```
#define IX_PERFPROF_ACC_XCYCLE_MAX_NUM_OF_MEASUREMENTS
```

Max number of measurement allowed. This constant is used when creating storage array for Xcycle. When run in continuous mode, Xcycle will wrap around and re-use buffer.

Definition at line **60** of file **IxPerfProfAcc.h**.

```
#define IX_PERFPROF_ACC_XSCALE_PMU_MAX_PROFILE_SAMPLES
```

This is the maximum number of profiling samples allowed, which can be modified according to the user's discretion.

Definition at line **38** of file **IxPerfProfAcc.h**.

```
#define IX_PERFPROF_ACC_XSCALE_PMU_SYMBOL_ACCURACY
```

Level of accuracy required for matching the PC Address to symbol address. This is used when the Intel XScale(R) Processor PMU time/event sampling functions get the PC address and search for the corresponding symbol address.

Definition at line **72** of file **IxPerfProfAcc.h**.

Enumeration Type Documentation

```
enum IxPerfProfAccBusPmuEventCounters1
```

Type of bus pmu events supported on PEC 1.

Lists all bus pmu events.

Enumeration values:

<code>IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEA_GRANT_SELECT</code>	Select North NPEA grant on PEC1.
<code>IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEB_GRANT_SELECT</code>	Select North NPEB grant on PEC1.
<code>IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEC_GRANT_SELECT</code>	Select North NPEC grant on PEC1.
<code>IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_BUS_IDLE_SELECT</code>	Select North bus idle on PEC1.
<code>IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEA_REQ_SELECT</code>	Select North NPEA req on PEC1.
<code>IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEB_REQ_SELECT</code>	Select North NPEB req on PEC1.
<code>IX_PERFPROF_ACC_BUS_PMU_PEC1_NORTH_NPEC_REQ_SELECT</code>	Select North NPEC req on PEC1.

<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_GSKT_GRANT_SELECT</i>	Select south gasket grant on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_ABB_GRANT_SELECT</i>	Select south abb grant on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_PCI_GRANT_SELECT</i>	Select south pci grant on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_APB_GRANT_SELECT</i>	Select south apb grant on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_GSKT_REQ_SELECT</i>	Select south gasket request on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_ABB_REQ_SELECT</i>	Select south abb request on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_PCI_REQ_SELECT</i>	Select south pci request on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SOUTH_APB_REQ_SELECT</i>	Select south apb request on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_0_HIT_SELECT</i>	Select sdram0 hit on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_1_HIT_SELECT</i>	Select sdram1 hit on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_2_HIT_SELECT</i>	Select sdram2 hit on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_3_HIT_SELECT</i>	Select sdram3 hit on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_4_MISS_SELECT</i>	Select sdram4 miss on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_5_MISS_SELECT</i>	Select sdram5 miss on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_6_MISS_SELECT</i>	Select sdram6 miss on PEC1.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC1_SDR_7_MISS_SELECT</i>	Select sdram7 miss on PEC1.

Definition at line **186** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccBusPmuEventCounters2
```

Type of bus pmu events supported on PEC 2.

Lists all bus pmu events.

Enumeration values:

<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEA_XFER_SELECT</i>	Select North NPEA transfer on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEB_XFER_SELECT</i>	Select North NPEB transfer on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEC_XFER_SELECT</i>	Select North NPEC transfer on PEC2.

<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_BUS_WRITE_SELECT</i>	Select North bus write on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEA_OWN_SELECT</i>	Select North NPEA own on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEB_OWN_SELECT</i>	Select North NPEB own on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_NORTH_NPEC_OWN_SELECT</i>	Select North NPEC own on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_GSKT_XFER_SELECT</i>	Select South gasket transfer on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_ABB_XFER_SELECT</i>	Select South abb transfer on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_PCI_XFER_SELECT</i>	Select South pci transfer on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_APB_XFER_SELECT</i>	Select South apb transfer on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_GSKT_OWN_SELECT</i>	Select South gasket own on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_ABB_OWN_SELECT</i>	Select South abb own on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_PCI_OWN_SELECT</i>	Select South pci own on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SOUTH_APB_OWN_SELECT</i>	Select South apb own transfer on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_1_HIT_SELECT</i>	Select sdram1 hit on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_2_HIT_SELECT</i>	Select sdram2 hit on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_3_HIT_SELECT</i>	Select sdram3 hit on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_4_HIT_SELECT</i>	Select sdram4 hit on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_5_MISS_SELECT</i>	Select sdram5 miss on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_6_MISS_SELECT</i>	Select sdram6 miss on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_7_MISS_SELECT</i>	Select sdram7 miss on PEC2.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC2_SDR_0_MISS_SELECT</i>	Select sdram0 miss on PEC2.

Definition at line **224** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccBusPmuEventCounters3
```

Type of bus pmu events supported on PEC 3.

Lists all bus pmu events.

Enumeration values:

<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEA_RETRY_SELECT</i>	Select north NPEA retry on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEB_RETRY_SELECT</i>	Select north NPEB retry on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEC_RETRY_SELECT</i>	Select north NPEC retry on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_BUS_READ_SELECT</i>	Select north bus read on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEA_WRITE_SELECT</i>	Select north NPEA write on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEB_WRITE_SELECT</i>	Select north NPEB write on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_NORTH_NPEC_WRITE_SELECT</i>	Select north NPEC write on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_GSKT_RETRY_SELECT</i>	Select south gasket retry on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_ABB_RETRY_SELECT</i>	Select south abb retry on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_PCI_RETRY_SELECT</i>	Select south pci retry on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_APB_RETRY_SELECT</i>	Select south apb retry on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_GSKT_WRITE_SELECT</i>	Select south gasket write on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_ABB_WRITE_SELECT</i>	Select south abb write on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_PCI_WRITE_SELECT</i>	Select south pci write on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SOUTH_APB_WRITE_SELECT</i>	Select south apb write on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_2_HIT_SELECT</i>	Select sdram2 hit on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_3_HIT_SELECT</i>	Select sdram3 hit on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_4_HIT_SELECT</i>	Select sdram4 hit on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_5_HIT_SELECT</i>	Select sdram5 hit on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_6_MISS_SELECT</i>	Select sdram6 miss on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_7_MISS_SELECT</i>	Select sdram7 miss on PEC3.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_0_MISS_SELECT</i>	Select sdram0 miss

<i>IX_PERFPROF_ACC_BUS_PMU_PEC3_SDR_1_MISS_SELECT</i>	on PEC3. Select sdram1 miss on PEC3.
---	--

Definition at line **262** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccBusPmuEventCounters4
```

Type of bus pmu events supported on PEC 4.

Lists all bus pmu events.

Enumeration values:

<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_PCI_SPLIT_SELECT</i>	Select south pci split on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_EXP_SPLIT_SELECT</i>	Select south expansion split on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_APB_GRANT_SELECT</i>	Select south apb grant on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_APB_XFER_SELECT</i>	Select south apb transfer on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_GSKT_READ_SELECT</i>	Select south gasket read on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_ABB_READ_SELECT</i>	Select south abb read on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_PCI_READ_SELECT</i>	Select south pci read on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SOUTH_APB_READ_SELECT</i>	Select south apb read on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_ABB_SPLIT_SELECT</i>	Select north abb split on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_NPEA_REQ_SELECT</i>	Select north NPEA req on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_NPEA_READ_SELECT</i>	Select north NPEA read on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_NPEB_READ_SELECT</i>	Select north NPEB read on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_NORTH_NPEC_READ_SELECT</i>	Select north NPEC read on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_3_HIT_SELECT</i>	Select sdram3 hit on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_4_HIT_SELECT</i>	Select sdram4 hit on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_5_HIT_SELECT</i>	Select sdram5 hit on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_6_HIT_SELECT</i>	Select sdram6 hit on PEC4.

<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_7_MISS_SELECT</i>	Select sdram7 miss on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_0_MISS_SELECT</i>	Select sdram0 miss on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_1_MISS_SELECT</i>	Select sdram1 miss on PEC4.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC4_SDR_2_MISS_SELECT</i>	Select sdram2 miss on PEC4.

Definition at line **300** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccBusPmuEventCounters5
```

Type of bus pmu events supported on PEC 5.

Lists all bus pmu events.

Enumeration values:

<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_GRANT_SELECT</i>	Select south abb grant on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_XFER_SELECT</i>	Select south abb transfer on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_RETRY_SELECT</i>	Select south abb retry on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_EXP_SPLIT_SELECT</i>	Select south expansion split on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_REQ_SELECT</i>	Select south abb request on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_ABB_OWN_SELECT</i>	Select south abb own on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SOUTH_BUS_IDLE_SELECT</i>	Select south bus idle on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_GRANT_SELECT</i>	Select north NPEB grant on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_XFER_SELECT</i>	Select north NPEB transfer on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_RETRY_SELECT</i>	Select north NPEB retry on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_REQ_SELECT</i>	Select north NPEB request on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_OWN_SELECT</i>	Select north NPEB own on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_WRITE_SELECT</i>	Select north NPEB write on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_NORTH_NPEB_READ_SELECT</i>	Select north NPEB read on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_4_HIT_SELECT</i>	

<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_5_HIT_SELECT</i>	Select north sdram4 hit on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_6_HIT_SELECT</i>	Select north sdram5 hit on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_7_HIT_SELECT</i>	Select north sdram6 hit on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_0_MISS_SELECT</i>	Select north sdram7 hit on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_1_MISS_SELECT</i>	Select north sdram0 miss on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_2_MISS_SELECT</i>	Select north sdram1 miss on PEC5.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC5_SDR_3_MISS_SELECT</i>	Select north sdram2 miss on PEC5.
	Select north sdram3 miss on PEC5.

Definition at line **336** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccBusPmuEventCounters6
```

Type of bus pmu events supported on PEC 6.

Lists all bus pmu events.

Enumeration values:

<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_GRANT_SELECT</i>	Select south pci grant on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_XFER_SELECT</i>	Select south pci transfer on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_RETRY_SELECT</i>	Select south pci retry on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_SPLIT_SELECT</i>	Select south pci split on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_REQ_SELECT</i>	Select south pci request on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_PCI_OWN_SELECT</i>	Select south pci own on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SOUTH_BUS_WRITE_SELECT</i>	Select south pci write on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_GRANT_SELECT</i>	Select north NPEC grant on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_XFER_SELECT</i>	Select north NPEC transfer on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_RETRY_SELECT</i>	Select north NPEC retry on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_REQ_SELECT</i>	Select north NPEC request on PEC6.

<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_OWN_SELECT</i>	Select north NPEC own on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEB_WRITE_SELECT</i>	Select north NPEB write on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_NORTH_NPEC_READ_SELECT</i>	Select north NPEC read on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_5_HIT_SELECT</i>	Select sdram5 hit on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_6_HIT_SELECT</i>	Select sdram6 hit on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_7_HIT_SELECT</i>	Select sdram7 hit on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_0_HIT_SELECT</i>	Select sdram0 hit on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_1_MISS_SELECT</i>	Select sdram1 miss on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_2_MISS_SELECT</i>	Select sdram2 miss on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_3_MISS_SELECT</i>	Select sdram3 miss on PEC6.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC6_SDR_4_MISS_SELECT</i>	Select sdram4 miss on PEC6.

Definition at line **373** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccBusPmuEventCounters7
```

Type of bus pmu events supported on PEC 7.

Lists all bus pmu events.

Enumeration values:

<i>IX_PERFPROF_ACC_BUS_PMU_PEC7_SOUTH_APB_RETRY_SELECT</i>	Select south apb retry on PEC7.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC7_SOUTH_APB_REQ_SELECT</i>	Select south apb request on PEC7.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC7_SOUTH_APB_OWN_SELECT</i>	Select south apb own on PEC7.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC7_SOUTH_BUS_READ_SELECT</i>	Select south bus read on PEC7.
<i>IX_PERFPROF_ACC_BUS_PMU_PEC7_CYCLE_COUNT_SELECT</i>	Select cycle count on PEC7.

Definition at line **410** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccBusPmuMode
```

State selection of counters.

These states will be used to determine the counters whose values are to be read.

Enumeration values:

IX_PERFPROF_ACC_BUS_PMU_MODE_HALT halt state
IX_PERFPROF_ACC_BUS_PMU_MODE_SOUTH south state
IX_PERFPROF_ACC_BUS_PMU_MODE_NORTH north state
IX_PERFPROF_ACC_BUS_PMU_MODE_SDRAM SDRAM state.

Definition at line **532** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccStatus
```

Invalid Status Definitions.

These status will be used by the APIs to return to the user.

Enumeration values:

<i>IX_PERFPROF_ACC_STATUS_SUCCESS</i>	success
<i>IX_PERFPROF_ACC_STATUS_FAIL</i>	fail
<i>IX_PERFPROF_ACC_STATUS_ANOTHER_UTIL_IN_PROGRESS</i>	another utility in progress
<i>IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_IN_PROGRESS</i>	measurement in progress
<i>IX_PERFPROF_ACC_STATUS_XCYCLE_NO_BASELINE</i>	no baseline yet
<i>IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_REQUEST_OUT_OF_RANGE</i>	Measurement chosen is out of range.
<i>IX_PERFPROF_ACC_STATUS_XCYCLE_PRIORITY_SET_FAIL</i>	Cannot set task priority.
<i>IX_PERFPROF_ACC_STATUS_XCYCLE_THREAD_CREATE_FAIL</i>	Fail create thread.
<i>IX_PERFPROF_ACC_STATUS_XCYCLE_PRIORITY_RESTORE_FAIL</i>	cannot restore priority
<i>IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_NOT_RUNNING</i>	xcycle not running
<i>IX_PERFPROF_ACC_STATUS_XSCALE_PMU_NUM_INVALID</i>	invalid number entered
<i>IX_PERFPROF_ACC_STATUS_XSCALE_PMU_EVENT_INVALID</i>	invalid pmu event
<i>IX_PERFPROF_ACC_STATUS_XSCALE_PMU_START_NOT_CALLED</i>	a start process was not called before attempting a stop or results

<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_MODE_ERROR</i>	get invalid mode
<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC1_ERROR</i>	invalid pec1 entered
<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC2_ERROR</i>	invalid pec2 entered
<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC3_ERROR</i>	invalid pec3 entered
<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC4_ERROR</i>	invalid pec4 entered
<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC5_ERROR</i>	invalid pec5 entered
<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC6_ERROR</i>	invalid pec6 entered
<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC7_ERROR</i>	invalid pec7 entered
<i>IX_PERFPROF_ACC_STATUS_BUS_PMU_START_NOT_CALLED</i>	a start process was not called before attempting a stop
<i>IX_PERFPROF_ACC_STATUS_COMPONENT_NOT_SUPPORTED</i>	Device or OS does not support component.

Definition at line **469** of file **IxPerfProfAcc.h**.

```
enum IxPerfProfAccXscalePmuEvent
```

Type of Intel XScale (R) Processor PMU events supported.

Lists all Intel XScale (R) Processor PMU events. The maximum is a default value that the user should not exceed.

Enumeration values:

<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_CACHE_MISS</i>	cache miss
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_CACHE_INSTRUCTION</i>	cache instruction
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_STALL</i>	event stall
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_INST_TLB_MISS</i>	instruction tlb miss
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_DATA_TLB_MISS</i>	data tlb miss
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_BRANCH_EXEC</i>	branch executed
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_BRANCH_MISPREDICT</i>	branch mispredict
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_INST_EXEC</i>	instruction executed
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_FULL_EVERYCYCLE</i>	Stall – data cache buffers are full.

<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_ONCE</i>	This event occurs every cycle where condition present Stall – data cache buffers are full. This event occurs once for each contiguous sequence.
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_DATA_CACHE_ACCESS</i>	data cache access
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_DATA_CACHE_MISS</i>	data cache miss
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_DATA_CACHE_WRITEBACK</i>	data cache writeback
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_SW_CHANGE_PC</i>	sw change pc
<i>IX_PERFPROF_ACC_XSCALE_PMU_EVENT_MAX</i>	max value

Definition at line **429** of file **IxPerfProfAcc.h**.

Function Documentation

```
ixPerfProfAccBusPmuPMSRGet ( UINT32 * pmsrValue )
```

Get values of PMSR.

This API gets the Previous Master Slave Register value and returns it to the calling function. This value indicates which master or slave accessed the north, south bus or sdram last. The value returned by this function is a 32 bit value and is read from location of an offset 0x0024 of the base value.

The PMSR value returned indicate the following:

```
*****
* Bit      * Name      * Description                                     *
*          *          *          *
*****
* [31:18]  *Reserved*
*****
* [17:12]  * PSS      * Indicates which of the slaves on
*          *          * ARBS was previously
*          *          * accessed by the AHBS.
*          *          * [000001] Expansion Bus
*          *          * [000010] SDRAM Controller
*          *          * [000100] PCI
*          *          * [001000] Queue Manager
*          *          * [010000] AHB-APB Bridge
*          *          * [100000] Reserved
*****
* [11:8]   * PSN      * Indicates which of the Slaves on
*          *          * ARBN was previously
*          *          * accessed the AHBN.
*          *          * [0001] SDRAM Controller
*          *          * [0010] AHB-AHB Bridge
*****
```

```

*          *          * [0100] Reserved                      *
*          *          * [1000] Reserved                      *
*****
* [7:4]   *   PMS    * Indicates which of the Masters on    *
*          *          * ARBS was previously                  *
*          *          * accessing the AHBS.                  *
*          *          * [0001] Gasket                        *
*          *          * [0010] AHB-AHB Bridge                *
*          *          * [0100] PCI                            *
*          *          * [1000] APB                            *
*****
* [3:0]   *   PMN    * Indicates which of the Masters on    *
*          *          * ARBN was previously                  *
*          *          * accessing the AHBN.                  *
*          *          * [0001] NPEA                          *
*          *          * [0010] NPEB                          *
*          *          * [0100] NPEC                          *
*          *          * [1000] Reserved                      *
*****

```

Parameters:

**psmrValue* UINT32 [out] – Pointer to return PMSR value. Users need to allocate storage for psmrValue.

Returns:

none

- Reentrant : no
- ISR Callable : no

ixPerfProfAccBusPmuResultsGet (*IxPerfProfAccBusPmuResults* * *BusPmuResults*)

Gets values of all counters.

This function is responsible for getting all the counter values from the lower API and putting it into an array for the user.

Parameters:

busPmuResults* **IxPerfProfAccBusPmuResults [out]
 ◇ Pointer to a structure of arrays to store all counter values.

Returns:

none

- Reentrant : no
- ISR Callable : no

```

ixPerfProfAccBusPmuStart ( IxPerfProfAccBusPmuMode mode,
IxPerfProfAccBusPmuEventCounters1 pecEvent1,
IxPerfProfAccBusPmuEventCounters2 pecEvent2,
IxPerfProfAccBusPmuEventCounters3 pecEvent3,
IxPerfProfAccBusPmuEventCounters4 pecEvent4,
IxPerfProfAccBusPmuEventCounters5 pecEvent5,
IxPerfProfAccBusPmuEventCounters6 pecEvent6,
IxPerfProfAccBusPmuEventCounters7 pecEvent7
)

```

Initializes all the counters and selects events to be monitored.

Function initializes all the counters and assigns the events associated with the counters. Users send in the mode and events they want to count. This API verifies if the combination chosen is appropriate and sets all the registers accordingly. Selecting HALT mode will result in an error. User should use **ixPerfProfAccBusPmuStop()** to HALT.

Parameters:

mode [in] – Mode selection.
pecEvent1 **IxPerfProfAccBusPmuEventCounters1** [in] – Event for PEC1.
pecEvent2 **IxPerfProfAccBusPmuEventCounters2** [in] – Event for PEC2.
pecEvent3 **IxPerfProfAccBusPmuEventCounters3** [in] – Event for PEC3.
pecEvent4 **IxPerfProfAccBusPmuEventCounters4** [in] – Event for PEC4.
pecEvent5 **IxPerfProfAccBusPmuEventCounters5** [in] – Event for PEC5.
pecEvent6 **IxPerfProfAccBusPmuEventCounters6** [in] – Event for PEC6.
pecEvent7 **IxPerfProfAccBusPmuEventCounters7** [in] – Event for PEC7.

Returns:

- ◇ IX_PERFPROF_ACC_STATUS_SUCCESS – Initialization executed successfully.
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_MODE_ERROR – Error in selection of mode. Only NORTH, SOUTH and SDRAM modes are allowed.
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC1_ERROR – Error in selection of event for PEC1
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC2_ERROR – Error in selection of event for PEC2
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC3_ERROR – Error in selection of event for PEC3
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC4_ERROR – Error in selection of event for PEC4
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC5_ERROR – Error in selection of event for PEC5
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC6_ERROR – Error in selection of event for PEC6
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_PEC7_ERROR – Error in selection of event for PEC7
- ◇ IX_PERFPROF_ACC_STATUS_ANOTHER_UTIL_IN_PROGRESS – another utility is running
- ◇ IX_PERFPROF_ACC_STATUS_FAIL – Failed to start because interrupt service routine fails to bind.

- Reentrant : no
- ISR Callable : no

ixPerfProfAccBusPmuStop (void)

Stops all counters.

This function stops all the PECs by setting the halt bit in the ESR.

Returns:

- ◇ IX_PERFPROF_ACC_STATUS_SUCCESS – Counters successfully halted.
- ◇ IX_PERFPROF_ACC_STATUS_FAIL – Counters could'nt be halted.
- ◇ IX_PERFPROF_ACC_STATUS_BUS_PMU_START_NOT_CALLED – the **ixPerfProfAccBusPmuStart()** function is not called.

- Reentrant : no
- ISR Callable : no

ixPerfProfAccXcycleBaselineRun (UINT32 * numBaselineCycle)

Perform baseline for Xcycle.

Parameters:

- *numBaselineCycle UINT32 [out] – pointer to baseline value after calibration. Calling function are responsible for allocating memory space for this pointer.

Global Data :

- None.

This function MUST be run before the Xcycle tool can be used. This function must be run immediately when the OS boots up with no other addition programs running. Addition note : This API will measure the time needed to perform a fix amount of CPU instructions (~ 1 second worth of loops) as a highest priority task and with interrupt disabled. The time measured is known as the baseline – interpreted as the shortest time needed to complete the amount of CPU instructions. The baseline is returned as unit of time in 66Mhz clock tick.

Returns:

- ◇ IX_PERFPROF_ACC_STATUS_SUCCESS – successful run, result is returned
- ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_PRIORITY_SET_FAIL – failed to change task priority
- ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_PRIORITY_RESTORE_FAIL – failed to restore task priority
- ◇ IX_PERFPROF_ACC_STATUS_ANOTHER_UTIL_IN_PROGRESS – another utility is running
- ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_IN_PROGRESS – Xcycle tool has already started

- Reentrant : no
- ISR Callable : no

ixPerfProfAccXcycleInProgress (void)

Check if Xcycle is running.

Parameters:

None Global Data :
 ◇ None.

Check if Xcycle measuring task is running.

Returns:

◇ TRUE – Xcycle is running
 ◇ FALSE – Xcycle is not running

- Reentrant : no
- ISR Callable : no

ixPerfProfAccXcycleResultsGet (**IxPerfProfAccXcycleResults * *xcycleResult*)**

Get the results of Xcycle measurement.

Parameters:

xcycleResult* **IxPerfProfAccXcycleResults [out] – Pointer to results of last measurements.
 Calling function are responsible for allocating memory space for this pointer.

Global Data :

- None.

Retrieve the results of last measurement. User should use **ixPerfProfAccXcycleInProgress()** to check if measurement is completed before getting the results.

Returns:

◇ IX_PERFPROF_ACC_STATUS_SUCCESS – successful
 ◇ IX_PERFPROF_ACC_STATUS_FAIL – result is not complete.
 ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_NO_BASELINE – baseline is performed
 ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_IN_PROGRESS – Xcycle tool is still running

- Reentrant : no
- ISR Callable : no

ixPerfProfAccXcycleStart (UINT32 *numMeasurementsRequested*)

Start the measurement.

Parameters:

numMeasurementsRequested UINT32 [in] – number of measurements to perform. Value can be 0 to IX_PERFPROF_ACC_XCYCLE_MAX_NUM_OF_MEASUREMENTS. 0 indicate continuous measurement.

Global Data :

- None.

Start the measurements immediately. *numMeasurementsRequested* specifies number of measurements to run. If *numMeasurementsRequested* is set to 0, the measurement will be performed continuously until *IxPerfProfAccXcycleStop()* is called. It is estimated that 1 measurement takes approximately 1 second during low CPU utilization, therefore 128 measurement takes approximately 128 sec. When CPU utilization is high, the measurement will take longer. This function spawn a task the perform the measurement and returns. The measurement may continue even if this function returns.

IMPORTANT: Under heavy CPU utilization, the task spawn by this function may starve and fail to respond to stop command. User may need to kill the task manually in this case.

There are only IX_PERFPROF_ACC_XCYCLE_MAX_NUM_OF_MEASUREMENTS storage available so storing is wrapped around if measurements are more than IX_PERFPROF_ACC_XCYCLE_MAX_NUM_OF_MEASUREMENTS.

Returns:

- ◇ IX_PERFPROF_ACC_STATUS_SUCCESS – successful start, a thread is created in the background to perform measurement.
- ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_PRIORITY_SET_FAIL – failed to set task priority
- ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_THREAD_CREATE_FAIL – failed to create thread to perform measurement.
- ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_NO_BASELINE – baseline is not available
- ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_REQUEST_OUT_OF_RANGE – value is larger than IX_PERFPROF_ACC_XCYCLE_MAX_NUM_OF_MEASUREMENTS
- ◇ IX_PERFPROF_ACC_STATUS_XCYCLE_MEASUREMENT_IN_PROGRESS – Xcycle tool has already started
- ◇ IX_PERFPROF_ACC_STATUS_ANOTHER_UTIL_IN_PROGRESS – another utility is running

- Reentrant : no
- ISR Callable : no

```
ixPerfProfAccXcycleStop ( void )
```

Stop the Xcycle measurement.

Parameters:

None Global Data :
◇ None.

Stop Xcycle measurements immediately. If the measurements have stopped or not started, return `IX_PERFPROF_STATUS_XCYCLE_MEASUREMENT_NOT_RUNNING`. Note: This function does not stop measurement cold. The measurement thread may need a few seconds to complete the last measurement. User needs to use `ixPerfProfAccXcycleInProgress()` to determine if measurement is indeed completed.

Returns:

- ◇ `IX_PERFPROF_ACC_STATUS_SUCCESS` – successful measurement is stopped
- ◇ `IX_PERFPROF_STATUS_XCYCLE_MEASUREMENT_NOT_RUNNING` – no measurement running

- Reentrant : no
- ISR Callable : no

```
ixPerfProfAccXscalePmuEventCountStart ( BOOL          clkCntDiv,
                                         UINT32       numEvents,
                                         IxPerfProfAccXscalePmuEvent pmuEvent1,
                                         IxPerfProfAccXscalePmuEvent pmuEvent2,
                                         IxPerfProfAccXscalePmuEvent pmuEvent3,
                                         IxPerfProfAccXscalePmuEvent pmuEvent4
                                         )
```

This API will start the clock and event counting.

Parameters:

- clkCntDiv* **BOOL** [in] – enables/disables the clock divider. When true, the divider is enabled and the clock count will be incremented by one at each 64th processor clock cycle. When false, the divider is disabled and the clock count will be incremented at every processor clock cycle.
- numEvents* **UINT32** [in] – the number of PMU events that are to be monitored as specified by the user. For clock counting only, this is set to zero.
- pmuEvent1* **IxPerfProfAccXscalePmuEvent** [in] – the specific PMU event to be monitored by counter 1
- pmuEvent2* **IxPerfProfAccXscalePmuEvent** [in] – the specific PMU event to be monitored by counter 2
- pmuEvent3* **IxPerfProfAccXscalePmuEvent** [in] – the specific PMU event to be monitored by counter 3
- pmuEvent4* **IxPerfProfAccXscalePmuEvent** [in] – the specific PMU event to be monitored by counter 4

This API will start the clock and Intel XScale (R) Processor PMU event counting. Up to 4 events can be monitored simultaneously. This API has to be called before `ixPerfProfAccXscalePmuEventCountStop` can be called.

Returns:

- ◇ IX_PERFPROF_ACC_STATUS_SUCCESS if clock and events counting are started successfully
- ◇ IX_PERFPROF_ACC_STATUS_FAIL if unable to start the counting
- ◇ IX_PERFPROF_ACC_STATUS_XSCALE_PMU_NUM_INVALID if the number of events specified is out of the valid range
- ◇ IX_PERFPROF_ACC_STATUS_XSCALE_PMU_EVENT_INVALID if the value of the PMU event specified does not exist
- ◇ IX_PERFPROF_ACC_STATUS_ANOTHER_UTIL_IN_PROGRESS – another utility is running

- Reentrant : no
- ISR Callable : no

```
ixPerfProfAccXscalePmuEventCountStop ( IxPerfProfAccXscalePmuResults * eventCountStopResults )
```

This API will stop the clock and event counting.

Parameters:

eventCountStopResults* **IxPerfProfAccXscalePmuResults [out] – pointer to struct containing results of counters and their overflow. It is the users's responsibility to allocate the memory for this pointer.

This API will stop the clock and Intel XScale (R) Processor PMU events that are being counted. The results of the clock and events count will be stored in the pointer allocated by the user. It can only be called once IxPerfProfAccEventCountStart has been called.

Returns:

- ◇ IX_PERFPROF_ACC_STATUS_SUCCESS if clock and events counting are stopped successfully
- ◇ IX_PERFPROF_ACC_STATUS_XSCALE_PMU_START_NOT_CALLED if ixPerfProfAccXscalePmuEventCountStart is not called first.

- Reentrant : no
- ISR Callable : no

```
ixPerfProfAccXscalePmuEventSampStart ( UINT32 numEvents,
                                         IxPerfProfAccXscalePmuEvent pmuEvent1,
                                         UINT32 eventRate1,
                                         IxPerfProfAccXscalePmuEvent pmuEvent2,
                                         UINT32 eventRate2,
                                         IxPerfProfAccXscalePmuEvent pmuEvent3,
                                         UINT32 eventRate3,
                                         IxPerfProfAccXscalePmuEvent pmuEvent4,
                                         UINT32 eventRate4
                                         )
```

Starts the event based sampling.

Parameters:

- numEvents* UINT32 [in] – the number of PMU events that are to be monitored as specified by the user. The value should be between 1–4 events at a time.
- pmuEvent1* **IXPerfProfAccXscalePmuEvent** [in] – the specific PMU event to be monitored by counter 1
- eventRate1* UINT32 [in] – sampling rate of counter 1. The rate is the number of events before a sample taken. If 0 is specified, the full counter value (0xFFFFFFFF) is used. The rate must not be greater than the full counter value.
- pmuEvent2* **IXPerfProfAccXscalePmuEvent** [in] – the specific PMU event to be monitored by counter 2
- eventRate2* UINT32 [in] – sampling rate of counter 2. The rate is the number of events before a sample taken. If 0 is specified, the full counter value (0xFFFFFFFF) is used. The rate must not be greater than the full counter value.
- pmuEvent3* **IXPerfProfAccXscalePmuEvent** [in] – the specific PMU event to be monitored by counter 3
- eventRate3* UINT32 [in] – sampling rate of counter 3. The rate is the number of events before a sample taken. If 0 is specified, the full counter value (0xFFFFFFFF) is used. The rate must not be greater than the full counter value.
- pmuEvent4* **IXPerfProfAccXscalePmuEvent** [in] – the specific PMU event to be monitored by counter 4
- eventRate4* UINT32 [in] – sampling rate of counter 4. The rate is the number of events before a sample taken. If 0 is specified, the full counter value (0xFFFFFFFF) is used. The rate must not be greater than the full counter value.

Starts the event based sampling to determine the frequency with which events are being executed. The sampling rate is the number of events, as specified by the user, before a counter overflow interrupt is generated. A sample is taken at each counter overflow interrupt. At each sample, the value of the program counter determines the corresponding location in the code. Each of these occurrences are recorded to determine the frequency with which the Xscale code in each event is executed. This API has to be called before ixPerfProfAccXscalePmuEventSampStop can be called.

Returns:

- ◇ IX_PERFPROF_ACC_STATUS_SUCCESS if event based sampling is started successfully
 - ◇ IX_PERFPROF_ACC_STATUS_FAIL if unable to start the sampling
 - ◇ IX_PERFPROF_ACC_STATUS_XSCALE_PMU_NUM_INVALID if the number of events specified is out of the valid range
 - ◇ IX_PERFPROF_ACC_STATUS_XSCALE_PMU_EVENT_INVALID if the value of the PMU event specified does not exist
 - IX_PERFPROF_ACC_STATUS_ANOTHER_UTIL_IN_PROGRESS – another utility is running
- Reentrant : no
 - ISR Callable : no

```
ixPerfProfAccXscalePmuEventSampStop ( IxPerfProfAccXscalePmuSamplePcProfile * eventProfile1,
IxPerfProfAccXscalePmuSamplePcProfile * eventProfile2,
IxPerfProfAccXscalePmuSamplePcProfile * eventProfile3,
IxPerfProfAccXscalePmuSamplePcProfile * eventProfile4
)
```

Stops the event based sampling.

Parameters:

- *eventProfile1* **IxPerfProfAccXscalePmuSamplePcProfile** [out] – pointer to the array of profiles for each program counter value; the user should set the size of the array to IX_PERFPROF_ACC_XSCALE_PMU_MAX_PROFILE_SAMPLES. It is the users's responsibility to allocate memory for this pointer.
- *eventProfile2* **IxPerfProfAccXscalePmuSamplePcProfile** [out] – pointer to the array of profiles for each program counter value; the user should set the size of the array to IX_PERFPROF_ACC_XSCALE_PMU_MAX_PROFILE_SAMPLES. It is the users's responsibility to allocate memory for this pointer.
- *eventProfile3* **IxPerfProfAccXscalePmuSamplePcProfile** [out] – pointer to the array of profiles for each program counter value; the user should set the size of the array to IX_PERFPROF_ACC_XSCALE_PMU_MAX_PROFILE_SAMPLES. It is the users's responsibility to allocate memory for this pointer.
- *eventProfile4* **IxPerfProfAccXscalePmuSamplePcProfile** [out] – pointer to the array of profiles for each program counter value; the user should set the size of the array to IX_PERFPROF_ACC_XSCALE_PMU_MAX_PROFILE_SAMPLES. It is the users's responsibility to allocate memory for this pointer.

This API stops the event based sampling. The results are stored in the pointers allocated by the user. It can only be called once ixPerfProfAccEventSampStart has been called.

Returns:

- ◇ IX_PERFPROF_ACC_STATUS_SUCCESS if event based sampling is stopped successfully
- ◇ IX_PERFPROF_ACC_STATUS_XSCALE_PMU_START_NOT_CALLED if ixPerfProfAccEventSampStart not called first.

- Reentrant : no
- ISR Callable : no

```
ixPerfProfAccXscalePmuResultsGet ( IxPerfProfAccXscalePmuResults * results )
```

Reads the current value of the counters and their overflow.

Parameters:

- *results* **IxPerfProfAccXscalePmuResults** [out] – pointer to the results struct. It is the user's responsibility to allocate memory for this pointer

This API reads the value of all four event counters and the clock counter, and the associated overflows. It does not give results associated with sampling, i.e. PC and their frequencies. This API can be called at any time once a process has been started. If it is called before a process has started the user should be aware that

the values it contains are default values and might be meaningless. The values of the counters are stored in the pointer allocated by the client.

Returns:

– none

- Reentrant : no
- ISR Callable : no

```
ixPerfProfAccXscalePmuTimeSampStart ( UINT32 samplingRate,  
                                       BOOL   clkCntDiv  
                                       )
```

Starts the time based sampling.

Parameters:

samplingRate UINT32 [in] – sampling rate is the number of clock counts before a counter overflow interrupt is generated, at which, a sample is taken; the rate specified cannot be greater than the counter size of 32bits or set to zero.

clkCntDiv BOOL [in] – enables/disables the clock divider. When true, the divider is enabled and the clock count will be incremented by one at each 64th processor clock cycle. When false, the divider is disabled and the clock count will be incremented at every processor clock cycle.

This API starts the time based sampling to determine the frequency with which lines of code are being executed. Sampling is done at the rate specified by the user. At each sample, the value of the program counter is determined. Each of these occurrences are recorded to determine the frequency with which the Xscale code is being executed. This API has to be called before ixPerfProfAccXscalePmuTimeSampStop can be called.

Returns:

◇ IX_PERFPROF_ACC_STATUS_SUCCESS if time based sampling is started successfully
◇ IX_PERFPROF_ACC_STATUS_FAIL if unable to start the sampling
◇ IX_PERFPROF_ACC_STATUS_ANOTHER_UTIL_IN_PROGRESS – another utility is running

- Reentrant : no
- ISR Callable : no

```
ixPerfProfAccXscalePmuTimeSampStop ( IxPerfProfAccXscalePmuEvtCnt * clkCount,  
                                     IxPerfProfAccXscalePmuSamplePcProfile * timeProfile  
                                     )
```

Stops the time based sampling.

Parameters:

clkCount* **IxPerfProfAccXscalePmuEvtCnt [out] – pointer to the struct containing the final clock count and its overflow. It is the user's responsibility to allocate the memory for

this pointer.

timeProfile* **IxPerfProfAccXscalePmuSamplePcProfile [out] – pointer to the array of profiles for each program counter value; the user should set the size of the array to **IX_PERFPROF_ACC_XSCALE_PMU_MAX_PROFILE_SAMPLES**. It is the user's responsibility to allocate the memory for this pointer.

This API stops the time based sampling. The results are stored in the pointers allocated by the user. It can only be called once **ixPerfProfAccXscalePmuTimeSampStart** has been called.

Returns:

- ◇ **IX_PERFPROF_ACC_STATUS_SUCCESS** if time based sampling is stopped successfully
- ◇ **IX_PERFPROF_ACC_STATUS_XSCALE_PMU_START_NOT_CALLED** if **ixPerfProfAccXscalePmuTimeSampStart** not called first

- Reentrant : no
- ISR Callable : no

IXP Queue Manager (qmgr) Public API

The public API for the IXP qmgr component.

Defines

```
#define IX_QMGR_QUELOW_GROUP  
    Backward compatability for QMgr queue group select identifier,  
    IX_QMGR_QUELOW_GROUP.  
  
#define IX_QMGR_QUEUPP_GROUP  
    Backward compatability for QMgr queue group select identifier,  
    IX_QMGR_QUEUPP_GROUP.
```

Typedefs

```
typedef void(* IxQMgrDispatcherFuncPtr )(IxQMgrDispatchGroup group)  
    QMgr Dispatcher Loop function pointer.
```

Enumerations

```
enum IxQMgrDispatcherState {  
    IX_QMGR_DISPATCHER_LOOP_FREE,  
    IX_QMGR_DISPATCHER_LOOP_BUSY  
}  
    Queue dispatcher State.  
  
enum IxQMgrDispatchGroup {  
    IX_QMGR_GROUP_Q0_TO_Q31,  
    IX_QMGR_GROUP_Q32_TO_Q63,  
    IX_QMGR_GROUP_MAX  
}  
    QMgr queue group select identifiers.
```

Functions

```
PUBLIC IX_STATUS ixQMgrInit (void)  
    Initialise the QMgr.  
  
PUBLIC IX_STATUS ixQMgrUnload (void)  
    Uninitialise the QMgr.  
  
PUBLIC void ixQMgrShow (void)
```

Describe queue configuration and statistics for active queues.

PUBLIC void **ixQMgrDispatcherLoopGet** (**IxQMgrDispatcherFuncPtr**
*qDispatcherFuncPtr)
Get QMgr DispatcherLoopRun for respective silicon device.

PUBLIC void **ixQMgrDispatcherLoopEnable** (void)
Enables the Queue Manager Dispatcher.

PUBLIC void **ixQMgrDispatcherLoopDisable** (void)
Disables the Queue Manager Dispatcher.

PUBLIC
IxQMgrDispatcherState ixQMgrDispatcherLoopStatusGet (void)
Gets the Queue dispatcher Loop status.

PUBLIC void **ixQMgrDispatcherInterruptModeSet** (BOOL mode)
Notifies the ixQMgr that the Dispatcher is in Interrupt mode.

Detailed Description

The public API for the IXP qmgr component.

IxQMgr is a low level public interface to the Queue Manager

Define Documentation

```
#define IX_QMGR_QUELOW_GROUP
```

Backward compatability for QMgr queue group select identifier, IX_QMGR_QUELOW_GROUP.

This #define provides backward compatability for the IX_QMGR_QUELOW_GROUP, which has been replaced by IX_QMGR_GROUP_Q0_TO_Q31.

This #define has been DEPRECATED and will be removed in a future release.

Definition at line **88** of file **IxQMgr.h**.

```
#define IX_QMGR_QUEUPP_GROUP
```

Backward compatability for QMgr queue group select identifier, IX_QMGR_QUEUPP_GROUP.

This #define provides backward compatability for the IX_QMGR_QUEUPP_GROUP, which has been replaced by IX_QMGR_GROUP_Q32_TO_Q63.

This #define has been DEPRECATED and will be removed in a future release.

Definition at line **104** of file **IxQMgr.h**.

Typedef Documentation

IxQMgrDispatcherFuncPtr

QMgr Dispatcher Loop function pointer.

This defines the interface for QMgr Dispatcher functions.

Parameters:

group **IxQMgrDispatchGroup** [in] – the group of the queue of which the dispatcher will run

Definition at line **118** of file **IxQMgr.h**.

Enumeration Type Documentation

enum IxQMgrDispatcherState

Queue dispatcher State.

Indicates the Queue dispatcher state busy or free.

Definition at line **47** of file **IxQMgr.h**.

enum IxQMgrDispatchGroup

QMgr queue group select identifiers.

This enum defines the groups into which the queues are divided. Each group contains 32 queues. Each qmgr interface function that works on a group of queues takes one of these identifiers as a parameter.

Enumeration values:

IX_QMGR_GROUP_Q0_TO_Q31 Queues 0–31.

IX_QMGR_GROUP_Q32_TO_Q63 Queues 32–63.

Definition at line **63** of file **IxQMgr.h**.

Function Documentation

```
void ixQMgrDispatcherInterruptModeSet ( BOOL mode )
```

Notifies the ixQMgr that the Dispatcher is in Interrupt mode.

Note:

This function records whether the Queue Dispatcher is bind to the QM Interrupt notification IRQ.

Parameters:

BOOL mode [in] – TRUE – dispatcher mode is bind to Queue Manager IRQ for queue notifications (0–63). FALSE – dispatcher is in poll mode.

Returns:

None

```
ixQMgrDispatcherLoopDisable ( void )
```

Disables the Queue Manager Dispatcher.

Note:

API used by the ixErrHdlAcc to disable the queue manager dispatcher to prevent QM Read/Write access.

Returns:

None

```
ixQMgrDispatcherLoopEnable ( void )
```

Enables the Queue Manager Dispatcher.

Note:

API used by the ixErrHdlAcc to re-enable the queue manager dispatcher.

Returns:

None

```
ixQMgrDispatcherLoopGet ( IxQMgrDispatcherFuncPtr * qDispatcherFuncPtr )
```

Get QMgr DispatcherLoopRun for respective silicon device.

```
IxQMgrDispatcherState ixQMgrDispatcherLoopStatusGet ( void )
```

Gets the Queue dispatcher Loop status.

Returns:

Returns an enum that indicates the dispatcher state (RUN or STOP)

```
ixQMgrInit ( void )
```

Initialise the QMgr.

This function must be called before any other QMgr function. It sets up internal data structures.

Returns:

◇ IX_SUCCESS, the IxQMgr successfully initialised

◇ IX_FAIL, failed to initialize the Qmgr

```
ixQMgrShow ( void )
```

Describe queue configuration and statistics for active queues.

This function shows active queues, their configurations and statistics.

Returns:

◇ void

```
ixQMgrUnload ( void )
```

Uninitialise the QMgr.

This function will perform the tasks required to unload the QMgr component cleanly. This includes unmapping kernel memory and unconfigures the access layer component's queue configuration.

This should be called before a soft reboot or unloading of a kernel module.

Precondition:

It should only be called if **ixQMgrInit** has already been called.

Postcondition:

No QMgr functions should be called until ixQMgrInit is called again.

Returns:

◇ IX_SUCCESS, the IxQMgr successfully uninitialised

◇ IX_FAIL, failed to uninitialize the Qmgr

Intel (R) IXP400 Software Queue Assignments

Queue Assignments used by Ethernet, HSS, ATM and DMA access libraries. Ethernet QoS traffic class definitions are mapped by EthDB in **IxEthDBQoS.h**.

Defines

```
#define IX_NPE_MPHYMULTIPORT
    Global compiler switch to select between 3 possible NPE Modes Define this macro to enable MPHY mode.

#define IX_NPE_A_TXDONE_QUEUE_HIGHWATERMARK
    The NPE reserves the High Watermark for its operation. But it must be set by the Xscale.

#define IX_NPE_A_QMQ_ATM_TX_DONE
    Queue ID for ATM Transmit Done queue.

#define IX_NPE_A_QMQ_ATM_TX0
    Queue ID for ATM transmit Queue in a single phy configuration.

#define IX_NPE_A_QMQ_ATM_TXID_MIN
    Queue Manager Queue ID for ATM transmit Queue with minimum number of queue.

#define IX_NPE_A_QMQ_ATM_TXID_MAX
    Queue Manager Queue ID for ATM transmit Queue with maximum number of queue.

#define IX_NPE_A_QMQ_ATM_RX_HI
    Queue Manager Queue ID for ATM Receive high Queue.

#define IX_NPE_A_QMQ_ATM_RX_LO
    Queue Manager Queue ID for ATM Receive low Queue.

#define IX_NPE_A_QMQ_ATM_TX1
    Queue ID for ATM transmit Queue Multiply from 1 to 11.

#define IX_NPE_A_QMQ_ATM_FREE_VC0
    Hardware QMgr Queue ID for ATM Free VC Queue.

#define IX_NPE_A_QMQ_ATM_RXFREE_MIN
    The minimum queue ID for FreeVC queue.

#define IX_NPE_A_QMQ_OAM_FREE_VC
    OAM Rx Free queue ID.

#define IX_NPE_A_QMQ_HSS0_CHL_RX_TRIG
    Hardware QMgr Queue ID for HSS Port 0 Channelized Receive trigger.

#define IX_NPE_A_QMQ_HSS0_PKT_RX
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive.

#define IX_NPE_A_QMQ_HSS0_PKT_TX0

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit queue 0.

#define IX_NPE_A_QMQ_HSS0_PKT_TX1

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit queue 1.

#define IX_NPE_A_QMQ_HSS0_PKT_TX2

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit queue 2.

#define IX_NPE_A_QMQ_HSS0_PKT_TX3

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit queue 3.

#define IX_NPE_A_QMQ_HSS0_PKT_RX_FREE0

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive Free queue 0.

#define IX_NPE_A_QMQ_HSS0_PKT_RX_FREE1

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive Free queue 1.

#define IX_NPE_A_QMQ_HSS0_PKT_RX_FREE2

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive Free queue 2.

#define IX_NPE_A_QMQ_HSS0_PKT_RX_FREE3

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive Free queue 3.

#define IX_NPE_A_QMQ_HSS0_PKT_TX_DONE

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit Done queue.

#define IX_NPE_A_QMQ_HSS1_CHL_RX_TRIG

Hardware QMgr Queue ID for HSS Port 1 Channelized Receive trigger.

#define IX_NPE_A_QMQ_HSS1_PKT_RX

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive.

#define IX_NPE_A_QMQ_HSS1_PKT_TX0

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit queue 0.

#define IX_NPE_A_QMQ_HSS1_PKT_TX1

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit queue 1.

#define IX_NPE_A_QMQ_HSS1_PKT_TX2

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit queue 2.

#define IX_NPE_A_QMQ_HSS1_PKT_TX3

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit queue 3.

#define IX_NPE_A_QMQ_HSS1_PKT_RX_FREE0

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive Free queue 0.

#define IX_NPE_A_QMQ_HSS1_PKT_RX_FREE1

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive Free queue 1.

#define IX_NPE_A_QMQ_HSS1_PKT_RX_FREE2

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive Free queue 2.

#define IX_NPE_A_QMQ_HSS1_PKT_RX_FREE3

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive Free queue 3.

#define IX_NPE_A_QMQ_HSS1_PKT_TX_DONE

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit Done queue.

#define IX_ETH_ACC_RX_FREE_NPEA_Q

Supply Rx Buffers Ethernet Q for NPEA.

#define IX_ETH_ACC_RX_FREE_NPEB_Q

Supply Rx Buffers Ethernet Q for NPEB (for single port images only).

#define IX_ETH_ACC_RX_FREE_NPEC_Q

Supply Rx Buffers Ethernet Q for NPEC.

#define IX_ETH_ACC_TX_NPEA_Q

Submit frame Q for NPEA.

#define IX_ETH_ACC_TX_NPEB_Q

Submit frame Q for NPEB.

#define IX_ETH_ACC_TX_NPEC_Q

Submit frame Q for NPEC.

#define IX_ETH_ACC_TX_DONE_Q

Transmit complete Q for all NPEs.

Detailed Description

Queue Assignments used by Ethernet, HSS, ATM and DMA access libraries. Ethernet QoS traffic class definitions are mapped by EthDB in **IxEthDBQoS.h**.

Define Documentation

```
#define IX_ETH_ACC_RX_FREE_NPEA_Q
```

Supply Rx Buffers Ethernet Q for NPEA.

Definition at line **582** of file **IxQueueAssignments.h**.


```
#define IX_ETH_ACC_RX_FREE_NPEB_Q
```

Supply Rx Buffers Ethernet Q for NPEB (for single port images only).

Definition at line **593** of file **IxQueueAssignments.h**.

```
#define IX_ETH_ACC_RX_FREE_NPEC_Q
```

Supply Rx Buffers Ethernet Q for NPEC.

Definition at line **604** of file **IxQueueAssignments.h**.

```
#define IX_ETH_ACC_TX_DONE_Q
```

Transmit complete Q for all NPEs.

Definition at line **649** of file **IxQueueAssignments.h**.

```
#define IX_ETH_ACC_TX_NPEA_Q
```

Submit frame Q for NPEA.

Definition at line **615** of file **IxQueueAssignments.h**.

```
#define IX_ETH_ACC_TX_NPEB_Q
```

Submit frame Q for NPEB.

Definition at line **627** of file **IxQueueAssignments.h**.

```
#define IX_ETH_ACC_TX_NPEC_Q
```

Submit frame Q for NPEC.

Definition at line **638** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_FREE_VC0
```

Hardware QMgr Queue ID for ATM Free VC Queue.

There are 32 Hardware QMgr Queue ID; from IX_NPE_A_QMQ_ATM_FREE_VC1 to IX_NPE_A_QMQ_ATM_FREE_VC30

Definition at line **173** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_RX_HI
```

Queue Manager Queue ID for ATM Receive high Queue.

Definition at line **153** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_RX_LO
```

Queue Manager Queue ID for ATM Receive low Queue.

Definition at line **154** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_RXFREE_MIN
```

The minimum queue ID for FreeVC queue.

Definition at line **214** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_TX0
```

Queue ID for ATM transmit Queue in a single phy configuration.

Definition at line **89** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_TX1
```

Queue ID for ATM transmit Queue Multiplier from 1 to 11.

Definition at line **140** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_TX_DONE
```

Queue ID for ATM Transmit Done queue.

Definition at line **79** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_TXID_MAX
```

Queue Manager Queue ID for ATM transmit Queue with maximum number of queue.

Definition at line **152** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_ATM_TXID_MIN
```

Queue Manager Queue ID for ATM transmit Queue with minimum number of queue.

Definition at line **151** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_CHL_RX_TRIG
```

Hardware QMgr Queue ID for HSS Port 0 Channelized Receive trigger.

Definition at line **251** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_RX
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive.

Definition at line **276** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_RX_FREE0
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive Free queue 0.

Definition at line **326** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_RX_FREE1
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive Free queue 1.

Definition at line **336** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_RX_FREE2
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive Free queue 2.

Definition at line **346** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_RX_FREE3
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Receive Free queue 3.

Definition at line **356** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_TX0
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit queue 0.

Definition at line **286** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_TX1
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit queue 1.

Definition at line **296** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_TX2
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit queue 2.

Definition at line **306** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_TX3
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit queue 3.

Definition at line **316** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS0_PKT_TX_DONE
```

Hardware QMgr Queue ID for HSS Port 0 Packetized Transmit Done queue.

Definition at line **366** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_CHL_RX_TRIG
```

Hardware QMgr Queue ID for HSS Port 1 Channelized Receive trigger.

Definition at line **378** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_RX
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive.

Definition at line **388** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_RX_FREE0
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive Free queue 0.

Definition at line **438** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_RX_FREE1
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive Free queue 1.

Definition at line **448** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_RX_FREE2
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive Free queue 2.

Definition at line **458** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_RX_FREE3
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Receive Free queue 3.

Definition at line **468** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_TX0
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit queue 0.

Definition at line **398** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_TX1
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit queue 1.

Definition at line **408** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_TX2
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit queue 2.

Definition at line **418** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_TX3
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit queue 3.

Definition at line **428** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_HSS1_PKT_TX_DONE
```

Hardware QMgr Queue ID for HSS Port 1 Packetized Transmit Done queue.

Definition at line **478** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_QMQ_OAM_FREE_VC
```

OAM Rx Free queue ID.

Definition at line **231** of file **IxQueueAssignments.h**.

```
#define IX_NPE_A_TXDONE_QUEUE_HIGHWATERMARK
```

The NPE reserves the High Watermark for its operation. But it must be set by the Xscale.

Definition at line **69** of file **IxQueueAssignments.h**.

```
#define IX_NPE_MPHYMULTIPOINT
```

Global compiler switch to select between 3 possible NPE Modes Define this macro to enable MPHY mode.

Default(No Switch) = MultiPHY Utopia2 IX_UTOPIAMODE = 1 for single Phy Utopia1
IX_MPHYSINGLEPORT = 1 for single Phy Utopia2

Definition at line **53** of file **IxQueueAssignments.h**.

Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API

Intel (R) IXP400 Software SSP Serial Port Access Public API.

Data Structures

```
struct IxSspAccStatsCounters
    contains counters of the SSP statistics

struct IxSspAccStatsCounters
    contains counters of the SSP statistics

struct IxSspInitVars
    contains all the variables required to initialize the SSP serial port hardware.

struct IxSspInitVars
    contains all the variables required to initialize the SSP serial port hardware.
```

Typedefs

```
typedef void(* RxFIFOOverrunHandler )(void)
    SSP Rx FIFO Overrun handler.

typedef void(* RxFIFOThresholdHandler )(void)
    SSP Rx FIFO Threshold hit or above handler.

typedef void(* TxFIFOThresholdHandler )(void)
    SSP Tx FIFO Threshold hit or below handler.
```

Enumerations

```
enum IxSspAccDataSize {
    DATA_SIZE_TOO_SMALL,
    DATA_SIZE_4,
    DATA_SIZE_5,
    DATA_SIZE_6,
    DATA_SIZE_7,
    DATA_SIZE_8,
    DATA_SIZE_9,
    DATA_SIZE_10,
    DATA_SIZE_11,
    DATA_SIZE_12,
    DATA_SIZE_13,
```

```

    DATA_SIZE_14,
    DATA_SIZE_15,
    DATA_SIZE_16,
    DATA_SIZE_TOO_BIG
}

```

The data sizes in bits that are supported by the protocol.

```

enum IxSspAccPortStatus {
    SSP_PORT_DISABLE,
    SSP_PORT_ENABLE,
    INVALID_SSP_PORT_STATUS
}

```

The status of the SSP port to be set to enable/disable.

```

enum IxSspAccFrameFormat {
    SPI_FORMAT,
    SSP_FORMAT,
    MICROWIRE_FORMAT,
    INVALID_FORMAT
}

```

The frame format that is to be used – SPI, SSP, or Microwire.

```

enum IxSspAccClkSource {
    ON_CHIP_CLK,
    EXTERNAL_CLK,
    INVALID_CLK_SOURCE
}

```

The source to produce the SSP serial clock.

```

enum IxSspAccSpiSclkPhase {
    START_ONE_END_HALF,
    START_HALF_END_ONE,
    INVALID_SPI_PHASE
}

```

The SPI SCLK Phase: 0 – SCLK is inactive one cycle at the start of a frame and 1/2 cycle at the end of a frame. 1 – SCLK is inactive 1/2 cycle at the start of a frame and one cycle at the end of a frame.

```

enum IxSspAccSpiSclkPolarity {
    SPI_POLARITY_LOW,
    SPI_POLARITY_HIGH,
    INVALID_SPI_POLARITY
}

```

The SPI SCLK Polarity can be set to either low or high.

```

enum IxSspAccMicrowireCtlWord {
    MICROWIRE_8_BIT,
    MICROWIRE_16_BIT,
    INVALID_MICROWIRE_CTL_WORD
}

```


The Microwire control word can be either 8 or 16 bit.

```
enum IxSspAccFifoThreshold {  
    FIFO_TSHLD_1,  
    FIFO_TSHLD_2,  
    FIFO_TSHLD_3,  
    FIFO_TSHLD_4,  
    FIFO_TSHLD_5,  
    FIFO_TSHLD_6,  
    FIFO_TSHLD_7,  
    FIFO_TSHLD_8,  
    FIFO_TSHLD_9,  
    FIFO_TSHLD_10,  
    FIFO_TSHLD_11,  
    FIFO_TSHLD_12,  
    FIFO_TSHLD_13,  
    FIFO_TSHLD_14,  
    FIFO_TSHLD_15,  
    FIFO_TSHLD_16,  
    INVALID_FIFO_TSHLD  
}
```

The threshold in frames (each frame is defined by IxSspAccDataSize) that can be set for the FIFO to trigger a threshold exceed when checking with the ExceedThresholdCheck functions or an interrupt when it is enabled.

```
enum IX_SSP_STATUS {  
    IX_SSP_SUCCESS,  
    IX_SSP_FAIL,  
    IX_SSP_RX_FIFO_OVERRUN_HANDLER_MISSING,  
    IX_SSP_RX_FIFO_HANDLER_MISSING,  
    IX_SSP_TX_FIFO_HANDLER_MISSING,  
    IX_SSP_FIFO_NOT_EMPTY_FOR_SETTING_CTL_CMD,  
    IX_SSP_INVALID_FRAME_FORMAT_ENUM_VALUE,  
    IX_SSP_INVALID_DATA_SIZE_ENUM_VALUE,  
    IX_SSP_INVALID_CLOCK_SOURCE_ENUM_VALUE,  
    IX_SSP_INVALID_TX_FIFO_THRESHOLD_ENUM_VALUE,  
    IX_SSP_INVALID_RX_FIFO_THRESHOLD_ENUM_VALUE,  
    IX_SSP_INVALID_SPI_PHASE_ENUM_VALUE,  
    IX_SSP_INVALID_SPI_POLARITY_ENUM_VALUE,  
    IX_SSP_INVALID_MICROWIRE_CTL_CMD_ENUM_VALUE,  
    IX_SSP_INT_UNBIND_FAIL,  
    IX_SSP_INT_BIND_FAIL,  
    IX_SSP_RX_FIFO_NOT_EMPTY,  
    IX_SSP_TX_FIFO_NOT_EMPTY,  
    IX_SSP_POLL_MODE_BLOCKING,  
    IX_SSP_TX_FIFO_HIT_BELOW_THRESHOLD,  
    IX_SSP_TX_FIFO_EXCEED_THRESHOLD,  
    IX_SSP_RX_FIFO_HIT_ABOVE_THRESHOLD,  
    IX_SSP_RX_FIFO_BELOW_THRESHOLD,  
    IX_SSP_BUSY,  
    IX_SSP_IDLE,
```

```

    IX_SSP_OVERRUN_OCCURRED,
    IX_SSP_NO_OVERRUN,
    IX_SSP_NOT_SUPPORTED,
    IX_SSP_NOT_INIT,
    IX_SSP_NULL_POINTER
}

```

The statuses that can be returned in a SSP Serial Port Access.

Functions

```

    PUBLIC
    IX_SSP_STATUS ixSspAccInit (IxSspInitVars *initVarsSelected)
        Initializes the SSP Access module.

    PUBLIC
    IX_SSP_STATUS ixSspAccUninit (void)
        Un-initializes the SSP Serial Port Access component.

    PUBLIC
    IX_SSP_STATUS ixSspAccFIFODataSubmit (UINT16 *data, UINT32 amtOfData)
        Inserts data into the SSP Serial Port's FIFO.

    PUBLIC
    IX_SSP_STATUS ixSspAccFIFODataReceive (UINT16 *data, UINT32 amtOfData)
        Extract data from the SSP Serial Port's FIFO.

    PUBLIC
    IX_SSP_STATUS ixSspAccTxFIFOHitOrBelowThresholdCheck (void)
        Check if the Tx FIFO threshold has been hit or fallen below.

    PUBLIC
    IX_SSP_STATUS ixSspAccRxFIFOHitOrAboveThresholdCheck (void)
        Check if the Rx FIFO threshold has been hit or exceeded.

    PUBLIC
    IX_SSP_STATUS ixSspAccSSPPortStatusSet (IxSspAccPortStatus portStatusSelected)
        Enables/disables the SSP Serial Port hardware.

    PUBLIC
    IX_SSP_STATUS ixSspAccFrameFormatSelect (IxSspAccFrameFormat frameFormatSelected)
        Sets the frame format for the SSP Serial Port hardware.

    PUBLIC
    IX_SSP_STATUS ixSspAccDataSizeSelect (IxSspAccDataSize dataSizeSelected)
        Sets the data size for transfers.

    PUBLIC
    IX_SSP_STATUS ixSspAccClockSourceSelect (IxSspAccClkSource clkSourceSelected)

```

Sets the clock source of the SSP Serial Port hardware.

PUBLIC

IX_SSP_STATUS ixSspAccSerialClockRateConfigure (UINT8 serialClockRateSelected)
Sets the on-chip Serial Clock Rate of the SSP Serial Port hardware.

PUBLIC

IX_SSP_STATUS ixSspAccRxFIFOIntEnable (**RxFIFOThresholdHandler** rxFIFOIntrHandler)
Enables service request interrupt whenever the Rx FIFO hits its threshold.

PUBLIC

IX_SSP_STATUS ixSspAccRxFIFOIntDisable (void)
Disables service request interrupt of the Rx FIFO.

PUBLIC

IX_SSP_STATUS ixSspAccTxFIFOIntEnable (**TxFIFOThresholdHandler** txFIFOIntrHandler)
Enables service request interrupt of the Tx FIFO.

PUBLIC

IX_SSP_STATUS ixSspAccTxFIFOIntDisable (void)
Disables service request interrupt of the Tx FIFO.

PUBLIC

IX_SSP_STATUS ixSspAccLoopbackEnable (BOOL loopbackEnable)
Enables/disables the loopback mode.

PUBLIC

IX_SSP_STATUS ixSspAccSpiSclkPolaritySet (**IxSspAccSpiSclkPolarity** spiSclkPolaritySelected)
Sets the SPI SCLK Polarity to Low or High.

PUBLIC

IX_SSP_STATUS ixSspAccSpiSclkPhaseSet (**IxSspAccSpiSclkPhase** spiSclkPhaseSelected)
Sets the SPI SCLK Phase.

PUBLIC **ixSspAccMicrowireControlWordSet** (**IxSspAccMicrowireCtlWord**

IX_SSP_STATUS microwireCtlWordSelected)
Sets the Microwire control word to 8 or 16 bit format.

PUBLIC

IX_SSP_STATUS ixSspAccTxFIFOThresholdSet (**IxSspAccFifoThreshold** txFIFOThresholdSelected)
Sets the Tx FIFO Threshold.

PUBLIC

IX_SSP_STATUS ixSspAccRxFIFOThresholdSet (**IxSspAccFifoThreshold** rxFIFOThresholdSelected)
Sets the Rx FIFO Threshold.

PUBLIC

IX_SSP_STATUS ixSspAccStatsGet (**IxSspAccStatsCounters** *sspStats)
Returns the SSP Statistics through the pointer passed in.

PUBLIC void **ixSspAccStatsReset** (void)

Resets the SSP Statistics.

PUBLIC

IX_SSP_STATUS ixSspAccShow (void)

Display SSP status registers and statistics counters.

PUBLIC

IX_SSP_STATUS ixSspAccSSPBusyCheck (void)

Determine the state of the SSP serial port hardware.

PUBLIC UINT8 **ixSspAccTxFIFOLevelGet** (void)

Obtain the Tx FIFO's level.

PUBLIC UINT8 **ixSspAccRxFIFOLevelGet** (void)

Obtain the Rx FIFO's level.

PUBLIC

IX_SSP_STATUS ixSspAccRxFIFOOverrunCheck (void)

Check if the Rx FIFO has overrun its FIFOs.

Detailed Description

Intel (R) IXP400 Software SSP Serial Port Access Public API.

Typedef Documentation

```
typedef void(* RxFIFOOverrunHandler)(void)
```

SSP Rx FIFO Overrun handler.

This function is called for the client to handle Rx FIFO Overrun that occurs in the SSP hardware

Definition at line **252** of file **IxSspAcc.h**.

```
typedef void(* RxFIFOThresholdHandler)(void)
```

SSP Rx FIFO Threshold hit or above handler.

This function is called for the client to handle Rx FIFO threshold hit or or above that occurs in the SSP hardware

Definition at line **262** of file **IxSspAcc.h**.

```
typedef void(* TxFIFOThresholdHandler)(void)
```

SSP Tx FIFO Threshold hit or below handler.

This function is called for the client to handle Tx FIFO threshold hit or or below that occurs in the SSP hardware

Definition at line **272** of file **IxSspAcc.h**.

Enumeration Type Documentation

```
enum IX_SSP_STATUS
```

The statuses that can be returned in a SSP Serial Port Access.

Enumeration values:

<i>IX_SSP_SUCCESS</i>	Success status.
<i>IX_SSP_FAIL</i>	Fail status.
<i>IX_SSP_RX_FIFO_OVERRUN_HANDLER_MISSING</i>	Rx FIFO Overrun handler is NULL.
<i>IX_SSP_RX_FIFO_HANDLER_MISSING</i>	Rx FIFO threshold hit or above handler is NULL.
<i>IX_SSP_TX_FIFO_HANDLER_MISSING</i>	Tx FIFO threshold hit or below handler is NULL.
<i>IX_SSP_FIFO_NOT_EMPTY_FOR_SETTING_CTL_CMD</i>	Tx FIFO not empty and therefore microwire control command size setting is not allowed.
<i>IX_SSP_INVALID_FRAME_FORMAT_ENUM_VALUE</i>	frame format selected is invalid
<i>IX_SSP_INVALID_DATA_SIZE_ENUM_VALUE</i>	data size selected is invalid
<i>IX_SSP_INVALID_CLOCK_SOURCE_ENUM_VALUE</i>	source clock selected is invalid
<i>IX_SSP_INVALID_TX_FIFO_THRESHOLD_ENUM_VALUE</i>	Tx FIFO threshold selected is invalid.
<i>IX_SSP_INVALID_RX_FIFO_THRESHOLD_ENUM_VALUE</i>	Rx FIFO threshold selected is invalid.
<i>IX_SSP_INVALID_SPI_PHASE_ENUM_VALUE</i>	SPI phase selected is invalid.
<i>IX_SSP_INVALID_SPI_POLARITY_ENUM_VALUE</i>	SPI polarity selected is invalid.
<i>IX_SSP_INVALID_MICROWIRE_CTL_CMD_ENUM_VALUE</i>	Microwire control command selected is invalid.
<i>IX_SSP_INT_UNBIND_FAIL</i>	Interrupt unbind fail to unbind SSP interrupt.
<i>IX_SSP_INT_BIND_FAIL</i>	Interrupt bind fail during init.
<i>IX_SSP_RX_FIFO_NOT_EMPTY</i>	Rx FIFO not empty while trying to change data size.
<i>IX_SSP_TX_FIFO_NOT_EMPTY</i>	Rx FIFO not empty while trying to change data size or microwire control command size.

<i>IX_SSP_POLL_MODE_BLOCKING</i>	poll mode selected blocks interrupt mode from being selected
<i>IX_SSP_TX_FIFO_HIT_BELOW_THRESHOLD</i>	Tx FIFO level hit or below threshold.
<i>IX_SSP_TX_FIFO_EXCEED_THRESHOLD</i>	Tx FIFO level exceeded threshold.
<i>IX_SSP_RX_FIFO_HIT_ABOVE_THRESHOLD</i>	Rx FIFO level hit or exceeded threshold.
<i>IX_SSP_RX_FIFO_BELOW_THRESHOLD</i>	Rx FIFO level below threshold.
<i>IX_SSP_BUSY</i>	SSP is busy.
<i>IX_SSP_IDLE</i>	SSP is idle.
<i>IX_SSP_OVERRUN_OCCURRED</i>	SSP has experienced an overrun.
<i>IX_SSP_NO_OVERRUN</i>	SSP did not experience an overrun.
<i>IX_SSP_NOT_SUPPORTED</i>	hardware does not support SSP
<i>IX_SSP_NOT_INIT</i>	SSP Access not initialized.
<i>IX_SSP_NULL_POINTER</i>	parameter passed in is NULL

Definition at line **181** of file **IxSspAcc.h**.

enum IxSspAccClkSource

The source to produce the SSP serial clock.

Definition at line **90** of file **IxSspAcc.h**.

enum IxSspAccDataSize

The data sizes in bits that are supported by the protocol.

Definition at line **35** of file **IxSspAcc.h**.

enum IxSspAccFifoThreshold

The threshold in frames (each frame is defined by IxSspAccDataSize) that can be set for the FIFO to trigger a threshold exceed when checking with the ExceedThresholdCheck functions or an interrupt when it is enabled.

Definition at line **153** of file **IxSspAcc.h**.

enum IxSspAccFrameFormat

The frame format that is to be used – SPI, SSP, or Microwire.

Definition at line **75** of file **IxSspAcc.h**.

enum IxSspAccMicrowireCtlWord

The Microwire control word can be either 8 or 16 bit.

Definition at line **136** of file **IxSspAcc.h**.

enum IxSspAccPortStatus

The status of the SSP port to be set to enable/disable.

Definition at line **61** of file **IxSspAcc.h**.

enum IxSspAccSpiSclkPhase

The SPI SCLK Phase: 0 – SCLK is inactive one cycle at the start of a frame and 1/2 cycle at the end of a frame. 1 – SCLK is inactive 1/2 cycle at the start of a frame and one cycle at the end of a frame.

Definition at line **108** of file **IxSspAcc.h**.

enum IxSspAccSpiSclkPolarity

The SPI SCLK Polarity can be set to either low or high.

Definition at line **122** of file **IxSspAcc.h**.

Function Documentation

ixSspAccClockSourceSelect (**IxSspAccClkSource** *clkSourceSelected*)

Sets the clock source of the SSP Serial Port hardware.

Parameters:

<i>IxSspAccClkSource</i> [in] <i>clkSourceSelected</i>	– The clock source from either external source on on–chip can be selected as the source
---	---

Global Data :

- None.

This API will set the clock source for the transfers via user input.

Returns:

- ◇ IX_SSP_SUCCESS – clock source set with valid enum value
- ◇ IX_SSP_INVALID_CLOCK_SOURCE_ENUM_VALUE – invalid enum value

◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

```
ixSspAccDataSizeSelect ( IxSspAccDataSize dataSizeSelected )
```

Sets the data size for transfers.

Parameters:

<i>IxSspAccDataSize</i> [in]	– The data size between 4 and 16 that can be selected for data transfers
<i>dataSizeSelected</i>	

Global Data :

- None.

This API will set the data size for the transfers via user input. It will disallow the change of the data size if either of the Rx/Tx FIFO is not empty to prevent data loss. *NOTE*: The SSP port will be disabled if the FIFOs are found to be empty and if between the check and disabling of the SSP (which clears the FIFOs) data is received into the FIFO, it might be lost. *NOTE*: The FIFOs can be cleared by disabling the SSP Port if necessary to force the data size change.

Returns:

◇ IX_SSP_SUCCESS – data size set with valid enum value
◇ IX_SSP_RX_FIFO_NOT_EMPTY – Rx FIFO not empty, data size change is not allowed.
◇ IX_SSP_TX_FIFO_NOT_EMPTY – Tx FIFO not empty, data size change is not allowed.
◇ IX_SSP_INVALID_DATA_SIZE_ENUM_VALUE – invalid enum value
◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

```
ixSspAccFIFODataReceive ( UINT16 * data,  
                          UINT32  amtOfData  
                          )
```

Extract data from the SSP Serial Port's FIFO.

Parameters:

<i>UINT16</i> [in]	– pointer to the location to receive the data into "UINT32 [in] amtOfData" –
<i>*data</i>	number of data to be received.

Global Data :

- None.

This API will extract the amount of data specified by "amtOfData" from the FIFO already received by the hardware into the buffer pointed to by "data".

Returns:

- ◇ IX_SSP_SUCCESS – Data extracted successfully from FIFO
- ◇ IX_SSP_FAIL – FIFO has no data
- ◇ IX_SSP_NULL_POINTER – data pointer passed by client is NULL
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

```
ixSspAccFIFODataSubmit ( UINT16 * data,
                        UINT32  amtOfData
                        )
```

Inserts data into the SSP Serial Port's FIFO.

Parameters:

- UINT16 [in]* – pointer to the location to transmit the data from "UINT32 [in] amtOfData" –
**data* number of data to be transmitted.

Global Data :

- None.

This API will insert the amount of data specified by "amtOfData" from buffer pointed to by "data" into the FIFO to be transmitted by the hardware.

Returns:

- ◇ IX_SSP_SUCCESS – Data inserted successfully into FIFO
- ◇ IX_SSP_FAIL – FIFO insufficient space
- ◇ IX_SSP_NULL_POINTER – data pointer passed by client is NULL
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

```
ixSspAccFrameFormatSelect ( IxSspAccFrameFormat frameFormatSelected )
```

Sets the frame format for the SSP Serial Port hardware.

Parameters:

- IxSspAccFrameFormat [in]* – The frame format of SPI, SSP or Microwire can be
frameFormatSelected selected as the format

Global Data :

- None.

This API will set the format for the transfers via user input. *NOTE*: The SSP hardware will be disabled to clear the FIFOs. Then its previous state (enabled/disabled) restored after changing the format.

Returns:

- ◇ IX_SSP_SUCCESS – frame format set with valid enum value
- ◇ IX_SSP_INVALID_FRAME_FORMAT_ENUM_VALUE – invalid frame format value
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

```
ixSspAccInit ( IxSspInitVars * initVarsSelected )
```

Initializes the SSP Access module.

Parameters:

IxSspAccInitVars [in] **initVarsSelected* – struct containing required variables for initialization

Global Data :

- None.

This API will initialize the SSP Serial Port hardware to the user specified configuration. Then it will enable the SSP Serial Port. *NOTE*: Once interrupt or polling mode is selected, the mode cannot be changed via the interrupt enable/disable function but the init needs to be called again to change it.

Returns:

- ◇ IX_SSP_SUCCESS – Successfully initialize and enable the SSP serial port.
- ◇ IX_SSP_RX_FIFO_HANDLER_MISSING – interrupt mode is selected but RX FIFO handler pointer is NULL
- ◇ IX_SSP_TX_FIFO_HANDLER_MISSING – interrupt mode is selected but TX FIFO handler pointer is NULL
- ◇ IX_SSP_RX_FIFO_OVERRUN_HANDLER_MISSING – interrupt mode is selected but RX FIFO Overrun handler pointer is NULL
- ◇ IX_SSP_RX_FIFO_NOT_EMPTY – Rx FIFO not empty, data size change is not allowed.
- ◇ IX_SSP_TX_FIFO_NOT_EMPTY – Tx FIFO not empty, data size change is not allowed.
- ◇ IX_SSP_INVALID_FRAME_FORMAT_ENUM_VALUE – frame format selected is invalid
- ◇ IX_SSP_INVALID_DATA_SIZE_ENUM_VALUE – data size selected is invalid
- ◇ IX_SSP_INVALID_CLOCK_SOURCE_ENUM_VALUE – clock source selected is invalid
- ◇ IX_SSP_INVALID_TX_FIFO_THRESHOLD_ENUM_VALUE – Tx FIFO threshold level selected is invalid
- ◇ IX_SSP_INVALID_RX_FIFO_THRESHOLD_ENUM_VALUE – Rx FIFO threshold level selected is invalid
- ◇ IX_SSP_INVALID_SPI_PHASE_ENUM_VALUE – SPI phase selected is invalid
- ◇ IX_SSP_INVALID_SPI_POLARITY_ENUM_VALUE – SPI polarity selected is invalid

- ◇ IX_SSP_INVALID_MICROWIRE_CTL_CMD_ENUM_VALUE – microwire control command size is invalid
- ◇ IX_SSP_INT_UNBIND_FAIL – interrupt handler failed to unbind SSP interrupt
- ◇ IX_SSP_INT_BIND_FAIL – interrupt handler failed to bind to SSP interrupt hardware trigger
- ◇ IX_SSP_NOT_SUPPORTED – hardware does not support SSP
- ◇ IX_SSP_NULL_POINTER – parameter passed in is NULL

ixSspAccLoopbackEnable (BOOL *loopbackEnable*)

Parameters:

Global Data :

This API will set the mode of operation to either loopback or normal mode according to the user input.

- Reentrant : yes
- ISR Callable : yes

ixSspAccMicrowireControlWordSet (**IxSspAccMicrowireCtlWord** *microwireCtlWordSelected*)

Global Data :

This API is only used for the Microwire frame format and will set the control word to 8 or 16 bit format

- ◇ IX_SSP_INVALID_MICROWIRE_CTL_CMD_ENUM_VALUE – invalid enum value
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

`ixSspAccRxFIFOHitOrAboveThresholdCheck (void)`

Check if the Rx FIFO threshold has been hit or exceeded.

Parameters:

- None

Global Data :

- None.

This API will return whether the Rx FIFO level is below threshold or not

Returns:

- ◇ IX_SSP_RX_FIFO_HIT_ABOVE_THRESHOLD – Rx FIFO level hit or exceeded threshold
- ◇ IX_SSP_RX_FIFO_BELOW_THRESHOLD – Rx FIFO level below threshold
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

`ixSspAccRxFIFOIntDisable (void)`

Disables service request interrupt of the Rx FIFO.

Parameters:

- None

Global Data :

- None.

This API will disable the service request interrupt of the Rx FIFO.

Returns:

- ◇ IX_SSP_SUCCESS – Rx FIFO Interrupt disabled successfully
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

```
ixSspAccRxFIFOIntEnable ( RxFIFOThresholdHandler rxFIFOIntrHandler )
```

Enables service request interrupt whenever the Rx FIFO hits its threshold.

Parameters:

void [in]

**rxFIFOIntrHandler(UINT32)*

- function pointer to the interrupt handler for the Rx FIFO exceeded.

Global Data :

- None.

This API will enable the service request interrupt for the Rx FIFO

Returns:

- ◇ `IX_SSP_SUCCESS` – Rx FIFO level interrupt enabled successfully
- ◇ `IX_SSP_RX_FIFO_HANDLER_MISSING` – missing handler for Rx FIFO level interrupt
- ◇ `IX_SSP_POLL_MODE_BLOCKING` – poll mode is selected at init, interrupt not allowed to be enabled. Use init to enable interrupt mode.
- ◇ `IX_SSP_NOT_INIT` – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccRxFIFOLevelGet (void)

Obtain the Rx FIFO's level.

Parameters:

- None

Global Data :

- None.

This API will return the level of the Rx FIFO

Returns:

- ◇ 0..16; 0 can also mean SSP not initialized and will need to be init.

- Reentrant : yes
- ISR Callable : yes

ixSspAccRxFIFOOverrunCheck (void)

Check if the Rx FIFO has overrun its FIFOs.

Parameters:

- None

Global Data :

- None.

This API will return whether the Rx FIFO has overrun its 16 FIFOs

Returns:

- ◇ IX_SSP_OVERRUN_OCCURRED – Rx FIFO overrun occurred
- ◇ IX_SSP_NO_OVERRUN – Rx FIFO did not overrun
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccRxFIFOThresholdSet (**IxSspAccFifoThreshold *rxFIFOThresholdSelected*)**

Sets the Rx FIFO Threshold.

Parameters:

IxSspAccFifoThreshold [in]
rxFIFOThresholdSelected

– Threshold that is set for a Tx FIFO service request to be triggered

Global Data :

- None.

This API will set the threshold for a Rx FIFO threshold to be triggered

Returns:

- ◇ IX_SSP_SUCCESS – Rx FIFO Threshold set with valid enum value
- ◇ IX_SSP_INVALID_RX_FIFO_THRESHOLD_ENUM_VALUE – invalid enum value
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccSerialClockRateConfigure (UINT8 *serialClockRateSelected*)

Sets the on-chip Serial Clock Rate of the SSP Serial Port hardware.

Parameters:

UINT8 [in]
serialClockRateSelected – The serial clock rate that can be set is between 7.2Kbps and 1.8432Mbps. The formula used is Bit rate = $3.6864 \times 10^6 / (2 \times (\text{SerialClockRateSelected} + 1))$

Global Data :

- None.

This API will set the serial clock rate for the transfers via user input.

Returns:

◊ IX_SSP_SUCCESS – Serial clock rate configured successfully
 ◊ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

```
ixSspAccShow ( void )
```

Display SSP status registers and statistics counters.

Parameters:

– None

Global Data :

- None.

This API will display the status registers of the SSP and the statistics counters.

Returns:

◊ IX_SSP_SUCCESS – SSP show called successfully.
 ◊ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

```
ixSspAccSpiSclkPhaseSet ( IxSspAccSpiSclkPhase spiSclkPhaseSelected )
```

Sets the SPI SCLK Phase.

Parameters:

IxSspAccSpiSclkPhase [in]
spiSclkPhaseSelected – Phase of either the SCLK is inactive one cycle at the start of a frame and 1/2 cycle at the end of a frame, OR the SCLK is inactive 1/2 cycle at the start of a frame and one cycle at the end of a frame.

Global Data :

- IX_SSP_SUCCESS – SPI Sclk phase set with valid enum value
- IX_SSP_INVALID_SPI_PHASE_ENUM_VALUE – invalid SPI phase value
- IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

This API is only used for the SPI frame format and will set the SPI SCLK phase according to user input.

Returns:

◇ None

- Reentrant : yes
- ISR Callable : yes

ixSspAccSpiSclkPolaritySet (**IxSspAccSpiSclkPolarity spiSclkPolaritySelected)**

Sets the SPI SCLK Polarity to Low or High.

Parameters:

- "IxSspAccSpiSclkPolarity [in] spiSclkPolaritySelected" – SPI SCLK polarity that can be selected to either high or low

Global Data :

- None.

This API is only used for the SPI frame format and will set the SPI SCLK polarity to either low or high

Returns:

- ◇ IX_SSP_SUCCESS – SPI Sclk polarity set with valid enum value
- ◇ IX_SSP_INVALID_SPI_POLARITY_ENUM_VALUE – invalid SPI polarity value
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccSSPBusyCheck (void)

Determine the state of the SSP serial port hardware.

Parameters:

- None

Global Data :

- None.

This API will return the state of the SSP serial port hardware – busy or idle

Returns:

- ◊ IX_SSP_BUSY – SSP is busy
- ◊ IX_SSP_IDLE – SSP is idle.
- ◊ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccSSPPortStatusSet (**IxSspAccPortStatus *portStatusSelected*)**

Enables/disables the SSP Serial Port hardware.

Parameters:

IxSspAccPortStatus [in] portStatusSelected – Set the SSP port to enable or disable

Global Data :

- None.

This API will enable/disable the SSP Serial Port hardware. NOTE: This function is called by init to enable the SSP after setting up the configurations and by uninit to disable the SSP.

Returns:

- ◊ IX_SSP_SUCCESS – Port status set with valid enum value
- ◊ IX_SSP_FAIL – invalid enum value
- ◊ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccStatsGet (**IxSspAccStatsCounters * *sspStats*)**

Returns the SSP Statistics through the pointer passed in.

Parameters:

IxSspAccStatsCounters [in] – SSP statistics counter will be read and written to the location pointed by this pointer.
**sspStats*

Global Data :

- None.

This API will return the statistics counters of the SSP transfers.

Returns:

- ◊ IX_SSP_SUCCESS – Stats obtained into the pointer provided successfully

◇ IX_SSP_FAIL – client provided pointer is NULL

- Reentrant : yes
- ISR Callable : yes

ixSspAccStatsReset (void)

Resets the SSP Statistics.

Parameters:

- None

Global Data :

- None.

This API will reset the SSP statistics counters.

Returns:

◇ None

- Reentrant : yes
- ISR Callable : yes

ixSspAccTxFIFOHitOrBelowThresholdCheck (void)

Check if the Tx FIFO threshold has been hit or fallen below.

Parameters:

- None

Global Data :

- None.

This API will return whether the Tx FIFO threshold has been exceeded or not

Returns:

- ◇ IX_SSP_TX_FIFO_HIT_BELOW_THRESHOLD – Tx FIFO level hit or below threshold .
- ◇ IX_SSP_TX_FIFO_EXCEED_THRESHOLD – Tx FIFO level exceeded threshold.
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccTxFIFOIntDisable (void)

Disables service request interrupt of the Tx FIFO.

Parameters:

- None

Global Data :

- None.

This API will disable the service request interrupt of the Tx FIFO

Returns:

- ◇ IX_SSP_SUCCESS – Tx FIFO Interrupt disabled successfully.
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccTxFIFOIntEnable (**TxFIFOThresholdHandler** *txFIFOIntrHandler*)

Enables service request interrupt of the Tx FIFO.

Parameters:

- | | |
|-----------------------------------|---|
| <i>void [in]</i> | – function pointer to the interrupt handler for the Tx FIFO |
| <i>*txFIFOIntrHandler(UINT32)</i> | exceeded. |

Global Data :

- None.

This API will enable the service request interrupt of the Tx FIFO.

Returns:

- ◇ IX_SSP_SUCCESS – Tx FIFO level interrupt enabled successfully
- ◇ IX_SSP_TX_FIFO_HANDLER_MISSING – missing handler for Tx FIFO level interrupt
- ◇ IX_SSP_POLL_MODE_BLOCKING – poll mode is selected at init, interrupt not allowed to be enabled. Use init to enable interrupt mode.
- ◇ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccTxFIFOLevelGet (void)

Obtain the Tx FIFO's level.

Parameters:

- None

Global Data :

- None.

This API will return the level of the Tx FIFO

Returns:

◊ 0..16; 0 can also mean SSP not initialized and will need to be init.

- Reentrant : yes
- ISR Callable : yes

ixSspAccTxFIFOThresholdSet (**IxSspAccFifoThreshold *txFIFOThresholdSelected*)**

Sets the Tx FIFO Threshold.

Parameters:

IxSspAccFifoThreshold [in]
txFIFOThresholdSelected

– Threshold that is set for a Tx FIFO service request to be triggered

Global Data :

- None.

This API will set the threshold for a Tx FIFO threshold to be triggered

Returns:

◊ IX_SSP_SUCCESS – Tx FIFO Threshold set with valid enum value
◊ IX_SSP_INVALID_TX_FIFO_THRESHOLD_ENUM_VALUE – invalid enum value
◊ IX_SSP_NOT_INIT – SSP not initialized. SSP init needs to be called.

- Reentrant : yes
- ISR Callable : yes

ixSspAccUninit (void)

Un-initializes the SSP Serial Port Access component.

Parameters:

- None

Global Data :

- None.

This API will disable the SSP Serial Port hardware. The client can call the init function again if they wish to enable the SSP.

Returns:

- ◊ IX_SSP_SUCCESS – successfully uninit SSP component
- ◊ IX_SSP_INT_UNBIND_FAIL – interrupt handler failed to unbind SSP interrupt

- Reentrant : yes
- ISR Callable : yes

Intel (R) IXP400 Software Timer Control (IxTimerCtrl) API

The public API for the IXP400 Timer Control Component.

Defines

#define **IX_TIMERCTRL_NO_FREE_TIMERS**
Timer schedule return code.

#define **IX_TIMERCTRL_PARAM_ERROR**
Timer schedule return code.

Typedefs

typedef void(* **IxTimerCtrlTimerCallback**)(void *userParam)
A typedef for a pointer to a timer callback function.

Enumerations

enum **IxTimerCtrlPurpose** {
 IxTimerCtrlAdslPurpose,
 IxTimerCtrlMaxPurpose
}
List used to identify the users of timers.

Functions

PUBLIC IxTimerCtrlSchedule (**IxTimerCtrlTimerCallback** func, void *userParam, **IX_STATUS IxTimerCtrlPurpose** purpose, UINT32 relativeTime, unsigned *timerId)
Schedules a callback function to be called after a period of "time". The callback function should not block or run for more than 100ms. This function.

PUBLIC IxTimerCtrlScheduleRepeating (**IxTimerCtrlTimerCallback** func, void *param, **IX_STATUS IxTimerCtrlPurpose** purpose, UINT32 interval, unsigned *timerId)
Schedules a callback function to be called after a period of "time". The callback function should not block or run for more than 100ms.

PUBLIC
IX_STATUS IxTimerCtrlCancel (unsigned id)
Cancels a scheduled callback.

ixTimerCtrlInit (void)

PUBLIC
IX_STATUS

Initialise the Timer Control Component.

PUBLIC void **ixTimerCtrlShow** (void)

Display the status of the Timer Control Component.

Detailed Description

The public API for the IXP400 Timer Control Component.

Define Documentation

```
#define IX_TIMERCTRL_NO_FREE_TIMERS
```

Timer schedule return code.

Indicates that the request to start a timer failed because all available timer resources are used.

Definition at line **48** of file **IxTimerCtrl.h**.

```
#define IX_TIMERCTRL_PARAM_ERROR
```

Timer schedule return code.

Indicates that the request to start a timer failed because the client has supplied invalid parameters.

Definition at line **61** of file **IxTimerCtrl.h**.

Typedef Documentation

```
typedef void(* IxTimerCtrlTimerCallback)(void *userParam)
```

A typedef for a pointer to a timer callback function.

void * – This parameter is supplied by the client when the timer is started and passed back to the client in the callback.

Note:

in general timer callback functions should not block or take longer than 100ms. This constraint is required to ensure that higher priority callbacks are not held up. All callbacks are called from the same thread. This thread is a shared resource. The parameter passed is provided when the timer is scheduled.

Enumeration Type Documentation

enum IxTimerCtrlPurpose

List used to identify the users of timers.

Note:

The order in this list indicates priority. Components appearing higher in the list will be given priority over components lower in the list. When adding components, please insert at an appropriate position for priority (i.e values should be less than IxTimerCtrlMaxPurpose) .

Definition at line **93** of file **IxTimerCtrl.h**.

Function Documentation

ixTimerCtrlCancel (unsigned *id*)

Cancels a scheduled callback.

Parameters:

id unsigned [in] – the id of the callback to be cancelled.

Returns:

- ◇ IX_SUCCESS – The timer was successfully stopped.
- ◇ IX_FAIL – The id parameter did not correspond to any running timer..

Note:

This function is re–entrant. The function accesses a list of running timers and may suspend the calling thread if this list is being accesed by another thread.

ixTimerCtrlInit (void)

Initialise the Timer Control Component.

Returns:

- ◇ IX_SUCCESS – The timer control component initialized successfully.
- ◇ IX_FAIL – The timer control component initialization failed, or the component was already initialized.

Note:

This must be done before any other API function is called. This function should be called once only and is not re–entrant.


```

ixTimerCtrlSchedule ( IxTimerCtrlTimerCallback func,
                      void *                      userParam,
                      IxTimerCtrlPurpose         purpose,
                      UINT32                       relativeTime,
                      unsigned *                   timerId
                      )

```

Schedules a callback function to be called after a period of "time". The callback function should not block or run for more than 100ms. This function.

Parameters:

func **IxTimerCtrlTimerCallback** [in] – the callback function to be called.
userParam void [in] – a parameter to send to the callback function, can be NULL.
purpose **IxTimerCtrlPurpose** [in] – the purpose of the callback, internally this component will decide the priority of callbacks with different purpose.
relativeTime UINT32 [in] – time relative to now in milliseconds after which the callback will be called. The time must be greater than the duration of one OS tick.
**timerId* unsigned [out] – An id for the callback scheduled. This id can be used to cancel the callback.

Returns:

- ◇ IX_SUCCESS – The timer was started successfully.
- ◇ IX_TIMERCTRL_NO_FREE_TIMERS – The timer was not started because the maximum number of running timers has been exceeded.
- ◇ IX_TIMERCTRL_PARAM_ERROR – The timer was not started because the client has supplied a NULL callback func, or the requested timeout is less than one OS tick.

Note:

This function is re-entrant. The function accesses a list of running timers and may suspend the calling thread if this list is being accessed by another thread.

```

ixTimerCtrlScheduleRepeating ( IxTimerCtrlTimerCallback func,
                              void *                      param,
                              IxTimerCtrlPurpose         purpose,
                              UINT32                       interval,
                              unsigned *                   timerId
                              )

```

Schedules a callback function to be called after a period of "time". The callback function should not block or run for more than 100ms.

Parameters:

func **IxTimerCtrlTimerCallback** [in] – the callback function to be called.
userParam void [in] – a parameter to send to the callback function, can be NULL.
purpose **IxTimerCtrlPurpose** [in] – the purpose of the callback, internally this component will decide the priority of callbacks with different purpose.
interval UINT32 [in] – the interval in milliseconds between calls to func.
timerId unsigned [out] – An id for the callback scheduled. This id can be used to cancel the

callback.

Returns:

- ◇ IX_SUCCESS – The timer was started successfully.
- ◇ IX_TIMERCTRL_NO_FREE_TIMERS – The timer was not started because the maximum number of running timers has been exceeded.
- ◇ IX_TIMERCTRL_PARAM_ERROR – The timer was not started because the client has supplied a NULL callback func, or the requested timeout is less than one OS tick.

Note:

This function is re-entrant. The function accesses a list of running timers and may suspend the calling thread if this list is being accessed by another thread.

```
ixTimerCtrlShow ( void )
```

Display the status of the Timer Control Component.

Returns:

void

Note:

Displays a list of running timers. This function is not re-entrant. This function does not suspend the calling thread.

Intel (R) IXP400 Software Time Sync Access Component API

Public API for IxTimeSyncAcc.

Data Structures

- struct **IxTimeSyncAccPtpMsgData**
Struct for data from the PTP message returned when TimeStamp available.
- struct **IxTimeSyncAccPtpMsgData**
Struct for data from the PTP message returned when TimeStamp available.
- struct **IxTimeSyncAccPtpMsgData**
Struct for data from the PTP message returned when TimeStamp available.
- struct **IxTimeSyncAccStats**
Statistics for the PTP messages.
- struct **IxTimeSyncAccStats**
Statistics for the PTP messages.
- struct **IxTimeSyncAccStats**
Statistics for the PTP messages.
- struct **IxTimeSyncAccTimeValue**
Struct to hold 64 bit SystemTime and TimeStamp values.
- struct **IxTimeSyncAccTimeValue**
Struct to hold 64 bit SystemTime and TimeStamp values.
- struct **IxTimeSyncAccTimeValue**
Struct to hold 64 bit SystemTime and TimeStamp values.
- struct **IxTimeSyncAccUuid**
Struct to hold 48 bit UUID values captured in Sync or Delay_Req messages.
- struct **IxTimeSyncAccUuid**
Struct to hold 48 bit UUID values captured in Sync or Delay_Req messages.
- struct **IxTimeSyncAccUuid**
Struct to hold 48 bit UUID values captured in Sync or Delay_Req messages.

Typedefs

```
typedef void(* IxTimeSyncAccTargetTimeCallback )(IxTimeSyncAccTimeValue targetTime)  
Callback for use by target time stamp interrupt.
```

```
typedef void(* IxTimeSyncAccAuxTimeCallback )(IxTimeSyncAccAuxMode auxMode,  
IxTimeSyncAccTimeValue auxTime)  
Callback for use by auxiliary time interrupts.
```

Enumerations

```
enum IxTimeSyncAccStatus {  
    IX_TIMESYNCACC_SUCCESS,  
    IX_TIMESYNCACC_INVALIDPARAM,  
    IX_TIMESYNCACC_NOTIMESTAMP,  
    IX_TIMESYNCACC_INTERRUPTMODEINUSE,  
    IX_TIMESYNCACC_FAILED  
}
```

The status as returned from the API.

```
enum IxTimeSyncAccAuxMode {  
    IX_TIMESYNCACC_AUXMODE_MASTER,  
    IX_TIMESYNCACC_AUXMODE_SLAVE,  
    IX_TIMESYNCACC_AUXMODE_INVALID  
}
```

Master or Slave Auxiliary Time Stamp (Snap Shot).

```
enum IxTimeSyncAcc1588PTPPort {  
    IX_TIMESYNCACC_NPE_A_1588PTP_PORT,  
    IX_TIMESYNCACC_NPE_B_1588PTP_PORT,  
    IX_TIMESYNCACC_NPE_C_1588PTP_PORT,  
    IX_TIMESYNCACC_NPE_1588PORT_INVALID  
}
```

IEEE 1588 PTP Communication Port(Channel).

```
enum IxTimeSyncAcc1588PTPPortMode {  
    IX_TIMESYNCACC_1588PTP_PORT_MASTER,  
    IX_TIMESYNCACC_1588PTP_PORT_SLAVE,  
    IX_TIMESYNCACC_1588PTP_PORT_ANYMODE,  
    IX_TIMESYNCACC_1588PTP_PORT_MODE_INVALID  
}
```

Master or Slave mode for IEEE 1588 PTP Communication Port.

```
enum IxTimeSyncAcc1588PTPMsgType {  
    IX_TIMESYNCACC_1588PTP_MSGTYPE_SYNC,  
    IX_TIMESYNCACC_1588PTP_MSGTYPE_DELAYREQ,  
    IX_TIMESYNCACC_1588PTP_MSGTYPE_UNKNOWN  
}
```

1588 PTP Messages types that can be detected on communication port

Functions

PUBLIC**ixTimeSyncAccPTPPortConfigSet** (**ixTimeSyncAcc1588PTPPort** ptpPort,
ixTimeSyncAccStatus ixTimeSyncAcc1588PTPPortMode ptpPortMode)

Configures the IEEE 1588 message detect on particular PTP port.

PUBLIC**ixTimeSyncAccPTPPortConfigGet** (**ixTimeSyncAcc1588PTPPort** ptpPort,
ixTimeSyncAccStatus ixTimeSyncAcc1588PTPPortMode *ptpPortMode)

Retrieves IEEE 1588 PTP operation mode on particular PTP port.

PUBLIC**ixTimeSyncAccPTPRxPoll** (**ixTimeSyncAcc1588PTPPort** ptpPort,
ixTimeSyncAccStatus ixTimeSyncAccPtpMsgData *ptpMsgData)

Polls the IEEE 1588 message/time stamp detect status on a particular PTP Port on the Receive side.

PUBLIC**ixTimeSyncAccPTPTxPoll** (**ixTimeSyncAcc1588PTPPort** ptpPort,
ixTimeSyncAccStatus ixTimeSyncAccPtpMsgData *ptpMsgData)

Polls the IEEE 1588 message/time stamp detect status on a particular PTP Port on the Transmit side.

PUBLIC
ixTimeSyncAccStatus ixTimeSyncAccSystemTimeSet (**ixTimeSyncAccTimeValue** systemTime)

Sets the System Time in the IEEE 1588 hardware assist block.

PUBLIC
ixTimeSyncAccStatus ixTimeSyncAccSystemTimeGet (**ixTimeSyncAccTimeValue** *systemTime)

Gets the System Time from the IEEE 1588 hardware assist block.

PUBLIC
ixTimeSyncAccStatus ixTimeSyncAccTickRateSet (UINT32 tickRate)

Sets the Tick Rate (Frequency Scaling Value) in the IEEE 1588 hardware assist block.

PUBLIC
ixTimeSyncAccStatus ixTimeSyncAccTickRateGet (UINT32 *tickRate)

Gets the Tick Rate (Frequency Scaling Value) from the IEEE 1588 hardware assist block.

PUBLIC**ixTimeSyncAccTargetTimeInterruptEnable**
ixTimeSyncAccStatus ixTimeSyncAccTargetTimeCallback targetTimeCallback)

Enables the interrupt to verify the condition where the System Time greater or equal to the Target Time in the IEEE 1588 hardware assist block. If the condition is true an interrupt will be sent to Intel XScale(R) Processor.

PUBLIC
ixTimeSyncAccStatus ixTimeSyncAccTargetTimeInterruptDisable (void)

*Disables the interrupt for the condition explained in the function description of **ixTimeSyncAccTargetTimeInterruptEnable**.*

PUBLIC**ixTimeSyncAccTargetTimePoll** (BOOL *ttmPollFlag,
IxTimeSyncAccStatus **ixTimeSyncAccTimeValue** *targetTime)
Poll to verify the condition where the System Time greater or equal to the Target Time in the IEEE 1588 hardware assist block. If the condition is true an event flag is set in the hardware.

PUBLIC
IxTimeSyncAccStatus **ixTimeSyncAccTargetTimeSet** (**IxTimeSyncAccTimeValue** targetTime)
Sets the Target Time in the IEEE 1588 hardware assist block.

PUBLIC
IxTimeSyncAccStatus **ixTimeSyncAccTargetTimeGet** (**IxTimeSyncAccTimeValue** *targetTime)
Gets the Target Time in the IEEE 1588 hardware assist block.

PUBLIC**ixTimeSyncAccAuxTimeInterruptEnable** (**IxTimeSyncAccAuxMode** auxMode,
IxTimeSyncAccStatus **ixTimeSyncAccAuxTimeCallback** auxTimeCallback)
Enables the interrupt notification for the given mode of Auxiliary Time Stamp in the IEEE 1588 hardware assist block.

PUBLIC
IxTimeSyncAccStatus **ixTimeSyncAccAuxTimeInterruptDisable** (**IxTimeSyncAccAuxMode** auxMode)
Disables the interrupt for the indicated mode of Auxiliary Time Stamp in the IEEE 1588 hardware assist block.

PUBLIC**ixTimeSyncAccAuxTimePoll** (**IxTimeSyncAccAuxMode** auxMode, BOOL
IxTimeSyncAccStatus *auxPollFlag, **IxTimeSyncAccTimeValue** *auxTime)
Poll for the Auxiliary Time Stamp captured for the mode indicated (Master or Slave).

PUBLIC
IxTimeSyncAccStatus **ixTimeSyncAccReset** (void)
Resets the IEEE 1588 hardware assist block.

PUBLIC
IxTimeSyncAccStatus **ixTimeSyncAccStatsGet** (**IxTimeSyncAccStats** *timeSyncStats)
Returns the IxTimeSyncAcc Statistics in the client supplied buffer.

PUBLIC void **ixTimeSyncAccStatsReset** (void)
Reset Time Sync statistics.

PUBLIC
IxTimeSyncAccStatus **ixTimeSyncAccShow** (void)
Displays the Time Sync current status.

Detailed Description

Public API for IxTimeSyncAcc.

Typedef Documentation

IxTimeSyncAccAuxTimeCallback

Callback for use by auxiliary time interrupts.

Definition at line **188** of file **IxTimeSyncAcc.h**.

IxTimeSyncAccTargetTimeCallback

Callback for use by target time stamp interrupt.

Definition at line **179** of file **IxTimeSyncAcc.h**.

Enumeration Type Documentation

enum IxTimeSyncAcc1588PTPMsgType

1588 PTP Messages types that can be detected on communication port

Note that client code can determine this based on master/slave mode in which it is already operating in and this information is made available for the sake of convenience only.

Enumeration values:

<i>IX_TIMESYNCACC_1588PTP_MSGTYPE_SYNC</i>	PTP Sync message sent by Master or received by Slave.
<i>IX_TIMESYNCACC_1588PTP_MSGTYPE_DELAYREQ</i>	PTP Delay_Req message sent by Slave or received by Master.
<i>IX_TIMESYNCACC_1588PTP_MSGTYPE_UNKNOWN</i>	Other PTP and non-PTP message sent or received by both Master and/or Slave.

Definition at line **106** of file **IxTimeSyncAcc.h**.

enum IxTimeSyncAcc1588PTPPort

IEEE 1588 PTP Communication Port(Channel).

Enumeration values:

<i>IX_TIMESYNCACC_NPE_A_1588PTP_PORT</i>	PTP Communication Port on NPE-A.
<i>IX_TIMESYNCACC_NPE_B_1588PTP_PORT</i>	PTP Communication Port on NPE-B.
<i>IX_TIMESYNCACC_NPE_C_1588PTP_PORT</i>	PTP Communication Port on NPE-C.

IX_TIMESYNCACC_NPE_1588PORT_INVALID

Invalid PTP
Communication Port.

Definition at line **70** of file **IxTimeSyncAcc.h**.

enum IxTimeSyncAcc1588PTPPortMode

Master or Slave mode for IEEE 1588 PTP Communication Port.

Enumeration values:

IX_TIMESYNCACC_1588PTP_PORT_MASTER

PTP Communication Port in Master Mode.

IX_TIMESYNCACC_1588PTP_PORT_SLAVE

PTP Communication Port in Slave Mode.

IX_TIMESYNCACC_1588PTP_PORT_ANYMODE

PTP Communication Port in ANY Mode allows time stamping of all messages including non-1588 PTP.

IX_TIMESYNCACC_1588PTP_PORT_MODE_INVALID Invalid PTP Port Mode.

Definition at line **85** of file **IxTimeSyncAcc.h**.

enum IxTimeSyncAccAuxMode

Master or Slave Auxiliary Time Stamp (Snap Shot).

Enumeration values:

IX_TIMESYNCACC_AUXMODE_MASTER Auxiliary Master Mode.

IX_TIMESYNCACC_AUXMODE_SLAVE Auxiliary Slave Mode.

IX_TIMESYNCACC_AUXMODE_INVALID Invalid Auxiliary Mode.

Definition at line **56** of file **IxTimeSyncAcc.h**.

enum IxTimeSyncAccStatus

The status as returned from the API.

Enumeration values:

IX_TIMESYNCACC_SUCCESS

Requested operation successful.

IX_TIMESYNCACC_INVALIDPARAM

An invalid parameter was passed.

IX_TIMESYNCACC_NOTIMESTAMP

While polling no time stamp available.

IX_TIMESYNCACC_INTERRUPTMODEINUSE

Polling not allowed while operating in interrupt mode.

IX_TIMESYNCACC_FAILED

Internal error occurred.

Function Documentation

IxTimeSyncAccStatus ixTimeSyncAccAuxTimeInterruptDisable (**IxTimeSyncAccAuxMode** *auxMode*)

Disables the interrupt for the indicated mode of Auxiliary Time Stamp in the IEEE 1588 hardware assist block.

Parameters:

auxMode [in] – Auxiliary time stamp mode (slave or master) using which the interrupt will be disabled.

This API will disable the Auxiliary Time Stamp Interrupt (Master or Slave)

- Re-entrant : yes
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Invalid parameters passed
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus ixTimeSyncAccAuxTimeInterruptEnable (**IxTimeSyncAccAuxMode** *auxMode*, **IxTimeSyncAccAuxTimeCallback** *auxTimeCallback*)

Enables the interrupt notification for the given mode of Auxiliary Time Stamp in the IEEE 1588 hardware assist block.

Parameters:

auxMode [in] – Auxiliary time stamp register (slave or master) to use
auxTimeCallback [in] – Callback to be invoked when interrupt fires

This API will enable the Auxiliary Master/Slave Time stamp Interrupt.

NOTE: 1) An individual callback is to be registered for each Slave and Master Auxiliary Time Stamp registers. Thus to register for both Master and Slave time stamp interrupts either the same callback or two separate callbacks the API has to be invoked twice.

2) On the IXDP465 Development Platform, the Auxiliary Timestamp signal for slave mode is tied to GPIO 8 pin. This signal is software routed by default to PCI for backwards compatibility with the IXDP425 Development Platform. This routing must be disabled for the auxiliary slave time stamp register to work properly. The following commands may be used to accomplish this. However, refer to the IXDP465 Development Platform Users Guide or the BSP/LSP documentation for more specific information.

For Linux* (at the Redboot prompt i.e., before loading zImage):

```

mfill -b 0x54100000 -1 -1 1 -p 8
mfill -b 0x54100001 -1 -1 1 -p 0x7f
For vxWorks*, at the prompt:
intDisable(25)
ixdp400FpgaIODetach(8)

```

- Re-entrant : no
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Null parameter passed for callback or invalid auxiliary snapshot mode
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

```

IxTimeSyncAccStatus ixTimeSyncAccAuxTimePoll ( IxTimeSyncAccAuxMode    auxMode,
                                                BOOL *                auxPollFlag,
                                                IxTimeSyncAccTimeValue * auxTime
                                                )

```

Poll for the Auxiliary Time Stamp captured for the mode indicated (Master or Slave).

Parameters:

- auxMode* [in] – Auxiliary Snapshot Register (Slave or Master) to be checked
- auxPollFlag* [out] – TRUE if the time stamp captured in auxiliary snapshot register FALSE if the time stamp not captured in auxiliary snapshot register
- auxTime* [out] – Copy the current Auxiliary Snapshot Register value into the client provided buffer

Polls for the Time stamp in the appropriate Auxiliary Snapshot Registers based on the mode specified. Return true and the contents of the Auxiliary snapshot, if it is available else return false.

Please refer to the note #2 of the API **ixTimeSyncAccAuxTimeInterruptEnable** for more information for Auxiliary Slave mode.

- Re-entrant : yes
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Null parameter passed for auxPollFlag, callback or invalid auxiliary snapshot mode
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred
- ◇ IX_TIMESYNCACC_INTERRUPTMODEINUSE – Interrupt mode in use

```

IxTimeSyncAccStatus ixTimeSyncAccPTPPortConfigGet ( IxTimeSyncAcc1588PTPPort ptpPort,
                                                         ptpPortMode

```

IxTimeSyncAcc1588PTPPortMode

*

)

Retrieves IEEE 1588 PTP operation mode on particular PTP port.

Parameters:

ptpPort [in] – PTP port

ptpPortMode [in]– Mode of operation of PTP port (Master or Slave)

This API will identify the time stamping capability of a PTP port by means of obtaining its mode of operation.

- Re–entrant : No
- ISR Callable : No

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Invalid parameters passed
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus

ixTimeSyncAccPTPPortConfigSet

(**IxTimeSyncAcc1588PTPPort**

ptpPort,

IxTimeSyncAcc1588PTPPortMode *ptpPortMode*

)

Configures the IEEE 1588 message detect on particular PTP port.

Parameters:

ptpPort [in] – PTP port to config

ptpPortMode [in]– Port to operate in Master or Slave mode

This API will enable the time stamping on a particular PTP port.

- Re–entrant : No
- ISR Callable : No

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Invalid parameters passed
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus *ixTimeSyncAccPTPRxPoll* (**IxTimeSyncAcc1588PTPPort** *ptpPort*,

IxTimeSyncAccPtpMsgData * *ptpMsgData*

)

Polls the IEEE 1588 message/time stamp detect status on a particular PTP Port on the Receive side.

Parameters:

ptpPort [in] – PTP port to poll
ptpMsgData [out] – Current TimeStamp and other Data

This API will poll for the availability of a time stamp on the received Sync (Slave) or Delay_Req (Master) messages. The client application will provide the buffer.

- Re-entrant : No
- ISR Callable : No

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Invalid parameters passed
- ◇ IX_TIMESYNCACC_NOTIMESTAMP – No time stamp available
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

```
IxTimeSyncAccStatus ixTimeSyncAccPTPTxPoll ( IxTimeSyncAcc1588PTPPort ptpPort,  
                                              IxTimeSyncAccPtpMsgData * ptpMsgData  
                                              )
```

Polls the IEEE 1588 message/time stamp detect status on a particular PTP Port on the Transmit side.

Parameters:

ptpPort [in] – PTP port to poll
ptpMsgData [out] – Current TimeStamp and other Data

This API will poll for the availability of a time stamp on the transmitted Sync (Master) or Delay_Req (Slave) messages. The client application will provide the buffer.

- Re-entrant : No
- ISR Callable : No

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Invalid parameters passed
- ◇ IX_TIMESYNCACC_NOTIMESTAMP – No time stamp available
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

```
IxTimeSyncAccStatus ixTimeSyncAccReset ( void )
```

Resets the IEEE 1588 hardware assist block.

Sets the reset bit in the IEEE1588 silicon which fully resets the silicon block

- Reentrant : yes
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus ixTimeSyncAccShow (void)

Displays the Time Sync current status.

This API will display status on the current configuration of the IEEE 1588 hardware assist block, contents of the various time stamp registers, outstanding interrupts and/or events.

Note that this is intended for debug only, and in contrast to the other functions, it does not clear the any of the status bits associated with active timestamps and so is passive in its nature.

- Reentrant : yes
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus ixTimeSyncAccStatsGet (**IxTimeSyncAccStats** * *timeSyncStats*)

Returns the IxTimeSyncAcc Statistics in the client supplied buffer.

Parameters:

timeSyncStats [out] – TimeSync statistics counter values

This API will return the statistics of the received or transmitted messages.

NOTE: 1) These counters are updated only when the client polls for the time stamps or interrupt are enabled. This is because the IxTimeSyncAcc module does not either transmit or receive messages and does only run the code when explicit requests received by client application.

2) These statistics reflect the number of valid PTP messages exchanged in Master and Slave modes but includes all the messages (including valid non-PTP messages) while operating in the Any mode.

- Reentrant : no
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – NULL parameter passed
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

void ixTimeSyncAccStatsReset (void)

Reset Time Sync statistics.

This API will reset the statistics counters of the TimeSync access layer.

- Reentrant : yes
- ISR Callable: no

Returns:

◇ None

IxTimeSyncAccStatus ixTimeSyncAccSystemTimeGet (**IxTimeSyncAccTimeValue** * *systemTime*)

Gets the System Time from the IEEE 1588 hardware assist block.

Parameters:

systemTime [out] – Copy the current System Time into the client application provided buffer

This API will get the SystemTime from IEEE1588 block and return to client

- Re-entrant : no
- ISR Callable : no

Returns:

◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
◇ IX_TIMESYNCACC_INVALIDPARAM – Invalid parameters passed
◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus ixTimeSyncAccSystemTimeSet (**IxTimeSyncAccTimeValue** *systemTime*)

Sets the System Time in the IEEE 1588 hardware assist block.

Parameters:

systemTime [in] – Value to set System Time

This API will set the SystemTime to given value.

- Re-entrant : yes
- ISR Callable : no

Returns:

◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus ixTimeSyncAccTargetTimeGet (**IxTimeSyncAccTimeValue** * *targetTime*)

Gets the Target Time in the IEEE 1588 hardware assist block.

Parameters:

targetTime [out] – Copy current time to client provided buffer

This API will get the Target Time from IEEE 1588 block and return to the client application

- Re-entrant : yes
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Null parameter passed
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus ixTimeSyncAccTargetTimeInterruptDisable (void)

Disables the interrupt for the condition explained in the function description of **ixTimeSyncAccTargetTimeInterruptEnable**.

This API will disable the Target Time interrupt.

NOTE: The client application needs to ensure that the APIs **ixTimeSyncAccTargetTimeInterruptEnable**, **ixTimeSyncAccTargetTimeSet** and **ixTimeSyncAccTargetTimeInterruptDisable** are accessed in mutual exclusive manner with respect to each other.

- Re-entrant : no
- ISR Callable : yes

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus (**IxTimeSyncAccTargetTimeCallback***targetTimeCallback*)
ixTimeSyncAccTargetTimeInterruptEnable

Enables the interrupt to verify the condition where the System Time greater or equal to the Target Time in the IEEE 1588 hardware assist block. If the condition is true an interrupt will be sent to Intel XScale(R) Processor.

Parameters:

targetTimeCallback [in] – Callback to be invoked when interrupt fires

This API will enable the Target Time reached/hit condition interrupt.

NOTE: The client application needs to ensure that the APIs **ixTimeSyncAccTargetTimeInterruptEnable**, **ixTimeSyncAccTargetTimeSet** and **ixTimeSyncAccTargetTimeInterruptDisable** are accessed in mutual exclusive manner with respect to each other.

- Re-entrant : no
- ISR Callable : yes

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Null parameter passed for callback
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

```
IxTimeSyncAccStatus ixTimeSyncAccTargetTimePoll ( BOOL * ttmPollFlag,
                                                    IxTimeSyncAccTimeValue * targetTime
                                                    )
```

Poll to verify the condition where the System Time greater or equal to the Target Time in the IEEE 1588 hardware assist block. If the condition is true an event flag is set in the hardware.

Parameters:

- ttmPollFlag* [out] – TRUE if the target time reached/hit condition event set FALSE if the target time reached/hit condition event is not set
- targetTime* [out] – Capture current targetTime into client provided buffer

Poll the target time reached/hit condition status. Return true and the current target time value, if the condition is true else return false.

NOTE: The client application will need to clear the event flag that will be set as long as the condition that the System Time greater or equal to the Target Time is valid, in one of the following ways: 1) Invoke the API to change the target time 2) Change the system timer value

- Re-entrant : yes
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Null parameter passed
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred
- ◇ IX_TIMESYNCACC_INTERRUPTMODEINUSE – Interrupt mode in use

```
IxTimeSyncAccStatus ixTimeSyncAccTargetTimeSet ( IxTimeSyncAccTimeValue targetTime )
```

Sets the Target Time in the IEEE 1588 hardware assist block.

Parameters:

- targetTime* [in] – Value to set Target Time

This API will set the Target Time to a given value.

NOTE: The client application needs to ensure that the APIs **ixTimeSyncAccTargetTimeInterruptEnable**, **ixTimeSyncAccTargetTimeSet** and **ixTimeSyncAccTargetTimeInterruptDisable** are accessed in mutual exclusive manner with respect to each other.

- Reentrant : no
- ISR Callable : yes

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus ixTimeSyncAccTickRateGet (UINT32 * *tickRate*)

Gets the Tick Rate (Frequency Scaling Value) from the IEEE 1588 hardware assist block.

Parameters:

tickRate [out] – Current Tick Rate value in the IEEE 1588 block

This API will get the TickRate on IEE15588 block. Refer to **ixTimeSyncAccTickRateSet** for notes on usage of this value.

- Reentrant : yes
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_INVALIDPARAM – Invalid parameters passed
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

IxTimeSyncAccStatus ixTimeSyncAccTickRateSet (UINT32 *tickRate*)

Sets the Tick Rate (Frequency Scaling Value) in the IEEE 1588 hardware assist block.

Parameters:

tickRate [in] – Value to set Tick Rate

This API will set the Tick Rate (Frequency Scaling Value) in the IEEE 1588 block to the given value. The Accumulator register (not client visible) is incremented by this TickRate value every clock cycle. When the Accumulator overflows, the SystemTime is incremented by one. This TickValue can therefore be used to adjust the system timer.

- Re-entrant : yes
- ISR Callable : no

Returns:

- ◇ IX_TIMESYNCACC_SUCCESS – Operation is successful
- ◇ IX_TIMESYNCACC_FAILED – Internal error occurred

Intel (R) IXP400 Software Types (IxTypes)

Basic data types used by the IXP400 project.

Defines

```
#define OK  
#define ERROR
```

Typedefs

```
typedef int(* FUNCPTR )(void)  
typedef int STATUS
```

Detailed Description

Basic data types used by the IXP400 project.

Intel (R) IXP400 Software UART Access (IxUARTAcc) API

IXP400 UARTAcc Driver Public API.

Modules

Defines for Default Values

Default values which can be used for UART configuration.

Defines for IOCTL Commands

*IOCTL Commands (Request codes) which can be used with **ixUARTIoctl**.*

Defines for IOCTL Arguments *POSIX style IOCTL arguments which can be used with **ixUARTIoctl**.*

Data Structures

struct **ixUARTDev** *Device descriptor for the UART.*

struct **ixUARTDev** *Device descriptor for the UART.*

struct **ixUARTStats** *Statistics for the UART.*

struct **ixUARTStats** *Statistics for the UART.*

Enumerations

```
enum ixUARTMode {  
    INTERRUPT,  
    POLLED,  
    LOOPBACK  
} The mode to set to UART to.
```

Functions

PUBLIC IX_STATUS **ixUARTInit** (**ixUARTDev** *pUART) *Initialise the UART. This puts the chip in a quiescent state.*

PUBLIC IX_STATUS **ixUARTPollOutput** (**ixUARTDev** *pUART, int outChar) *Transmit a character in*

polled mode.

PUBLIC IX_STATUS **ixUARTPollInput** (ixUARTDev *pUART, char *inChar) *Receive a character in polled mode.*

PUBLIC IX_STATUS **ixUARTIoctl** (ixUARTDev *pUART, int cmd, void *arg) *Perform I/O control routines on the device.*

Detailed Description

IXP400 UARTAcc Driver Public API.

Enumeration Type Documentation

enum ixUARTMode

The mode to set to UART to.

Enumeration values:

INTERRUPT Interrupt mode – Not supported yet.

POLLED Polled mode.

LOOPBACK Loopback mode.

Definition at line **308** of file **IxUART.h**.

Function Documentation

IX_STATUS ixUARTInit (**ixUARTDev** * *pUART*)

Initialise the UART. This puts the chip in a quiescent state.

Parameters:

pUART **ixUARTDev** [in] – pointer to UART structure describing our device.

Precondition:

The base address for the UART must contain a valid value. Also the baud rate and hardware options must contain sensible values otherwise the defaults will be used as defined in ixUART.h

Postcondition:

UART is initialized and ready to send and receive data.

Note:

This function should only be called once per device.

Return values:

- IX_SUCCESS* – UART device successfully initialised.
- IX_FAIL* – Critical error, device not initialised.

```
IX_STATUS ixUARTIoctl ( ixUARTDev * pUART,
                        int          cmd,
                        void *       arg
                        )
```

Perform I/O control routines on the device.

Parameters:

- pUART* **ixUARTDev** [in] – pointer to UART structure describing our device.
- cmd* int [in] – an ioctl request code.
- arg* void* [in] – optional argument used to set the device mode, baud rate, and hardware options.

Return values:

- IX_SUCCESS* – requested feature was set/read successfully.
- IX_FAIL* – error setting/reading the requested feature.

See also:

IoctlCommandDefines

IoctlArgDefines

```
IX_STATUS ixUARTPollInput ( ixUARTDev * pUART,
                           char *       inChar
                           )
```

Receive a character in polled mode.

Parameters:

- pUART* **ixUARTDev** [in] – pointer to UART structure describing our device.
- *inChar* char [in] – character read from the device.

Precondition:

UART device must be initialised.

Return values:

- IX_SUCCESS* – character was successfully read.
- IX_FAIL* – input buffer empty (try again).

```
IX_STATUS ixUARTPollOutput ( ixUARTDev * pUART,  
                             int           outChar  
                             )
```

Transmit a character in polled mode.

Parameters:

pUART **ixUARTDev** [out] – pointer to UART structure describing our device.

outChar int [out] – character to transmit.

Precondition:

UART device must be initialised.

Return values:

IX_SUCCESS – character was successfully transmitted.

IX_FAIL – output buffer is full (try again).

Defines for Default Values

[Intel (R) IXP400 Software UART Access (IxUARTAcc) API]

Default values which can be used for UART configuration.

Defines

#define IX_UART_DEF_OPTS

The default hardware options to set the UART to – no flow control, 8 bit word, 1 stop bit, no parity.

#define IX_UART_DEF_XMIT

The default UART FIFO size – must be no bigger than 64.

#define IX_UART_DEF_BAUD

The default UART baud rate – 9600.

#define IX_UART_MIN_BAUD

The minimum UART baud rate – 9600.

#define IX_UART_MAX_BAUD

The maximum UART baud rate – 926100.

#define IX_UART_XTAL

The UART clock speed.

Detailed Description

Default values which can be used for UART configuration.

See also:

ixUARTDev

Define Documentation

#define IX_UART_DEF_BAUD

The default UART baud rate – 9600.

Definition at line **72** of file **IxUART.h**.

#define IX_UART_DEF_OPTS

The default hardware options to set the UART to – no flow control, 8 bit word, 1 stop bit, no parity.

Definition at line **54** of file **IxUART.h**.

```
#define IX_UART_DEF_XMIT
```

The default UART FIFO size – must be no bigger than 64.

Definition at line **63** of file **IxUART.h**.

```
#define IX_UART_MAX_BAUD
```

The maximum UART baud rate – 926100.

Definition at line **90** of file **IxUART.h**.

```
#define IX_UART_MIN_BAUD
```

The minimum UART baud rate – 9600.

Definition at line **81** of file **IxUART.h**.

```
#define IX_UART_XTAL
```

The UART clock speed.

Definition at line **99** of file **IxUART.h**.

Defines for IOCTL Commands

[Intel (R) IXP400 Software UART Access (IxUARTAcc) API]

IOCTL Commands (Request codes) which can be used with **ixUARTIoctl**.

Defines

#define IX_BAUD_SET
Set the baud rate.

#define IX_BAUD_GET
Get the baud rate.

#define IX_MODE_SET
Set the UART mode of operation.

#define IX_MODE_GET
Get the current UART mode of operation.

#define IX_OPTS_SET
Set the UART device options.

#define IX_OPTS_GET
Get the UART device options.

#define IX_STATS_GET
Get the UART statistics.

Detailed Description

IOCTL Commands (Request codes) which can be used with **ixUARTIoctl**.

Define Documentation

```
#define IX_BAUD_GET
```

Get the baud rate.

Definition at line **129** of file **IxUART.h**.

```
#define IX_BAUD_SET
```

Set the baud rate.

Definition at line **120** of file **IxUART.h**.

```
#define IX_MODE_GET
```

Get the current UART mode of operation.

Definition at line **145** of file **IxUART.h**.

```
#define IX_MODE_SET
```

Set the UART mode of operation.

Definition at line **136** of file **IxUART.h**.

```
#define IX_OPTS_GET
```

Get the UART device options.

Definition at line **163** of file **IxUART.h**.

```
#define IX_OPTS_SET
```

Set the UART device options.

Definition at line **154** of file **IxUART.h**.

```
#define IX_STATS_GET
```

Get the UART statistics.

Definition at line **172** of file **IxUART.h**.

Defines for IOCTL Arguments

[Intel (R) IXP400 Software UART Access (IxUARTAcc) API]

POSIX style IOCTL arguments which can be used with **ixUARTIoctl**.

Defines

#define CLOCAL

Software flow control.

#define CREAD

Enable interrupt receiver.

#define CSIZE

Characters size.

#define CS5

5 bits

#define CS6

6 bits

#define CS7

7 bits

#define CS8

8 bits

#define STOPB

Send two stop bits (else one).

#define PARENB

Parity detection enabled (else disabled).

#define PARODD

Odd parity (else even).

Detailed Description

POSIX style IOCTL arguments which can be used with **ixUARTIoctl**.

See also:

ixUARTMode

Define Documentation

#define CLOCAL

Software flow control.

Definition at line **197** of file **IxUART.h**.

#define CREAD

Enable interrupt receiver.

Definition at line **209** of file **IxUART.h**.

#define CS5

5 bits

Definition at line **233** of file **IxUART.h**.

#define CS6

6 bits

Definition at line **245** of file **IxUART.h**.

#define CS7

7 bits

Definition at line **257** of file **IxUART.h**.

#define CS8

8 bits

Definition at line **269** of file **IxUART.h**.

#define CSIZE

Characters size.

Definition at line **221** of file **IxUART.h**.

```
#define PARENB
```

Parity detection enabled (else disabled).

Definition at line **290** of file **IxUART.h**.

```
#define PARODD
```

Odd parity (else even).

Definition at line **302** of file **IxUART.h**.

```
#define STOPB
```

Send two stop bits (else one).

Definition at line **278** of file **IxUART.h**.

Intel (R) IXP400 Software Version ID (IxVersionId)

Version Identifiers.

Defines

#define IX_VERSION_ID

Version Identifier String.

#define IX_VERSION_ADSL_ID

This string will be updated with each customer release of the IXP400 ADSL driver package.

#define IX_VERSION_USBRNDIS_ID

This string will be updated with each customer release of the IXP400 USB Client driver package.

#define IX_VERSION_I2C_LINUX_ID

This string will be updated with each customer release of the IXP400 I2C Linux driver package.*

#define LINUX_ETHERNET_DRIVER_PATCH_ID

Linux Ethernet Driver Patch Version Identifier String.*

#define LINUX_ETHERNET_README_ID

Linux Ethernet Readme version Identifier String.*

#define LINUX_I2C_DRIVER_README_ID

Linux I2C driver Readme version Identifier String.*

#define IX_VERSION_INTERNAL_ID

Internal Release Identifier String.

#define IX_VERSION_COMPATIBLE_TORNADO

Compatible Tornado Version Identifier.

#define IX_VERSION_COMPATIBLE_LINUX

Compatible Linux Version Identifier.*

Detailed Description

Version Identifiers.

Define Documentation

```
#define IX_VERSION_ADSL_ID
```

This string will be updated with each customer release of the IXP400 ADSL driver package.

Definition at line **36** of file **IxVersionId.h**.

```
#define IX_VERSION_COMPATIBLE_LINUX
```

Compatible Linux* Version Identifier.

Definition at line **88** of file **IxVersionId.h**.

```
#define IX_VERSION_COMPATIBLE_TORNADO
```

Compatible Tornado Version Identifier.

Definition at line **83** of file **IxVersionId.h**.

```
#define IX_VERSION_I2C_LINUX_ID
```

This string will be updated with each customer release of the IXP400 I2C Linux* driver package.

Definition at line **49** of file **IxVersionId.h**.

```
#define IX_VERSION_ID
```

Version Identifier String.

This string will be updated with each customer release of the IXP400 Software.

Definition at line **30** of file **IxVersionId.h**.

```
#define IX_VERSION_INTERNAL_ID
```

Internal Release Identifier String.

This string will be updated with each internal release (SQA drop) of the IXP400 Software.

Definition at line **78** of file **IxVersionId.h**.

```
#define IX_VERSION_USBRNDIS_ID
```

This string will be updated with each customer release of the IXP400 USB Client driver package.

Definition at line **43** of file **IxVersionId.h**.

```
#define LINUX_ETHERNET_DRIVER_PATCH_ID
```

Linux* Ethernet Driver Patch Version Identifier String.

This string will be updated with each release of Linux* Ethernet Patch

Definition at line **56** of file **IxVersionId.h**.

```
#define LINUX_ETHERNET_README_ID
```

Linux* Ethernet Readme version Identifier String.

This string will be updated with each release of Linux* Ethernet Readme

Definition at line **63** of file **IxVersionId.h**.

```
#define LINUX_I2C_DRIVER_README_ID
```

Linux* I2C driver Readme version Identifier String.

This string will be updated with each release of Linux* I2C Driver Readme

Definition at line **70** of file **IxVersionId.h**.

IX_OSAL_ATTRIBUTE_PACKED Struct Reference

[Intel (R) IXP400 Software Ethernet Database (IxEthDB) API]

The IEEE 802.3 Ethernet MAC address structure.

Data Fields

UINT8 **macAddress** [IX_IEEE803_MAC_ADDRESS_SIZE]

Detailed Description

The IEEE 802.3 Ethernet MAC address structure.

The data should be packed with bytes xx:xx:xx:xx:xx:xx

Note:

The data must be packed in network byte order.

Definition at line **236** of file **IxEthDB.h**.

The documentation for this struct was generated from the following file:

- **IxEthDB.h**

IxAtmdAccUtopiaConfig Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia configuration.

Data Fields

IxAtmdAccUtopiaConfig::UtTxConfig_ utTxConfig
Tx config Utopia register.

IxAtmdAccUtopiaConfig::UtTxStatsConfig_ utTxStatsConfig
Tx stats config Utopia register.

IxAtmdAccUtopiaConfig::UtTxDefineIdle_ utTxDefineIdle
Tx idle cell config Utopia register.

IxAtmdAccUtopiaConfig::UtTxEnableFields_ utTxEnableFields
Tx enable Utopia register.

IxAtmdAccUtopiaConfig::UtTxTransTable0_ utTxTransTable0
Tx translation table.

IxAtmdAccUtopiaConfig::UtTxTransTable1_ utTxTransTable1
Tx translation table.

IxAtmdAccUtopiaConfig::UtTxTransTable2_ utTxTransTable2
Tx translation table.

IxAtmdAccUtopiaConfig::UtTxTransTable3_ utTxTransTable3
Tx translation table.

IxAtmdAccUtopiaConfig::UtTxTransTable4_ utTxTransTable4
Tx translation table.

IxAtmdAccUtopiaConfig::UtTxTransTable5_ utTxTransTable5
Tx translation table.

IxAtmdAccUtopiaConfig::UtRxConfig_ utRxConfig
Rx config Utopia register.

IxAtmdAccUtopiaConfig::UtRxStatsConfig_ utRxStatsConfig
Rx stats config Utopia register.

IxAtmdAccUtopiaConfig::UtRxDefineIdle_ utRxDefineIdle
Rx idle cell config Utopia register.

IxAtmdAccUtopiaConfig::UtRxEnableFields_	utRxEnableFields <i>Rx enable Utopia register.</i>
IxAtmdAccUtopiaConfig::UtRxTransTable0_	utRxTransTable0 <i>Rx translation table.</i>
IxAtmdAccUtopiaConfig::UtRxTransTable1_	utRxTransTable1 <i>Rx translation table.</i>
IxAtmdAccUtopiaConfig::UtRxTransTable2_	utRxTransTable2 <i>Rx translation table.</i>
IxAtmdAccUtopiaConfig::UtRxTransTable3_	utRxTransTable3 <i>Rx translation table.</i>
IxAtmdAccUtopiaConfig::UtRxTransTable4_	utRxTransTable4 <i>Rx translation table.</i>
IxAtmdAccUtopiaConfig::UtRxTransTable5_	utRxTransTable5 <i>Rx translation table.</i>
IxAtmdAccUtopiaConfig::UtSysConfig_	utSysConfig <i>NPE debug config.</i>

Detailed Description

Utopia configuration.

This structure is used to set the Utopia parameters

- contains the values of Utopia registers, to be set during initialisation
- contains debug commands for NPE, to be used during development steps

Note:

- the exact description of all parameters is done in the Utopia reference documents.

Definition at line **979** of file **IxAtmdAccCtrl.h**.

Field Documentation

```
struct IxAtmdAccUtopiaConfig::UtRxConfig_ IxAtmdAccUtopiaConfig::utRxConfig
```

Rx config Utopia register.

```
struct IxAtmdAccUtopiaConfig::UtRxDefineIdle_ IxAtmdAccUtopiaConfig::utRxDefineIdle
```

Rx idle cell config Utopia register.

```
struct IxAtmdAccUtopiaConfig::UtRxEnableFields_ IxAtmdAccUtopiaConfig::utRxEnableFields
```

Rx enable Utopia register.

```
struct IxAtmdAccUtopiaConfig::UtRxStatsConfig_ IxAtmdAccUtopiaConfig::utRxStatsConfig
```

Rx stats config Utopia register.

```
struct IxAtmdAccUtopiaConfig::UtRxTransTable0_ IxAtmdAccUtopiaConfig::utRxTransTable0
```

Rx translation table.

```
struct IxAtmdAccUtopiaConfig::UtRxTransTable1_ IxAtmdAccUtopiaConfig::utRxTransTable1
```

Rx translation table.

```
struct IxAtmdAccUtopiaConfig::UtRxTransTable2_ IxAtmdAccUtopiaConfig::utRxTransTable2
```

Rx translation table.

```
struct IxAtmdAccUtopiaConfig::UtRxTransTable3_ IxAtmdAccUtopiaConfig::utRxTransTable3
```

Rx translation table.

```
struct IxAtmdAccUtopiaConfig::UtRxTransTable4_ IxAtmdAccUtopiaConfig::utRxTransTable4
```

Rx translation table.

```
struct IxAtmdAccUtopiaConfig::UtRxTransTable5_ IxAtmdAccUtopiaConfig::utRxTransTable5
```

Rx translation table.

```
struct IxAtmdAccUtopiaConfig::UtSysConfig_ IxAtmdAccUtopiaConfig::utSysConfig
```

NPE debug config.

```
struct IxAtmdAccUtopiaConfig::UtTxConfig_ IxAtmdAccUtopiaConfig::utTxConfig
```

Tx config Utopia register.

```
struct IxAtmdAccUtopiaConfig::UtTxDefineIdle_ IxAtmdAccUtopiaConfig::utTxDefineIdle
```

Tx idle cell config Utopia register.

```
struct IxAtmdAccUtopiaConfig::UtTxEnableFields_ IxAtmdAccUtopiaConfig::utTxEnableFields
```

Tx enable Utopia register.

```
struct IxAtmdAccUtopiaConfig::UtTxStatsConfig_ IxAtmdAccUtopiaConfig::utTxStatsConfig
```

Tx stats config Utopia register.

```
struct IxAtmdAccUtopiaConfig::UtTxTransTable0_ IxAtmdAccUtopiaConfig::utTxTransTable0
```

Tx translation table.

```
struct IxAtmdAccUtopiaConfig::UtTxTransTable1_ IxAtmdAccUtopiaConfig::utTxTransTable1
```

Tx translation table.

```
struct IxAtmdAccUtopiaConfig::UtTxTransTable2_ IxAtmdAccUtopiaConfig::utTxTransTable2
```

Tx translation table.

```
struct IxAtmdAccUtopiaConfig::UtTxTransTable3_ IxAtmdAccUtopiaConfig::utTxTransTable3
```

Tx translation table.

```
struct IxAtmdAccUtopiaConfig::UtTxTransTable4_ IxAtmdAccUtopiaConfig::utTxTransTable4
```

Tx translation table.

```
struct IxAtmdAccUtopiaConfig::UtTxTransTable5_ IxAtmdAccUtopiaConfig::utTxTransTable5
```

Tx translation table.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxConfig_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx config Register.

Data Fields

unsigned

int **rxInterface**:1

[31] Utopia Receive Interface

unsigned

int **rxMode**:1

[30] Utopia Receive Mode

unsigned

int **rxOctet**:1

[29] Utopia Receive cell transfer protocol

unsigned

int **rxParity**:1

[28] Utopia Receive Parity Checking enable

unsigned

int **rxEvenParity**:1

[27] Utopia Receive Parity Mode

- 1 – Check for Even Parity
- 0 – Check for Odd Parity.

unsigned

int **rxHEC**:1

[26] RxHEC Header Error Check Mode

unsigned

int **rxCOSET**:1

[25] If enabled the HEC is Exclusive–ORÆed with the value 0x55 before being tested with the received HEC

unsigned

int **rxHECpass**:1

[24] Specifies if the incoming cell HEC byte should be transferred after optional processing to the

NPE2 Coprocessor Bus Interface or if it should be discarded

unsigned

int **reserved_1**:1

[23] These bits are always 0

unsigned

int **rxCellSize**:7

[22:16] Receive cell size

unsigned

int **rxHashEnbGFC**:1

[15] Specifies if the VPI field [11:8]/GFC field should be included in the Hash data input or if the bits should be padded with 1Æb0

unsigned

int **rxPreHash**:1

[14] Enable Pre-hash value generation

unsigned

int **reserved_2**:1

[13] These bits are always 0

unsigned

int **rxAddrRange**:5

[12:8] In ATM master, MPHY mode, this register specifies the upper limit of the PHY polling logical range

unsigned

int **reserved_3**:3

[7-5] These bits are always 0 .

unsigned

int **rxPHYAddr**:5

[4:0] When configured as a slave in an MPHY system this register specifies the physical address of the PHY

Detailed Description

Utopia Rx config Register.

Definition at line **1316** of file **IxAtmdAccCtrl.h**.

Field Documentation

```
unsigned int IxAtmdAccUtopiaConfig::UtrxConfig::reserved_1
```


[23] These bits are always 0

Definition at line **1359** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::reserved_2
```

[13] These bits are always 0

Definition at line **1376** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::reserved_3
```

[7–5] These bits are always 0 .

Definition at line **1383** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::rxAddrRange
```

[12:8] In ATM master, MPHY mode, this register specifies the upper limit of the PHY polling logical range

The number of active PHYs are RxAddrRange + 1.

Definition at line **1378** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::rxCellSize
```

[22:16] Receive cell size

Configures the receive cell size. Values between 52–64 are valid

Definition at line **1361** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::rxCOSET
```

[25] If enabled the HEC is Exclusive-ORed with the value 0x55 before being tested with the received HEC

- 1 – Enable HEC ExOR with value 0x55.
- 0 – Use generated HEC value.

Definition at line **1348** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::rxEvenParity
```

[27] Utopia Receive Parity Mode

- 1 – Check for Even Parity
- 0 – Check for Odd Parity.

Definition at line **1339** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::rxHashEnbGFC
```

[15] Specifies if the VPI field [11:8]/GFC field should be included in the Hash data input or if the bits should be padded with 1Æb0

- 1 – VPI [11:8]/GFC field valid and used in Hash residue calculation.
- 0 – VPI [11:8]/GFC field padded with 1Æb0

Definition at line **1364** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::rxHEC
```

[26] RxHEC Header Error Check Mode

Enables/disables cell header error checking on the received cell header.

- 1 – HEC checking enabled
- 0 – HEC checking disabled

Definition at line **1343** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::rxHECpass
```

[24] Specifies if the incoming cell HEC byte should be transferred after optional processing to the NPE2 Coprocessor Bus Interface or if it should be discarded

- 1 – HEC maintained 53-byte/UDC cell sent to NPE2.
- 0 – HEC discarded 52-byte/UDC cell sent to NPE2 coprocessor.

Definition at line **1353** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig::rxInterface
```

[31] Utopia Receive Interface

The following encoding is used to set the Utopia Receive interface as ATM master or PHY slave:

- 1 – PHY

- 0 – ATM

Definition at line **1319** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig_::rxMode
```

[30] Utopia Receive Mode

The following encoding is used to set the Utopia Receive mode to SPHY or MPHY:

- 1 – SPHY
- 0 – MPHY

Definition at line **1324** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig_::rxOctet
```

[29] Utopia Receive cell transfer protocol

Used to set the Utopia cell transfer protocol to Octet–level handshaking. Note this is only applicable in SPHY mode.

- 1 – Octet–handshaking enabled
- 0 – Cell–handshaking enabled

Definition at line **1329** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig_::rxParity
```

[28] Utopia Receive Parity Checking enable

- 1 – Parity checking enabled
- 0 – Parity checking disabled

Definition at line **1335** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig_::rxPHYAddr
```

[4:0] When configured as a slave in an MPHY system this register specifies the physical address of the PHY

Definition at line **1384** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxConfig_::rxPreHash
```

[14] Enable Pre-hash value generation

Specifies if the incoming cell data should be pre-hashed to allow VPI/VCI header look-up in a hash table.

- 1 – Pre-hashing enabled
- 0 – Pre-hashing disabled

Definition at line **1370** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxDefinIdle_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx idle cells config Register.

Data Fields

unsigned int **vpi**:12

[31:20] ATM VPI [11:0] OR GFC [3:0] and VPI [7:0]

- *Note: if VCIdleRxGFC is set to 0 the GFC field is ignored in test*

unsigned int **vci**:16

[19:4] ATM VCI [15:0]

unsigned int **pti**:3

[3:1] ATM PTI PTI [2:0]

- *Note: if VCIdleRxPTI is set to 0 the PTI field is ignored in test.*

unsigned int **clp**:1

[0] ATM CLP [0]

- *Note: if VCIdleRxCLP is set to 0 the CLP field is ignored in test.*

Detailed Description

Utopia Rx idle cells config Register.

Definition at line **1418** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtRxDefineIdle_::clp

[0] ATM CLP [0]

- Note: if VCIdleRxCLP is set to 0 the CLP field is ignored in test.

Definition at line **1429** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxDefineIdle_::pti

[3:1] ATM PTI PTI [2:0]

- Note: if VCIdleRxPTI is set to 0 the PTI field is ignored in test.

Definition at line **1426** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxDefineIdle_::vci

[19:4] ATM VCI [15:0]

Definition at line **1424** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxDefineIdle_::vpi

[31:20] ATM VPI [11:0] OR GFC [3:0] and VPI [7:0]

- Note: if VCIdleRxGFC is set to 0 the GFC field is ignored in test

Definition at line **1421** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxEnableFields_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx enable Register.

Data Fields

unsigned

int **defineRxIdleGFC**:1

[31] This register is used to include or exclude the GFC field of the ATM header when testing for Idle cells

unsigned

int **defineRxIdlePTI**:1

[30] This register is used to include or exclude the PTI field of the ATM header when testing for Idle cells

unsigned

int **defineRxIdleCLP**:1

[29] This register is used to include or exclude the CLP field of the ATM header when testing for Idle cells

unsigned

int **phyStatsRxEnb**:1

[28] This register is used to enable or disable ATM statistics gathering based on the specified PHY address as defined in RxStatsConfig register

unsigned

int **vcStatsRxEnb**:1

[27] This register is used to enable or disable ATM statistics gathering based on a specific VPI/VCI address

unsigned

int **vcStatsRxGFC**:1

[26] This register is used to include or exclude the GFC field of the ATM header when ATM VPI/VCI statistics are enabled

unsigned

int **vcStatsRxPTI**:1

[25] This register is used to include or exclude the PTI field of the ATM header when ATM VPI/VCI statistics are enabled

unsigned

int **vcStatsRxCLP**:1

[24] This register is used to include or exclude the CLP field of the ATM header when ATM VPI/VCI statistics are enabled

unsigned

int **discardHecErr**:1

[23] Discard cells with an invalid HEC

unsigned

int **discardParErr**:1

[22] Discard cells containing parity errors

unsigned

int **discardIdle**:1

[21] Discard Idle Cells based on DefineIdle register values

- 1 – Discard IDLE cells
- 0 – IDLE cells passed

unsigned

int **enbHecErrCnt**:1

[20] Enable Receive HEC Error Count

unsigned

int **enbParErrCnt**:1

[19] Enable Parity Error Count

- 1 – Enable count of received cells containing Parity errors
- 0 – No count is maintained

unsigned

int **enbIdleCellCnt**:1

[18] Enable Receive Idle Cell Count

unsigned

int **enbSizeErrCnt**:1

[17] Enable Receive Size Error Count

unsigned

int **enbRxCellCnt**:1

[16] Enable Receive Valid Cell Count of non-idle/non-error cells

unsigned

int **reserved_1**:3

[15:13] These bits are always 0

unsigned

int **rxCellOvrInt**:1

[12] Enable CBI Utopia Receive Status Condition if the RxCellCount register overflows

unsigned

int **invalidHecOvrInt**:1

[11] Enable CBI Receive Status Condition if the InvalidHecCount register overflows

unsigned

int **invalidParOvrInt**:1

[10] Enable CBI Receive Status Condition if the InvalidParCount register overflows

- 1 – CBI Receive Condition asserted

unsigned

int **invalidSizeOvrInt**:1

[9] Enable CBI Receive Status Condition if the InvalidSizeCount register overflows

unsigned

int **rxIdleOvrInt**:1

[8] Enable CBI Receive Status Condition if the RxIdleCount overflows

unsigned

int **reserved_2**:3

[7:5] These bits are always 0

unsigned

int **rxAddrMask**:5

[4:0] This register is used as a mask to allow the user to increase the PHY receive address range

Detailed Description

Utopia Rx enable Register.

Definition at line **1438** of file **IxAtmdAccCtrl.h**.

Field Documentation

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::defineRxIdleCLP
```

[29] This register is used to include or exclude the CLP field of the ATM header when testing for Idle cells

- 1 – CLP field is valid.
- 0 – CLP field ignored.

Definition at line **1451** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::defineRxIdleGFC
```

[31] This register is used to include or exclude the GFC field of the ATM header when testing for Idle cells

- 1 – GFC field is valid.
- 0 – GFC field ignored.

Definition at line **1441** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::defineRxIdlePTI
```

[30] This register is used to include or exclude the PTI field of the ATM header when testing for Idle cells

- 1 – PTI field is valid.
- 0 – PTI field ignored.

Definition at line **1446** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::discardHecErr
```

[23] Discard cells with an invalid HEC

- 1 – Discard cells with HEC errors
- 0 – Cells with HEC errors are passed

Definition at line **1483** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::discardIdle
```

[21] Discard Idle Cells based on DefineIdle register values

- 1 – Discard IDLE cells
- 0 – IDLE cells passed

Definition at line **1491** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::discardParErr
```

[22] Discard cells containing parity errors

- 1 – Discard cells with parity errors
- 0 – Cells with parity errors are passed

Definition at line **1487** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::enbHecErrCnt

[20] Enable Receive HEC Error Count

- 1 – Enable count of received cells containing HEC errors
- 0 – No count is maintained.

Definition at line **1495** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::enbIdleCellCnt

[18] Enable Receive Idle Cell Count

- 1 – Enable count of Idle cells received.
- 0 – No count is maintained.

Definition at line **1503** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::enbParErrCnt

[19] Enable Parity Error Count

- 1 – Enable count of received cells containing Parity errors
- 0 – No count is maintained

Definition at line **1499** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::enbRxCellCnt

[16] Enable Receive Valid Cell Count of non-idle/non-error cells

- 1 – Enable count of valid cells received – non-idle/non-error
- 0 – No count is maintained.

Definition at line **1511** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::enbSizeErrCnt

[17] Enable Receive Size Error Count

- 1 – Enable count of received cells of incorrect size

- 0 – No count is maintained.

Definition at line **1507** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtrxEnableFields_::invalidHecOvrInt
```

[11] Enable CBI Receive Status Condition if the InvalidHecCount register overflows

- 1 – CBI Receive Condition asserted.
- 0 – No CBI Receive Condition asserted

Definition at line **1522** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtrxEnableFields_::invalidParOvrInt
```

[10] Enable CBI Receive Status Condition if the InvalidParCount register overflows

- 1 – CBI Receive Condition asserted
- 0 – No CBI Receive Condition asserted

Definition at line **1527** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtrxEnableFields_::invalidSizeOvrInt
```

[9] Enable CBI Receive Status Condition if the InvalidSizeCount register overflows

- 1 – CBI Receive Status Condition asserted.
- 0 – No CBI Receive Status asserted

Definition at line **1532** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtrxEnableFields_::phyStatsRxEnb
```

[28] This register is used to enable or disable ATM statistics gathering based on the specified PHY address as defined in RxStatsConfig register

- 1 – Enable statistics for specified receive PHY address.
- 0 – Disable statistics for specified receive PHY address.

Definition at line **1456** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtrxEnableFields_::reserved_1
```

[15:13] These bits are always 0

Definition at line **1515** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::reserved_2
```

[7:5] These bits are always 0

Definition at line **1541** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::rxAddrMask
```

[4:0] This register is used as a mask to allow the user to increase the PHY receive address range

The register should be programmed with the address-range limit, i.e. if set to 0x3 the address range increases to a maximum of 4 addresses.

Definition at line **1543** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::rxCellOvrInt
```

[12] Enable CBI Utopia Receive Status Condition if the RxCellCount register overflows

- 1 – CBI Receive Status asserted.
- 0 – No CBI Receive Status asserted.

Definition at line **1517** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::rxIdleOvrInt
```

[8] Enable CBI Receive Status Condition if the RxIdleCount overflows

- 1 – CBI Receive Condition asserted.
- 0 – No CBI Receive Condition asserted

Definition at line **1537** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxEnableFields_::vcStatsRxCLP
```

[24] This register is used to include or exclude the CLP field of the ATM header when ATM VPI/VCI statistics are enabled

- 1 – CLP field is valid.
- 0 – CLP field ignored.

Definition at line **1478** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtrxEnableFields_::vcStatsRxEnb
```

[27] This register is used to enable or disable ATM statistics gathering based on a specific VPI/VCI address

- 1 – Enable statistics for specified VPI/VCI address.
- 0 – Disable statistics for specified VPI/VCI address.

Definition at line **1462** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtrxEnableFields_::vcStatsRxGFC
```

[26] This register is used to include or exclude the GFC field of the ATM header when ATM VPI/VCI statistics are enabled

GFC is only available at the UNI and uses the first 4-bits of the VPI field.

- 1 – GFC field is valid.
- 0 – GFC field ignored.

Definition at line **1467** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtrxEnableFields_::vcStatsRxPTI
```

[25] This register is used to include or exclude the PTI field of the ATM header when ATM VPI/VCI statistics are enabled

- 1 – PTI field is valid.
- 0 – PTI field ignored.

Definition at line **1473** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxStatsConfig_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx stats config Register.

Data Fields

unsigned int **vpi**:12

[31:20] ATM VPI VPI [11:0] OR GFC [3:0] and VPI [7:0]

- *Note: if VCStatsRxGFC is set to 0 the GFC field is ignored in test*

unsigned int **vci**:16

[19:4] VCI [15:0] or PHY Address [4]

unsigned int **pti**:3

[3:1] PTI [2:0] or or PHY Address [3:1]

- *Note: if VCStatsRxPTI is set to 0 the PTI field is ignored in test*

unsigned int **clp**:1

[0] CLP [0] or PHY Address [0]

- *Note: if VCStatsRxCLP is set to 0 the CLP field is ignored in test*

Detailed Description

Utopia Rx stats config Register.

Definition at line **1394** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtRxStatsConfig_::clp

[0] CLP [0] or PHY Address [0]

- Note: if VCStatsRxCLP is set to 0 the CLP field is ignored in test
- Note: if VCStatsRxEnb is set to 0 only the PHY port address is used for statistics gathering..

Definition at line **1407** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxStatsConfig_::pti

[3:1] PTI [2:0] or or PHY Address [3:1]

- Note: if VCStatsRxPTI is set to 0 the PTI field is ignored in test
- Note: if VCStatsRxEnb is set to 0 only the PHY port address is used for statistics gathering..

Definition at line **1402** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxStatsConfig_::vci

[19:4] VCI [15:0] or PHY Address [4]

Definition at line **1400** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxStatsConfig_::vpi

[31:20] ATM VPI VPI [11:0] OR GFC [3:0] and VPI [7:0]

- Note: if VCStatsRxGFC is set to 0 the GFC field is ignored in test

Definition at line **1397** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxTransTable0_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx translation table Register.

Data Fields

- unsigned int **phy0**:5
[31–27] Rx Mapping value of logical phy 0
- unsigned int **phy1**:5
[26–22] Rx Mapping value of logical phy 1
- unsigned int **phy2**:5
[21–17] Rx Mapping value of logical phy 2
- unsigned int **reserved_1**:1
[16] These bits are always 0
- unsigned int **phy3**:5
[15–11] Rx Mapping value of logical phy 3
- unsigned int **phy4**:5
[10–6] Rx Mapping value of logical phy 4
- unsigned int **phy5**:5
[5–1] Rx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0
-

Detailed Description

Utopia Rx translation table Register.

Definition at line 1554 of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable0_::phy0

[31–27] Rx Mapping value of logical phy 0

Definition at line **1557** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable0_::phy1
```

[26–22] Rx Mapping value of logical phy 1

Definition at line **1559** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable0_::phy2
```

[21–17] Rx Mapping value of logical phy 2

Definition at line **1561** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable0_::phy3
```

[15–11] Rx Mapping value of logical phy 3

Definition at line **1565** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable0_::phy4
```

[10–6] Rx Mapping value of logical phy 4

Definition at line **1567** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable0_::phy5
```

[5–1] Rx Mapping value of logical phy 5

Definition at line **1569** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable0_::reserved_1
```

[16] These bits are always 0

Definition at line **1563** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable0_::reserved_2
```

[0] These bits are always 0

Definition at line **1571** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxTransTable1_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx translation table Register.

Data Fields

- unsigned int **phy6**:5
[31–27] Rx Mapping value of logical phy 6
- unsigned int **phy7**:5
[26–22] Rx Mapping value of logical phy 7
- unsigned int **phy8**:5
[21–17] Rx Mapping value of logical phy 8
- unsigned int **reserved_1**:1
[16–0] These bits are always 0
- unsigned int **phy9**:5
[15–11] Rx Mapping value of logical phy 3
- unsigned int **phy10**:5
[10–6] Rx Mapping value of logical phy 4
- unsigned int **phy11**:5
[5–1] Rx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Rx translation table Register.

Definition at line 1581 of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable1_::phy10

[10–6] Rx Mapping value of logical phy 4

Definition at line **1594** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable1_::phy11
```

[5–1] Rx Mapping value of logical phy 5

Definition at line **1596** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable1_::phy6
```

[31–27] Rx Mapping value of logical phy 6

Definition at line **1584** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable1_::phy7
```

[26–22] Rx Mapping value of logical phy 7

Definition at line **1586** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable1_::phy8
```

[21–17] Rx Mapping value of logical phy 8

Definition at line **1588** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable1_::phy9
```

[15–11] Rx Mapping value of logical phy 3

Definition at line **1592** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable1_::reserved_1
```

[16–0] These bits are always 0

Definition at line **1590** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable1_::reserved_2
```

[0] These bits are always 0

Definition at line **1598** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxTransTable2_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx translation table Register.

Data Fields

- unsigned int **phy12**:5
[31–27] Rx Mapping value of logical phy 6
- unsigned int **phy13**:5
[26–22] Rx Mapping value of logical phy 7
- unsigned int **phy14**:5
[21–17] Rx Mapping value of logical phy 8
- unsigned int **reserved_1**:1
[16–0] These bits are always 0
- unsigned int **phy15**:5
[15–11] Rx Mapping value of logical phy 3
- unsigned int **phy16**:5
[10–6] Rx Mapping value of logical phy 4
- unsigned int **phy17**:5
[5–1] Rx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Rx translation table Register.

Definition at line **1608** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable2_::phy12

[31–27] Rx Mapping value of logical phy 6

Definition at line **1611** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable2_::phy13
```

[26–22] Rx Mapping value of logical phy 7

Definition at line **1613** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable2_::phy14
```

[21–17] Rx Mapping value of logical phy 8

Definition at line **1615** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable2_::phy15
```

[15–11] Rx Mapping value of logical phy 3

Definition at line **1619** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable2_::phy16
```

[10–6] Rx Mapping value of logical phy 4

Definition at line **1621** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable2_::phy17
```

[5–1] Rx Mapping value of logical phy 5

Definition at line **1623** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable2_::reserved_1
```

[16–0] These bits are always 0

Definition at line **1617** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable2_::reserved_2
```


[0] These bits are always 0

Definition at line **1625** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxTransTable3_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx translation table Register.

Data Fields

- unsigned int **phy18**:5
[31–27] Rx Mapping value of logical phy 6
- unsigned int **phy19**:5
[26–22] Rx Mapping value of logical phy 7
- unsigned int **phy20**:5
[21–17] Rx Mapping value of logical phy 8
- unsigned int **reserved_1**:1
[16–0] These bits are always 0
- unsigned int **phy21**:5
[15–11] Rx Mapping value of logical phy 3
- unsigned int **phy22**:5
[10–6] Rx Mapping value of logical phy 4
- unsigned int **phy23**:5
[5–1] Rx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Rx translation table Register.

Definition at line 1633 of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable3_::phy18

[31–27] Rx Mapping value of logical phy 6

Definition at line **1636** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable3_::phy19
```

[26–22] Rx Mapping value of logical phy 7

Definition at line **1638** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable3_::phy20
```

[21–17] Rx Mapping value of logical phy 8

Definition at line **1640** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable3_::phy21
```

[15–11] Rx Mapping value of logical phy 3

Definition at line **1644** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable3_::phy22
```

[10–6] Rx Mapping value of logical phy 4

Definition at line **1646** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable3_::phy23
```

[5–1] Rx Mapping value of logical phy 5

Definition at line **1648** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable3_::reserved_1
```

[16–0] These bits are always 0

Definition at line **1642** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable3_::reserved_2
```

[0] These bits are always 0

Definition at line **1650** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxTransTable4_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx translation table Register.

Data Fields

- unsigned int **phy24**:5
[31–27] Rx Mapping value of logical phy 6
- unsigned int **phy25**:5
[26–22] Rx Mapping value of logical phy 7
- unsigned int **phy26**:5
[21–17] Rx Mapping value of logical phy 8
- unsigned int **reserved_1**:1
[16–0] These bits are always 0
- unsigned int **phy27**:5
[15–11] Rx Mapping value of logical phy 3
- unsigned int **phy28**:5
[10–6] Rx Mapping value of logical phy 4
- unsigned int **phy29**:5
[5–1] Rx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Rx translation table Register.

Definition at line **1658** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable4_::phy24

[31–27] Rx Mapping value of logical phy 6

Definition at line **1661** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable4_::phy25
```

[26–22] Rx Mapping value of logical phy 7

Definition at line **1663** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable4_::phy26
```

[21–17] Rx Mapping value of logical phy 8

Definition at line **1665** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable4_::phy27
```

[15–11] Rx Mapping value of logical phy 3

Definition at line **1669** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable4_::phy28
```

[10–6] Rx Mapping value of logical phy 4

Definition at line **1671** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable4_::phy29
```

[5–1] Rx Mapping value of logical phy 5

Definition at line **1673** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable4_::reserved_1
```

[16–0] These bits are always 0

Definition at line **1667** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable4_::reserved_2
```

[0] These bits are always 0

Definition at line **1675** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtRxTransTable5_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx translation table Register.

Data Fields

unsigned int **phy30**:5
[31–27] Rx Mapping value of logical phy 6

unsigned int **reserved_1**:27
[26–0] These bits are always 0

Detailed Description

Utopia Rx translation table Register.

Definition at line **1683** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable5_::phy30

[31–27] Rx Mapping value of logical phy 6

Definition at line **1686** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtRxTransTable5_::reserved_1

[26–0] These bits are always 0

Definition at line **1688** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtSysConfig_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

NPE setup Register.

Data Fields

unsigned int **reserved_1**:2

[31–30] These bits are always 0

unsigned int **txEnbFSM**:1

[29] Enables the operation of the Utopia Transmit FSM

- 1 – FSM enabled
- 0 – FSM inactive

unsigned int **rxEnbFSM**:1

[28] Enables the operation of the Utopia Receive FSM

- 1 – FSM enabled
- 0 – FSM inactive

unsigned int **disablePins**:1

[27] Disable Utopia interface I/O pins forcing the signals to an inactive state

unsigned int **tstLoop**:1

[26] Test Loop Back Enable

unsigned int **txReset**:1

[25] Resets the Utopia Coprocessor transmit module to a known state

unsigned int **rxReset**:1

[24] Resets the Utopia Coprocessor receive module to a known state

unsigned int **reserved_2**:24

[23–0] These bits are always 0

Detailed Description

NPE setup Register.

Definition at line **1697** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtSysConfig_::disablePins

[27] Disable Utopia interface I/O pins forcing the signals to an inactive state

Note that this bit is set on reset and must be de-asserted

- 0 – Normal data transfer
- 1 – Utopia interface pins are forced inactive

Definition at line **1709** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtSysConfig_::reserved_1

[31–30] These bits are always 0

Definition at line **1700** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtSysConfig_::reserved_2

[23–0] These bits are always 0

Definition at line **1736** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtSysConfig_::rxEnbFSM

[28] Enables the operation of the Utopia Receive FSM

- 1 – FSM enabled
- 0 – FSM inactive

Definition at line **1705** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtSysConfig_::rxReset

[24] Resets the Utopia Coprocessor receive module to a known state

- Note: All receive configuration and status registers will be reset to their reset values.
- 0 – Normal operating mode
- 1 – Reset receive modules

Definition at line **1729** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtSysConfig_::tstLoop
```

[26] Test Loop Back Enable

- Note: For loop back to function RxMode and Tx Mode must both be set to single PHY mode.
- 0 – Loop back
- 1 – Normal operating mode

Definition at line **1715** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtSysConfig_::txEnbFSM
```

[29] Enables the operation of the Utopia Transmit FSM

- 1 – FSM enabled
- 0 – FSM inactive

Definition at line **1701** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtSysConfig_::txReset
```

[25] Resets the Utopia Coprocessor transmit module to a known state

- Note: All transmit configuration and status registers will be reset to their reset values.
- 0 – Normal operating mode,
- 1 – Reset transmit modules

Definition at line **1722** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxConfig_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx Config Register.

Data Fields

unsigned

int **reserved_1**:1

[31] These bits are always 0.

unsigned

int **txInterface**:1

[30] Utopia Transmit Interface

unsigned

int **txMode**:1

[29] Utopia Transmit Mode

unsigned

int **txOctet**:1

[28] Utopia Transmit cell transfer protocol

unsigned

int **txParity**:1

[27] Utopia Transmit parity enabled when set

unsigned

int **txEvenParity**:1

[26] Utopia Transmit Parity Mode

- 1 – Even Parity Generated

unsigned

int **txHEC**:1

[25] Header Error Check Insertion Mode

unsigned

int **txCOSET**:1

[24] If enabled the HEC is Exclusive-ORÆed with the value 0x55 before being presented on the Utopia bus

unsigned

int **reserved_2**:1

[23] These bits are always 0

unsigned

int **txCellSize**:7

[22:16] Transmit expected cell size

unsigned

int **reserved_3**:3

[15:13] These bits are always 0

unsigned

int **txAddrRange**:5

[12:8] When configured as an ATM master in MPHY mode this register specifies the upper limit of the PHY polling logical range

unsigned

int **reserved_4**:3

[7:5] These bits are always 0

unsigned

int **txPHYAddr**:5

[4:0] When configured as a slave in an MPHY system this register specifies the physical address of the PHY

Detailed Description

Utopia Tx Config Register.

Definition at line **986** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxConfig::reserved_1

[31] These bits are always 0.

Definition at line **989** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxConfig::reserved_2

[23] These bits are always 0

Definition at line **1027** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::reserved_3

[15:13] These bits are always 0

Definition at line **1032** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::reserved_4

[7:5] These bits are always 0

Definition at line **1037** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txAddrRange

[12:8] When configured as an ATM master in MPHY mode this register specifies the upper limit of the PHY polling logical range

The number of active PHYs are TxAddrRange + 1.

Definition at line **1033** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txCellSize

[22:16] Transmit expected cell size

Configures the cell size for the transmit module: Values between 52–64 are valid.

Definition at line **1029** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txCOSET

[24] If enabled the HEC is Exclusive–ORÆed with the value 0x55 before being presented on the Utopia bus

- 1 – Enable HEC ExOR with value 0x55
- 0 – Use generated HEC value.

Definition at line **1021** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txEvenParity

[26] Utopia Transmit Parity Mode

- 1 – Even Parity Generated

- 0 – Odd Parity Generated.

Definition at line **1012** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txHEC
```

[25] Header Error Check Insertion Mode

Specifies if the transmit cell header check byte is calculated and inserted when set.

- 1 – Generate HEC.
- 0 – Disable HEC generation.

Definition at line **1016** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txInterface
```

[30] Utopia Transmit Interface

The following encoding is used to set the Utopia Transmit interface as ATM master or PHY slave:

- 1 – PHY
- 0 – ATM

Definition at line **990** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txMode
```

[29] Utopia Transmit Mode

The following encoding is used to set the Utopia Transmit mode to SPHY or MPHY:

- 1 – SPHY
- 0 – MPHY

Definition at line **996** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txOctet
```

[28] Utopia Transmit cell transfer protocol

Used to set the Utopia cell transfer protocol to Octet–level handshaking. Note this is only applicable in SPHY mode.

- 1 – Octet–handshaking enabled

- 0 – Cell–handshaking enabled

Definition at line **1001** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txParity
```

[27] Utopia Transmit parity enabled when set

TxEvenParity defines the parity format odd/even.

- 1 – Enable Parity generation.
- 0 – ut_op_prtly held low.

Definition at line **1007** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxConfig_::txPHYAddr
```

[4:0] When configured as a slave in an MPHY system this register specifies the physical address of the PHY

Definition at line **1038** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxDefinIdle_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx idle cells Register.

Data Fields

unsigned int **vpi**:12

[31:20] ATM VPI [11:0] OR GFC [3:0] and VPI [7:0]

- *Note: if VCIdleTxGFC is set to 0 the GFC field is ignored in test*

unsigned int **vci**:16

[19:4] ATM VCI [15:0]

unsigned int **pti**:3

[3:1] ATM PTI PTI [2:0]

- *Note: if VCIdleTxPTI is set to 0 the PTI field is ignored in test.*

unsigned int **clp**:1

[0] ATM CLP [0]

- *Note: if VCIdleTxCLP is set to 0 the CLP field is ignored in test.*

Detailed Description

Utopia Tx idle cells Register.

Definition at line **1076** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxDefineIdle_::clp

[0] ATM CLP [0]

- Note: if VCIdleTxCLP is set to 0 the CLP field is ignored in test.

Definition at line **1087** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxDefineIdle_::pti

[3:1] ATM PTI PTI [2:0]

- Note: if VCIdleTxPTI is set to 0 the PTI field is ignored in test.

Definition at line **1084** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxDefineIdle_::vci

[19:4] ATM VCI [15:0]

Definition at line **1082** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxDefineIdle_::vpi

[31:20] ATM VPI [11:0] OR GFC [3:0] and VPI [7:0]

- Note: if VCIdleTxGFC is set to 0 the GFC field is ignored in test

Definition at line **1079** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxEnableFields_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx ienable fields Register.

Data Fields

- unsigned int **defineTxIdleGFC**:1
[31] This register is used to include or exclude the GFC field of the ATM header when testing for Idle cells
- unsigned int **defineTxIdlePTI**:1
[30] This register is used to include or exclude the PTI field of the ATM header when testing for Idle cells
- unsigned int **defineTxIdleCLP**:1
[29] This register is used to include or exclude the CLP field of the ATM header when testing for Idle cells
- unsigned int **phyStatsTxEnb**:1
[28] This register is used to enable or disable ATM statistics gathering based on the specified PHY address as defined in TxStatsConfig register
- unsigned int **vcStatsTxEnb**:1
[27] This register is used to change the ATM statistics—gathering mode from the specified logical PHY address to a specific VPI/VCI address
- unsigned int **vcStatsTxGFC**:1
[26] This register is used to include or exclude the GFC field of the ATM header when ATM VPI/VCI statistics are enabled
- unsigned int **vcStatsTxPTI**:1
[25] This register is used to include or exclude the PTI field of the ATM header when ATM VPI/VCI statistics are enabled
- unsigned int **vcStatsTxCLP**:1
[24] This register is used to include or exclude the CLP field of the ATM header when ATM VPI/VCI statistics are enabled
- unsigned int **reserved_1**:3
[23–21] These bits are always 0
- unsigned int **txPollStsInt**:1
[20] Enable the assertion of the ucp_tx_poll_sts condition where there is a change in

polling status

unsigned int **txCellOvrInt**:1

[19] Enable TxCellCount overflow CBI Transmit Status condition assertion

unsigned int **txIdleCellOvrInt**:1

[18] Enable TxIdleCellCount overflow Transmit Status Condition

- 1 – If TxIdleCellCountOvr is set assert the Transmit Status Condition
- 0 – No CBI Transmit Status condition assertion..

unsigned int **enbIdleCellCnt**:1

[17] Enable Transmit Idle Cell Count

unsigned int **enbTxCellCnt**:1

[16] Enable Transmit Valid Cell Count of non-idle/non-error cells

- 1 – Enable count of valid cells transmitted– non-idle/non-error
- 0 – No count is maintained.

unsigned int **reserved_2**:16

[15:0] These bits are always 0

Detailed Description

Utopia Tx ienable fields Register.

Definition at line **1098** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::defineTxIdleCLP

[29] This register is used to include or exclude the CLP field of the ATM header when testing for Idle cells

- 1 – CLP field is valid.
- 0 – CLP field ignored.

Definition at line **1111** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::defineTxIdleGFC

[31] This register is used to include or exclude the GFC field of the ATM header when testing for Idle cells

- 1 – GFC field is valid.
- 0 – GFC field ignored.

Definition at line **1101** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::defineTxIdlePTI
```

[30] This register is used to include or exclude the PTI field of the ATM header when testing for Idle cells

- 1 – PTI field is valid
- 0 – PTI field ignored.

Definition at line **1106** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::enbIdleCellCnt
```

[17] Enable Transmit Idle Cell Count

- 1 – Enable count of Idle cells transmitted.
- 0 – No count is maintained.

Definition at line **1161** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::enbTxCellCnt
```

[16] Enable Transmit Valid Cell Count of non-idle/non-error cells

- 1 – Enable count of valid cells transmitted–
non-idle/non-error
- 0 – No count is maintained.

Definition at line **1165** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::phyStatsTxEnb
```

[28] This register is used to enable or disable ATM statistics gathering based on the specified PHY address as defined in TxStatsConfig register

- 1 – Enable statistics for specified transmit PHY address.
- 0 – Disable statistics for specified transmit PHY address.

Definition at line **1116** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::reserved_1

[23–21] These bits are always 0

Definition at line **1145** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::reserved_2

[15:0] These bits are always 0

Definition at line **1169** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::txCellOvrInt

[19] Enable TxCellCount overflow CBI Transmit Status condition assertion

- 1 – If TxCellCountOvr is set assert the Transmit Status Condition.
- 0 – No CBI Transmit Status condition assertion

Definition at line **1152** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::txIdleCellOvrInt

[18] Enable TxIdleCellCount overflow Transmit Status Condition

- 1 – If TxIdleCellCountOvr is set assert the Transmit Status Condition
- 0 – No CBI Transmit Status condition assertion..

Definition at line **1157** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::txPollStsInt

[20] Enable the assertion of the ucp_tx_poll_sts condition where there is a change in polling status

- 1 – ucp_tx_poll_sts asserted whenever there is a change in status
- 0 – ucp_tx_poll_sts asserted if ANY transmit PHY is available

Definition at line **1147** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::vcStatsTxCLP

[24] This register is used to include or exclude the CLP field of the ATM header when ATM VPI/VCI statistics are enabled

- 1 – CLP field is valid
- 0 – CLP field ignored.

Definition at line **1140** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::vcStatsTxEnb
```

[27] This register is used to change the ATM statistics–gathering mode from the specified logical PHY address to a specific VPI/VCI address

- 1 – Enable statistics for specified VPI/VCI address.
- 0 – Disable statistics for specified VPI/VCI address

Definition at line **1122** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::vcStatsTxGFC
```

[26] This register is used to include or exclude the GFC field of the ATM header when ATM VPI/VCI statistics are enabled

GFC is only available at the UNI and uses the first 4–bits of the VPI field.

- 1 – GFC field is valid
- 0 – GFC field ignored.

Definition at line **1128** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxEnableFields_::vcStatsTxPTI
```

[25] This register is used to include or exclude the PTI field of the ATM header when ATM VPI/VCI statistics are enabled

- 1 – PTI field is valid
- 0 – PTI field ignored.

Definition at line **1135** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxStatsConfig_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx stats Register.

Data Fields

unsigned int **vpi**:12

[31:20] ATM VPI [11:0] OR GFC [3:0] and VPI [7:0]

- *Note: if VCStatsTxGFC is set to 0 the GFC field is ignored in test*

unsigned int **vci**:16

[19:4] ATM VCI [15:0] or PHY Address[4]

unsigned int **pti**:3

[3:1] ATM PTI [2:0] or PHY Address[3:1]

- *Note: if VCStatsTxPTI is set to 0 the PTI field is ignored in test*

unsigned int **clp**:1

[0] ATM CLP or PHY Address [0]

- *Note: if VCStatsTxCLP is set to 0 the CLP field is ignored in test*

Detailed Description

Utopia Tx stats Register.

Definition at line **1050** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxStatsConfig_::clp

[0] ATM CLP or PHY Address [0]

- Note: if VCStatsTxCLP is set to 0 the CLP field is ignored in test
- Note: if VCStatsTxEnb is set to 0 only the transmit PHY port address as defined by this register is used for ATM statistics [4:0].

Definition at line **1063** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxStatsConfig_::pti

[3:1] ATM PTI [2:0] or PHY Address[3:1]

- Note: if VCStatsTxPTI is set to 0 the PTI field is ignored in test
- Note: if VCStatsTxEnb is set to 0 only the transmit PHY port address as defined by this register is used for ATM statistics [4:0].

Definition at line **1058** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxStatsConfig_::vci

[19:4] ATM VCI [15:0] or PHY Address[4]

Definition at line **1056** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxStatsConfig_::vpi

[31:20] ATM VPI [11:0] OR GFC [3:0] and VPI [7:0]

- Note: if VCStatsTxGFC is set to 0 the GFC field is ignored in test

Definition at line **1053** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxTransTable0_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx translation table Register.

Data Fields

- unsigned int **phy0**:5
[31–27] Tx Mapping value of logical phy 0
- unsigned int **phy1**:5
[26–22] Tx Mapping value of logical phy 1
- unsigned int **phy2**:5
[21–17] Tx Mapping value of logical phy 2
- unsigned int **reserved_1**:1
[16] These bits are always 0.
- unsigned int **phy3**:5
[15–11] Tx Mapping value of logical phy 3
- unsigned int **phy4**:5
[10–6] Tx Mapping value of logical phy 4
- unsigned int **phy5**:5
[5–1] Tx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Tx translation table Register.

Definition at line 1177 of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable0_::phy0

[31–27] Tx Mapping value of logical phy 0

Definition at line **1180** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable0_::phy1
```

[26–22] Tx Mapping value of logical phy 1

Definition at line **1182** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable0_::phy2
```

[21–17] Tx Mapping value of logical phy 2

Definition at line **1184** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable0_::phy3
```

[15–11] Tx Mapping value of logical phy 3

Definition at line **1188** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable0_::phy4
```

[10–6] Tx Mapping value of logical phy 4

Definition at line **1190** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable0_::phy5
```

[5–1] Tx Mapping value of logical phy 5

Definition at line **1192** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable0_::reserved_1
```

[16] These bits are always 0.

Definition at line **1186** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable0_::reserved_2
```

[0] These bits are always 0

Definition at line **1194** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxTransTable1_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx translation table Register.

Data Fields

- unsigned int **phy6**:5
[31–27] Tx Mapping value of logical phy 6
- unsigned int **phy7**:5
[26–22] Tx Mapping value of logical phy 7
- unsigned int **phy8**:5
[21–17] Tx Mapping value of logical phy 8
- unsigned int **reserved_1**:1
[16–0] These bits are always 0
- unsigned int **phy9**:5
[15–11] Tx Mapping value of logical phy 3
- unsigned int **phy10**:5
[10–6] Tx Mapping value of logical phy 4
- unsigned int **phy11**:5
[5–1] Tx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Tx translation table Register.

Definition at line **1202** of file **IxAtmdAccCtrl.h**.

Field Documentation

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable1_::phy10
```

[10–6] Tx Mapping value of logical phy 4

Definition at line **1215** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable1_::phy11
```

[5–1] Tx Mapping value of logical phy 5

Definition at line **1217** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable1_::phy6
```

[31–27] Tx Mapping value of logical phy 6

Definition at line **1205** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable1_::phy7
```

[26–22] Tx Mapping value of logical phy 7

Definition at line **1207** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable1_::phy8
```

[21–17] Tx Mapping value of logical phy 8

Definition at line **1209** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable1_::phy9
```

[15–11] Tx Mapping value of logical phy 3

Definition at line **1213** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable1_::reserved_1
```

[16–0] These bits are always 0

Definition at line **1211** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable1_::reserved_2
```

[0] These bits are always 0

Definition at line **1219** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxTransTable2_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx translation table Register.

Data Fields

- unsigned int **phy12**:5
[31–27] Tx Mapping value of logical phy 6
- unsigned int **phy13**:5
[26–22] Tx Mapping value of logical phy 7
- unsigned int **phy14**:5
[21–17] Tx Mapping value of logical phy 8
- unsigned int **reserved_1**:1
[16–0] These bits are always 0
- unsigned int **phy15**:5
[15–11] Tx Mapping value of logical phy 3
- unsigned int **phy16**:5
[10–6] Tx Mapping value of logical phy 4
- unsigned int **phy17**:5
[5–1] Tx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Tx translation table Register.

Definition at line 1227 of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable2_::phy12

[31–27] Tx Mapping value of logical phy 6

Definition at line **1230** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable2_::phy13
```

[26–22] Tx Mapping value of logical phy 7

Definition at line **1232** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable2_::phy14
```

[21–17] Tx Mapping value of logical phy 8

Definition at line **1234** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable2_::phy15
```

[15–11] Tx Mapping value of logical phy 3

Definition at line **1238** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable2_::phy16
```

[10–6] Tx Mapping value of logical phy 4

Definition at line **1240** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable2_::phy17
```

[5–1] Tx Mapping value of logical phy 5

Definition at line **1242** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable2_::reserved_1
```

[16–0] These bits are always 0

Definition at line **1236** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable2_::reserved_2
```

[0] These bits are always 0

Definition at line **1244** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxTransTable3_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx translation table Register.

Data Fields

- unsigned int **phy18**:5
[31–27] Tx Mapping value of logical phy 6
- unsigned int **phy19**:5
[26–22] Tx Mapping value of logical phy 7
- unsigned int **phy20**:5
[21–17] Tx Mapping value of logical phy 8
- unsigned int **reserved_1**:1
[16–0] These bits are always 0
- unsigned int **phy21**:5
[15–11] Tx Mapping value of logical phy 3
- unsigned int **phy22**:5
[10–6] Tx Mapping value of logical phy 4
- unsigned int **phy23**:5
[5–1] Tx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Tx translation table Register.

Definition at line 1252 of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable3_::phy18

[31–27] Tx Mapping value of logical phy 6

Definition at line **1255** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable3_::phy19

[26–22] Tx Mapping value of logical phy 7

Definition at line **1257** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable3_::phy20

[21–17] Tx Mapping value of logical phy 8

Definition at line **1259** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable3_::phy21

[15–11] Tx Mapping value of logical phy 3

Definition at line **1263** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable3_::phy22

[10–6] Tx Mapping value of logical phy 4

Definition at line **1265** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable3_::phy23

[5–1] Tx Mapping value of logical phy 5

Definition at line **1267** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable3_::reserved_1

[16–0] These bits are always 0

Definition at line **1261** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable3_::reserved_2

[0] These bits are always 0

Definition at line **1269** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxTransTable4_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx translation table Register.

Data Fields

- unsigned int **phy24**:5
[31–27] Tx Mapping value of logical phy 6
- unsigned int **phy25**:5
[26–22] Tx Mapping value of logical phy 7
- unsigned int **phy26**:5
[21–17] Tx Mapping value of logical phy 8
- unsigned int **reserved_1**:1
[16–0] These bits are always 0
- unsigned int **phy27**:5
[15–11] Tx Mapping value of logical phy 3
- unsigned int **phy28**:5
[10–6] Tx Mapping value of logical phy 4
- unsigned int **phy29**:5
[5–1] Tx Mapping value of logical phy 5
- unsigned int **reserved_2**:1
[0] These bits are always 0

Detailed Description

Utopia Tx translation table Register.

Definition at line 1277 of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable4_::phy24

[31–27] Tx Mapping value of logical phy 6

Definition at line **1280** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable4_::phy25
```

[26–22] Tx Mapping value of logical phy 7

Definition at line **1282** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable4_::phy26
```

[21–17] Tx Mapping value of logical phy 8

Definition at line **1284** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable4_::phy27
```

[15–11] Tx Mapping value of logical phy 3

Definition at line **1288** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable4_::phy28
```

[10–6] Tx Mapping value of logical phy 4

Definition at line **1290** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable4_::phy29
```

[5–1] Tx Mapping value of logical phy 5

Definition at line **1292** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable4_::reserved_1
```

[16–0] These bits are always 0

Definition at line **1286** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable4_::reserved_2
```

[0] These bits are always 0

Definition at line **1294** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaConfig::UtTxTransTable5_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx translation table Register.

Data Fields

unsigned int **phy30**:5
[31–27] Tx Mapping value of logical phy 6

unsigned int **reserved_1**:27
[26–0] These bits are always 0

Detailed Description

Utopia Tx translation table Register.

Definition at line **1302** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable5_::phy30

[31–27] Tx Mapping value of logical phy 6

Definition at line **1305** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaConfig::UtTxTransTable5_::reserved_1

[26–0] These bits are always 0

Definition at line **1307** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaStatus Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia status.

Data Fields

unsigned int **utTxCellCount**
count of cells transmitted

unsigned int **utTxIdleCellCount**
count of idle cells transmitted

IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_ utTxCellConditionStatus
Tx cells condition status.

unsigned int **utRxCellCount**
count of cell received

unsigned int **utRxIdleCellCount**
count of idle cell received

unsigned int **utRxInvalidHECount**
count of invalid cell received because of HEC errors

unsigned int **utRxInvalidParCount**
count of invalid cell received because of parity errors

unsigned int **utRxInvalidSizeCount**
count of invalid cell received because of cell size errors

IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_ utRxCellConditionStatus
Rx cells condition status.

Detailed Description

Utopia status.

This structure is used to set/get the Utopia status parameters

- contains debug cell counters, to be accessed during a read operation

Note:

- the exact description of all parameters is done in the Utopia reference documents.

Definition at line **1753** of file **IxAtmdAccCtrl.h**.

Field Documentation

```
struct IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_  
IxAtmdAccUtopiaStatus::utRxCellConditionStatus
```

Rx cells condition status.

```
unsigned int IxAtmdAccUtopiaStatus::utRxCellCount
```

count of cell received

Definition at line **1794** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::utRxIdleCellCount
```

count of idle cell received

Definition at line **1795** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::utRxInvalidHECount
```

count of invalid cell received because of HEC errors

Definition at line **1796** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::utRxInvalidParCount
```

count of invalid cell received because of parity errors

Definition at line **1799** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::utRxInvalidSizeCount
```

count of invalid cell received because of cell size errors

Definition at line **1802** of file **IxAtmdAccCtrl.h**.

```
struct IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_  
IxAtmdAccUtopiaStatus::utTxCellConditionStatus
```

Tx cells condition status.

```
unsigned int IxAtmdAccUtopiaStatus::utTxCellCount
```

count of cells transmitted

Definition at line **1756** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::utTxIdleCellCount
```

count of idle cells transmitted

Definition at line **1758** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Rx Status Register.

Data Fields

unsigned int **reserved_1**:3

[31:29] These bits are always 0.

unsigned int **rxCellCountOvr**:1

[28] This bit is set if the RxCellCount register overflows

unsigned int **invalidHecCountOvr**:1

[27] This bit is set if the InvalidHecCount register overflows.

unsigned int **invalidParCountOvr**:1

[26] This bit is set if the InvalidParCount register overflows.

unsigned int **invalidSizeCountOvr**:1

[25] This bit is set if the InvalidSizeCount register overflows.

unsigned int **rxIdleCountOvr**:1

[24] This bit is set if the RxIdleCount register overflows.

unsigned int **reserved_2**:4

[23:20] These bits are always 0

unsigned int **rxFIFO2Underflow**:1

[19] This bit is set if 64–byte Receive FIFO2 indicates a FIFO underflow error condition

unsigned int **rxFIFO1Underflow**:1

[18] This bit is set if 64–byte Receive FIFO1 indicates a FIFO underflow error condition

unsigned int **rxFIFO2Overflow**:1

[17] This bit is set if 64–byte Receive FIFO2 indicates a FIFO overflow error condition

unsigned int **rxFIFO1Overflow**:1

[16] This bit is set if 64–byte Receive FIFO1 indicates a FIFO overflow error condition

unsigned int **reserved_3**:16

[15:0] These bits are always 0

Detailed Description

Utopia Rx Status Register.

Definition at line **1812** of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::invalidHecCountOvr

[27] This bit is set if the InvalidHecCount register overflows.

Definition at line **1817** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::invalidParCountOvr

[26] This bit is set if the InvalidParCount register overflows.

Definition at line **1818** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::invalidSizeCountOvr

[25] This bit is set if the InvalidSizeCount register overflows.

Definition at line **1819** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::reserved_1

[31:29] These bits are always 0.

Definition at line **1815** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::reserved_2

[23:20] These bits are always 0

Definition at line **1821** of file **IxAtmdAccCtrl.h**.

unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::reserved_3

[15:0] These bits are always 0

Definition at line **1834** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::rxCellCountOvr
```

[28] This bit is set if the RxCellCount register overflows

Definition at line **1816** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::rxFIFO1Overflow
```

[16] This bit is set if 64–byte Receive FIFO1 indicates a FIFO overflow error condition

Definition at line **1831** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::rxFIFO1Underflow
```

[18] This bit is set if 64–byte Receive FIFO1 indicates a FIFO underflow error condition

Definition at line **1825** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::rxFIFO2Overflow
```

[17] This bit is set if 64–byte Receive FIFO2 indicates a FIFO overflow error condition

Definition at line **1828** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::rxFIFO2Underflow
```

[19] This bit is set if 64–byte Receive FIFO2 indicates a FIFO underflow error condition

Definition at line **1822** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtRxCellConditionStatus_::rxIdleCountOvr
```

[24] This bit is set if the RxIdleCount register overflows.

Definition at line **1820** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_ Struct Reference

[Intel (R) IXP400 Software ATM Driver Access (IxAtmdAcc) Utopia Control API]

Utopia Tx Status Register.

Data Fields

unsigned int **reserved_1**:2

[31:30] These bits are always 0

unsigned int **txFIFO2Underflow**:1

[29] This bit is set if 64-byte Transmit FIFO2 indicates a FIFO underflow error condition

unsigned int **txFIFO1Underflow**:1

[28] This bit is set if 64-byte Transmit FIFO1 indicates a FIFO underflow error condition

unsigned int **txFIFO2Overflow**:1

[27] This bit is set if 64-byte Transmit FIFO2 indicates a FIFO overflow error condition

unsigned int **txFIFO1Overflow**:1

[26] This bit is set if 64-byte Transmit FIFO1 indicates a FIFO overflow error condition

unsigned int **txIdleCellCountOvr**:1

[25] This bit is set if the TxIdleCellCount register overflows

unsigned int **txCellCountOvr**:1

[24] This bit is set if the TxCellCount register overflows

unsigned int **reserved_2**:24

[23:0] These bits are always 0

Detailed Description

Utopia Tx Status Register.

Definition at line 1765 of file **IxAtmdAccCtrl.h**.

Field Documentation

unsigned int IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_::reserved_1

[31:30] These bits are always 0

Definition at line **1768** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_::reserved_2
```

[23:0] These bits are always 0

Definition at line **1791** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_::txCellCountOvr
```

[24] This bit is set if the TxCellCount register overflows

Definition at line **1788** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_::txFIFO1Overflow
```

[26] This bit is set if 64–byte Transmit FIFO1 indicates a FIFO overflow error condition

Definition at line **1781** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_::txFIFO1Underflow
```

[28] This bit is set if 64–byte Transmit FIFO1 indicates a FIFO underflow error condition

Definition at line **1773** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_::txFIFO2Overflow
```

[27] This bit is set if 64–byte Transmit FIFO2 indicates a FIFO overflow error condition

Definition at line **1777** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_::txFIFO2Underflow
```

[29] This bit is set if 64–byte Transmit FIFO2 indicates a FIFO underflow error condition

Definition at line **1769** of file **IxAtmdAccCtrl.h**.

```
unsigned int IxAtmdAccUtopiaStatus::UtTxCellConditionStatus_::txIdleCellCountOvr
```

[25] This bit is set if the TxIdleCellCount register overflows

Definition at line **1785** of file **IxAtmdAccCtrl.h**.

The documentation for this struct was generated from the following file:

- **IxAtmdAccCtrl.h**

IxAtmmPortCfg Struct Reference

[Intel (R) IXP400 Software ATM Manager (IxAtmm) API]

Structure contains port-specific information required to initialize IxAtmm, and specifically, the IXP400 UTOPIA Level-2 device.

Data Fields

unsigned **reserved_1**:11

[31:21] Should be zero

unsigned **UtopiaTxPhyAddr**:5

[20:16] Address of the transmit (Tx) PHY for this port on the 5-bit UTOPIA Level-2 address bus

unsigned **reserved_2**:11

[15:5] Should be zero

unsigned **UtopiaRxPhyAddr**:5

[4:0] Address of the receive (Rx) PHY for this port on the 5-bit UTOPIA Level-2 address bus

Detailed Description

Structure contains port-specific information required to initialize IxAtmm, and specifically, the IXP400 UTOPIA Level-2 device.

Definition at line **161** of file **IxAtmm.h**.

Field Documentation

unsigned IxAtmmPortCfg::reserved_1

[31:21] Should be zero

Definition at line **162** of file **IxAtmm.h**.

unsigned IxAtmmPortCfg::reserved_2

[15:5] Should be zero

Definition at line **167** of file **IxAtmm.h**.

unsigned IxAtmmPortCfg::UtopiaRxPhyAddr

[4:0] Address of the receive (Rx) PHY for this port on the 5-bit UTOPIA Level-2 address bus

Definition at line **168** of file **IxAtmm.h**.

unsigned IxAtmmPortCfg::UtopiaTxPhyAddr

[20:16] Address of the transmit (Tx) PHY for this port on the 5-bit UTOPIA Level-2 address bus

Definition at line **163** of file **IxAtmm.h**.

The documentation for this struct was generated from the following file:

- **IxAtmm.h**

IxAtmmVc Struct Reference

[Intel (R) IXP400 Software ATM Manager (IxAtmm) API]

This structure describes the required attributes of a virtual connection.

Data Fields

unsigned **vpi**
VPI value of this virtual connection.

unsigned **vci**
VCI value of this virtual connection.

IxAtmmVcDirection **direction**
VC direction.

IxAtmTrafficDescriptor **trafficDesc**
Traffic descriptor of this virtual connection.

Detailed Description

This structure describes the required attributes of a virtual connection.

Definition at line **136** of file **IxAtmm.h**.

Field Documentation

IxAtmmVcDirection IxAtmmVc::direction

VC direction.

Definition at line **139** of file **IxAtmm.h**.

IxAtmTrafficDescriptor IxAtmmVc::trafficDesc

Traffic descriptor of this virtual connection.

This structure is defined by the **Intel (R) IXP400 Software ATM Transmit Scheduler (IxAtmSch) API** component.

Definition at line **143** of file **IxAtmm.h**.

unsigned IxAtmmVc::vci

VCI value of this virtual connection.

Definition at line **138** of file **IxAtmm.h**.

unsigned IxAtmmVc::vpi

VPI value of this virtual connection.

Definition at line **137** of file **IxAtmm.h**.

The documentation for this struct was generated from the following file:

- **IxAtmm.h**

IxAtmScheduleTable Struct Reference

[Intel (R) IXP400 Software ATM Types (IxAtmTypes)]

This structure defines a schedule table which gives details on which data (from which VCs) should be transmitted for a forthcoming period of time for a particular port and the order in which that data should be transmitted.

Data Fields

unsigned **tableSize**
Number of entries.

unsigned **totalCellSlots**
Number of cells.

IxAtmScheduleTableEntry * table
Pointer to schedule entries.

Detailed Description

This structure defines a schedule table which gives details on which data (from which VCs) should be transmitted for a forthcoming period of time for a particular port and the order in which that data should be transmitted.

The schedule table consists of a series of entries each of which will schedule one or more cells from a particular registered VC. The total number of cells scheduled and the total number of entries in the table are also indicated.

Definition at line **355** of file **IxAtmTypes.h**.

Field Documentation

IxAtmScheduleTableEntry* IxAtmScheduleTable::table

Pointer to schedule entries.

Pointer to an array containing tableSize entries

Definition at line **368** of file **IxAtmTypes.h**.

unsigned IxAtmScheduleTable::tableSize

Number of entries.

Indicates the total number of entries in the table.

Definition at line **357** of file **IxAtmTypes.h**.

unsigned IxAtmScheduleTable::totalCellSlots

Number of cells.

Indicates the total number of ATM cells which are scheduled by all the entries in the table.

Definition at line **362** of file **IxAtmTypes.h**.

The documentation for this struct was generated from the following file:

- **IxAtmTypes.h**

IxAtmScheduleTableEntry Struct Reference

[Intel (R) IXP400 Software ATM Types (IxAtmTypes)]

ATM Schedule Table entry.

Data Fields

IxAtmConnId connId

connection Id

unsigned int **numberOfCells**

number of cells to transmit

Detailed Description

ATM Schedule Table entry.

This IxAtmScheduleTableEntry is used by an ATM scheduler to inform IxAtmdAcc about the data to transmit (in term of cells per VC)

This structure defines

- the number of cells to be transmitted (numberOfCells)
- the VC connection to be used for transmission (connId).

Note:

- When the connection Id value is IX_ATM_IDLE_CELLS_CONNID, the corresponding number of idle cells will be transmitted to the hardware.

Definition at line **323** of file **IxAtmTypes.h**.

Field Documentation

IxAtmConnId IxAtmScheduleTableEntry::connId

connection Id

Identifier of VC from which cells are to be transmitted. When this value is IX_ATM_IDLE_CELLS_CONNID, this indicates that the system should transmit the specified number of idle cells. Unknown connIds result in the transmission of idle cells.

Definition at line **325** of file **IxAtmTypes.h**.

unsigned int IxAtmScheduleTableEntry::numberOfCells

number of cells to transmit

The number of contiguous cells to schedule from this VC at this point. The valid range is from 1 to *IX_ATM_SCHEDULETABLE_MAXCELLS_PER_ENTRY*. This number can swap over mbufs and pdus. OverScheduling results in the transmission of idle cells.

Definition at line **333** of file **IxAtmTypes.h**.

The documentation for this struct was generated from the following file:

- **IxAtmTypes.h**

IxAtmTrafficDescriptor Struct Reference

[Intel (R) IXP400 Software ATM Types (IxAtmTypes)]

Structure describing an ATM traffic contract for a Virtual Connection (VC).

Data Fields

IxAtmServiceCategory atmService

ATM service category.

UINT64 **pcr**

Peak Cell Rate – cells per second.

UINT64 **cdvt**

Cell Delay Variation Tolerance – in nanoseconds.

UINT64 **scr**

Sustained Cell Rate – cells per second.

UINT64 **mbs**

Max Burst Size – cells.

UINT64 **mcr**

Minimum Cell Rate – cells per second.

UINT64 **mfs**

Max Frame Size – cells.

Detailed Description

Structure describing an ATM traffic contract for a Virtual Connection (VC).

Structure is used to specify the requested traffic contract for a VC to the IxAtmSch component using the **ixAtmSchVcModelSetup** interface.

These parameters are defined by the ATM forum working group (<http://www.atmforum.com>).

Note:

Typical values for a voice channel 64 Kbit/s

◇ atmService *IX_ATM_RTVBR*

◇ pcr 400 (include IP overhead, and AAL5 trailer)

◇ cdvt 5000000 (5 ms)

◇ scr = pcr

Typical values for a data channel 800 Kbit/s

- ◇ atmService *IX_ATM_UBR*
- ◇ pcr 1962 (include IP overhead, and AAL5 trailer)
- ◇ cdvt 5000000 (5 ms)

Definition at line **262** of file **IxAtmTypes.h**.

Field Documentation

IxAtmServiceCategory IxAtmTrafficDescriptor::atmService

ATM service category.

Definition at line **264** of file **IxAtmTypes.h**.

UINT64 IxAtmTrafficDescriptor::cdvt

Cell Delay Variation Tolerance – in nanoseconds.

Definition at line **266** of file **IxAtmTypes.h**.

UINT64 IxAtmTrafficDescriptor::mbs

Max Burst Size – cells.

Definition at line **268** of file **IxAtmTypes.h**.

UINT64 IxAtmTrafficDescriptor::mcr

Minimum Cell Rate – cells per second.

Definition at line **269** of file **IxAtmTypes.h**.

UINT64 IxAtmTrafficDescriptor::mfs

Max Frame Size – cells.

Definition at line **270** of file **IxAtmTypes.h**.

UINT64 IxAtmTrafficDescriptor::pcr

Peak Cell Rate – cells per second.

Definition at line **265** of file **IxAtmTypes.h**.

UINT64 IxAtmTrafficDescriptor::scr

Sustained Cell Rate – cells per second.

Definition at line **267** of file **IxAtmTypes.h**.

The documentation for this struct was generated from the following file:

- **IxAtmTypes.h**

IxErrHdlAccRecoveryStatistics Struct Reference

[IXP400 Soft–Error Handler Driver (ixErrHdlAcc) API]

Debug Statistical Data Structure.

Data Fields

UINT32 **totalNPEAEvent**
UINT32 **totalNPEBEvent**
UINT32 **totalNPECEvent**
UINT32 **totalAQMEvent**
UINT32 **totalNPEARecoveryPass**
UINT32 **totalNPEBRecoveryPass**
UINT32 **totalNPECRecoveryPass**
UINT32 **totalAQMRecoveryPass**

Detailed Description

Debug Statistical Data Structure.

Definition at line **101** of file **IxErrHdlAcc.h**.

The documentation for this struct was generated from the following file:

- **IxErrHdlAcc.h**

IxEthAccMacAddr Struct Reference

[Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API]

Definition of the IEEE 802.3 Ethernet MAC address structure.

Data Fields

UINT8 **macAddress** [IX_IEEE803_MAC_ADDRESS_SIZE]
MAC address.

Detailed Description

Definition of the IEEE 802.3 Ethernet MAC address structure.

The data should be packed with bytes xx:xx:xx:xx:xx:xx

Note:

The data must be packed in network byte order.

Definition at line **99** of file **IxEthAcc.h**.

Field Documentation

UINT8 IxEthAccMacAddr::macAddress[IX_IEEE803_MAC_ADDRESS_SIZE]

MAC address.

Definition at line **101** of file **IxEthAcc.h**.

The documentation for this struct was generated from the following file:

- **IxEthAcc.h**

IxEthAccNe Struct Reference

[Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API, Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API, Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API]

Definition of service-specific informations.

Data Fields

UINT32 **ixReserved_next**

reserved for chaining

UINT32 **ixReserved_lengths**

reserved for buffer lengths

UINT32 **ixReserved_data**

reserved for buffer pointer

UINT8 **ixDestinationPortId**

Destination portId for this packet, if known by NPE.

UINT8 **ixSourcePortId**

Source portId for this packet.

UINT16 **ixFlags**

BitField of option for this frame.

UINT8 **ixQoS**

QoS class of the frame.

UINT8 **ixPadLength**

Size of pad field in bytes (min 0 – max 16).

UINT16 **ixVlanTCI**

Vlan TCI.

UINT8 **ixDestMac** [IX_IEEE803_MAC_ADDRESS_SIZE]

Destination MAC address.

UINT8 **ixSourceMac** [IX_IEEE803_MAC_ADDRESS_SIZE]

Source MAC address.

Detailed Description

Definition of service-specific informations.

This structure defines the Ethernet service-specific informations and enable QoS and VLAN features.

Definition at line **170** of file **IxEthAcc.h**.

Field Documentation

UINT8 IxEthAccNe::ixDestinationPortId

Destination portId for this packet, if known by NPE.

Definition at line **175** of file **IxEthAcc.h**.

UINT8 IxEthAccNe::ixDestMac[IX_IEEE803_MAC_ADDRESS_SIZE]

Destination MAC address.

Definition at line **181** of file **IxEthAcc.h**.

UINT16 IxEthAccNe::ixFlags

BitField of option for this frame.

Definition at line **177** of file **IxEthAcc.h**.

UINT8 IxEthAccNe::ixPadLength

Size of pad field in bytes (min 0 – max 16).

Definition at line **179** of file **IxEthAcc.h**.

UINT8 IxEthAccNe::ixQoS

QoS class of the frame.

Definition at line **178** of file **IxEthAcc.h**.

UINT32 IxEthAccNe::ixReserved_data

reserved for buffer pointer

Definition at line **174** of file **IxEthAcc.h**.

UINT32 IxEthAccNe::ixReserved_lengths

reserved for buffer lengths

Definition at line **173** of file **IxEthAcc.h**.

UINT32 IxEthAccNe::ixReserved_next

reserved for chaining

Definition at line **172** of file **IxEthAcc.h**.

UINT8 IxEthAccNe::ixSourceMac[IX_IEEE803_MAC_ADDRESS_SIZE]

Source MAC address.

Definition at line **182** of file **IxEthAcc.h**.

UINT8 IxEthAccNe::ixSourcePortId

Source portId for this packet.

Definition at line **176** of file **IxEthAcc.h**.

UINT16 IxEthAccNe::ixVlanTCI

Vlan TCI.

Definition at line **180** of file **IxEthAcc.h**.

The documentation for this struct was generated from the following file:

- **IxEthAcc.h**

IxEthDBPortDefinition Struct Reference

[Intel (R) IXP400 Software Ethernet Database Port Definitions
(IxEthDBPortDefs)]

Port Definition – a structure contains the Port type and capabilities.

Data Fields

IxEthDBPortType type
IxEthDBPortCapability capabilities

Detailed Description

Port Definition – a structure contains the Port type and capabilities.

Definition at line **46** of file **IxEthDBPortDefs.h**.

The documentation for this struct was generated from the following file:

- **IxEthDBPortDefs.h**

IxEthDBWiFiRecData Struct Reference

[Intel (R) IXP400 Software Ethernet Database (IxEthDB) API]

The user wi-fi input parameters structure.

Data Fields

IxEthDBWiFiRecordType	recType
IxEthDBWiFiVlanTag	vlanTagFlag
	UINT32 logicalPortID
	UINT8 padLength
	UINT8 gatewayMacAddr [IX_IEEE803_MAC_ADDRESS_SIZE]
	UINT8 bssid [IX_IEEE803_MAC_ADDRESS_SIZE]

Detailed Description

The user wi-fi input parameters structure.

Note:

The data must be packed in network byte order.

Definition at line **275** of file **IxEthDB.h**.

The documentation for this struct was generated from the following file:

- **IxEthDB.h**

IxEthEthObjStats Struct Reference

[Intel (R) IXP400 Software Ethernet Access (IxEthAcc) API]

This struct defines the statistics returned by this component.

Data Fields

UINT32 **dot3StatsAlignmentErrors**

link error count (rx)

UINT32 **dot3StatsFCSErrors**

link error count (rx)

UINT32 **dot3StatsInternalMacReceiveErrors**

link error count (rx)

UINT32 **RxOverrunDiscards**

NPE: discarded frames count (rx).

UINT32 **RxLearnedEntryDiscards**

NPE: discarded frames count(rx).

UINT32 **RxLargeFramesDiscards**

NPE: discarded frames count(rx).

UINT32 **RxSTPBlockedDiscards**

NPE: discarded frames count(rx).

UINT32 **RxVLANTypeFilterDiscards**

NPE: discarded frames count (rx).

UINT32 **RxVLANIdFilterDiscards**

NPE: discarded frames count (rx).

UINT32 **RxInvalidSourceDiscards**

NPE: discarded frames count (rx).

UINT32 **RxBlackListDiscards**

NPE: discarded frames count (rx).

UINT32 **RxWhiteListDiscards**

NPE: discarded frames count (rx).

UINT32 **RxUnderflowEntryDiscards**

NPE: discarded frames count (rx).

UINT32 **dot3StatsSingleCollisionFrames**

link error count (tx)

UINT32 **dot3StatsMultipleCollisionFrames**

link error count (tx)

UINT32 **dot3StatsDeferredTransmissions**

link error count (tx)

UINT32 **dot3StatsLateCollisions**

link error count (tx)

UINT32 **dot3StatsExcessiveCollisions**

link error count (tx)

UINT32 **dot3StatsInternalMacTransmitErrors**

link error count (tx)

UINT32 **dot3StatsCarrierSenseErrors**

link error count (tx)

UINT32 **TxLargeFrameDiscards**

NPE: discarded frames count (tx).

UINT32 **TxVLANIdFilterDiscards**

NPE: discarded frames count (tx).

UINT32 **TxUnderrunDiscards**

NPE: discarded frames count (tx).

UINT32 **MacRecoveryTriggered**

MAC recovery count.

UINT32 **RxValidFramesTotalOctets**

UINT32 **RxUcastPkts**

UINT32 **RxBcastPkts**

UINT32 **RxMcastPkts**

UINT32 **RxPkts64Octets**

UINT32 **RxPkts65to127Octets**

UINT32 **RxPkts128to255Octets**

UINT32 **RxPkts256to511Octets**

UINT32 **RxPkts512to1023Octets**

UINT32 **RxPkts1024to1518Octets**

UINT32 **RxInternalNPETransmitErrors**

UINT32 **TxInternalNPETransmitErrors**

Detailed Description

This struct defines the statistics returned by this component.

The component returns MIB2 EthObj variables which are obtained from the hardware or maintained by this component.

Definition at line **2458** of file **IxEthAcc.h**.

Field Documentation

UINT32 IxEthEthObjStats::dot3StatsAlignmentErrors

link error count (rx)

Definition at line **2463** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsCarrierSenseErrors

link error count (tx)

Definition at line **2482** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsDeferredTransmissions

link error count (tx)

Definition at line **2478** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsExcessiveCollisions

link error count (tx)

Definition at line **2480** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsFCSErrors

link error count (rx)

Definition at line **2464** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsInternalMacReceiveErrors

link error count (rx)

Definition at line **2465** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsInternalMacTransmitErrors

link error count (tx)

Definition at line **2481** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsLateCollisions

link error count (tx)

Definition at line **2479** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsMultipleCollisionFrames

link error count (tx)

Definition at line **2477** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::dot3StatsSingleCollisionFrames

link error count (tx)

Definition at line **2476** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::MacRecoveryTriggered

MAC recovery count.

Definition at line **2486** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxBlackListDiscards

NPE: discarded frames count (rx).

Definition at line **2473** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxInvalidSourceDiscards

NPE: discarded frames count (rx).

Definition at line **2472** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxLargeFramesDiscards

NPE: discarded frames count(rx).

Definition at line **2468** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxLearnedEntryDiscards

NPE: discarded frames count(rx).

Definition at line **2467** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxOverrunDiscards

NPE: discarded frames count (rx).

Definition at line **2466** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxSTPBlockedDiscards

NPE: discarded frames count(rx).

Definition at line **2469** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxUnderflowEntryDiscards

NPE: discarded frames count (rx).

Definition at line **2475** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxVLANIdFilterDiscards

NPE: discarded frames count (rx).

Definition at line **2471** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxVLANTypeFilterDiscards

NPE: discarded frames count (rx).

Definition at line **2470** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::RxWhiteListDiscards

NPE: discarded frames count (rx).

Definition at line **2474** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::TxLargeFrameDiscards

NPE: discarded frames count (tx).

Definition at line **2483** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::TxUnderrunDiscards

NPE: discarded frames count (tx).

Definition at line **2485** of file **IxEthAcc.h**.

UINT32 IxEthEthObjStats::TxVLANIdFilterDiscards

NPE: discarded frames count (tx).

Definition at line **2484** of file **IxEthAcc.h**.

The documentation for this struct was generated from the following file:

- **IxEthAcc.h**

IxHssAccConfigParams Struct Reference

[Intel (R) IXP400 Software HSS Access (IxHssAcc) API]

Structure containing HSS configuration parameters.

Data Fields

IxHssAccPortConfig txPortConfig

HSS tx port configuration.

IxHssAccPortConfig rxPortConfig

HSS rx port configuration.

unsigned **numChannelised**

The number of channelised timeslots (0–32).

unsigned **hssPktChannelCount**

The number of packetised clients (0 – 4).

UINT8 **channelisedIdlePattern**

The byte to be transmitted on channelised service when there is no client data to tx.

BOOL **loopback**

The HSS loopback state.

unsigned **packetizedIdlePattern**

The data to be transmitted on packetised service when there is no client data to tx.

IxHssAccClkSpeed clkSpeed

The HSS clock speed.

Detailed Description

Structure containing HSS configuration parameters.

Definition at line **563** of file **IxHssAcc.h**.

Field Documentation

UINT8 IxHssAccConfigParams::channelisedIdlePattern

The byte to be transmitted on channelised service when there is no client data to tx.

Definition at line **571** of file **IxHssAcc.h**.

IxHssAccClkSpeed IxHssAccConfigParams::clkSpeed

The HSS clock speed.

Definition at line **578** of file **IxHssAcc.h**.

unsigned IxHssAccConfigParams::hssPktChannelCount

The number of packetised clients (0 – 4).

Definition at line **569** of file **IxHssAcc.h**.

BOOL IxHssAccConfigParams::loopback

The HSS loopback state.

Definition at line **574** of file **IxHssAcc.h**.

unsigned IxHssAccConfigParams::numChannelised

The number of channelised timeslots (0–32).

Definition at line **567** of file **IxHssAcc.h**.

unsigned IxHssAccConfigParams::packetizedIdlePattern

The data to be transmitted on packetised service when there is no client data to tx.

Definition at line **575** of file **IxHssAcc.h**.

IxHssAccPortConfig IxHssAccConfigParams::rxPortConfig

HSS rx port configuration.

Definition at line **566** of file **IxHssAcc.h**.

IxHssAccPortConfig IxHssAccConfigParams::txPortConfig

HSS tx port configuration.

Definition at line **565** of file **IxHssAcc.h**.

The documentation for this struct was generated from the following file:

- **IxHssAcc.h**

IxHssAccHdlcMode Struct Reference

[Intel (R) IXP400 Software HSS Access (IxHssAcc) API]

This structure contains 56Kbps, HDLC–mode configuration parameters.

Data Fields

BOOL **hdlc56kMode**

56kbps(TRUE)/64kbps(FALSE) HDLC

IxHssAcc56kEndianness **hdlc56kEndian**

56kbps data endianness

- *ignored if hdlc56kMode is FALSE*

BOOL **hdlc56kUnusedBitPolarity0**

The polarity '0'(TRUE)/'1'(FALSE) of the unused bit while in 56kbps mode

- *ignored if hdlc56kMode is FALSE.*

Detailed Description

This structure contains 56Kbps, HDLC–mode configuration parameters.

Definition at line **585** of file **IxHssAcc.h**.

Field Documentation

IxHssAcc56kEndianness IxHssAccHdlcMode::hdlc56kEndian

56kbps data endianness

- ignored if hdlc56kMode is FALSE

Definition at line **588** of file **IxHssAcc.h**.

BOOL IxHssAccHdlcMode::hdlc56kMode

56kbps(TRUE)/64kbps(FALSE) HDLC

Definition at line **587** of file **IxHssAcc.h**.

BOOL IxHssAccHdlcMode::hdlc56kUnusedBitPolarity0

The polarity '0'(TRUE)/'1'(FALSE) of the unused bit while in 56kbps mode

- ignored if hdlc56kMode is FALSE.

Definition at line **590** of file **IxHssAcc.h**.

The documentation for this struct was generated from the following file:

- **IxHssAcc.h**

IxHssAccPktHdlcFraming Struct Reference

[Intel (R) IXP400 Software HSS Access (IxHssAcc) API]

This structure contains information required by the NPE to configure the HDLC co-processor.

Data Fields

IxHssAccPktHdlcIdleType **hdlcIdleType**

What to transmit when a HDLC port is idle.

IxHssAccBitEndian **dataEndian**

The HDLC data endianness.

IxHssAccPktCrcType **crcType**

The CRC type to be used for this HDLC port.

Detailed Description

This structure contains information required by the NPE to configure the HDLC co-processor.

Definition at line **600** of file **IxHssAcc.h**.

Field Documentation

IxHssAccPktCrcType IxHssAccPktHdlcFraming::crcType

The CRC type to be used for this HDLC port.

Definition at line **604** of file **IxHssAcc.h**.

IxHssAccBitEndian IxHssAccPktHdlcFraming::dataEndian

The HDLC data endianness.

Definition at line **603** of file **IxHssAcc.h**.

IxHssAccPktHdlcIdleType IxHssAccPktHdlcFraming::hdlcIdleType

What to transmit when a HDLC port is idle.

Definition at line **602** of file **IxHssAcc.h**.

The documentation for this struct was generated from the following file:

- **IxHssAcc.h**

IxHssAccPortConfig Struct Reference

[Intel (R) IXP400 Software HSS Access (IxHssAcc) API]

Structure containing HSS port configuration parameters.

Data Fields

IxHssAccFrmSyncType frmSyncType
frame sync pulse type (tx/rx)

IxHssAccFrmSyncEnable frmSyncIO
how the frame sync pulse is used (tx/rx)

IxHssAccClkEdge frmSyncClkEdge
frame sync clock edge type (tx/rx)

IxHssAccClkEdge dataClkEdge
data clock edge type (tx/rx)

IxHssAccClkDir clkDirection
clock direction (tx/rx)

IxHssAccFrmPulseUsage frmPulseUsage
whether to use the frame sync pulse or not (tx/rx)

IxHssAccDataRate dataRate
data rate in relation to the clock (tx/rx)

IxHssAccDataPolarity dataPolarity
data polarity type (tx/rx)

IxHssAccBitEndian dataEndianness
data endianness (tx/rx)

IxHssAccDrainMode drainMode
tx pin open drain mode (tx)

IxHssAccSOFType fBitUsage
start of frame types (tx/rx)

IxHssAccDataEnable dataEnable
whether or not to drive the data pins (tx)

IxHssAccTxSigType voice56kType
how to drive the data pins for voice56k type (tx)

IxHssAccTxSigType unassignedType

how to drive the data pins for unassigned type (tx)

IxHssAccFbType fBitType

how to drive the Fbit (tx)

IxHssAcc56kEndianness voice56kEndian

56k data endianness when using the 56k type (tx)

IxHssAcc56kSel voice56kSel

56k data transmission type when using the 56k type (tx)

unsigned **frmOffset**

frame pulse offset in bits wrt the first timeslot (0–1023) (tx/rx)

unsigned **maxFrmSize**

frame size in bits (1–1024) (tx/rx)

Detailed Description

Structure containing HSS port configuration parameters.

Note: All of these are used for TX. Only some are specific to RX.

Definition at line **525** of file **IxHssAcc.h**.

Field Documentation

IxHssAccClkDir IxHssAccPortConfig::clkDirection

clock direction (tx/rx)

Definition at line **533** of file **IxHssAcc.h**.

IxHssAccClkEdge IxHssAccPortConfig::dataClkEdge

data clock edge type (tx/rx)

Definition at line **532** of file **IxHssAcc.h**.

IxHssAccDataEnable IxHssAccPortConfig::dataEnable

whether or not to drive the data pins (tx)

Definition at line **542** of file **IxHssAcc.h**.

IxHssAccBitEndian IxHssAccPortConfig::dataEndianness

data endianness (tx/rx)

Definition at line **539** of file **IxHssAcc.h**.

IxHssAccDataPolarity IxHssAccPortConfig::dataPolarity

data polarity type (tx/rx)

Definition at line **538** of file **IxHssAcc.h**.

IxHssAccDataRate IxHssAccPortConfig::dataRate

data rate in relation to the clock (tx/rx)

Definition at line **536** of file **IxHssAcc.h**.

IxHssAccDrainMode IxHssAccPortConfig::drainMode

tx pin open drain mode (tx)

Definition at line **540** of file **IxHssAcc.h**.

IxHssAccFbType IxHssAccPortConfig::fBitType

how to drive the Fbit (tx)

Definition at line **548** of file **IxHssAcc.h**.

IxHssAccSOFTType IxHssAccPortConfig::fBitUsage

start of frame types (tx/rx)

Definition at line **541** of file **IxHssAcc.h**.

unsigned IxHssAccPortConfig::frmOffset

frame pulse offset in bits wrt the first timeslot (0–1023) (tx/rx)

Definition at line **553** of file **IxHssAcc.h**.

IxHssAccFrmPulseUsage IxHssAccPortConfig::frmPulseUsage

whether to use the frame sync pulse or not (tx/rx)

Definition at line **534** of file **IxHssAcc.h**.

IxHssAccClkEdge IxHssAccPortConfig::frmSyncClkEdge

frame sync clock edge type (tx/rx)

Definition at line **530** of file **IxHssAcc.h**.

IxHssAccFrmSyncEnable IxHssAccPortConfig::frmSyncIO

how the frame sync pulse is used (tx/rx)

Definition at line **528** of file **IxHssAcc.h**.

IxHssAccFrmSyncType IxHssAccPortConfig::frmSyncType

frame sync pulse type (tx/rx)

Definition at line **527** of file **IxHssAcc.h**.

unsigned IxHssAccPortConfig::maxFrmSize

frame size in bits (1–1024) (tx/rx)

Definition at line **555** of file **IxHssAcc.h**.

IxHssAccTxSigType IxHssAccPortConfig::unassignedType

how to drive the data pins for unassigned type (tx)

Definition at line **546** of file **IxHssAcc.h**.

IxHssAcc56kEndianness IxHssAccPortConfig::voice56kEndian

56k data endianness when using the 56k type (tx)

Definition at line **549** of file **IxHssAcc.h**.

IxHssAcc56kSel IxHssAccPortConfig::voice56kSel

56k data transmission type when using the 56k type (tx)

Definition at line **551** of file **IxHssAcc.h**.

IxHssAccTxSigType IxHssAccPortConfig::voice56kType

how to drive the data pins for voice56k type (tx)

Definition at line **544** of file **IxHssAcc.h**.

The documentation for this struct was generated from the following file:

- **IxHssAcc.h**

IxI2cInitVars Struct Reference

[Intel (R) IXP400 Software I2C Driver(IxI2cDrv) API]

contains all the variables required to initialize the I2C unit

Data Fields

IxI2cSpeedMode I2cSpeedSelect

Select either normal (100kbps) or fast mode (400kbps).

IxI2cFlowMode I2cFlowSelect

Select interrupt or poll mode.

IxI2cMasterReadCallbackP MasterReadCBP

The master read callback pointer.

IxI2cMasterWriteCallbackP MasterWriteCBP

The master write callback pointer.

IxI2cSlaveReadCallbackP SlaveReadCBP

The slave read callback pointer.

IxI2cSlaveWriteCallbackP SlaveWriteCBP

The slave write callback pointer.

IxI2cGenCallCallbackP GenCallCBP

The general call callback pointer.

BOOL I2cGenCallResponseEnable

Enable/disable the unit to respond to general calls.

BOOL I2cSlaveAddrResponseEnable

Enable/disable the unit to respond to the slave address set in ISAR.

BOOL SCLEnable

Enable/disable the unit from driving the SCL line during master mode operation.

UINT8 I2cHWAddr

The address the unit will response to as a slave device.

Detailed Description

contains all the variables required to initialize the I2C unit

Structure to be filled and used for calling initialization

Definition at line **253** of file **IxI2cDrv.h**.

Field Documentation

IxI2cGenCallCallbackP IxI2cInitVars::GenCallCBP

The general call callback pointer.

Definition at line **267** of file **IxI2cDrv.h**.

IxI2cFlowMode IxI2cInitVars::I2cFlowSelect

Select interrupt or poll mode.

Definition at line **257** of file **IxI2cDrv.h**.

BOOL IxI2cInitVars::I2cGenCallResponseEnable

Enable/disable the unit to respond to general calls.

Definition at line **268** of file **IxI2cDrv.h**.

UINT8 IxI2cInitVars::I2cHWAddr

The address the unit will response to as a slave device.

Definition at line **276** of file **IxI2cDrv.h**.

BOOL IxI2cInitVars::I2cSlaveAddrResponseEnable

Enable/disable the unit to respond to the slave address set in ISAR.

Definition at line **270** of file **IxI2cDrv.h**.

IxI2cSpeedMode IxI2cInitVars::I2cSpeedSelect

Select either normal (100kbps) or fast mode (400kbps).

Definition at line **255** of file **IxI2cDrv.h**.

IxI2cMasterReadCallbackP IxI2cInitVars::MasterReadCBP

The master read callback pointer.

Definition at line **259** of file **IxI2cDrv.h**.

IxI2cMasterWriteCallbackP IxI2cInitVars::MasterWriteCBP

The master write callback pointer.

Definition at line **261** of file **IxI2cDrv.h**.

BOOL IxI2cInitVars::SCLEnable

Enable/disable the unit from driving the SCL line during master mode operation.

Definition at line **273** of file **IxI2cDrv.h**.

IxI2cSlaveReadCallbackP IxI2cInitVars::SlaveReadCBP

The slave read callback pointer.

Definition at line **263** of file **IxI2cDrv.h**.

IxI2cSlaveWriteCallbackP IxI2cInitVars::SlaveWriteCBP

The slave write callback pointer.

Definition at line **265** of file **IxI2cDrv.h**.

The documentation for this struct was generated from the following file:

- **IxI2cDrv.h**

Ixl2cStatsCounters Struct Reference

[Intel (R) IXP400 Software I2C Driver(Ixl2cDrv) API]

contains results of counters and their overflow

Data Fields

UINT32 **ixI2cMasterXmitCounter**

Total bytes transmitted as master.

UINT32 **ixI2cMasterFailedXmitCounter**

Total bytes failed for transmission as master.

UINT32 **ixI2cMasterRcvCounter**

Total bytes received as master.

UINT32 **ixI2cMasterFailedRcvCounter**

Total bytes failed for receival as master.

UINT32 **ixI2cSlaveXmitCounter**

Total bytes transmitted as slave.

UINT32 **ixI2cSlaveFailedXmitCounter**

Total bytes failed for transmission as slave.

UINT32 **ixI2cSlaveRcvCounter**

Total bytes received as slave.

UINT32 **ixI2cSlaveFailedRcvCounter**

Total bytes failed for receival as slave.

UINT32 **ixI2cGenAddrCallSucceedCounter**

Total bytes successfully transmitted for general address.

UINT32 **ixI2cGenAddrCallFailedCounter**

Total bytes failed transmission for general address.

UINT32 **ixI2cArbLossCounter**

Total instances of arbitration loss has occured.

Detailed Description

contains results of counters and their overflow

Structure contains all values of counters and associated overflows.

Definition at line **285** of file **IxI2cDrv.h**.

Field Documentation

UINT32 IxI2cStatsCounters::ixI2cArbLossCounter

Total instances of arbitration loss has occurred.

Definition at line **307** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cGenAddrCallFailedCounter

Total bytes failed transmission for general address.

Definition at line **305** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cGenAddrCallSucceedCounter

Total bytes successfully transmitted for general address.

Definition at line **303** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cMasterFailedRcvCounter

Total bytes failed for receival as master.

Definition at line **293** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cMasterFailedXmitCounter

Total bytes failed for transmission as master.

Definition at line **289** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cMasterRcvCounter

Total bytes received as master.

Definition at line **291** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cMasterXmitCounter

Total bytes transmitted as master.

Definition at line **287** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cSlaveFailedRcvCounter

Total bytes failed for receival as slave.

Definition at line **301** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cSlaveFailedXmitCounter

Total bytes failed for transmission as slave.

Definition at line **297** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cSlaveRcvCounter

Total bytes received as slave.

Definition at line **299** of file **IxI2cDrv.h**.

UINT32 IxI2cStatsCounters::ixI2cSlaveXmitCounter

Total bytes transmitted as slave.

Definition at line **295** of file **IxI2cDrv.h**.

The documentation for this struct was generated from the following file:

- **IxI2cDrv.h**

IxNpeDIImageId Struct Reference

[Intel (R) IXP Image ID Definition]

Image Id to identify each image contained in an image library.

Data Fields

IxNpeDINpeId npeId
NPE ID.

IxNpeDIDeviceId deviceId
Device Id.

IxNpeDIFunctionalityId functionalityId
Build ID indicates functionality of image.

IxNpeDIMajor major
Major Release Number.

IxNpeDIMinor minor
Minor Revision Number.

Detailed Description

Image Id to identify each image contained in an image library.

See **ixNpeDINpeInitAndStart** for more information.

Definition at line **251** of file **IxNpeDI.h**.

Field Documentation

IxNpeDIDeviceId IxNpeDIImageId::deviceId

Device Id.

Definition at line **254** of file **IxNpeDI.h**.

IxNpeDIFunctionalityId IxNpeDIImageId::functionalityId

Build ID indicates functionality of image.

Definition at line **255** of file **IxNpeDl.h**.

IxNpeDlMajor IxNpeDlImageId::major

Major Release Number.

Definition at line **256** of file **IxNpeDl.h**.

IxNpeDlMinor IxNpeDlImageId::minor

Minor Revision Number.

Definition at line **257** of file **IxNpeDl.h**.

IxNpeDlNpeId IxNpeDlImageId::npeId

NPE ID.

Definition at line **253** of file **IxNpeDl.h**.

The documentation for this struct was generated from the following file:

- **IxNpeDl.h**

IxNpeMhMessage Struct Reference

[Intel (R) IXP Software NPE Message Handler (IxNpeMh) API]

The 2–word message structure to send to and receive from the NPEs.

Data Fields

UINT32 **data** [2]

the actual data of the message

Detailed Description

The 2–word message structure to send to and receive from the NPEs.

Definition at line **93** of file **IxNpeMh.h**.

Field Documentation

UINT32 IxNpeMhMessage::data[2]

the actual data of the message

Definition at line **95** of file **IxNpeMh.h**.

The documentation for this struct was generated from the following file:

- **IxNpeMh.h**

IxParityENAccAHBErrorTransaction Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

The Master and Slave on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

Data Fields

IxParityENAccAHBErrorMaster **ahbErrorMaster**
Master on AHB bus.

IxParityENAccAHBErrorSlave **ahbErrorSlave**
Slave on AHB bus.

Detailed Description

The Master and Slave on the AHB bus interface whose transaction might have resulted in the parity error notification to Intel XScale(R) Processor.

NOTE: This information may be used in the data abort exception handler to differentiate between the Intel XScale(R) Processor and non–Intel XScale(R) Processor access to the SDRAM memory.

Definition at line **368** of file **IxParityENAcc.h**.

Field Documentation

IxParityENAccAHBErrorMaster IxParityENAccAHBErrorTransaction::ahbErrorMaster

Master on AHB bus.

Definition at line **370** of file **IxParityENAcc.h**.

IxParityENAccAHBErrorSlave IxParityENAccAHBErrorTransaction::ahbErrorSlave

Slave on AHB bus.

Definition at line **371** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccEbcConfig Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

Expansion Bus Controller parity detection is to be enabled or disabled.

Data Fields

IxParityENAccConfigOption ebcCs0Enabled

Expansion Bus Controller – Chip Select 0.

IxParityENAccConfigOption ebcCs1Enabled

Expansion Bus Controller – Chip Select 1.

IxParityENAccConfigOption ebcCs2Enabled

Expansion Bus Controller – Chip Select 2.

IxParityENAccConfigOption ebcCs3Enabled

Expansion Bus Controller – Chip Select 3.

IxParityENAccConfigOption ebcCs4Enabled

Expansion Bus Controller – Chip Select 4.

IxParityENAccConfigOption ebcCs5Enabled

Expansion Bus Controller – Chip Select 5.

IxParityENAccConfigOption ebcCs6Enabled

Expansion Bus Controller – Chip Select 6.

IxParityENAccConfigOption ebcCs7Enabled

Expansion Bus Controller – Chip Select 7.

IxParityENAccConfigOption ebcExtMstEnabled

External Master on Expansion bus.

IxParityENAccParityType parityOddEven

Parity – Odd or Even.

Detailed Description

Expansion Bus Controller parity detection is to be enabled or disabled.

Note: All the Chip Select(s) and External Masters will have the same parity

Definition at line 113 of file **IxParityENAcc.h**.

Field Documentation

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcCs0Enabled

Expansion Bus Controller – Chip Select 0.

Definition at line 115 of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcCs1Enabled

Expansion Bus Controller – Chip Select 1.

Definition at line 116 of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcCs2Enabled

Expansion Bus Controller – Chip Select 2.

Definition at line 117 of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcCs3Enabled

Expansion Bus Controller – Chip Select 3.

Definition at line 118 of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcCs4Enabled

Expansion Bus Controller – Chip Select 4.

Definition at line 119 of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcCs5Enabled

Expansion Bus Controller – Chip Select 5.

Definition at line 120 of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcCs6Enabled

Expansion Bus Controller – Chip Select 6.

Definition at line **121** of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcCs7Enabled

Expansion Bus Controller – Chip Select 7.

Definition at line **122** of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccEbcConfig::ebcExtMstEnabled

External Master on Expansion bus.

Definition at line **123** of file **IxParityENAcc.h**.

IxParityENAccParityType IxParityENAccEbcConfig::parityOddEven

Parity – Odd or Even.

Definition at line **124** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccEbcParityErrorStats Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

Expansion Bus Controller parity error statistics.

Data Fields

UINT32 **parityErrorsInbound**

Odd bit parity errors on inbound transfers.

UINT32 **parityErrorsOutbound**

Odd bit parity errors on outbound transfers.

Detailed Description

Expansion Bus Controller parity error statistics.

Definition at line **216** of file **IxParityENAcc.h**.

Field Documentation

UINT32 IxParityENAccEbcParityErrorStats::parityErrorsInbound

Odd bit parity errors on inbound transfers.

Definition at line **218** of file **IxParityENAcc.h**.

UINT32 IxParityENAccEbcParityErrorStats::parityErrorsOutbound

Odd bit parity errors on outbound transfers.

Definition at line **219** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccHWParityConfig Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

Parity error configuration of the Hardware Blocks.

Data Fields

IxParityENAccNpeConfig npeAConfig

NPE A parity detection is to be enabled/disabled.

IxParityENAccNpeConfig npeBConfig

NPE B parity detection is to be enabled/disabled.

IxParityENAccNpeConfig npeCConfig

NPE C parity detection is to be enabled/disabled.

IxParityENAccMcuConfig mcuConfig

MCU pairty detection is to be enabled/disabled.

IxParityENAccConfigOption swcpEnabled

SWCP parity detection is to be enabled.

IxParityENAccConfigOption aqmEnabled

AQM parity detection is to be enabled.

IxParityENAccPbcConfig pbcConfig

PCI Bus Controller parity detection is to be enabled/disabled.

IxParityENAccEbcConfig ebcConfig

Expansion Bus Controller parity detection is to be enabled/disabled.

Detailed Description

Parity error configuration of the Hardware Blocks.

Definition at line 149 of file IxParityENAcc.h.

Field Documentation

IxParityENAccConfigOption IxParityENAccHWParityConfig::aqmEnabled

AQM parity detection is to be enabled.

Definition at line **156** of file **IxParityENAcc.h**.

IxParityENAccEbcConfig IxParityENAccHWParityConfig::ebcConfig

Expansion Bus Controller parity detection is to be enabled/disabled.

Definition at line **158** of file **IxParityENAcc.h**.

IxParityENAccMcuConfig IxParityENAccHWParityConfig::mcuConfig

MCU pairty detection is to be enabled/disabled.

Definition at line **154** of file **IxParityENAcc.h**.

IxParityENAccNpeConfig IxParityENAccHWParityConfig::npeAConfig

NPE A parity detection is to be enabled/disabled.

Definition at line **151** of file **IxParityENAcc.h**.

IxParityENAccNpeConfig IxParityENAccHWParityConfig::npeBConfig

NPE B parity detection is to be enabled/disabled.

Definition at line **152** of file **IxParityENAcc.h**.

IxParityENAccNpeConfig IxParityENAccHWParityConfig::npeCConfig

NPE C parity detection is to be enabled/disabled.

Definition at line **153** of file **IxParityENAcc.h**.

IxParityENAccPbcConfig IxParityENAccHWParityConfig::pbcConfig

PCI Bus Controller parity detection is to be enabled/disabled.

Definition at line **157** of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccHWParityConfig::swcpEnabled

SWCP parity detection is to be enabled.

Definition at line **155** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccMcuConfig Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

MCU pairty detection is to be enabled/disabled.

Data Fields

IxParityENAccConfigOption singlebitDetectEnabled

Single-bit parity error detection.

IxParityENAccConfigOption singlebitCorrectionEnabled

Single-bit parity error correction.

IxParityENAccConfigOption multibitDetectionEnabled

Multi-bit parity error detection.

Detailed Description

MCU pairty detection is to be enabled/disabled.

Definition at line **96** of file **IxParityENAcc.h**.

Field Documentation

IxParityENAccConfigOption IxParityENAccMcuConfig::multibitDetectionEnabled

Multi-bit parity error detection.

Definition at line **100** of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccMcuConfig::singlebitCorrectionEnabled

Single-bit parity error correction.

Definition at line **99** of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccMcuConfig::singlebitDetectEnabled

Single-bit parity error detection.

Definition at line **98** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccMcuParityErrorStats Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

DDR Memory Control Unit parity error statistics.

Data Fields

UINT32 **parityErrorsSingleBit**

Parity errors of the type Single-Bit.

UINT32 **parityErrorsMultiBit**

Parity errors of the type Multi-Bit.

UINT32 **parityErrorsOverflow**

Parity errors when more than two parity errors occurred.

Detailed Description

DDR Memory Control Unit parity error statistics.

Note: There could be two outstanding parity errors at any given time whose address details captured. If there is no room for the new interrupt then it would be treated as overflow parity condition.

Definition at line **187** of file **IxParityENAcc.h**.

Field Documentation

UINT32 IxParityENAccMcuParityErrorStats::parityErrorsMultiBit

Parity errors of the type Multi-Bit.

Definition at line **190** of file **IxParityENAcc.h**.

UINT32 IxParityENAccMcuParityErrorStats::parityErrorsOverflow

Parity errors when more than two parity errors occurred.

Definition at line **191** of file **IxParityENAcc.h**.

UINT32 IxParityENAccMcuParityErrorStats::parityErrorsSingleBit

Parity errors of the type Single-Bit.

Definition at line **189** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccNpeConfig Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

NPE parity detection is to be enabled/disabled.

Data Fields

IxParityENAccConfigOption ideEnabled

NPE IMem, DMem and External.

IxParityENAccParityType parityOddEven

Parity – Odd or Even.

Detailed Description

NPE parity detection is to be enabled/disabled.

Definition at line **82** of file **IxParityENAcc.h**.

Field Documentation

IxParityENAccConfigOption IxParityENAccNpeConfig::ideEnabled

NPE IMem, DMem and External.

Definition at line **84** of file **IxParityENAcc.h**.

IxParityENAccParityType IxParityENAccNpeConfig::parityOddEven

Parity – Odd or Even.

Definition at line **85** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccNpeParityErrorStats Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

NPE parity error statistics.

Data Fields

UINT32 **parityErrorsIMem**

Parity errors in Instruction Memory.

UINT32 **parityErrorsDMMem**

Parity errors in Data Memory.

UINT32 **parityErrorsExternal**

Parity errors in NPE External Entities.

Detailed Description

NPE parity error statistics.

Definition at line **169** of file **IxParityENAcc.h**.

Field Documentation

UINT32 IxParityENAccNpeParityErrorStats::parityErrorsDMMem

Parity errors in Data Memory.

Definition at line **172** of file **IxParityENAcc.h**.

UINT32 IxParityENAccNpeParityErrorStats::parityErrorsExternal

Parity errors in NPE External Entities.

Definition at line **173** of file **IxParityENAcc.h**.

UINT32 IxParityENAccNpeParityErrorStats::parityErrorsIMem

Parity errors in Instruction Memory.

Definition at line **171** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccParityErrorContextMessage Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

Parity Error Context Message.

Data Fields

IxParityENAccParityErrorSource **pecParitySource**

Source info of parity error.

IxParityENAccParityErrorAccess **pecAccessType**

Read or Write Access Read – NPE, SWCP, AQM, DDR MCU, PCI Bus Ctrlr, Exp Bus Ctrlr (Outbound) Write – DDR MCU, PCI Bus Ctrlr, Exp Bus Ctrlr (Inbound i.e., External Master).

IxParityENAccParityErrorAddress **pecAddress**

Address faulty location Valid only for AQM, DDR MCU, Exp Bus Ctrlr.

IxParityENAccParityErrorData **pecData**

Data read from the faulty location Valid only for AQM and DDR MCU For DDR MCU it is the bit location of the Single-bit parity.

IxParityENAccParityErrorRequester **pecRequester**

Requester of SDRAM memory access Valid only for the DDR MCU.

IxParityENAccAHBErrorTransaction **ahbErrorTran**

Master and Slave information on the last AHB Error Transaction.

Detailed Description

Parity Error Context Message.

Definition at line 381 of file **IxParityENAcc.h**.

Field Documentation

IxParityENAccAHBErrorTransaction IxParityENAccParityErrorContextMessage::ahbErrorTran

Master and Slave information on the last AHB Error Transaction.

Definition at line **400** of file **IxParityENAcc.h**.

IxParityENAccParityErrorAccess IxParityENAccParityErrorContextMessage::pecAccessType

Read or Write Access Read – NPE, SWCP, AQM, DDR MCU, PCI Bus Ctrlr, Exp Bus Ctrlr (Outbound)
Write – DDR MCU, PCI Bus Ctrlr, Exp Bus Ctrlr (Inbound i.e., External Master).

Definition at line **384** of file **IxParityENAcc.h**.

IxParityENAccParityErrorAddress IxParityENAccParityErrorContextMessage::pecAddress

Address faulty location Valid only for AQM, DDR MCU, Exp Bus Ctrlr.

Definition at line **391** of file **IxParityENAcc.h**.

IxParityENAccParityErrorData IxParityENAccParityErrorContextMessage::pecData

Data read from the faulty location Valid only for AQM and DDR MCU For DDR MCU it is the bit location of the Single-bit parity.

Definition at line **394** of file **IxParityENAcc.h**.

IxParityENAccParityErrorSource IxParityENAccParityErrorContextMessage::pecParitySource

Source info of parity error.

Definition at line **383** of file **IxParityENAcc.h**.

IxParityENAccParityErrorRequester IxParityENAccParityErrorContextMessage::pecRequester

Requester of SDRAM memory access Valid only for the DDR MCU.

Definition at line **398** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccParityErrorStats Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

Parity Error Statistics for the all the hardware blocks.

Data Fields

IxParityENAccNpeParityErrorStats npeStats

NPE parity error statistics.

IxParityENAccMcuParityErrorStats mcuStats

MCU parity error statistics.

IxParityENAccPbcParityErrorStats pbcStats

PBC parity error statistics.

IxParityENAccEbcParityErrorStats ebcStats

EBC parity error statistics.

UINT32 **swcpStats**

SWCP parity error statistics.

UINT32 **aqmStats**

AQM parity error statistics.

Detailed Description

Parity Error Statistics for the all the hardware blocks.

Definition at line **230** of file **IxParityENAcc.h**.

Field Documentation

UINT32 IxParityENAccParityErrorStats::aqmStats

AQM parity error statistics.

Definition at line **237** of file **IxParityENAcc.h**.

IxParityENAccEbcParityErrorStats IxParityENAccParityErrorStats::ebcStats

EBC parity error statistics.

Definition at line **235** of file **IxParityENAcc.h**.

IxParityENAccMcuParityErrorStats IxParityENAccParityErrorStats::mcuStats

MCU parity error statistics.

Definition at line **233** of file **IxParityENAcc.h**.

IxParityENAccNpeParityErrorStats IxParityENAccParityErrorStats::npeStats

NPE parity error statistics.

Definition at line **232** of file **IxParityENAcc.h**.

IxParityENAccPbcParityErrorStats IxParityENAccParityErrorStats::pbcStats

PBC parity error statistics.

Definition at line **234** of file **IxParityENAcc.h**.

UINT32 IxParityENAccParityErrorStats::swcpStats

SWCP parity error statistics.

Definition at line **236** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccPbcConfig Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

PCI Bus Controller parity detection is to be enabled or disabled.

Data Fields

IxParityENAccConfigOption pbcInitiatorEnabled

PCI Bus Controller as PCI Initiator.

IxParityENAccConfigOption pbcTargetEnabled

PCI Bus Controller as PCI Target.

Detailed Description

PCI Bus Controller parity detection is to be enabled or disabled.

Definition at line 135 of file **IxParityENAcc.h**.

Field Documentation

IxParityENAccConfigOption IxParityENAccPbcConfig::pbcInitiatorEnabled

PCI Bus Controller as PCI Initiator.

Definition at line 137 of file **IxParityENAcc.h**.

IxParityENAccConfigOption IxParityENAccPbcConfig::pbcTargetEnabled

PCI Bus Controller as PCI Target.

Definition at line 138 of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxParityENAccPbcParityErrorStats Struct Reference

[Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API, Intel (R) IXP400 Software Parity Error Notifier (IxParityENAcc) API]

PCI Bus Controller parity error statistics.

Data Fields

UINT32 **parityErrorsPciInitiator**
Parity errors received as a PCI Initiator.

UINT32 **parityErrorsPciTarget**
Parity errors received as a PCI Target.

Detailed Description

PCI Bus Controller parity error statistics.

Definition at line **202** of file **IxParityENAcc.h**.

Field Documentation

UINT32 IxParityENAccPbcParityErrorStats::parityErrorsPciInitiator

Parity errors received as a PCI Initiator.

Definition at line **204** of file **IxParityENAcc.h**.

UINT32 IxParityENAccPbcParityErrorStats::parityErrorsPciTarget

Parity errors received as a PCI Target.

Definition at line **205** of file **IxParityENAcc.h**.

The documentation for this struct was generated from the following file:

- **IxParityENAcc.h**

IxPerfProfAccBusPmuResults Struct Reference

[Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API]

Results obtained from running the Bus Pmu component. The results are obtained when the get functions is called.

Data Fields

UINT32 **statsToGetLower27Bit** [IX_PERFPROF_ACC_BUS_PMU_MAX_PECs]
Lower 27 Bit of counter value.

UINT32 **statsToGetUpper32Bit** [IX_PERFPROF_ACC_BUS_PMU_MAX_PECs]
Upper 32 Bit of counter value.

Detailed Description

Results obtained from running the Bus Pmu component. The results are obtained when the get functions is called.

Definition at line **167** of file **IxPerfProfAcc.h**.

Field Documentation

UINT32
IxPerfProfAccBusPmuResults::statsToGetLower27Bit[IX_PERFPROF_ACC_BUS_PMU_MAX_PECs]

Lower 27 Bit of counter value.

Definition at line **169** of file **IxPerfProfAcc.h**.

UINT32
IxPerfProfAccBusPmuResults::statsToGetUpper32Bit[IX_PERFPROF_ACC_BUS_PMU_MAX_PECs]

Upper 32 Bit of counter value.

Definition at line **170** of file **IxPerfProfAcc.h**.

The documentation for this struct was generated from the following file:

- **IxPerfProfAcc.h**

IxPerfProfAccXcycleResults Struct Reference

[Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API]

Results obtained from Xcycle run.

Data Fields

float **maxIdlePercentage**
maximum percentage of Idle cycles

float **minIdlePercentage**
minimum percentage of Idle cycles

float **aveIdlePercentage**
average percentage of Idle cycles

UINT32 **totalMeasurements**
total number of measurement made

Detailed Description

Results obtained from Xcycle run.

Definition at line **153** of file **IxPerfProfAcc.h**.

Field Documentation

float IxPerfProfAccXcycleResults::aveIdlePercentage

average percentage of Idle cycles

Definition at line **157** of file **IxPerfProfAcc.h**.

float IxPerfProfAccXcycleResults::maxIdlePercentage

maximum percentage of Idle cycles

Definition at line **155** of file **IxPerfProfAcc.h**.

float IxPerfProfAccXcycleResults::minIdlePercentage

minimum percentage of Idle cycles

Definition at line **156** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXcycleResults::totalMeasurements

total number of measurement made

Definition at line **158** of file **IxPerfProfAcc.h**.

The documentation for this struct was generated from the following file:

- **IxPerfProfAcc.h**

IxPerfProfAccXscalePmuEvtCnt Struct Reference

[Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API]

contains results of a counter

Data Fields

UINT32 **lower32BitsEventCount**

lower 32bits value of the event counter

UINT32 **upper32BitsEventCount**

upper 32bits value of the event counter

Detailed Description

contains results of a counter

Structure contains the results of a counter, which are split into the lower and upper 32 bits of the final count

Definition at line **123** of file **IxPerfProfAcc.h**.

Field Documentation

UINT32 IxPerfProfAccXscalePmuEvtCnt::lower32BitsEventCount

lower 32bits value of the event counter

Definition at line **125** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuEvtCnt::upper32BitsEventCount

upper 32bits value of the event counter

Definition at line **126** of file **IxPerfProfAcc.h**.

The documentation for this struct was generated from the following file:

- **IxPerfProfAcc.h**

IxPerfProfAccXscalePmuResults Struct Reference

[Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API]

contains results of counters and their overflow

Data Fields

UINT32 **clk_value**

current value of clock counter

UINT32 **clk_samples**

number of clock counter overflows

UINT32 **event1_value**

current value of event 1 counter

UINT32 **event1_samples**

number of event 1 counter overflows

UINT32 **event2_value**

current value of event 2 counter

UINT32 **event2_samples**

number of event 2 counter overflows

UINT32 **event3_value**

current value of event 3 counter

UINT32 **event3_samples**

number of event 3 counter overflows

UINT32 **event4_value**

current value of event 4 counter

UINT32 **event4_samples**

number of event 4 counter overflows

Detailed Description

contains results of counters and their overflow

Structure contains all values of counters and associated overflows. The specific event and clock counters are determined by the user

Definition at line **135** of file **IxPerfProfAcc.h**.

Field Documentation

UINT32 IxPerfProfAccXscalePmuResults::clk_samples

number of clock counter overflows

Definition at line **138** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::clk_value

current value of clock counter

Definition at line **137** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::event1_samples

number of event 1 counter overflows

Definition at line **140** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::event1_value

current value of event 1 counter

Definition at line **139** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::event2_samples

number of event 2 counter overflows

Definition at line **142** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::event2_value

current value of event 2 counter

Definition at line **141** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::event3_samples

number of event 3 counter overflows

Definition at line **144** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::event3_value

current value of event 3 counter

Definition at line **143** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::event4_samples

number of event 4 counter overflows

Definition at line **146** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuResults::event4_value

current value of event 4 counter

Definition at line **145** of file **IxPerfProfAcc.h**.

The documentation for this struct was generated from the following file:

- **IxPerfProfAcc.h**

IxPerfProfAccXscalePmuSamplePcProfile Struct Reference

[Intel (R) IXP400 Software Performance Profiling (IxPerfProfAcc) API]

contains summary of samples taken

Data Fields

UINT32 **programCounter**

the program counter value of the sample

UINT32 **freq**

the frequency of the occurrence of the sample

Detailed Description

contains summary of samples taken

Structure contains all details of each program counter value – frequency that PC occurs

Definition at line **111** of file **IxPerfProfAcc.h**.

Field Documentation

UINT32 IxPerfProfAccXscalePmuSamplePcProfile::freq

the frequency of the occurrence of the sample

Definition at line **114** of file **IxPerfProfAcc.h**.

UINT32 IxPerfProfAccXscalePmuSamplePcProfile::programCounter

the program counter value of the sample

Definition at line **113** of file **IxPerfProfAcc.h**.

The documentation for this struct was generated from the following file:

- **IxPerfProfAcc.h**

IxSspAccStatsCounters Struct Reference

[Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API, Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API]

contains counters of the SSP statistics

Data Fields

UINT32 **ixSspRcvCounter**
Total frames received.

UINT32 **ixSspXmitCounter**
Total frames transmitted.

UINT32 **ixSspOverflowCounter**
Total occurrences of overflow.

Detailed Description

contains counters of the SSP statistics

Structure contains all values of counters and associated overflows.

Definition at line **348** of file **IxSspAcc.h**.

Field Documentation

UINT32 IxSspAccStatsCounters::ixSspOverflowCounter

Total occurrences of overflow.

Definition at line **352** of file **IxSspAcc.h**.

UINT32 IxSspAccStatsCounters::ixSspRcvCounter

Total frames received.

Definition at line **350** of file **IxSspAcc.h**.

UINT32 IxSspAccStatsCounters::ixSspXmitCounter

Total frames transmitted.

Definition at line **351** of file **IxSspAcc.h**.

The documentation for this struct was generated from the following file:

- **IxSspAcc.h**

IxSspInitVars Struct Reference

[Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API, Intel (R) IXP400 Software SSP Serial Port Access (IxSspAcc) API]

contains all the variables required to initialize the SSP serial port hardware.

Data Fields

IxSspAccFrameFormat FrameFormatSelected

Select between SPI, SSP and Microwire.

IxSspAccDataSize DataSizeSelected

Select between 4 and 16.

IxSspAccClkSource ClkSourceSelected

Select clock source to be on-chip or external.

IxSspAccFifoThreshold TxFIFOThresholdSelected

Select Tx FIFO threshold between 1 to 16.

IxSspAccFifoThreshold RxFIFOThresholdSelected

Select Rx FIFO threshold between 1 to 16.

BOOL RxFIFOIntrEnable

Enable/disable Rx FIFO threshold interrupt.

BOOL TxFIFOIntrEnable

Enable/disable Tx FIFO threshold interrupt.

RxFIFOThresholdHandler RxFIFOThsldHdlr

Pointer to function to handle a Rx FIFO interrupt.

TxFIFOThresholdHandler TxFIFOThsldHdlr

Pointer to function to handle a Tx FIFO interrupt.

RxFIFOOverrunHandler RxFIFOOverrunHdlr

Pointer to function to handle a Rx FIFO overrun interrupt.

BOOL LoopbackEnable

Select operation mode to be normal or loopback mode.

IxSspAccSpiSclkPhase SpiSclkPhaseSelected

Select SPI SCLK phase to start with one inactive cycle and end with 1/2 inactive cycle or start with 1/2 inactive cycle and end with one inactive cycle.

IxSspAccSpiSclkPolarity SpiSclkPolaritySelected

Select SPI SCLK idle state to be low or high.

IxSspAccMicrowireCtlWord MicrowireCtlWordSelected

Select Microwire control format to be 8 or 16-bit.

UINT8 SerialClkRateSelected

Select between 0 (1.8432Mbps) and 255 (7.2Kbps).

Detailed Description

contains all the variables required to initialize the SSP serial port hardware.

Structure to be filled and used for calling initialization

Definition at line **286** of file **IxSspAcc.h**.

Field Documentation

IxSspAccClkSource IxSspInitVars::ClkSourceSelected

Select clock source to be on-chip or external.

Definition at line **291** of file **IxSspAcc.h**.

IxSspAccDataSize IxSspInitVars::DataSizeSelected

Select between 4 and 16.

Definition at line **290** of file **IxSspAcc.h**.

IxSspAccFrameFormat IxSspInitVars::FrameFormatSelected

Select between SPI, SSP and Microwire.

Definition at line **288** of file **IxSspAcc.h**.

BOOL IxSspInitVars::LoopbackEnable

Select operation mode to be normal or loopback mode.

Definition at line **315** of file **IxSspAcc.h**.

IxSspAccMicrowireCtlWord IxSspInitVars::MicrowireCtlWordSelected

Select Microwire control format to be 8 or 16-bit.

(Only used in Microwire format).

Definition at line **330** of file **IxSspAcc.h**.

BOOL IxSspInitVars::RxFIFOIntrEnable

Enable/disable Rx FIFO threshold interrupt.

Disabling this interrupt will require the use of the polling function **RxFIFOExceedThresholdCheck**.

Definition at line **299** of file **IxSspAcc.h**.

RxFIFOOverrunHandler IxSspInitVars::RxFIFOOverrunHdlr

Pointer to function to handle a Rx FIFO overrun interrupt.

Definition at line **313** of file **IxSspAcc.h**.

IxSspAccFifoThreshold IxSspInitVars::RxFIFOThresholdSelected

Select Rx FIFO threshold between 1 to 16.

Definition at line **297** of file **IxSspAcc.h**.

RxFIFOThresholdHandler IxSspInitVars::RxFIFOThsldHdlr

Pointer to function to handle a Rx FIFO interrupt.

Definition at line **309** of file **IxSspAcc.h**.

UINT8 IxSspInitVars::SerialClkRateSelected

Select between 0 (1.8432Mbps) and 255 (7.2Kbps).

The formula used is Bit rate = $3.6864 \times 10^6 / (2 \times (\text{SerialClkRateSelect} + 1))$

Definition at line **333** of file **IxSspAcc.h**.

IxSspAccSpiSclkPhase IxSspInitVars::SpiSclkPhaseSelected

Select SPI SCLK phase to start with one inactive cycle and end with 1/2 inactive cycle or start with 1/2 inactive cycle and end with one inactive cycle.

(Only used in SPI format).

Definition at line **318** of file **IxSspAcc.h**.

IxSspAccSpiSclkPolarity IxSspInitVars::SpiSclkPolaritySelected

Select SPI SCLK idle state to be low or high.

(Only used in SPI format).

Definition at line **326** of file **IxSspAcc.h**.

BOOL IxSspInitVars::TxFIFOIntrEnable

Enable/disable Tx FIFO threshold interrupt.

Disabling this interrupt will require the use of the polling function `TxFIFOExceedThresholdCheck`.

Definition at line **304** of file **IxSspAcc.h**.

IxSspAccFifoThreshold IxSspInitVars::TxFIFOThresholdSelected

Select Tx FIFO threshold between 1 to 16.

Definition at line **294** of file **IxSspAcc.h**.

TxFIFOThresholdHandler IxSspInitVars::TxFIFOThsldHdlr

Pointer to function to handle a Tx FIFO interrupt.

Definition at line **311** of file **IxSspAcc.h**.

The documentation for this struct was generated from the following file:

- **IxSspAcc.h**

IxTimeSyncAccPtpMsgData Struct Reference

[Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API]

Struct for data from the PTP message returned when TimeStamp available.

Data Fields

IxTimeSyncAcc1588PTPMsgType **ptpMsgType**

PTP Messages type.

IxTimeSyncAccTimeValue **ptpTimeStamp**

64 bit TimeStamp value from PTP Message

IxTimeSyncAccUuid **ptpUuid**

48 bit UUID value from the PTP Message

UINT16 **ptpSequenceNumber**

16 bit Sequence Number from PTP Message

Detailed Description

Struct for data from the PTP message returned when TimeStamp available.

Definition at line **151** of file **IxTimeSyncAcc.h**.

Field Documentation

IxTimeSyncAcc1588PTPMsgType IxTimeSyncAccPtpMsgData::ptpMsgType

PTP Messages type.

Definition at line **153** of file **IxTimeSyncAcc.h**.

UINT16 IxTimeSyncAccPtpMsgData::ptpSequenceNumber

16 bit Sequence Number from PTP Message

Definition at line **156** of file **IxTimeSyncAcc.h**.

IxTimeSyncAccTimeValue IxTimeSyncAccPtpMsgData::ptpTimeStamp

64 bit TimeStamp value from PTP Message

Definition at line **154** of file **IxTimeSyncAcc.h**.

IxTimeSyncAccUuid IxTimeSyncAccPtpMsgData::ptpUuid

48 bit UUID value from the PTP Message

Definition at line **155** of file **IxTimeSyncAcc.h**.

The documentation for this struct was generated from the following file:

- **IxTimeSyncAcc.h**

IxTimeSyncAccStats Struct Reference

[Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API]

Statistics for the PTP messages.

Data Fields

UINT32 **rxMsgs**

Count of timestamps for received PTP Messages.

UINT32 **txMsgs**

Count of timestamps for transmitted PTP Messages.

Detailed Description

Statistics for the PTP messages.

Definition at line **166** of file **IxTimeSyncAcc.h**.

Field Documentation

UINT32 IxTimeSyncAccStats::rxMsgs

Count of timestamps for received PTP Messages.

Definition at line **168** of file **IxTimeSyncAcc.h**.

UINT32 IxTimeSyncAccStats::txMsgs

Count of timestamps for transmitted PTP Messages.

Definition at line **169** of file **IxTimeSyncAcc.h**.

The documentation for this struct was generated from the following file:

- **IxTimeSyncAcc.h**

IxTimeSyncAccTimeValue Struct Reference

[Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API]

Struct to hold 64 bit SystemTime and TimeStamp values.

Data Fields

UINT32 **timeValueLowWord**

Lower 32 bits of the time value.

UINT32 **timeValueHighWord**

Upper 32 bits of the time value.

Detailed Description

Struct to hold 64 bit SystemTime and TimeStamp values.

Definition at line **125** of file **IxTimeSyncAcc.h**.

Field Documentation

UINT32 IxTimeSyncAccTimeValue::timeValueHighWord

Upper 32 bits of the time value.

Definition at line **128** of file **IxTimeSyncAcc.h**.

UINT32 IxTimeSyncAccTimeValue::timeValueLowWord

Lower 32 bits of the time value.

Definition at line **127** of file **IxTimeSyncAcc.h**.

The documentation for this struct was generated from the following file:

- **IxTimeSyncAcc.h**

IxTimeSyncAccUuid Struct Reference

[Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API, Intel (R) IXP400 Software Time Sync Access Component API]

Struct to hold 48 bit UUID values captured in Sync or Delay_Req messages.

Data Fields

UINT32 **uuidValueLowWord**

The lower 32 bits of the UUID.

UINT16 **uuidValueHighHalfword**

The upper 16 bits of the UUID.

Detailed Description

Struct to hold 48 bit UUID values captured in Sync or Delay_Req messages.

Definition at line **138** of file **IxTimeSyncAcc.h**.

Field Documentation

UINT16 IxTimeSyncAccUuid::uuidValueHighHalfword

The upper 16 bits of the UUID.

Definition at line **141** of file **IxTimeSyncAcc.h**.

UINT32 IxTimeSyncAccUuid::uuidValueLowWord

The lower 32 bits of the UUID.

Definition at line **140** of file **IxTimeSyncAcc.h**.

The documentation for this struct was generated from the following file:

- **IxTimeSyncAcc.h**

ixUARTDev Struct Reference

[Intel (R) IXP400 Software UART Access (IxUARTAcc) API, Intel (R) IXP400 Software UART Access (IxUARTAcc) API]

Device descriptor for the UART.

Data Fields

UINT8 * **addr**
device base address

ixUARTMode **mode**
interrupt, polled or loopback

int **baudRate**
baud rate

int **freq**
UART clock frequency.

int **options**
hardware options

int **fifoSize**
FIFO xmit size.

ixUARTStats **stats**
device statistics

Detailed Description

Device descriptor for the UART.

Definition at line 333 of file **IxUART.h**.

Field Documentation

UINT8* ixUARTDev::addr

device base address

Definition at line 335 of file **IxUART.h**.

int ixUARTDev::baudRate

baud rate

Definition at line **337** of file **IxUART.h**.

int ixUARTDev::fifoSize

FIFO xmit size.

Definition at line **340** of file **IxUART.h**.

int ixUARTDev::freq

UART clock frequency.

Definition at line **338** of file **IxUART.h**.

ixUARTMode ixUARTDev::mode

interrupt, polled or loopback

Definition at line **336** of file **IxUART.h**.

int ixUARTDev::options

hardware options

Definition at line **339** of file **IxUART.h**.

ixUARTStats ixUARTDev::stats

device statistics

Definition at line **342** of file **IxUART.h**.

The documentation for this struct was generated from the following file:

- **IxUART.h**

ixUARTStats Struct Reference

[Intel (R) IXP400 Software UART Access (IxUARTAcc) API, Intel (R) IXP400 Software UART Access (IxUARTAcc) API]

Statistics for the UART.

Data Fields

UINT32 **rxCount**
UINT32 **txCount**
UINT32 **overrunErr**
UINT32 **parityErr**
UINT32 **framingErr**
UINT32 **breakErr**

Detailed Description

Statistics for the UART.

Definition at line **319** of file **IxUART.h**.

The documentation for this struct was generated from the following file:

- **IxUART.h**